

Safety Data Sheet

tert-Butyl Acrylate (TBA)

Revision date : 2025/10/06

Version: 5.0

Page: 1/14

(30041990/SDS_GEN_MX/EN)

1. Identification

Product identifier used on the label

tert-Butyl Acrylate (TBA)

Recommended use of the chemical and restriction on use

Recommended use*: Monomer.

Recommended use*: Monomer.

Unsuitable for use: Not intended for sale to or use by the general public.

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF Mexicana S.A. de C.V.

Av. Insurgentes Sur 975

Col. CD. De Los Deportes,

C.P. 03710 Ciudad de México

MÉXICO

Telephone: +52 55 5325 2600

Emergency telephone number

24 Hour Emergency Response Information

SETIQ: 1800-00-214-(Rep. Mexicana) or 55-59-15-88 (CDMX)

Telephone: +1-800-849-5204 or +1-833-229-1000

Other means of identification

Chemical family: acrylates

2. Hazards Identification

According to Regulation NOM-018-STPS-2015

Classification of the product

Flam. Liq.

2

Flammable liquids

Acute Tox.

3 (Inhalation - vapour)

Acute toxicity

Acute Tox.

4 (oral)

Acute toxicity

Safety Data Sheet

tert-Butyl Acrylate (TBA)

Revision date: 2025/10/06

Version: 5.0

Page: 2/14

(30041990/SDS_GEN_MX/EN)

Acute Tox.	4 (dermal)	Acute toxicity
Skin Irrit.	2	Skin irritation
Skin Sens.	1	Skin sensitization
STOT SE	3 (irritating to respiratory system)	Specific target organ toxicity — single exposure
Aquatic Acute	2	Hazardous to the aquatic environment - acute
Aquatic Chronic	2	Hazardous to the aquatic environment - chronic

Label elements

Pictogram:



Signal Word:
Danger

Hazard Statement:

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H331	Toxic if inhaled.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H302 + H312	Harmful if swallowed or in contact with skin.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves and eye protection or face protection.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist or vapour.
P273	Avoid release to the environment.
P243	Take action to prevent static discharges.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P272	Contaminated work clothing should not be allowed out of the workplace.
P270	Do not eat, drink or smoke when using this product.
P264	Wash contaminated body parts thoroughly after handling.
P242	Use non-sparking tools.
P240	Ground and bond container and receiving equipment.

Precautionary Statements (Response):

P311	Call a POISON CENTER or physician.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P361 + P364	Take off immediately all contaminated clothing and wash it before reuse.
P330	Rinse mouth.
P391	Collect spillage.
P370 + P378	In case of fire: Use water spray, dry powder, foam or carbon dioxide for extinction.

Safety Data Sheet

tert-Butyl Acrylate (TBA)

Revision date: 2025/10/06

Version: 5.0

Page: 3/14

(30041990/SDS_GEN_MX/EN)

Precautionary Statements (Storage):

P233 Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents/container in accordance with local regulations.

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture. See section 12 - Results of PBT and vPvB assessment.

Labeling of special preparations (GHS):

Risk of hazardous polymerization under certain conditions (e.g. elevated temperatures, low inhibitor and oxygen concentration). Do not blanket with nitrogen.

3. Composition / Information on Ingredients

According to Regulation NOM-018-STPS-2015

tert-butyl acrylate

CAS Number: 1663-39-4
Content (W/W): ≥ 80.0 - $\leq 100.0\%$
Synonym: 2-Propenoic acid 1,1-dimethylethyl ester

2-methylpropene

CAS Number: 115-11-7
Content (W/W): ≥ 0.1 - $\leq 1.5\%$
Synonym: 2-Methyl-1-propen

acrylic acid

CAS Number: 79-10-7
Content (W/W): ≥ 0.1 - $\leq 1.0\%$
Synonym: 2-Propenoic acid; Acrylic acid

The actual concentration is withheld as a trade secret.

4. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

Safety Data Sheet

tert-Butyl Acrylate (TBA)

Revision date: 2025/10/06

Version: 5.0

Page: 4/14

(30041990/SDS_GEN_MX/EN)

If on skin:

Immediately wash thoroughly with soap and water, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: Overexposure may cause: Eye irritation, skin irritation, erythema, allergic contact dermatitis, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps, Inhalation may provoke the following symptoms: irritation of respiratory tract, coughing

Hazards: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. (Further) symptoms and / or effects are not known so far

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
dry powder, water spray, carbon dioxide, foam

Unsuitable extinguishing media for safety reasons:
water jet

Additional information:
Use extinguishing measures to suit surroundings.

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
Risk of violent self-polymerization if overheated in a container. Cool endangered containers with water-spray.

Flammable. See SDS section 7 - Handling and storage.

Advice for fire-fighters

Protective equipment for fire-fighting:
Wear a self-contained breathing apparatus. Special protective equipment for firefighters

Further information:

Extend fire extinguishing measures to the surroundings. Fight fire from maximum distance. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

Safety Data Sheet

tert-Butyl Acrylate (TBA)

Revision date: 2025/10/06

Version: 5.0

Page: 5/14

(30041990/SDS_GEN_MX/EN)

In case of a fire in the vicinity a restabilization system should be used if the temperature in the bulk storage-tank reaches 45°C. Evacuate area of all unnecessary personnel. In case of a fire in the vicinity evacuate all personnel in a greater area if the temperature in the bulk storage-tank reaches 60°C.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Impact Sensitivity:

Remarks: Based on the chemical structure there is no shock-sensitivity.

6. Accidental release measures

Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

Release of substance/product can cause fire or explosion. Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

Personal precautions, protective equipment and emergency procedures

Handle in accordance with good industrial hygiene and safety practice.

Avoid all sources of ignition: heat, sparks, open flame. Use antistatic tools.

Environmental precautions

Discharge into the environment must be avoided. Collect contaminated washing water for appropriate disposal.

Methods and material for containment and cleaning up

For large amounts: Pump off product.

Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations. Ensure adequate ventilation. Suppress gases/vapours/mists with water spray jet. Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Cleaning operations should be carried out only while wearing breathing apparatus. Pick up with suitable appliance and dispose of.

7. Handling and Storage

Precautions for safe handling

The substance/ product may be handled only by appropriately trained personnel. Facility parts must be checked for polymer residues and cleaned on regular basis in order to avoid hazardous reactions.

Ensure thorough ventilation of stores and work areas. Encapsulation or exhaust ventilation required. When filling, transferring, or emptying of containers, adequate local exhaust ventilation is necessary. Vent waste air to atmosphere only through suitable separators. Check the condition of seals and connector screw threads.

The temperatures which must be avoided are to be considered. Protect against heat. Protect from direct sunlight. Protect contents from the effects of light. Do not open warm or swollen product containers. Remove persons to safety and alert fire brigade.

Safety Data Sheet

tert-Butyl Acrylate (TBA)

Revision date: 2025/10/06
Version: 5.0

Page: 6/14
(30041990/SDS_GEN_MX/EN)

Ensure adequate inhibitor and dissolved oxygen level.

Avoid inhalation of dusts/mists/vapours. Avoid aerosol formation. Avoid all direct contact with the substance/product.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Substance/product can form explosive mixture with air. Ground all transfer equipment properly to prevent electrostatic discharge. It is recommended that all conductive parts of the machinery are grounded. Explosion-proof equipment is not necessary when loading and processing of the product takes place at a minimum of 5 °C below the flash point.

Heated containers should be cooled to prevent polymerization. If exposed to fire, keep containers cool by spraying with water. Emergency cooling must be provided for the eventuality of a fire in the vicinity.

Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Prior to storage ensure that the transfer equipment used and the intended storage containers do not contain other substances/products. Before transfer to stock the identity of the product must be proved to be without doubt. The entrance to storage rooms is to be granted only to appropriately trained personnel.

The stabilizer is only effective in the presence of oxygen. Maintain contact with atmosphere containing 5 - 21% oxygen. Never use tanks with inert-gas installation for storage.

Risk of polymerization. Protect against heat. Protect from direct sunlight. Avoid UV-light and other radiation with high energy. Protect against contamination.

In case of bulk storage, the storage-tanks should at least be equipped with two high temperature alert devices.

Even if the product is stored and handled as prescribed/indicated it should be used up within the indicated duration of storage.

Storage stability:

Storage temperature: < 35 °C

Storage duration: 12 Months

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

acrylic acid	OEL, MX:	Skin Designation ; The substance can be absorbed through the skin.
	OEL, MX:	TWA value 2 ppm ;

Advice on system design:

Ensure adequate ventilation.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator as needed.

Safety Data Sheet

tert-Butyl Acrylate (TBA)

Revision date: 2025/10/06

Version: 5.0

Page: 7/14

(30041990/SDS_GEN_MX/EN)

Hand protection:

Chemical resistant protective gloves

Eye protection:

Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

General safety and hygiene measures:

Avoid contact with skin. Avoid inhalation of vapour. Wearing of closed work clothing is required additionally to the stated personal protection equipment. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

Physical state:	liquid	
Form:	liquid	
Odour:	ester-like	
Odour threshold:	not determined	
Colour:	colourless	
pH value:	not applicable	
Freezing point:	approx. -69 °C	
	Literature data.	
Melting point:	No data available.	
Boiling point:	119.2 °C	
	(1,013 hPa)	
Boiling range:	No data available.	
Flash point:	14 °C	(DIN 51755, closed cup)
Flammability:	Highly flammable.	(derived from flash - and boiling point)
Lower explosion limit:	For liquids not relevant for classification and labelling. The lower explosion point may be 5 - 15 °C below the flash point.	
	0.7 %(V)	
	(7.5 °C)	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
	7 %(V)	
	(46 °C)	
Autoignition:	400 °C	
	Literature data.	
SADT:	Not a substance/mixture liable to self-decomposition according to GHS.	
Vapour pressure:	20 hPa	(measured)
	(23.4 °C)	
	84.7 hPa	
	(50 °C)	
Density:	0.88 g/cm3	(pycnometer)
	(20 °C)	
Relative density:	0.88	
	(20 °C)	

Safety Data Sheet

tert-Butyl Acrylate (TBA)

Revision date: 2025/10/06

Version: 5.0

Page: 8/14

(30041990/SDS_GEN_MX/EN)

Relative vapour density:	4.41 (20 °C) Heavier than air.	(calculated)
Partitioning coefficient n-octanol/water (log Pow):	2.32 (25 °C)	(OECD Guideline 107)
Self-ignition temperature:	Based on its structural properties the product is not classified as self-igniting.	
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Viscosity, dynamic:	approx. 0.5 - 1.0 mPa.s (20 °C) By analogy with a product of similar composition	
Viscosity, kinematic:	(20 °C) not determined	
Solubility in water:	approx. 2 g/l (25 °C)	
Solubility (qualitative):	miscible solvent(s): organic solvents,	
Molecular weight:	128.17 g/mol	
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.	

Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular form.

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

No corrosive effect on metal.

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

Formation of
flammable gases:

Remarks:

Forms no flammable gases in the presence of water.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

Explosion and fire hazard exists under confined conditions. Ignitable air mixtures can form when the product is heated above the flash point and/or when sprayed or atomized. Formation of explosive gas/air mixtures.

Polymerization coupled with heat formation.

Risk of spontaneous polymerization by oxygen depletion of the liquid phase. Risk of spontaneous polymerization when heated or in the presence of UV radiation. Risk of spontaneous and violent self-

Safety Data Sheet

tert-Butyl Acrylate (TBA)

Revision date: 2025/10/06

Version: 5.0

Page: 9/14

(30041990/SDS_GEN_MX/EN)

polymerization if inhibitor is lost or product is exposed to excessive heat. Polymerization produces gases which may burst closed or confined containers. Reactions may cause ignition.

Risk of spontaneous polymerization in the presence of starters for radical chain reactions (e.g. peroxides). Reacts with nitric acid. Risk of spontaneous polymerization in the presence of oxidizing agents.

Hazardous reactions in presence of mentioned substances to avoid.

The product is stabilized against spontaneous polymerization prior to despatch. The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid

Avoid heat. Avoid oxygen content above the product of less than 5 %. Avoid UV-light and other radiation with high energy. Avoid direct sunlight. Avoid prolonged storage. Avoid inhibitor loss. Avoid excessive temperatures. Avoid all sources of ignition: heat, sparks, open flame. Avoid freezing. Avoid moisture.

Incompatible materials

radical formers, free radical initiators, peroxides, mercaptans, nitro-compounds, perborates, azides, ether, ketones, aldehydes, amines, nitrates, nitrites, oxidizing agents, reducing agents, strong bases, alkaline reactive substances, acid anhydrides, acid chlorides, concentrated mineral acids, metal salts
Inert gas

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Of moderate toxicity after short-term skin contact. Of moderate toxicity after single ingestion. Of pronounced toxicity after short-term inhalation.

Oral

Type of value: LD50

Species: rat (male/female)

Value: approx. 1,047 mg/kg (BASF-Test)

Inhalation

Type of value: LC50

Species: rat (male/female)

Value: 7 mg/l (BASF-Test)

Exposure time: 4 h

Safety Data Sheet

tert-Butyl Acrylate (TBA)

Revision date: 2025/10/06

Version: 5.0

Page: 10/14

(30041990/SDS_GEN_MX/EN)

The vapour was tested.

Dermal

Type of value: LD50

Species: rabbit

Value: 2,000 mg/kg (BASF-Test)

Assessment other acute effects

Assessment of STOT single:

Causes temporary irritation of the respiratory tract.

Irritation / corrosion

Assessment of irritating effects: Skin contact causes irritation. Not irritating to the eyes.

Skin

Species: rabbit

Result: Irritant.

Method: BASF-Test

Eye

Species: rabbit

Result: non-irritant

Method: BASF-Test

Sensitization

Assessment of sensitization: Sensitization after skin contact possible.

Mouse Local Lymph Node Assay (LLNA)

Species: mouse

Result: skin sensitizing

Method: OECD Guideline 429

Aspiration Hazard

not applicable

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: The substance may cause damage to the olfactory epithelium after repeated inhalation.

Genetic toxicity

Assessment of mutagenicity: The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture. The substance was not mutagenic in a test with mammals.

Carcinogenicity

Assessment of carcinogenicity: In long-term animal studies in which the substance was given by inhalation, a carcinogenic effect was not observed. The substance showed no carcinogenic activity in animals after chronic administration to the skin. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Reproductive toxicity

Assessment of reproduction toxicity: Animal studies gave no indication of a fertility impairing effect at doses which were not toxic to the parental animals. The chemical structure does not suggest a specific alert for such an effect. The results were determined in a Screening test (OECD 421/422).

Safety Data Sheet

tert-Butyl Acrylate (TBA)

Revision date: 2025/10/06

Version: 5.0

Page: 11/14

(30041990/SDS_GEN_MX/EN)

Teratogenicity

Assessment of teratogenicity: Animal studies gave no indication of a developmental toxic effect at doses that were not toxic to the parental animals. The chemical structure does not suggest a specific alert for such an effect. The results were determined in a Screening test (OECD 421/422).

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Acutely toxic for aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish

LC50 (96 h) 2.37 mg/l, *Leuciscus idus* (DIN 38412 Part 15, static)

Aquatic invertebrates

EC50 (48 h) 8.74 mg/l, *Daphnia magna* (OECD Guideline 202, part 1, static)

The statement of the toxic effect relates to the analytically determined concentration. The product is highly volatile. Tested in a closed test system.

Aquatic plants

EC50 (72 h) 14.6 mg/l (growth rate), *Desmodesmus subspicatus* (OECD Guideline 201, static)

The product is highly volatile. Tested in a closed test system. The statement of the toxic effect relates to the analytically determined concentration.

Chronic toxicity to fish

Study scientifically not justified.

Chronic toxicity to aquatic invertebrates

No observed effect concentration (21 d) 0.136 mg/l, *Daphnia magna* (OECD Guideline 211, semistatic)

The statement of the toxic effect relates to the analytically determined concentration. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

No observed effect concentration (21 d) 0.19 mg/l, *Daphnia magna* (Flow through.)

The statement of the toxic effect relates to the analytically determined concentration. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Assessment of terrestrial toxicity

No toxic effects have been observed in studies with soil living organisms.

Study scientifically not justified.

Soil living organisms

Toxicity to soil dwelling organisms:

EC50 (28 d) > 1,000 mg/kg, soil dwelling microorganisms (OECD Guideline 217)

Toxicity to terrestrial plants

No data available.

Safety Data Sheet

tert-Butyl Acrylate (TBA)

Revision date: 2025/10/06

Version: 5.0

Page: 12/14

(30041990/SDS_GEN_MX/EN)

Other terrestrial non-mammals

No data available.

Microorganisms/Effect on activated sludge

Toxicity to microorganisms

OECD Guideline 209 aquatic

activated sludge, domestic/EC20 (0.5 h): approx. 950 mg/l

Nominal concentration.

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

Moderately/partially biodegradable. Not readily biodegradable (by OECD criteria).

Elimination information

50 - 60 % CO₂ formation relative to the theoretical value (28 d) (ISO 14593) (aerobic, activated sludge, domestic)

Assessment of stability in water

In contact with water the substance will hydrolyse slowly.

Information on Stability in Water (Hydrolysis)

$t_{1/2} > 365$ d (25 °C, pH value 7), (calculated, pH 7)

In contact with water the substance will hydrolyse slowly.

Bioaccumulative potential

Assessment bioaccumulation potential

Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

Bioaccumulation potential

Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

Mobility in soil

Assessment transport between environmental compartments

The substance will not evaporate into the atmosphere from the water surface.

Adsorption to solid soil phase is not expected.

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. Do not discharge into drains/surface waters/groundwater.

Container disposal:

Uncleaned empties should be disposed of in the same manner as the contents.

Safety Data Sheet

tert-Butyl Acrylate (TBA)

Revision date: 2025/10/06
Version: 5.0

Page: 13/14
(30041990/SDS_GEN_MX/EN)

14. Transport Information

Land transport

TDG

Hazard class: 3
Packing group: II
ID number: UN 1992
Hazard label: 3, 6.1, EHSM
Proper shipping name: FLAMMABLE LIQUID, TOXIC, N.O.S. (contains TERT-BUTYLACRYLATE, STABILIZED)

Sea transport

IMDG

Hazard class: 3
Packing group: II
ID number: UN 1992
Hazard label: 3, 6.1, EHSM
Marine pollutant: YES
Proper shipping name: FLAMMABLE LIQUID, TOXIC, N.O.S. (contains TERT-BUTYLACRYLATE, STABILIZED)

Air transport

IATA/ICAO

Hazard class: 3
Packing group: II
ID number: UN 1992
Hazard label: 3, 6.1
Proper shipping name: FLAMMABLE LIQUID, TOXIC, N.O.S. (contains TERT-BUTYLACRYLATE, STABILIZED)

15. Regulatory Information

Federal Regulations

Not applicable

NFPA Hazard codes:

Health: 2 Fire: 3 Reactivity: 2 Special:

HMIS III rating

Health: 2 α Flammability: 3 Physical hazard: 1

Assessment of the hazard classes according to UN GHS criteria (most recent version):

Flam. Liq.	2	Flammable liquids
Aquatic Acute	2	Hazardous to the aquatic environment - acute
Aquatic Chronic	2	Hazardous to the aquatic environment - chronic
Acute Tox.	4 (oral)	Acute toxicity
Acute Tox.	4 (dermal)	Acute toxicity

Safety Data Sheet

tert-Butyl Acrylate (TBA)

Revision date: 2025/10/06

Version: 5.0

Page: 14/14

(30041990/SDS_GEN_MX/EN)

Acute Tox.	3 (Inhalation - vapour)	Acute toxicity
Skin Sens.	1	Skin sensitization
STOT SE	3 (irritating to respiratory system)	Specific target organ toxicity — single exposure
Skin Irrit.	2	Skin irritation

16. Other Information

SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2025/10/06

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

This information is considered accurate but is not exhaustive and shall only be used as a guideline based on current knowledge of the chemical substance or mixture. Safety precautions suitable for the product must be applied.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

Date / Revised: 2025/10/06

Version: 5.0

Date / Previous version: 2023/10/17

Previous version: 4.0

END OF DATA SHEET