

Safety Data Sheet

Kollidon® 25

Revision date : 2025/08/18

Version: 7.0

Page: 1/10

(30034967/SDS_GEN_MX/EN)

1. Identification

Product identifier used on the label

Kollidon® 25

Recommended use of the chemical and restriction on use

Recommended use*: pharmaceutical excipient

Unsuitable for use: Not intended for sale to or use by the general public.

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF Mexicana S.A. de C.V.
Av. Insurgentes Sur 975
Col. CD. De Los Deportes,
C.P. 03710 Ciudad de México
MÉXICO

Telephone: +52 55 5325 2600

Emergency telephone number

24 Hour Emergency Response Information

SETIQ: 1800-00-214-(Rep. Mexicana) or 55-59-15-88 (CDMX)

Telephone: +1-800-849-5204 or +1-833-229-1000

Other means of identification

Synonyms: Polyvinylpyrrolidone

2. Hazards Identification

According to Regulation NOM-018-STPS-2015

Classification of the product

Combustible Dust

Combustible Dust (1)

Combustible Dust

Label elements

Safety Data Sheet

Kollidon® 25

Revision date: 2025/08/18
Version: 7.0

Page: 2/10
(30034967/SDS_GEN_MX/EN)

Signal Word:
Warning

Hazard Statement:
May form combustible dust concentration in air.

Hazards not otherwise classified

The product is under certain conditions capable of dust explosion.

3. Composition / Information on Ingredients

According to Regulation NOM-018-STPS-2015

Under the referenced regulation, this product does not contain any components classified for health hazards above the relevant cut off value.

4. First-Aid Measures

Description of first aid measures

General advice:
Remove contaminated clothing.

If inhaled:
Keep patient calm, remove to fresh air.

If on skin:
Wash thoroughly with soap and water

If in eyes:
Wash affected eyes for at least 15 minutes under running water with eyelids held open.

If swallowed:
Rinse mouth and then drink 200-300 ml of water.

Most important symptoms and effects, both acute and delayed

Symptoms: No applicable information available.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Symptomatic treatment (decontamination, vital functions).

5. Fire-Fighting Measures

Extinguishing media

Safety Data Sheet

Kollidon® 25

Revision date: 2025/08/18
Version: 7.0

Page: 3/10
(30034967/SDS_GEN_MX/EN)

Suitable extinguishing media:
water spray, foam, dry powder

Additional information:
Avoid whirling up the material/product because of the danger of dust explosion.

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
cyanides, nitrogen oxides, carbon oxides
The substances/groups of substances mentioned can be released in case of fire.

Dust explosion hazard.

Advice for fire-fighters

Protective equipment for fire-fighting:
Wear a self-contained breathing apparatus.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Dusty conditions may ignite explosively in the presence of an ignition source causing flash fire.

6. Accidental release measures

Further accidental release measures:

Avoid the formation and build-up of dust - danger of dust explosion. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition. Avoid dispersal of dust in the air (e.g. by clearing dusty surfaces with compressed air).

Personal precautions, protective equipment and emergency procedures

Wear appropriate respiratory protection. Use personal protective clothing. Ensure adequate ventilation.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Contain with dust binding material and dispose of.
For large amounts: Sweep/shovel up.
Dispose of absorbed material in accordance with regulations. Avoid raising dust.

Nonsparking tools should be used.

7. Handling and Storage

Precautions for safe handling

Avoid dust formation. Provide exhaust ventilation if dust is formed.

Protection against fire and explosion:

Safety Data Sheet

Kollidon® 25

Revision date: 2025/08/18

Version: 7.0

Page: 4/10

(30034967/SDS_GEN_MX/EN)

Avoid dust formation. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Refer to NFPA 660 (2025) Standard for Combustible Dust and Particulate Solids. NFPA 660 is a combination of Standards NFPA 61 (Agriculture and Food), NFPA 484 (Metals), NFPA 652 (Fundamentals of Combustible Dusts), NFPA 654 (Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids), NFPA 65 (Sulfur), and NFPA 664 (Woodworking/Processing). Consult NFPA 660 standard for relevant commodity-specific and general safety information.

Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Avoid extreme heat. Keep container tightly closed and dry.

Storage stability:

No specific storage temperature specified.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Formic Acid	OEL, MX:	TWA value 5 ppm ;
	OEL, MX:	STEL value 10 ppm ;

Advice on system design:

Provide local exhaust ventilation to control dusts/mists. It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen deficient environment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Use only appropriately classified electrical equipment and powered industrial trucks.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator as needed.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Safety glasses with side-shields.

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is recommended. Wear protective clothing as necessary to minimize contact. No eating, drinking, smoking or tobacco use at the place of work. Hands and/or face should be washed before breaks and at the end of the shift. Store work clothing separately.

Safety Data Sheet

Kollidon® 25

Revision date: 2025/08/18
Version: 7.0

Page: 5/10
(30034967/SDS_GEN_MX/EN)

9. Physical and Chemical Properties

Physical state:	solid
Form:	powder
Odour:	almost odourless
Odour threshold:	not determined
Colour:	white to cream
pH value:	3.0 - 5.0
melting range:	$\geq 130\text{ }^{\circ}\text{C}$ The substance / product decomposes.
freezing range:	No data available.
Boiling point:	dropped
Flash point:	not applicable, the product is a solid
Flammability:	not highly flammable (VDI 2263, sheet 1, 1.2 (May 1990))
Lower explosion limit:	For solids not relevant for classification and labelling.
Upper explosion limit:	For solids not relevant for classification and labelling.
SADT:	Not a substance liable to self-decomposition according to UN transport regulations, class 4.1.
Vapour pressure:	negligible
Density:	No information is available for the absolute density. Instead the bulk density was determined as a more relevant value.
Bulk density:	400 - 490 kg/m ³
Relative vapour density:	The product is a non-volatile solid.
Partitioning coefficient n-octanol/water (log Pow):	No data available.
Thermal decomposition:	225 °C (DSC (DIN 51007))
Viscosity, dynamic:	not relevant
Viscosity, kinematic:	No data available.
Solubility in water:	fully soluble
Solubility (qualitative):	soluble
	solvent(s): organic solvents,
Molecular weight:	No data available.
Evaporation rate:	negligible

Particle characteristics

Particle size distribution: typically $> 30\text{ }\mu\text{m}$ (D50, Volumetric Distribution, ISO 13320-1)

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

Corrosive effects to metal are not anticipated.

Oxidizing properties:

not fire-propagating

Safety Data Sheet

Kollidon® 25

Revision date: 2025/08/18
Version: 7.0

Page: 6/10
(30034967/SDS_GEN_MX/EN)

Minimum ignition energy:

The product is capable of dust explosion.

Formation of
flammable gases:

Remarks:

Forms no flammable gases in the
presence of water.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

Dust explosion hazard.

Conditions to avoid

Avoid dust formation. Avoid electro-static discharge. Avoid all sources of ignition: heat, sparks, open flame.

Incompatible materials

strong alkalis

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

225 °C (DSC (DIN 51007))

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation.

Oral

Type of value: LD50

Species: rat

Value: > 2,000 mg/kg (BASF-Test)

Inhalation

Type of value: LC50

Species: rat

Value: > 5.2 mg/l (OECD Guideline 403)

Exposure time: 4 h

Safety Data Sheet

Kollidon® 25

Revision date: 2025/08/18
Version: 7.0

Page: 7/10
(30034967/SDS_GEN_MX/EN)

Dermal

No data available.

Assessment other acute effects

No data available.

Irritation / corrosion

Assessment of irritating effects: Not irritating to the skin. Not irritating to the eyes.

Skin

Species: rabbit

Result: non-irritant

Method: Draize test

Eye

Species: rabbit

Result: non-irritant

Method: Draize test

Sensitization

Assessment of sensitization: No data available.

Aspiration Hazard

not applicable

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: No data available.

Genetic toxicity

Assessment of mutagenicity: The substance was not mutagenic in studies with mammals.

Carcinogenicity

Assessment of carcinogenicity: In long-term animal studies in which the substance was given in high doses by feed, a carcinogenic effect was not observed.

Reproductive toxicity

Assessment of reproduction toxicity: No data available.

Reproduction

Experimental/calculated data: No data available.

Teratogenicity

Assessment of teratogenicity: No indications of a developmental toxic / teratogenic effect were seen in animal studies.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Safety Data Sheet

Kollidon® 25

Revision date: 2025/08/18
Version: 7.0

Page: 8/10
(30034967/SDS_GEN_MX/EN)

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish

LC50 (96 h) > 10,000 mg/l, *Leuciscus idus* (DIN 38412 Part 15, static)

Microorganisms/Effect on activated sludge

Toxicity to microorganisms

OECD Guideline 209 aerobic

activated sludge, industrial/EC20 (0.5 h): > 1,995 mg/l

Persistence and degradability

Assessment biodegradation and elimination (H2O)

Poorly eliminated from water.

Poorly eliminated from water.

Elimination information

< 10 % DOC reduction (15 d) (OECD Guideline 302 B) (aerobic, activated sludge, industrial) Poorly eliminated from water.

Bioaccumulative potential

Bioaccumulation potential

Based on its structural properties, the polymer is not biologically available. Accumulation in organisms is not to be expected.

Mobility in soil

Assessment transport between environmental compartments

No data available.

Additional information

Other ecotoxicological advice:

No data available.

13. Disposal considerations

Waste disposal of substance:

Do not discharge into drains/surface waters/groundwater. Dispose of in accordance with national, state and local regulations.

Container disposal:

Uncontaminated packaging can be re-used. Packs that cannot be cleaned should be disposed of in the same manner as the contents.

14. Transport Information

Safety Data Sheet

Kollidon® 25

Revision date: 2025/08/18
Version: 7.0

Page: 9/10
(30034967/SDS_GEN_MX/EN)

Land transport TDG

Not classified as a dangerous good under transport regulations

Sea transport IMDG

Not classified as a dangerous good under transport regulations

Air transport IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Not applicable

NFPA Hazard codes:

Health: 0 Fire: 1 Reactivity: 0 Special:

HMIS III rating

Health: 0 Flammability: 1 Physical hazard: 0

16. Other Information

SDS Prepared by:

BASF NA Product Regulations
SDS Prepared on: 2025/08/18

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Kollidon® 25 is a registered trademark of BASF Mexicana or BASF SE

This information is considered accurate but is not exhaustive and shall only be used as a guideline based on current knowledge of the chemical substance or mixture. Safety precautions suitable for the product must be applied.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO

Safety Data Sheet

Kollidon® 25

Revision date: 2025/08/18

Version: 7.0

Page: 10/10

(30034967/SDS_GEN_MX/EN)

DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

Date / Revised: 2025/08/18

Version: 7.0

Date / Previous version: 2022/11/03

Previous version: 6.0

END OF DATA SHEET