

# FoamStar<sup>®</sup> ST 2412

## Product description

FoamStar ST 2412 represents a novel series of defoamers based on new defoamer chemistry. It is the first new defoamer chemistry in over 30 years.

FoamStar is a defoaming molecule that defoams by a different mechanism. Unlike conventional defoamers (mineral oil or silicone), FoamStar defoams on a molecular level. It also has wetting properties not found in other conventional defoamers.

## Chemical nature

Molecule compounded in an enhanced mineral-oil system

## Properties

### Physical form

Opaque, off-white liquid

### Technical data (not supply specification)

Bulk density	lbs/gal	~ 7.0
Moisture	%	~ 0.5
Active substance	%	100
Dispersibility (10% in H <sub>2</sub> O)		non-dispersible

## Applications

FoamStar ST 2412 has the following advantages:

- Use 1/3 - 1/2 Less Defoamer
- Save at least 20 % on Defoamer Costs
- Non-separating & non-settling
- Extremely Effective in Low VOC coatings.
- Very Fast bubble-break versus conventional defoamers
- Effective against Microfoam

### Formulation guideline

In the grind portion of a flat paint formula, use 0.25 - 0.50 pounds of FoamStar ST 2412 per 100 gallons. In semi-gloss paint grind, use 0.50 - 1.0 pounds of FoamStar ST 2412 per 100 gallons. The rest of the FoamStar ST 2412 addition can be made to the letdown. FoamStar ST 2412 will be equally effective in both the letdown and the grind.

## Storage

FoamStar ST 2412 is subject to appropriate storage under the usual storage and temperature conditions, our products are durable for at least 1 year. FoamStar ST 2412 is shipped in 55 gallon (200 liter) steel drums and plastic tote tanks. If subjected to below freezing temperatures, product may congeal or stratify. Warm to room temperature and mix well before using.

**Contacts worldwide**

Asia  
BASF East Asia Regional Headquarters Ltd  
45/F, Jardine House  
No. 1 Connaught Place  
Central Hong Kong  
China  
[formulation-additives-asia@basf.com](mailto:formulation-additives-asia@basf.com)

Europe  
BASF SE  
Formulation Additives  
67056 Ludwigshafen  
Germany  
[formulation-additives-europe@basf.com](mailto:formulation-additives-europe@basf.com)

North America  
BASF Corporation  
11501 Steele Creek Road  
Charlotte, NC 28273  
USA  
[formulation-additives-nafta@basf.com](mailto:formulation-additives-nafta@basf.com)

South America  
BASF S.A  
Rochavérá - Crystal Tower  
Av. das Nações Unidas, 14.171  
Morumbi - São Paulo-SP  
Brazil  
[formulation-additives-south-america@basf.com](mailto:formulation-additives-south-america@basf.com)

**Validity**

This Technical Data Sheet is valid for all versions of the 0BFoamStar® ST 2412.

**Safety**

When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

**Note**

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = Registered trademark

™ = Trademark of the BASF Group, unless otherwise noted

[www.basf.com/formulation-additives](http://www.basf.com/formulation-additives)