

# Foamaster® NO 2306

**Product description** Defoamer

**Key benefits**

- Defoamer for aqueous paints and adhesives, free of mineral oils
- Outstanding defoaming properties

**Chemical nature** Based on alkyl poly(alkoxy esters) and fatty esters, mineral oil free

## Properties

**Physical form** Slightly amber turbid liquid

**Technical data**

(not supply specification)

Density	ISO 2811-3 (25°C)	0.960 – 1.000 g/cm <sup>3</sup>
pH – value	ISO 4316 (10 %, 20 °C)	7.5 – 9,5
Viscosity, dynamic	ISO 2555 (Brookfield LVF( 25 °C))	50 – 800 mPa.s

---

## Application

Foamaster® NO 2306 is a mineral-oil free defoamer for water-based paints and adhesives. It shows outstanding defoaming properties when used in emulsion paints, latex-based masonry finishes and adhesives based on acrylics, styrene acrylics, vinyl acetate ethylene copolymers and alkyd emulsions.

## Recommended concentrations

0.1 – 0.3 % on total formulation

Best results are obtained if half of the defoamer is added prior to grinding and the remainder at the let-down stage.

---

## Storage

Foamaster® NO 2306 should be stored in a cool dry place.

During storage of Foamaster® NO 2306 a slight sedimentation or phase separation might occur.

The defoaming properties of Foamaster® NO 2306 are not affected, if the product is mixed thoroughly prior to use.

### Contacts worldwide

Asia  
BASF East Asia Regional Headquarters Limited  
36/F, Two Taikoo Place,  
Taikoo Place,  
979 King's Road,  
Quarry Bay, Hong Kong  
[formulation-additives-asia@basf.com](mailto:formulation-additives-asia@basf.com)

North America  
BASF Corporation  
11501 Steele Creek Road  
Charlotte, NC 28273  
USA  
[formulation-additives-nafta@basf.com](mailto:formulation-additives-nafta@basf.com)

Europe  
BASF SE  
Formulation Additives  
67056 Ludwigshafen  
Germany  
[formulation-additives-europe@basf.com](mailto:formulation-additives-europe@basf.com)

South America  
BASF S.A.  
Rochaverá - Crystal Tower  
Av. das Nações Unidas, 14.171  
Morumbi - São Paulo-SP  
Brazil  
[formulation-additives-south-america@basf.com](mailto:formulation-additives-south-america@basf.com)

### Validity

This Technical Data Sheet is valid for all versions of the Foamaster® NO 2306.

### Safety

When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

### Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = Registered trademark

™ = Trademark of the BASF Group, unless otherwise noted

[www.basf.com/formulation-additives](http://www.basf.com/formulation-additives)