

Safety Data Sheet Kollidon® 30 Origin Germany

Revision date: 2025/08/13 Page: 1/10

Version: 9.0 (30034974/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

Kollidon® 30 Origin Germany

Recommended use of the chemical and restriction on use

Recommended use*: Polymer, pharmaceutical excipient Unsuitable for use: Not intended for sale to or use by the general public.

Details of the supplier of the safety data sheet

Company:
BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300

BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Synonyms: 2-Pyrrolidinone, 1-ethenyl-, homopolymer

2. Hazards Identification

According to Regulation 2024 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Combustible Dust Combustible Dust (1) Combustible Dust

Label elements

Signal Word: Warning

^{*} The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Kollidon® 30 Origin Germany

Revision date: 2025/08/13 Page: 2/10 Version: 9.0 (30034974/SDS_GEN_US/EN)

Hazard Statement:

May form combustible dust concentration in air.

Hazards not otherwise classified

The product is under certain conditions capable of dust explosion.

3. Composition / Information on Ingredients

According to Regulation 2024 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Under the referenced regulation, this product does not contain any components classified for health hazards above the relevant cut off value.

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air.

If on skin:

Wash thoroughly with soap and water

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open.

If swallowed:

Rinse mouth and then drink 200-300 ml of water.

Most important symptoms and effects, both acute and delayed

Symptoms: No data available.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Symptomatic treatment (decontamination, vital functions).

5. Fire-Fighting Measures

Extinguishing media

Kollidon® 30 Origin Germany

Revision date: 2025/08/13 Page: 3/10 Version: 9.0 (30034974/SDS GEN US/EN)

Suitable extinguishing media: water spray, foam, dry powder, carbon dioxide

Special hazards arising from the substance or mixture

Hazards during fire-fighting: carbon dioxide, nitrogen oxides

The substances/groups of substances mentioned can be released in case of fire.

Advice for fire-fighters

Protective equipment for fire-fighting:

Wear a self-contained breathing apparatus.

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Dusty conditions may ignite explosively in the presence of an ignition source causing flash fire.

6. Accidental release measures

Further accidental release measures:

Avoid the formation and build-up of dust - danger of dust explosion. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition. Avoid dispersal of dust in the air (e.g. by clearing dusty surfaces with compressed air).

Personal precautions, protective equipment and emergency procedures

Wear appropriate respiratory protection. Use personal protective clothing. Ensure adequate ventilation.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Sweep/shovel up. For large amounts: Sweep/shovel up.

Dispose of absorbed material in accordance with regulations. Avoid raising dust.

Nonsparking tools should be used.

7. Handling and Storage

Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid dust formation.

Protection against fire and explosion:

Avoid dust formation. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate

Safety Data Sheet Kollidon® 30 Origin Germany

Revision date: 2025/08/13 Page: 4/10 Version: 9.0 (30034974/SDS GEN US/EN)

precautions, such as electrical grounding and bonding, or inert atmospheres. Refer to NFPA 660 (2025) Standard for Combustible Dust and Particulate Solids. NFPA 660 is a combination of Standards NFPA 61 (Agriculture and Food), NFPA 484 (Metals), NFPA 652 (Fundamentals of Combustible Dusts), NFPA 654 (Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids), NFPA 65 (Sulfur), and NFPA 664 (Woodworking/Processing). Consult NFPA 660 standard for relevant commodity-specific and general safety information.

Conditions for safe storage, including any incompatibilities

No applicable information available.

Further information on storage conditions: Keep container tightly closed and dry.

8. Exposure Controls/Personal Protection

No substance specific occupational exposure limits known.

Advice on system design:

It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen deficient environment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Use only appropriately classified electrical equipment and powered industrial trucks.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator as needed.

Hand protection:

Wear impermeable chemical resistant protective gloves.

Eye protection:

Wear safety goggles (chemical goggles) if there is potential for airborne dust exposures.

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is recommended. Avoid contact with the skin, eyes and clothing. No eating, drinking, smoking or tobacco use at the place of work. Hands and/or face should be washed before breaks and at the end of the shift. Store work clothing separately.

9. Physical and Chemical Properties

Physical state: solid Form: powder

Odour: almost odourless
Odour threshold: not determined
Colour: white to cream

Kollidon® 30 Origin Germany

Revision date: 2025/08/13 Page: 5/10 Version: 9.0 (30034974/SDS_GEN_US/EN)

pH value: 3 - 5

(10 %(m), 20 °C)

onset of melting: 131 °C The substance / product

decomposes.

Freezing point: No data available. Boiling point: not applicable

Sublimation point: No applicable information available. Flash point: not applicable, the product is a solid

Flammability: not highly flammable (VDI 2263, sheet 1, 1.1 (May 1990))

Lower explosion limit: For solids not relevant for

classification and labelling. For solids not relevant for

Upper explosion limit: For solids not relevant for classification and labelling.

Vapour pressure: dropped

Density: No information is available for the

absolute density. Instead the bulk density was determined as a more

relevant value.

Bulk density: 400 - 600 kg/m3

Relative vapour density: The product is a non-volatile solid.

Partitioning coefficient n- not determined

octanol/water (log Pow):

Thermal decomposition: 150 °C (DSC (DIN 51007))

It is not a self-decompositionable substance. 150 °C, > 230 kJ/kg (DSC (DIN 51007))

Viscosity, kinematic: not applicable, the product is a solid

Solubility in water: fully soluble soluble soluble

solvent(s): organic solvents,

Molecular weight: No data available.

Evaporation rate: The product is a non-volatile solid.

Particle characteristics

Particle size distribution: typically > 30 µm (D50, Volumetric Distribution,

ISO 13320-1)

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

Corrosive effects to metal are not anticipated.

Oxidizing properties: not fire-propagating

Dust explosivity characteristics: Kst: 223 m.bar/s (VDI 2263)

Minimum ignition energy:

The product is capable of dust explosion.

Kollidon® 30 Origin Germany

Revision date: 2025/08/13 Page: 6/10 Version: 9.0 (30034974/SDS_GEN_US/EN)

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

Dust explosion hazard.

Conditions to avoid

Avoid dust formation. Avoid electro-static discharge. Avoid all sources of ignition: heat, sparks, open flame.

Incompatible materials

strong alkalies

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

150 °C (DSC (DIN 51007))

It is not a self-decompositionable substance.

150 °C (DSC (DIN 51007))

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation.

Oral

Type of value: LD50

Species: rat

Value: > 2,000 mg/kg (BASF-Test)

<u>Inhalation</u>

Type of value: LC50

Species: rat

Value: > 5.2 mg/l (OECD Guideline 403)

Exposure time: 4 h

Dermal

No applicable information available.

Assessment other acute effects

Kollidon® 30 Origin Germany

Revision date: 2025/08/13 Page: 7/10
Version: 9.0 (30034974/SDS_GEN_US/EN)

No data available.

Irritation / corrosion

Assessment of irritating effects: Not irritating to the skin. Not irritating to the eyes.

<u>Skin</u>

Species: rabbit Result: non-irritant Method: Draize test

<u>Eye</u>

Species: rabbit Result: non-irritant Method: Draize test

Sensitization

Assessment of sensitization: No sensitizing effect.

Aspiration Hazard not applicable

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: No data available.

Experimental/calculated data: No data available.

Genetic toxicity

Assessment of mutagenicity: The substance was not mutagenic in studies with mammals.

Carcinogenicity

Assessment of carcinogenicity: In long-term animal studies in which the substance was given in high doses by feed, a carcinogenic effect was not observed.

Reproductive toxicity

Assessment of reproduction toxicity: No data available.

Reproduction

Experimental/calculated data: No data available.

Teratogenicity

Assessment of teratogenicity: No indications of a developmental toxic / teratogenic effect were seen in animal studies.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Kollidon® 30 Origin Germany

Revision date: 2025/08/13 Page: 8/10 Version: 9.0 (30034974/SDS_GEN_US/EN)

Toxicity to fish

LC50 (96 h) > 10,000 mg/l, Leuciscus idus (DIN 38412 Part 15, static)

Assessment of terrestrial toxicity

No data available.

Microorganisms/Effect on activated sludge

Toxicity to microorganisms

OECD Guideline 209 aerobic

activated sludge, industrial/EC20 (0.5 h): > 1,995 mg/l

Persistence and degradability

Assessment biodegradation and elimination (H2O)

Poorly eliminated from water.

Elimination information

< 10 % DOC reduction (15 d) (OECD Guideline 302 B) (aerobic, activated sludge, industrial) Poorly eliminated from water.

Bioaccumulative potential

Bioaccumulation potential

Based on its structural properties, the polymer is not biologically available. Accumulation in organisms is not to be expected.

Mobility in soil

Assessment transport between environmental compartments

No data available.

Additional information

Other ecotoxicological advice:

No data available.

13. Disposal considerations

Waste disposal of substance:

Do not discharge into drains/surface waters/groundwater. Dispose of in accordance with national, state and local regulations.

Container disposal:

Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport

USDOT

Hazard class: 4.2 Packing group: III

ID number: UN 3088 Hazard label: 4.2

Kollidon® 30 Origin Germany

Revision date: 2025/08/13 Page: 9/10 Version: 9.0 (30034974/SDS GEN US/EN)

Proper shipping name: SELF-HEATING SOLID, ORGANIC, N.O.S. (contains 1-ETHENYL-

2-PYRROLIDINONE, HOMOPOLYMER)

Sea transport

IMDG

Hazard class: 4.2 Packing group: III

ID number: UN 3088 Hazard label: 4.2 Marine pollutant: NO

Proper shipping name: SELF-HEATING SOLID, ORGANIC, N.O.S. (contains 1-ETHENYL-

2-PYRROLIDINONE, HOMOPOLYMER)

Air transport

IATA/ICAO

Hazard class: 4.2
Packing group: III

ID number: UN 3088 Hazard label: 4.2

Proper shipping name: SELF-HEATING SOLID, ORGANIC, N.O.S. (contains 1-ETHENYL-

2-PYRROLIDINONE, HOMOPOLYMER)

Further information

Not dangerous goods of class 4.2 in packages up to 3000 litres capacity.

15. Regulatory Information

Federal Regulations

Registration status:

Pharma TSCA, US released / exempt

Chemical TSCA, US released / listed

Chemical TSCA, US

All substances are TSCA listed and active.

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including ACETALDEHYDE, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:

Health: 0 Fire: 1 Reactivity: 1 Special:

HMIS III rating

Health: 0 Flammability: 1 Physical hazard: 1

Safety Data Sheet Kollidon® 30 Origin Germany

Revision date: 2025/08/13 Page: 10/10 Version: 9.0 (30034974/SDS GEN US/EN)

16. Other Information

SDS Prepared by:

BASF NA Product Regulations SDS Prepared on: 2025/08/13

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Kollidon® 30 Origin Germany is a registered trademark of BASF Corporation or BASF SE IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

Date / Revised: 2025/08/13 Version: 9.0
Date / Previous version: 2024/03/07 Previous version: 8.0

END OF DATA SHEET