

Helaian Data Keselamatan

Safety data sheet

Mukasurat (Page): 1/26

BASF Helaian Data Keselamatan (BASF Safety data sheet)

Tarikh / Disemak (Date / Revised): 30.04.2025

Versi (Version): 3.0

Produk (Product): **Citronellal**

(30035052/SDS_GEN_MY/MS)

Tarikh cetakan (Date of print): 17.10.2025

1. Pengenalan bahan kimia dan pembekal

Citronellal

Nama bahan kimia: Citronellal

Nombor CAS: 106-23-0

Kegunaan: Kimia, Bahan kimia untuk detergen, Bahan kimia kosmetik dan jagaan mulut, bahan perasa

Syarikat:

BASF (Malaysia) Sdn Bhd
Lot 19.02 Level 19, 1 Powerhouse
No 1 Persiaran Bandar Utama
47800 Petaling Jaya
Selangor D.E, MALAYSIA
Nombor Telefon: +60 3 7612 1888
Nombor Telefax: +60 3 7612 1777

Maklumat kecemasan:

Nombor Kecemasan Kebangsaan
+603 7612 1999
Nombor Kecemasan Antarabangsa:
Nombor Telefon: +49 180 2273-112

2. Pengenalan Bahaya

Pengelasan bahan dan campuran:

Kreng. Kulit 2

Kreng. Mata 2

Pem. Kulit 1B

Bagi pengelasan yang tidak ditulis dengan penuh dalam bahagian ini, teks lengkap boleh didapati di bahagian 16.

Unsur label dan pernyataan berjaga-jaga:

Piktogram:



Kata Isyarat:
Amaran

Pernyataan Bahaya:

H319	Menyebabkan kerengsaan mata yang serius.
H315	Menyebabkan kerengsaan kulit.
H317	Boleh menyebabkan tindak balas kulit alergi.

Pernyataan Berjaga-jaga (Pencegahan):

P280	Pakai sarung tangan perlindungan dan perlindungan mata atau perlindungan muka.
P261	Elak daripada menghirup kabus atau wap atau semburan.
P272	Pakaian kerja yang tercemar tidak boleh dibawa keluar dari tempat kerja.
P264	Basuh bahagian badan yang tercemar dengan sepenuhnya selepas pengendalian.

Pernyataan Berjaga-jaga (Tindak Balas):

P305 + P351 + P338	JIKA TERKENA MATA: Bilas berhati-hati dengan air selama beberapa minit. Tanggalkan kanta lekap, jika ada dan dapat dilakukan dengan mudah. Teruskan membilas.
P333 + P313	JIKA TERKENA KULIT: Basuh dengan sabun dan air yang banyak. Jika berlaku kerengsaan kulit atau ruam: Dapatkan nasihat/rawatan perubatan.
P332 + P313	Jika berlaku kerengsaan kulit: Dapatkan nasihat/rawatan perubatan.
P362 + P364	Tanggalkan pakaian yang tercemar dan basuh sebelum menggunakannya semula.
P337 + P313	Jika kerengsaan mata berterusan: Dapatkan nasihat/rawatan perubatan.

Pernyataan Berjaga-jaga (Pelupusan):

P501	Buangkan kandungan dan bekas ke tempat pengumpulan bahan sisa merbahaya atau khas.
------	--

Bahaya lain yang tidak menyebabkan pengelasan:

Apabila tersebar halus pada bahan berliang, swapencucuhan mungkin berlaku.

3. Komposisi dan Maklumat Mengenai Ramuan Bahan Kimia

Kedaaan kimia

citronellal

Nombor CAS: 106-23-0

Bagi pengelasan yang tidak ditulis dengan penuh dalam bahagian ini, teks lengkap boleh didapati di bahagian 16.

4. Langkah-Langkah Pertolongan Cemas

Nasihat am:

Tanggalkan pakaian yang tercemar.

Jika tersedut:

Tenangkan pesakit, alihkan ke tempat berudara bersih, dapatkan rawatan perubatan.

Apabila terkena kulit:

Basuh bersih-bersih dengan sabun dan air.

Apabila terkena mata:

basuh mata yang terkena bahan selama sekurang-kurangnya 15 minit dibawah air yang mengalir dengan kelopak mata dibuka, rujuk kepada pakar mata.

Apabila tertelan:

Segera berkumur, kemudian minum 200-300 ml air, dapatkan rawatan perubatan.

Nota kepada doktor:

Gejala: Maklumat, iaitu maklumat tambahan mengenai simptom dan kesan boleh termasuk di dalam fasa palabelan GHS yang tersedia ada dalam Seksyen 2 dan di dalam penaksiran Toksikologi yang tersedia ada dalam Seksyen 11., Simptom dan/atau kesan tidak diketahui setakat ini

Nota kepada doktor:

Rawatan: Rawat mengikut gejala (nyahcemar, fungsi utama), tiada penawar khusus diketahui.

5. Langkah-Langkah Pemadaman Kebakaran

Bahan pemadam yang sesuai:

karbon dioksida, busa, serbuk kering

Alat memadam yang tidak sesuai untuk tujuan keselamatan:

air

Bahaya tertentu:

karbon oksida, wap yang merbahaya

Bahan/kumpulan bahan yang dinyatakan boleh dibebaskan jika berlaku kebakaran. Cecair mudah terbakar

Peralatan perlindungan khusus:

Gunakan alat pernafasan serba lengkap dan pakaian pelindung kimia.

Maklumat lanjut:

Kumpul air pemadam api yang tercemar secara berasingan, jangan biarkan ia mengalir ke dalam sistem pembetung atau efluen. Lupuskan sisa kebakaran dan air pemadam api yang tercemar menurut peraturan rasmi. Sejukkan bekas yang berbahaya dengan semburan air.

6. Langkah-Langkah Pelepasan Tidak Sengaja

Perlindungan diri, kelengkapan pelindung dan tatacara kecemasan:

Gunakan pakaian pelindung diri. Maklumat berhubung dengan langkah pencegahan diri lihat bahagian 8. Pastikan pengalihudaraan yang mencukupi. Jangan bernafaskan wap/semburan. Elakkan dari bersentuhan dengan kulit, mata dan pakaian.

Langkah berjaga-jaga untuk alam sekitar:

Jangan lepaskan ke dalam parit/air permukaan/air tanah.

Kaedah pembersihan atau penyerapan:

Bagi sejumlah kecil: Kutip dengan bahap penyerap yang sesuai. Jangan gunakan habuk gergaji atau bahan boleh terbakar yang lain sebagai penyerap semasa pencucian.

Bagi sejumlah besar: Bina benteng tumpahan. Tutup dengan selimut buih (alkohol tahan busa). Pam produk.

Lupuskan bahan yang diserap mengikut peraturan. Mengelap tumpahan dengan penyerap tidak mudah terbakar (seperti vermiculite, tikar tumpah) Tekstil kotor/kain pembersih/penyerap dan silika berupaya secara pencucuhan diri dan perlu dibasahkan dengan air dan mesti dibuang mengikut keadah yang selamat.

Maklumat tambahan: Apabila tersebar halus pada bahan berliang, swapencucuhan mungkin berlaku. Tekstil / kain pembersih yang kotor diperbuat daripada serat semulajadi (misalnya berasal dari bulu tulen atau dari kapas tulen) adalah mampu menyala dan tidak harus diguna dan/atau harus dibuang melalui cara yang selamat.

7. Pengendalian dan Penyimpanan

Pengendalian

Pastikan pengalihudaraan menyeluruh di kawasan simpanan dan di tempat kerja. Pakai pakaian perlindungan dan perlindungan mata/muka yang sesuai. Elakkan dari bersentuhan dengan kulit, mata dan pakaian. Pastikan bekas tertutup rapat. Produk ini boleh menyebabkan kerengsaan; basuh tangan anda setiap kali selepas terkena produk.

Perlindungan terhadap kebakaran dan letupan:

Bahaya pencucuhan sendiri apabila kawasan permukaan yang luas dihasilkan Tekstil kotor/kain pembersih/penyerap dan silika berupaya secara pencucuhan diri dan perlu dibasahkan dengan air dan mesti dibuang mengikut keadah yang selamat.

Jauhkan dari semua sumber pencucuhan: haba, percikan api, nyalaan terbuka. Ambil langkah berjaga-jaga terhadap luahan statik.

Penyimpanan

Sensitif bau: Asingkan daripada produk yang mengeluarkan bau.

Maklumat lanjut tentang keadaan penyimpanan: Pastikan bekas tertutup rapat dan kering; simpan di tempat yang dingin. Lindungi daripada haba.

8. Kawalan pendedahan dan perlindungan diri

Komponen dengan parameter kawalan tempat kerja

Tiada had pendedahan pekerjaan tertentu yang diketahui.

Peralatan perlindungan peribadi

Perlindungan pernafasan:

Perlindungan pernafasan yang sesuai bagi kepekatan yang tinggi atau kesan jangka panjang:

Penapis gas bagi gas/wap sebatian organik (takat didih >65°C, cth EN 14387 Jenis A)

Perlindungan tangan:

Sarung tangan kalis kimia yang sesuai (EN ISO 374-1) jika terkena secara langsung yang berpanjangan (Disyorkan: Indeks pelindung 6, sama dengan masa penelapan > 480 minit mengikut EN ISO 374-1): Misalnya getah nitril (0.4 mm), getah kloroprena (0.5 mm), polivinilklorida (0.7 mm) dan lainnya.

Nota tambahan : Spesifikasi adalah berdasarkan ujian –ujian, data penerbitan dan maklumat dari pengeluar sarung tangan atau diambil yang serupa secara analogi. Oleh sebab banyak keadaan yang perlu dipertimbangkan (misalnya suhu), perlulah diambil kira, bahawa secara praktikalnya tempoh penggunaan sarung tangan pelindung kimia mungkin lebih pendek daripada tempoh penelapan yang ditentukan menurut ujian.

Arahan penggunaan pengilang hendaklah dipatuhi kerana jenisnya yang pelbagai.

Perlindungan mata:

Kaca mata keselamatan dengan pelindung sisi (gogal berbingkai) (contohnya EN 166)

Perlindungan badan:

Perlindungan badan mesti dipilih bergantung kepada aktiviti dan pendedahan, contohnya apron, kasut perlindungan, pakaian perlindungan bahan kimia (Berdasarkan DIN-EN 465)

Langkah kebersihan dan keselamatan am:

Kendalikan mengikut amalan kesihatan dan keselamatan industri yang baik. Disyorkan memakai pakaian kerja yang tertutup. Elakkan dari bersentuhan dengan kulit, mata dan pakaian. Jangan makan, minum, merokok atau menggunakan tembakau di tempat kerja. Tangan dan/atau muka hendaklah dibasuh sebelum rehat dan setelah tamat waktu bekerja. Simpan pakaian kerja secara berasingan.

9. Sifat Fizikal dan Kimia

Bentuk:	cecair
Warna:	tidak berwarna hingga kekuningan
Bau:	buah
Ambang bau:	< 100 ppm
nilai pH:	dianggarkan 7
takat lebur:	< -20 °C (1,013 hPa)
takat didih:	206.9 °C (1,013 hPa)
	Data penulisan.

BASF Helaian Data Keselamatan (BASF Safety data sheet)

Tarikh / Disemak (Date / Revised): 30.04.2025

Versi (Version): 3.0

Produk (Product): **Citronellal**

(30035052/SDS_GEN_MY/MS)

Tarikh cetakan (Date of print): 17.10.2025

Takat kilat:	74 °C	(cawan tertutup)
	Data penulisan.	
Tahap penyejatan:	Nilai boleh dianggarkan berdasarkan Pemalar Hukum Henry atau tekanan wap.	
Kemudahbakaran (pepejal/gas):	Cecair boleh terbakar.	(diterbitkan daripada takat kilat)
Had letupan bawah:	Untuk cecair tiada kaitan untuk pengelasan dan pelabelan., Had letupan bawah mungkin 5 - 15 °C dibawah takat kilat.	
Had letupan atas:	Untuk cecair tiada kaitan untuk pengelasan dan pelabelan.	
Suhu pencucuhan:	202 °C	(DIN 51794)
Penguraian terma:	>= 190 °C	(DSC (DIN 51007))
pencucuhan sendiri:	Berdasarkan ciri strukturnya produk tidak dikelaskan sebagai mencucuh-sendiri.	Jenis ujian: Swanyalaan spontan pada suhu bilik.
Bahaya letupan:	Berdasarkan struktur kimia tiada petunjuk ciri-ciri mudah meletup.	
Sifat yang menggalakkan kebakaran:	Berdasarkan sifat strukturnya produk ini tidak dikelasifikasikan sebagai pengoksida.	
Tekanan Wap:	0.16 hPa (20 °C) dinamik	(OECD Guideline 104)
	1.73 hPa (50 °C) dinamik	(OECD Guideline 104)
Kepekatan:	0.85 g/cm ³ (20 °C)	
ketumpatan relatif:	0.86 (20 °C)	
Ketumpatan wap relatif (udara):	5.31 (20 °C) Lebih berat daripada udara	(dikira)
Keterlarutan dalam air:	88 mg/l (25 °C)	
Keterlarutan (kualitatif) pelarut:	pelarut organik terlarut	
Pekali petakan n-oktanol/air (log Pow):	3.62 (25 °C)	(Arahan 92/69/EEC, A.4)
Penjerapan/air-tanah:	KOC: 147.7; log KOC: 2.169	(dikira)

BASF Helaian Data Keselamatan (BASF Safety data sheet)

Tarikh / Disemak (Date / Revised): 30.04.2025

Versi (Version): 3.0

Produk (Product): **Citronellal**

(30035052/SDS_GEN_MY/MS)

Tarikh cetakan (Date of print): 17.10.2025

Tegangan permukaan:

Berdasarkan struktur kimia, aktiviti permukaan adalah tidak dijangka.

Kelikatan, dinamik:

1.48 mPa.s

(20 °C)

0.52 mPa.s

(100 °C)

Kelikatan, kinematik:

1.82 mm²/s

(20 °C)

1.33 mm²/s

(40 °C)

(OECD 114)

Jisim molar:

154.25 g/mol

10. Kestabilan dan Kereaktifan

Keadaan yang perlu dielakkan:

Jauhkan dari semua sumber pencucuhan: haba, percikan api, nyalaan terbuka. Lihat MSDS bahagian 7 - Pengendalian dan Penyimpanan.

Penguraian terma:

>= 190 °C (DSC (DIN 51007))

Bahan yang perlu dielakkan:

asid, alkali

Kakisan kepada

Kesan mengakis pada logam tidak dijangka.

logam:

Tindak balas berbahaya:

Penyalaan diri mungkin boleh berlaku apabila disebarkan secara halus di atas permukaan mudah terbakar dalam persekitaran berudara.

Bahan penguraian berbahaya:

Tiada produk penguraian yang berbahaya jika disimpan dan dikendalikan seperti yang ditetapkan/dinyatakan.

Kereaktifan:

Tiada produk penguraian yang berbahaya jika disimpan dan dikendalikan seperti yang ditetapkan/dinyatakan.

Kestabilan kimia:

Produk adalah stabil jika disimpan dan dikendalikan sebagaimana

11. Maklumat Toksikologi

Ketoksikan akut

Penilaian ketoksikan akut:

Ketoksikan yang rendah selepas sekali tertelan. Ketoksikan rendah selepas terkena kulit untuk jangka pendek.

BASF Helaian Data Keselamatan (BASF Safety data sheet)

Tarikh / Disemak (Date / Revised): 30.04.2025

Produk (Product): **Citronellal**

Versi (Version): 3.0

(30035052/SDS_GEN_MY/MS)

Tarikh cetakan (Date of print): 17.10.2025

Data eksperimen/dikira:

LD50 tikus (melalui mulut): 2,423 mg/kg (Ujian BASF)

LD50 arnab (dermal): > 2,500 - < 5,000 mg/kg

Kerengsaan

Penilaian kesan merengsa:

Terkena kulit boleh menyebabkan kerengsaan. Sentuhan dengan mata boleh menyebabkan kerengsaan.

Data eksperimen/dikira:

Kakisan/Kerengsaan kulit arnab: Merengsa (Ujian BASF)

Kerosakkan/kerengsaan mata yang serius arnab: Merengsa (Ujian BASF)

Pemekaan pernafasan/kulit

Penilaian pemekaan:

Menyebabkan pemekaan dalam kajian haiwan.

Data eksperimen/dikira:

Ujian pemaksimum tikus kasturi marmut: pemekaan kulit

Kemutagenan sel germa

Penilaian kemutagenan:

Bahan tidak mutagen dalam bakteria. Bahan tidak mutagen dalam kultur sel mamalia.

Kekarsinogenan

Penilaian kekarsinogenan:

Keputusan daripada beberapa kajian kekarsinogenan jangka panjang dapat diperolehi. Dengan mengambil kira semua maklumat tersebut, bahan itu sendiri tidak menunjukkan karsinogen. Produk belum diuji. Penyataan diambil daripada bahan/produk yang mempunyai struktur dan komposisi yang sama.

Ketoksikan pembiakan

Penilaian ketoksikan pembiakan:

Keputusan kajian haiwan tidak menunjukkan kesan gangguan kesuburan. Produk belum diuji. Penyataan diambil daripada bahan/produk yang mempunyai struktur dan komposisi yang sama.

Ketoksikan perkembangan

Penilaian keteratogenan:

Kajian haiwan tidak menunjukkan kesan yang menjejaskan kesuburan pada dos yang tidak toksik kepada haiwan induk. Produk belum diuji. Penyataan diambil daripada bahan/produk yang mempunyai struktur dan komposisi yang sama.

Ketoksikan khusus organ sasaran (sekali pendedahan):

Penilaian sekali STOT:

Berdasarkan data yang ada, kriteria pengelasan tidak dipenuhi.

Ketoksikan dos berulang dan Ketoksikan organ sasaran tertentu (pendedahan berulang)

Penilaian ketoksikan dos berulang:

Pendedahan secara berpanjangan atau berulang menyebabkan proses degeneratif mudah terbakar dalam saluran pernafasan tikus. Menyebabkan kesan merengsakan pada esofagus dan saluran gastrousus. Produk belum diuji. Penyataan diambil daripada bahan/produk yang mempunyai struktur dan komposisi yang sama.

Bahaya penyedutan

Tiada bahaya penyedutan dijangka.

12. Maklumat Ekologi

Keekotoksikan

Penilaian ketoksikan akuatik:

Toksik secara akut kepada organisma akuatik. Perencatan aktiviti degradasi di dalam enap cemar yang diaktifkan tidak dijangka akan berlaku semasa bahan berkepekatan rendah dimasukkan kedalam loji rawatan biologi.

Ketoksikan kepada ikan:

LC50 (96 h) dianggarkan 22 mg/l, *Leuciscus idus* (DIN 38412 Bahagian 15, statik)

Perincian kesan toksik berkaitan dengan kepekatan nominal.

Invertebrat air:

EC50 (48 h) 8.7 mg/l, *Daphnia magna* (Arahan 79/831/EEC, statik)

Perincian kesan toksik berkaitan dengan kepekatan nominal. Keterlarutan produk adalah rendah dalam medium ujian. Larutan akueus disediakan dengan pelarut telah diuji.

Tumbuhan akuatik:

EC50 (72 h) 13.33 mg/l (kadar pertumbuhan), *Scenedesmus subspicatus* (DIN 38412 Bahagian 9, statik)

Perincian kesan toksik berkaitan dengan kepekatan nominal.

Mikroorganisma/Kesan ke atas enap cemar diaktifkan:

EC20 (0.5 h) dianggarkan 400 mg/l, Enap cemar diaktifkan, domestik (Garis panduan OECD 209, statik)

Perincian kesan toksik berkaitan dengan kepekatan nominal.

Ketoksikan kronik kepada ikan:

Kajian secara saintifiknya tidak wajar.

Ketoksikan kronik kepada invertebrata akuatik:

Kajian secara saintifiknya tidak wajar.

Penilaian ketoksikan daratan:

Tiada data diperolehi.

Kajian secara saintifiknya tidak wajar.

Mobiliti

Penilaian pengangkutan di antara bahagian di persekitaran:
Bahan akan tersejat dengan perlahan-lahan ke atmosfera daripada permukaan air.
Penjerapan kepada fasa tanah pejal tidak dijangka

Keterusan dan boleh keterdegradasikan

Maklumat penyingkiran:
83 % Pembentukan CO₂ relatif kepada nilai teori (28 hari) (OECD 301B; ISO 9439; 92/69/EEC, C.4-C) (aerobik, enap cemar diaktifkan, domestik, tidak disesuaikan)

Penilaian kestabilan dalam air:
Bahan ini mudah terbiodegradasikan, oleh itu hidrolisis mungkin tidak berkaitan.

Potensi Biotumpukan

Penilaian potensi bioakumulasi:
Akumulasi yang ketara dalam organisma tidak dijangka.
Produk belum diuji. Penyataan diambil daripada struktur produk.

Potensi Biotumpukan:
Faktor Kebiopekatan: 113.6 (dikira)
Produk belum diuji. Penyataan diambil daripada struktur produk.

13. Maklumat Pelupusan

Patuhi keperluan undang-undang negara dan tempatan.

14. Maklumat Pengangkutan

Pengangkutan domestik:

Tidak dikelaskan sebagai berbahaya di bawah peraturan pengangkutan

Pengangkutan laut

IMDG

Tidak dikelaskan sebagai berbahaya di bawah peraturan pengangkutan

Pengangkutan udara

IATA/ICAO

Tidak dikelaskan sebagai berbahaya di bawah peraturan pengangkutan

Pengangkutan secara pukal menurut Lampiran II MARPOL dan IBC

Peraturan:	Tidak dinilai
Penghantaran yang diluluskan:	Tidak dinilai
Nama pencemaran:	Tidak dinilai
Kategori pencemaran:	Tidak dinilai
Jenis Kapal:	Tidak dinilai

15. Maklumat Pengawalseliaan

Peraturan-Peraturan Keselamatan dan Kesihatan Pekerjaan (Pengelasan, Pelabelan dan Helaian Data Keselamatan Bahan kimia Berbahaya) 2013
Akta OSHA 1994 dan peraturan berkaitan
Akta Kualiti Alam Sekeliling 1974

Maklumat tentang peraturan-peraturan tidak meliputi kesemuanya. Peraturan-peraturan lain mungkin dikenakan kepada bahan ini.

Peraturan lain

Jika maklumat peraturan lain yang berkenaan tidak dinyatakan dibahagian lain didalam risalah data keselamatan ini, ianya akan dinyatakan bahagian ini.

16. Maklumat lain

Tarikh Penyediaan / Tarikh Penyemakan: 30.04.2025

Sumber Maklumat dan Rujukan :

SDS ini disediakan dengan menggunakan data dan maklumat tersimpan di dalam sistem berasaskan IT dalaman kami dan dibekalkan oleh pembekal perkhidmatan syarikat kami.

Singkatan Petunjuk:

ATE - Anggaran Ketoksikan Akut

GHS - Sistem Terharmoni Global

IATA / ICAO - Persatuan Pengangkutan Udara Antarabangsa / Organisasi Penerbangan Awam Antarabangsa

IBC - Kontena Pukal Pertengahan

IMDG - Barangan Merbahaya Kelautan Antarabangsa

LC - Kepekatan Maut

LD - Dos Maut

OECD - Organisasi Untuk Kerjasama dan Pembangunan Ekonomi

OEL - Had Pendedahan Pekerjaan

OSHA - Akta Keselamatan dan Kesihatan Pekerjaan

STOT - Ketoksikan Organ Sasaran Khusus

Sebarang tujuan penggunaan lain hendaklah dibincangkan dengan pengeluar. Kadar perlindungan keselamatan untuk perkerjaan yang berkenaan hendaklah dipatuhi.

Teks penuh pengelasan, simbol bahaya dan pernyataan bahaya, jika dinyatakan dalam seksyen 2 atau 3:

BASF Helaian Data Keselamatan (BASF Safety data sheet)

Tarikh / Disemak (Date / Revised): 30.04.2025

Versi (Version): 3.0

Produk (Product): **Citronellal**

(30035052/SDS_GEN_MY/MS)

Tarikh cetakan (Date of print): 17.10.2025

Bhn. Ltp. T. Stab.	Bahan letup tidak stabil
Bhn. Ltp. 1.1	Bahan letup divisyen 1.1
Bhn. Ltp. 1.2	Bahan letup divisyen 1.2
Bhn. Ltp. 1.3	Bahan letup divisyen 1.3
Bhn. Ltp. 1.4	Bahan letup divisyen 1.4
Bhn. Ltp. 1.5	Bahan letup divisyen 1.5
Bhn. Ltp. 1.6	Bahan letup divisyen 1.6
Gas M. Bkr 1	Gas mudah terbakar kategori 1
Gas M. Bkr 2	Gas mudah terbakar kategori 2
Aerosol M. Bkr1	Aerosol mudah terbakar kategori 1
Aerosol M. Bkr 2	Aerosol mudah terbakar kategori 2
Cec. M. Bkr 1	Cecair mudah terbakar kategori 1
Cec. M. Bkr 2	Cecair mudah terbakar kategori 2
Cec. M. Bkr 3	Cecair mudah terbakar kategori 3
Pep. M. Bkr 1	Pepejal mudah terbakar kategori 1
Pep. M. Bkr 2	Pepejal mudah terbakar kategori 2
Gas Oks. 1	Gas mengoksida kategori 1
Cec. Oks. 1	Cecair mengoksida kategori 1
Cec. Oks. 2	Cecair mengoksida kategori 2
Cec. Oks. 3	Cecair mengoksida kategori 3
Pep. Oks. 1	Pepejal mengoksida kategori 1
Pep. Oks. 2	Pepejal mengoksida kategori 2
Pep. Oks. 3	Pepejal mengoksida kategori 3
Gas Tkn.	Gas di bawah tekanan
Swareak. A	Bahan kimia swareaktif jenis A
Swareak. B	Bahan kimia swareaktif jenis B
Swareak. CD	Bahan kimia swareaktif jenis C dan D
Swareak. EF	Bahan kimia swareaktif jenis E dan F
Swareak. G	Bahan kimia swareaktif jenis G
Cec. Pir. 1	Cecair piroforik kategori 1
Pep. Pir. 1	Pepejal piroforik kategori 1
Swapanas. 1	Bahan kimia swapanasan kategori 1
Swapanas. 2	Bahan kimia swapanasan kategori 2
Tdk. Bls. Air 1	Bahan kimia yang, jika terkena air, membebaskan gas mudah terbakar kategori 1
Tdk. Bls. Air 2	Bahan kimia yang, jika terkena air, membebaskan gas mudah terbakar kategori 2
Tdk. Bls. Air 3	Bahan kimia yang, jika terkena air, membebaskan gas mudah terbakar kategori 3
Peroks. Org. A	Peroksida organik jenis A
Peroks. Org. B	Peroksida organik jenis B
Peroks. Org. CD	Peroksida organik jenis C and D
Peroks. Org. EF	Peroksida organik jenis E and F
Peroks. Org. G	Peroksida organik jenis G
Kakis. Log. 1	Mengakis logam kategori 1
Toks. Akut 1	Ketoksikan akut kategori 1
Toks. Akut 2	Ketoksikan akut kategori 2
Toks. Akut 3	Ketoksikan akut kategori 3
Toks. Akut 4	Ketoksikan akut kategori 4
Kks. Kulit 1A	Kakisan atau kerengsaan kulit kategori 1A
Kks. Kulit 1B	Kakisan atau kerengsaan kulit kategori 1B
Kks. Kulit 1C	Kakisan atau kerengsaan kulit kategori 1C
Kreng. Kulit 2	Kakisan atau kerengsaan kulit kategori 2

BASF Helaian Data Keselamatan (BASF Safety data sheet)

Tarikh / Disemak (Date / Revised): 30.04.2025

Versi (Version): 3.0

Produk (Product): **Citronellal**

(30035052/SDS_GEN_MY/MS)

Tarikh cetakan (Date of print): 17.10.2025

Kros. Mata 1	Kerosakan mata atau kerengsaan mata yang serius kategori 1
Kreng. Mata 2	Kerosakan mata atau kerengsaan mata yang serius kategori 2
Pem. Naf. 1	Pemekaan pernafasan kategori 1
Pem. Kulit 1	Pemekaan kulit kategori 1
Muta. 1A	Kemutagenan sel germa kategori 1A
Muta. 1B	Kemutagenan sel germa kategori 1B
Muta. 2	Kemutagenan sel germa kategori 2
Kars. 1A	Kekarsinogenan kategori 1A
Kars. 1B	Kekarsinogenan kategori 1B
Kars. 2	Kekarsinogenan kategori 2
Pemb. 1A	Ketoksikan pembiakan kategori 1A
Pemb. 1B	Ketoksikan pembiakan kategori 1B
Pemb. 2	Ketoksikan pembiakan kategori 2
Laktasi	Kesan ke atas atau melalui penyusuan
STOT SE 1	Ketoksikan organ sasaran khusus - pendedahan tunggal kategori 1
STOT SE 2	Ketoksikan organ sasaran khusus - pendedahan tunggal kategori 2
STOT SE 3	Ketoksikan organ sasaran khusus - pendedahan tunggal kategori 3
STOT RE 1	Ketoksikan organ sasaran khusus - pendedahan berulang kategori 1
STOT RE 2	Ketoksikan organ sasaran khusus - pendedahan berulang kategori 2
Bhy. Asp.	Bahaya aspirasi kategori 1
Akuatik Akut 1	Berbahaya kepada persekitaran akuatik – bahaya akut kategori 1
Akuatik Kronik 1	Berbahaya kepada persekitaran akuatik – bahaya kronik kategori 1
Akuatik Kronik 2	Berbahaya kepada persekitaran akuatik – bahaya kronik kategori 2
Akuatik Kronik 3	Berbahaya kepada persekitaran akuatik – bahaya kronik kategori 3
Akuatik Kronik 4	Berbahaya kepada persekitaran akuatik – bahaya kronik kategori 4
Ozon	Berbahaya bagi lapisan ozon kategori 1

Garis menegak pada margin sebelah kiri tangan menunjukkan pindaan dari versi sebelumnya.

Data yang terdapat dalam risalah data keselamatan ini adalah berdasarkan pengetahuan dan pengalaman kami, dan menerangkan tentang produk yang berkaitan dengan keperluan keselamatan sahaja. Data tidak menyatakan ciri produk (spesifikasi produk). Data dalam risalah data keselamatan ini juga tidak menyatakan apa-apa ciri khusus atau kesesuaian produk yang dipersetujui untuk apa-apa tujuan tertentu. Penerima produk bertanggungjawab untuk memastikan bahawa apa-apa hak pemilikan serta undang-undang dan perundangan sedia ada dipatuhi.

1. Identification of the chemical and of the supplier

Citronellal

Chemical name: Citronellal

CAS Number: 106-23-0

Use: Chemical, Chemical for detergents, Cosmetic and oral care chemical, flavoring substance

Company:

BASF (Malaysia) Sdn Bhd
Lot 19.02 Level 19, 1 Powerhouse
No 1 Persiaran Bandar Utama
47800 Petaling Jaya
Selangor D.E, MALAYSIA
Telephone: +60 3 7612 1888
Telefax number: +60 3 7612 1777

Emergency information:

National emergency number:

+603 7612 1999

International emergency number:

Telephone: +49 180 2273-112

2. Hazard identification

Classification of the substance and mixture:

Skin Irrit. 2

Eye Irrit. 2

Skin Sens. 1B

For the classifications not written out in full in this section the full text can be found in section 16.

Label elements and precautionary statement:

Pictogram:



Signal Word:

Warning

Hazard Statement:

BASF Helaian Data Keselamatan (BASF Safety data sheet)

Tarikh / Disemak (Date / Revised): 30.04.2025

Versi (Version): 3.0

Produk (Product): **Citronellal**

(30035052/SDS_GEN_MY/MS)

Tarikh cetakan (Date of print): 17.10.2025

H319 Causes serious eye irritation.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.

Precautionary Statements (Prevention):

P280 Wear protective gloves and eye protection or face protection.
P261 Avoid breathing mist or vapour or spray.
P272 Contaminated work clothing should not be allowed out of the workplace.
P264 Wash contaminated body parts thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P332 + P313 If skin irritation occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P337 + P313 If eye irritation persists: Get medical attention.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste collection point.

Other hazards which do not result in classification:

When finely distributed on porose material, self-ignition is possible.

3. Composition/information on ingredients

Chemical nature

citronellal

CAS Number: 106-23-0

For the classifications not written out in full in this section the full text can be found in section 16.

4. First-Aid Measures

General advice:

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

Wash thoroughly with soap and water

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Note to physician:

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

Note to physician:

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Suitable extinguishing media:

carbon dioxide, foam, dry powder

Unsuitable extinguishing media for safety reasons:

water

Specific hazards:

carbon oxides, harmful vapours

The substances/groups of substances mentioned can be released in case of fire. Combustible Liquid

Special protective equipment:

Wear self-contained breathing apparatus and chemical-protective clothing.

Further information:

Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Cool endangered containers with water-spray.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

Use personal protective clothing. Information regarding personal protective measures, see section 8. Ensure adequate ventilation. Do not breathe vapour/spray. Avoid contact with the skin, eyes and clothing.

Environmental precautions:

Do not discharge into drains/surface waters/groundwater.

Methods for cleaning up or taking up:

For small amounts: Pick up with suitable absorbent material. Do not use saw-dust or other combustible substances as an absorbant during cleanup.

For large amounts: Dike spillage. Cover with blanket of foam (alcohol-resistant foam). Pump off product.

Dispose of absorbed material in accordance with regulations. Mop up spills with non-flammable adsorbents (e.g. vermiculite, spill mats). Soiled textiles / cleaning rags / adsorbents and Silica are capable of self ignition and should be wetted with water and must be disposed of in a safe manner.

Additional information: When finely distributed on porose material, self-ignition is possible. Soiled textiles/cleaning rags made of natural fibres (e.g. of pure wool or of pure cotton) are capable of ignition and should not be used and/or must be desposed of in a safe manner.

7. Handling and Storage

Handling

Ensure thorough ventilation of stores and work areas. Wear suitable protective clothing and eye/face protection. Avoid contact with the skin, eyes and clothing. Keep container tightly sealed. This product may cause irritations; wash your hands after every contact.

Protection against fire and explosion:

Risk of self-ignition when a large surface area is produced due to fine dispersion. Soiled textiles / cleaning rags / adsorbents and Silica are capable of self ignition and should be wetted with water and must be disposed of in a safe manner. Avoid all sources of ignition: heat, sparks, open flame. Take precautionary measures against static discharges.

Storage

Odour-sensitive: Segregate from products releasing odours.

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place. Protect against heat.

8. Exposure controls and personal protection

Components with occupational exposure limits

No substance specific occupational exposure limits known.

Personal protective equipment

Respiratory protection:

Suitable respiratory protection for higher concentrations or long-term effect: Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:

Suitable chemical resistant safety gloves (EN ISO 374-1) also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): E.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) etc. Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g.

temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is recommended. Avoid contact with the skin, eyes and clothing. No eating, drinking, smoking or tobacco use at the place of work. Hands and/or face should be washed before breaks and at the end of the shift. Store work clothing separately.

9. Physical and Chemical Properties

Form:	liquid	
Colour:	colourless to yellowish	
Odour:	fruity	
Odour threshold:	< 100 ppm	
pH value:	approx. 7	
Melting point:	< -20 °C (1,013 hPa)	
Boiling point:	206.9 °C (1,013 hPa) Literature data.	
Flash point:	74 °C Literature data.	(closed cup)
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.	
Flammability (solid/gas):	Combustible liquid.	(derived from flash point)
Lower explosion limit:	For liquids not relevant for classification and labelling., The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Ignition temperature:	202 °C	(DIN 51794)
Thermal decomposition:	>= 190 °C	(DSC (DIN 51007))

Self ignition:	Based on its structural properties the product is not classified as self-igniting.	Test type: Spontaneous self-ignition at room-temperature.
Explosion hazard:	Based on the chemical structure there is no indication of explosive properties.	
Fire promoting properties:	Based on its structural properties the product is not classified as oxidizing.	
Vapour pressure:	0.16 hPa (20 °C) dynamic	(OECD Guideline 104)
	1.73 hPa (50 °C) dynamic	(OECD Guideline 104)
Density:	0.85 g/cm ³ (20 °C)	
Relative density:	0.86 (20 °C)	
Relative vapour density (air):	5.31 (20 °C) Heavier than air.	(calculated)
Solubility in water:	88 mg/l (25 °C)	
Solubility (qualitative) solvent(s):	organic solvents soluble	
Partitioning coefficient n-octanol/water (log Pow):	3.62 (25 °C)	(Directive 92/69/EEC, A.8)
Adsorption/water - soil:	KOC: 147.7; log KOC: 2.169	(calculated)
Surface tension:	Based on chemical structure, surface activity is not to be expected.	
Viscosity, dynamic:	1.48 mPa.s (20 °C) 0.52 mPa.s (100 °C)	
Viscosity, kinematic:	1.82 mm ² /s (20 °C) 1.33 mm ² /s (40 °C)	(OECD Guideline 114)
Molar mass:	154.25 g/mol	

10. Stability and Reactivity

Conditions to avoid:

Avoid all sources of ignition: heat, sparks, open flame. See SDS section 7 - Handling and storage.

Thermal decomposition:

$\geq 190\text{ }^{\circ}\text{C}$ (DSC (DIN 51007))

Substances to avoid:

acids, bases

Corrosion to metals: Corrosive effects to metal are not anticipated.

Hazardous reactions:

Self-ignition is possible when finely distributed on flammable surfaces in the presence of air.

Hazardous decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Reactivity:

No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability:

The product is stable if stored and handled as prescribed/indicated.

11. Toxicological Information

Acute toxicity

Assessment of acute toxicity:

Of low toxicity after single ingestion. Of low toxicity after short-term skin contact.

Experimental/calculated data:

LD50 rat (oral): 2,423 mg/kg (BASF-Test)

LD50 rabbit (dermal): $> 2,500 - < 5,000$ mg/kg

Irritation

Assessment of irritating effects:

Skin contact causes irritation. Eye contact causes irritation.

Experimental/calculated data:

Skin corrosion/irritation rabbit: Irritant. (BASF-Test)

Serious eye damage/irritation rabbit: Irritant. (BASF-Test)

Respiratory/Skin sensitization

Assessment of sensitization:

Caused skin sensitization in animal studies.

Experimental/calculated data:

Guinea pig maximization test guinea pig: skin sensitizing

Germ cell mutagenicity

Assessment of mutagenicity:

The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture.

Carcinogenicity

Assessment of carcinogenicity:

Results from a number of long-term carcinogenicity studies are available. Taking into account all of the information, there is no indication that the substance itself is carcinogenic. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Reproductive toxicity

Assessment of reproduction toxicity:

The results of animal studies gave no indication of a fertility impairing effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Developmental toxicity

Assessment of teratogenicity:

Animal studies gave no indication of a developmental toxic effect at doses that were not toxic to the parental animals. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Specific target organ toxicity (single exposure):

Assessment of STOT single:

Based on available data, the classification criteria are not met.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Prolonged repeated exposure caused inflammable degenerative processes in the respiratory tract of rats. Causes irritating effects at esophagus and the gastro-intestinal tract. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aspiration hazard

No aspiration hazard expected.

12. Ecological Information**Ecotoxicity**

Assessment of aquatic toxicity:

Acutely toxic for aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish:

LC50 (96 h) approx. 22 mg/l, *Leuciscus idus* (DIN 38412 Part 15, static)

The details of the toxic effect relate to the nominal concentration.

Aquatic invertebrates:

EC50 (48 h) 8.7 mg/l, *Daphnia magna* (Directive 79/831/EEC, static)

The details of the toxic effect relate to the nominal concentration. The product has low solubility in the test medium. An aqueous solution prepared with solubilizers has been tested.

Aquatic plants:

EC50 (72 h) 13.33 mg/l (growth rate), *Scenedesmus subspicatus* (DIN 38412 Part 9, static)

The details of the toxic effect relate to the nominal concentration.

Microorganisms/Effect on activated sludge:

EC20 (0.5 h) approx. 400 mg/l, activated sludge, domestic (OECD Guideline 209, static)

The details of the toxic effect relate to the nominal concentration.

Chronic toxicity to fish:

Study scientifically not justified.

Chronic toxicity to aquatic invertebrates:

Study scientifically not justified.

Assessment of terrestrial toxicity:

No data available.

Study scientifically not justified.

Mobility

Assessment transport between environmental compartments:

The substance will slowly evaporate into the atmosphere from the water surface.

Adsorption to solid soil phase is not expected.

Persistence and degradability

Elimination information:

83 % CO₂ formation relative to the theoretical value (28 d) (OECD 301B; ISO 9439; 92/69/EWG, C.4-C) (aerobic, activated sludge, domestic, non-adapted)

Assessment of stability in water:

Substance is readily biodegradable, therefore hydrolysis is not expected to be relevant.

Bioaccumulation potential

Assessment bioaccumulation potential:

Significant accumulation in organisms is not to be expected.

The product has not been tested. The statement has been derived from the structure of the product.

Bioaccumulation potential:

Bioconcentration factor: 113.6 (calculated)

The product has not been tested. The statement has been derived from the structure of the product.

BASF Helaian Data Keselamatan (BASF Safety data sheet)

Tarikh / Disemak (Date / Revised): 30.04.2025

Produk (Product): **Citronellal**

Versi (Version): 3.0

(30035052/SDS_GEN_MY/MS)

Tarikh cetakan (Date of print): 17.10.2025

13. Disposal Information

Observe national and local legal requirements.

14. Transportation Information

Domestic transport:

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

Transport in bulk according to Annex II of MARPOL and the IBC Code

Regulation: Not evaluated

Shipment approved: Not evaluated

Pollution name: Not evaluated

Pollution category: Not evaluated

Ship Type: Not evaluated

15. Regulatory Information

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

OSHA 1994 and relevant regulations

Environmental Quality Act, 1974

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Other regulations

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

16. Other Information

Date of Preparation / Date of Revision: 30.04.2025

Information Source and References:

This SDS is prepared using data and information saved in our internal IT-based system and supplied by our company's service providers.

Key Abbreviations:

ATE - Acute Toxicity Estimates

GHS - Globally Harmonized System

IATA / ICAO - International Air Transport Association / International Civil Aviation Organization

IBC - Intermediate Bulk Container

IMDG - International Maritime Dangerous Goods

LC - Lethal Concentration

LD - Lethal Dose

OECD - Organisation for Economic Co-operation and Development

OEL - Occupational Exposure Limit

OSHA - Occupational Safety and Health Act

STOT - Specific Target Organ Toxicity

Any other intended applications should be discussed with the manufacturer. Corresponding occupational protection measurements must be followed.

Full text of classifications, hazard symbols and hazard statements, if mentioned in section 2 or 3:

Unst. Expl.	Unstable explosives
Expl. 1.1	Explosives division 1.1
Expl. 1.2	Explosives division 1.2
Expl. 1.3	Explosives division 1.3
Expl. 1.4	Explosives division 1.4
Expl. 1.5	Explosives division 1.5
Expl. 1.6	Explosives division 1.6
Flam. Gas 1	Flammable gases category 1
Flam. Gas 2	Flammable gases category 2
Flam. Aerosol 1	Flammable aerosols category 1
Flam. Aerosol 2	Flammable aerosols category 2
Flam. Liq. 1	Flammable liquids category 1
Flam. Liq. 2	Flammable liquids category 2
Flam. Liq. 3	Flammable liquids category 3
Flam. Sol. 1	Flammable solids category 1
Flam. Sol. 2	Flammable solids category 2
Ox. Gas 1	Oxidizing gases category 1
Ox. Liq. 1	Oxidizing liquids category 1
Ox. Liq. 2	Oxidizing liquids category 2
Ox. Liq. 3	Oxidizing liquids category 3
Ox. Sol. 1	Oxidizing solids category 1
Ox. Sol. 2	Oxidizing solids category 2
Ox. Sol. 3	Oxidizing solids category 3
Press. Gas	Gases under pressure
Self-react. A	Self-reactive chemicals type A
Self-react. B	Self-reactive chemicals type B
Self-react. CD	Self-reactive chemicals type C and D
Self-react. EF	Self-reactive chemicals type E and F
Self-react. G	Self-reactive chemicals type G
Pyr. Liq. 1	Pyrophoric liquids category 1

BASF Helaian Data Keselamatan (BASF Safety data sheet)

Tarikh / Disemak (Date / Revised): 30.04.2025

Versi (Version): 3.0

Produk (Product): **Citronellal**

(30035052/SDS_GEN_MY/MS)

Tarikh cetakan (Date of print): 17.10.2025

Pyr. Sol. 1	Pyrophoric solids category 1
Self-heat. 1	Self-heating chemicals category 1
Self-heat. 2	Self-heating chemicals category 2
Water-react. 1	Chemicals which, if in contact with water, emits flammable gases category 1
Water-react. 2	Chemicals which, if in contact with water, emits flammable gases category 2
Water-react. 3	Chemicals which, if in contact with water, emits flammable gases category 3
Org. Perox. A	Organic peroxides type A
Org. Perox. B	Organic peroxides type B
Org. Perox. CD	Organic peroxides type C and D
Org. Perox. EF	Organic peroxides type E and F
Org. Perox. G	Organic peroxides type G
Met. Corr. 1	Corrosive to metals category 1
Acute Tox. 1	Acute toxicity category 1
Acute Tox. 2	Acute toxicity category 2
Acute Tox. 3	Acute toxicity category 3
Acute Tox. 4	Acute toxicity category 4
Skin Corr. 1A	Skin corrosion or irritation category 1A
Skin Corr. 1B	Skin corrosion or irritation category 1B
Skin Corr. 1C	Skin corrosion or irritation category 1C
Skin Irrit. 2	Skin corrosion or irritation category 2
Eye Dam. 1	Serious eye damage or eye irritation category 1
Eye Irrit. 2	Serious eye damage or eye irritation category 2
Resp. Sens. 1	Respiratory sensitization category 1
Skin Sens. 1	Skin sensitization category 1
Muta. 1A	Germ cell mutagenicity category 1A
Muta. 1B	Germ cell mutagenicity category 1B
Muta. 2	Germ cell mutagenicity category 2
Carc. 1A	Carcinogenicity category 1A
Carc. 1B	Carcinogenicity category 1B
Carc. 2	Carcinogenicity category 2
Repr. 1A	Reproductive toxicity category 1A
Repr. 1B	Reproductive toxicity category 1B
Repr. 2	Reproductive toxicity category 2
Lact.	Effect on or via lactation
STOT SE 1	Specific target organ toxicity – single exposure category 1
STOT SE 2	Specific target organ toxicity – single exposure category 2
STOT SE 3	Specific target organ toxicity – single exposure category 3
STOT RE 1	Specific target organ toxicity – repeated exposure category 1
STOT RE 2	Specific target organ toxicity – repeated exposure category 2
Asp. Haz.	Aspiration hazard category 1
Aquatic Acute 1	Hazardous to the aquatic environment – acute hazard category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – chronic hazard category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – chronic hazard category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – chronic hazard category 3
Aquatic Chronic 4	Hazardous to the aquatic environment – chronic hazard category 4
Ozone	Hazardous to the ozone layer category 1

Vertical lines in the left hand margin indicate an amendment from the previous version.

BASF Helaian Data Keselamatan (BASF Safety data sheet)

Tarikh / Disemak (Date / Revised): 30.04.2025

Versi (Version): 3.0

Produk (Product): **Citronellal**

(30035052/SDS_GEN_MY/MS)

Tarikh cetakan (Date of print): 17.10.2025

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.