

## Safety data sheet

Page: 1/129

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

## **Linalyl Acetate**

Chemical name: Linalyl acetate

CAS Number: 115-95-7

REACH registration number: 01-2119454789-19-0000

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Chemical, Chemical for detergents, Cosmetic and oral care chemical, flavoring substance

For the detailed identified uses of the product see appendix of the safety data sheet.

#### 1.3. Details of the supplier of the safety data sheet

Company: BASF SE 67056 Ludwigshafen GERMANY Contact address: BASF France SAS 176, rue Montmartre 75002 PARIS FRANCE

Telephone: +33 1 4964-5732

E-mail address: securite-produits.france@basf.com

## 1.4. Emergency telephone number

Tél.: 01 45 42 59 59 (APPEL D'URGENCE ORFILA)

Fax: 01 49 64 53 80 (heures de bureau)

International emergency number (Numéro d'urgence international):

contact speaking the language of the calling country (contact parlant la langue du pays d'appel)

Telephone: +49 180 2273-112

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

#### **SECTION 2: Hazards Identification**

#### 2.1. Classification of the substance or mixture

According to Regulation (EC) No 1272/2008 [CLP]

Skin Corr./Irrit. 2 H315 Causes skin irritation.

Eye Dam./Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1B H317 May cause an allergic skin reaction.

For the classifications not written out in full in this section the full text can be found in section 16.

#### 2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

Pictogram:



#### Signal Word:

Warning

Hazard Statement:

H319 Causes serious eye irritation. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

Precautionary Statements (Prevention):

P280 Wear protective gloves and eye protection or face protection.

P261 Avoid breathing mist or vapour or spray.

Precautionary Statements (Response):

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P333 + P313 If skin irritation or rash occurs: Get medical attention.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste

collection point.

#### 2.3. Other hazards

## According to Regulation (EC) No 1272/2008 [CLP]

The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria. Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

## **SECTION 3: Composition/Information on Ingredients**

#### 3.1. Substances

Chemical nature

Linalyl acetate

Skin Corr./Irrit. 2
CAS Number: 115-95-7
EC-Number: 204-116-4
Skin Sens. 1B
H319, H315, H317

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

## 3.2. Mixtures

Not applicable

#### **SECTION 4: First-Aid Measures**

## 4.1. Description of first aid measures

Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

Wash thoroughly with soap and water

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

## 4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

to Regulation (EC) No 1907/2006. Date / Revised: 29.08.2022

Version: 1.0 Previous version: none

Date previous version: not applicable
Date / First version: 29 08 2022

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

## 4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

## **SECTION 5: Fire-Fighting Measures**

#### 5.1. Extinguishing media

Suitable extinguishing media: dry powder, foam, carbon dioxide

Unsuitable extinguishing media for safety reasons: water

## 5.2. Special hazards arising from the substance or mixture

Endangering substances: carbon oxides, harmful vapours Advice: The substances/groups of substances mentioned can be released in case of fire. Combustible Liquid

## 5.3. Advice for fire-fighters

Special protective equipment:

Wear self-contained breathing apparatus and chemical-protective clothing.

#### Further information:

Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Cool endangered containers with water-spray.

#### **SECTION 6: Accidental Release Measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective clothing. Information regarding personal protective measures, see section 8. Do not breathe vapour/spray. Avoid contact with the skin, eyes and clothing. Avoid all sources of ignition: heat, sparks, open flame.

## 6.2. Environmental precautions

Do not discharge into drains/surface waters/groundwater.

#### 6.3. Methods and material for containment and cleaning up

For large amounts: Dike spillage. Cover with blanket of foam (alcohol-resistant foam). Pump off product.

Date / Revised: 29.08.2022

Version: 1.0 Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: Linalyl Acetate

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

For residues: Contain with absorbent material (e.g. sand, silica gel, acid binder, general purpose binder, sawdust).

Dispose of absorbed material in accordance with regulations.

#### 6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

## **SECTION 7: Handling and Storage**

## 7.1. Precautions for safe handling

Ensure thorough ventilation of stores and work areas. Wear suitable protective clothing and eye/face protection. Avoid contact with the skin, eyes and clothing. Keep container tightly sealed. This product may cause irritations; wash your hands after every contact.

Protection against fire and explosion:

The product is combustible. Avoid all sources of ignition: heat, sparks, open flame. Take precautionary measures against static discharges. If exposed to fire, keep containers cool by spraying with water. Vapours may form explosive mixture with air.

## 7.2. Conditions for safe storage, including any incompatibilities

Odour-sensitive: Segregate from products releasing odours.

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

Protect against heat. Protect contents from the effects of light.

## 7.3. Specific end use(s)

See exposure scenario(s) in the attachment to this safety data sheet.

#### **SECTION 8: Exposure Controls/Personal Protection**

#### 8.1. Control parameters

Components with occupational exposure limits

No substance specific occupational exposure limits known.

**PNEC** 

freshwater: 0,011 mg/l

marine water: 0,0011 mg/l

intermittent release: 0,11 mg/l

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

sediment (freshwater): 0,609 mg/kg

sediment (marine water): 0,0609 mg/kg

soil: 0,115 mg/kg

STP: 10 mg/l

**DNEL** 

worker:

Long-term exposure- systemic effects, Inhalation: 2,75 mg/m3

worker:

Long-term exposure- systemic effects, dermal: 2,5 mg/kg bw/day

worker:

Long- and short-term exposure - local effects, dermal: 236,2 µg/cm<sup>2</sup>

consumer:

Long-term exposure- systemic effects, Inhalation: 0,68 mg/m3

consumer:

Long-term exposure- systemic effects, oral: 0,2 mg/kg bw/day

consumer:

Long-term exposure- systemic effects, dermal: 1,25 mg/kg bw/day

consumer:

Long- and short-term exposure - local effects, dermal: 236,2 μg/cm<sup>2</sup>

#### 8.2. Exposure controls

## Personal protective equipment

Respiratory protection:

Suitable respiratory protection for higher concentrations or long-term effect: Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

## Hand protection:

Suitable chemical resistant safety gloves (EN ISO 374-1) also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1): E.g. nitrile rubber (0.4 mm), chloroprene rubber (0.5 mm), butyl rubber (0.7 mm) etc. Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Manufacturer's directions for use should be observed because of great diversity of types.

Consider the risk management measures as outlined in the exposure scenario.

Date / Revised: 29.08.2022 Version: 1.0 Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: Linalyl Acetate

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

#### Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Consider the risk management measures as outlined in the exposure scenario.

#### Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

Consider the risk management measures as outlined in the exposure scenario.

#### General safety and hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with the skin, eyes and clothing. Wearing of closed work clothing is recommended. No eating, drinking, smoking or tobacco use at the place of work. Hands and/or face should be washed before breaks and at the end of the shift. Store work clothing separately.

## **SECTION 9: Physical and Chemical Properties**

#### 9.1. Information on basic physical and chemical properties

State of matter: liauid Form: liquid Colour: colourless Odour: sweetish Odour threshold: < 100 ppm -100 °C Melting point:

(OECD Guideline 102) glass transition temperature: -112 °C (OECD Guideline 102)

Boiling point: 220 °C

> (1.013,25 hPa) Literature data.

Combustible Liquid

(derived from flash point) Flammability:

Lower explosion limit: 0,9 %(V)

(117,5 °C)

Upper explosion limit: 4 %(V)

(117,5 °C)

Flash point: 85 °C (closed cup)

Literature data.

(Directive 84/449/EEC, A.15) Auto-ignition temperature: 270 °C

Thermal decomposition: 220 °C (DSC (DIN 51007))

pH value:

(approx. 23 °C)

2,77 mm2/s (OECD 114) Viscosity, kinematic:

(20 °C)

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0

Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

Viscosity, dynamic: 2,50 mPa.s (OECD 114)

(20 °C)

The value was determined by calculation from the detected

kinematic viscosity.

Solubility in water: slow decomposition

40 mg/l (20 °C)

Solubility (qualitative) solvent(s): organic solvents

soluble

Partitioning coefficient n-octanol/water (log Kow): 3,9 (OECD Guideline 107)

(25 °C)

Vapour pressure: 1 mbar

(20 °C) 2 mbar (50 °C)

Relative density: 0,9018

(20 °C)

Literature data.

Density: 0,9018 g/cm3

(20 °C)

Literature data.

Relative vapour density (air):> 1 (calculated)

(20 °C)

Heavier than air.

#### 9.2. Other information

#### Information with regard to physical hazard classes

**Explosives** 

Explosion hazard: Based on the chemical structure

there is no indication of explosive

properties.

Impact sensitivity:

Based on the chemical structure there is no shock-sensitivity.

(other)

Oxidizing properties

Fire promoting properties: Based on its structural properties (other)

the product is not classified as

oxidizing.

Pyrophoric properties

Self-ignition temperature: Test type: Spontaneous self-ignition at room-temperature.

Based on its structural properties the product is not classified as self-

igniting.

Self-heating substances and mixtures

Self heating ability: not applicable, the product is a liquid

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date previous version: not applicable Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

#### Substances and mixtures, which emit flammable gases in contact with water

Formation of flammable gases:

Forms no flammable gases in the presence of water.

Corrosion to metals

No corrosive effect on metal.

#### Other safety characteristics

pKA:

The substance does not dissociate.

Adsorption/water - soil:

KOC: 517,9; log KOC: 2,7 (calculated)

Surface tension:

Based on chemical structure, surface

activity is not to be expected.

Molar mass:

196,29 g/mol

SAPT-Temperature:

Study scientifically not justified.

Evaporation rate:

Value can be approximated from Henry's Law Constant or vapor

pressure.

## **SECTION 10: Stability and Reactivity**

#### 10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals: No corrosive effect on metal.

Formation of Remarks: Forms no flammable gases in the

flammable gases: presence of water.

#### 10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

## 10.3. Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

#### 10.4. Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. See SDS section 7 - Handling and storage.

#### 10.5. Incompatible materials

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

Substances to avoid: acids

## 10.6. Hazardous decomposition products

Hazardous decomposition products: No hazardous decomposition products known.

## **SECTION 11: Toxicological Information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Assessment of acute toxicity:

Virtually nontoxic after a single ingestion. Virtually nontoxic after a single skin contact.

Experimental/calculated data:

LD50 rat (oral): > 9.000 mg/kg (BASF-Test)

No mortality was observed.

LD50 rabbit (dermal): > 5.000 mg/kg

#### Irritation

Assessment of irritating effects:

Skin contact causes irritation. Eye contact causes irritation.

Experimental/calculated data:

Skin corrosion/irritation

rabbit: Irritant. (OECD Guideline 404)

Serious eye damage/irritation

rabbit: Irritant. (OECD Guideline 405)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

## Respiratory/Skin sensitization

Assessment of sensitization:

Caused skin sensitization in animal studies.

Experimental/calculated data:

Mouse Local Lymph Node Assay (LLNA) mouse: skin sensitizing (OECD Guideline 429)

Version: 1.0

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022

Date previous version: not applicable Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

Previous version: none

#### Germ cell mutagenicity

#### Assessment of mutagenicity:

Results from a number of mutagenicity studies with microorganisms, mammalian cell culture and mammals are available. Taking into account all of the information, there is no indication that the substance is mutagenic. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

#### Carcinogenicity

#### Assessment of carcinogenicity:

No reliable data was available concerning carcinogenic activity. Study does not need to be conducted.

#### Reproductive toxicity

## Assessment of reproduction toxicity:

The results of animal studies gave no indication of a fertility impairing effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

#### **Developmental toxicity**

#### Assessment of teratogenicity:

Animal studies gave no indication of a developmental toxic effect at doses that were not toxic to the parental animals. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

## Specific target organ toxicity (single exposure)

#### Assessment of STOT single:

Based on available data, the classification criteria are not met.

#### Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

## Assessment of repeated dose toxicity:

Effects on the kidney of male rats were detected after repeated exposure. These effects are specific for the male rat and are known to be of no relevance to humans. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

#### Aspiration hazard

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

No data available.

Interactive effects

No data available.

#### 11.2. Information on other hazards

#### **Endocrine disrupting properties**

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACh Article 59 for having endocrine disrupting properties.

#### **SECTION 12: Ecological Information**

#### 12.1. Toxicity

#### Assessment of aquatic toxicity:

Harmful to aquatic life. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

#### Toxicity to fish:

LC50 (96 h) 11 mg/l, Cyprinus carpio (OECD Guideline 203, Flow through.)

The statement of the toxic effect relates to the analytically determined concentration. The product may hydrolyse. The test result maybe partially due to degradation products.

## Aquatic invertebrates:

EC50 (48 h) 15 mg/l, Daphnia magna (OECD Guideline 202, part 1, static)

The details of the toxic effect relate to the nominal concentration. The product may hydrolyse. The test result maybe partially due to degradation products.

#### Aquatic plants:

EC50 (72 h) 62 mg/l (growth rate), Desmodesmus subspicatus (OECD Guideline 201, static) The details of the toxic effect relate to the nominal concentration. The product may hydrolyse. The test result maybe partially due to degradation products.

Microorganisms/Effect on activated sludge: EC20 (30 min) > 1.000 mg/l, (DIN EN ISO 8192, aerobic)

Chronic toxicity to fish:

Study scientifically not justified.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

Chronic toxicity to aquatic invertebrates: Study scientifically not justified.

Assessment of terrestrial toxicity: No data available concerning terrestrial toxicity. Study scientifically not justified.

## 12.2. Persistence and degradability

Assessment biodegradation and elimination (H2O): Readily biodegradable (according to OECD criteria).

Elimination information:

70 - 80 % BOD of the ThOD (28 d) (OECD 301F; ISO 9408; 92/69/EEC, C.4-D) (aerobic, activated sludge, domestic)

Assessment of stability in water:

In contact with water the substance will hydrolyse rapidly.

Information on Stability in Water (Hydrolysis):  $t_{1/2} < 1$  d, (Directive 92/69/EEC, C.7, pH 7)

#### 12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

#### 12.4. Mobility in soil

Assessment transport between environmental compartments:

Volatility: The substance will rapidly evaporate into the atmosphere from the water surface. Adsorption in soil: Adsorption to solid soil phase is not expected.

## 12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative). Self classification

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

## 12.6. Endocrine disrupting properties

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACh Article 59 for having endocrine disrupting properties.

#### 12.7. Other adverse effects

The substance is not listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

## **SECTION 13: Disposal Considerations**

#### 13.1. Waste treatment methods

Observe national and local legal requirements.

## **SECTION 14: Transport Information**

#### **Land transport**

ADR

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

RID

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

#### **Inland waterway transport**

ADN

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022

Product: Linalyl Acetate

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user:

Transport in inland waterway vessel

Not evaluated

#### Sea transport

#### **IMDG**

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

## Air transport

#### IATA/ICAO

Not classified as a dangerous good under transport regulations

UN number or ID number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

#### 14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

#### 14.2. UN proper shipping name

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

## 14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

#### 14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

#### 14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

#### 14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

#### 14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

## **SECTION 15: Regulatory Information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 3

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU): Listed in above regulation: no

Storage class in France (Nomenclature ICPE): 1436

Occupational Disease Number in France (Code de la Sécurité Sociale, Art. L 461-1 à L 461-8): 84

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

#### 15.2. Chemical Safety Assessment

Chemical Safety Assessment performed

#### **SECTION 16: Other Information**

Assessment of the hazard classes according to UN GHS criteria (most recent version)

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

Skin Corr./Irrit. 2 Eye Dam./Irrit. 2B Flam. Liq. 4 Aquatic Acute 3 Skin Sens. 1B

Any other intended applications should be discussed with the manufacturer. Corresponding occupational protection measurements must be followed.

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned

in section 2 or 3:

Skin Corr./Irrit. Skin corrosion/irritation

Eye Dam./Irrit. Serious eye damage/eye irritation

Skin Sens. Skin sensitization

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

#### **Abbreviations**

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Page: 18/129

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022

Version: 1.0 Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: Linalyl Acetate

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

## **Annex: Exposure Scenarios**

#### Index

1. Compounding, (use in industrial settings) ERC2; PROC1, PROC3, PROC5, PROC8a, PROC8b, PROC9, PROC15

2. Use in/as Formulation, (use in industrial settings) ERC2; PROC1, PROC3, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15

**3.** Use in Cleaning Agents, (use in industrial settings) ERC4; PROC1, PROC2, PROC4, PROC7, PROC8b, PROC10, PROC13

**4.** Use as an intermediate, (use in industrial settings) ERC6a; PROC1, PROC2, PROC3, PROC8b, PROC9, PROC15

**5.** Use in Cleaning Agents, (use in professional settings) ERC8a, ERC8d; PROC1, PROC2, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13

**6.** Use in Cleaning Agents, (consumer use) ERC8a, ERC8d; PC31, PC35

7. Use in/as Air care products, (consumer use) ERC8a; PC3

**8.** other consumer applications than fragrance, (consumer use) ERC8a, ERC8d; PC8

**9.** Use in cosmetics, (consumer use) ERC8a; PC28, PC39

\* \* \* \* \* \* \* \* \* \* \* \* \* \* \* \*

## 1. Short title of exposure scenario

Compounding, (use in industrial settings) ERC2; PROC1, PROC3, PROC5, PROC8a, PROC8b, PROC9, PROC15

#### Control of exposure and risk management measures

Contributing exposure scenario		
Use descriptors covered	ERC2: Formulation into mixture	
Operational conditions		
Annual amount per site	250.000 kg	
Minimum emission days per year	250	

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none
Date / First version: 29.08.2022

Product: Linalyl Acetate

(ID no. 30034993/SDS\_GEN\_FR/EN)

Emission factor air	2,5 %	
Emission factor water	0,2 %	
Emission factor soil	0 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Type of STP		Municipal STP
Assumed sewage treatment plant flow (m3/d)		2.000 m3/d
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,938623	
	Risk from environmental ex	rposure is driven by soil.
	1.065,4	
Maximum amount of safe use	kg/d	
Risk from environmental exposure is driven by soil.		

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.  Use domain: industrial
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	60 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Wear chemically resistant gloves in	
combination with 'basic' employee training.	Effectiveness: 90 %
Avoid skin contact. Ensure	
minimization of manual phases	

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Use suitable eye protection., Wear chemically resistant gloves in combination with 'basic' employee training.	
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0034 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001371
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - local
Exposure estimate	1 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,004234
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0164 mg/m³
Risk Characterization Ratio (RCR)	0,005948
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/	tra

Contributing exposure scenario		
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial	
Operational conditions		
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	100 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	240 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		
Local exhaust ventilation	Effectiveness: 90 %	
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %	
Avoid skin contact. Ensure minimization of manual phases		
Use suitable eye protection., Wear chemically resistant gloves in		

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

combination with 'basic' employee training.	
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0686 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,027429
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - local
Exposure estimate	20 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,084674
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	1,4721 mg/m³
Risk Characterization Ratio (RCR)	0,535325
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	/tra

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial
Operational conditions	1
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Local exhaust ventilation	Effectiveness: 90 %
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Avoid skin contact. Ensure minimization of manual phases	
Use suitable eye protection., Wear chemically resistant gloves in combination with 'basic' employee training.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, Workplace measurements
	Worker - dermal, long-term - systemic

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Exposure estimate	0,0691 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,027656
Assessment method	EASY TRA v4.1, Workplace measurements
	Worker - dermal, long-term - local
Exposure estimate	10,08 µg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,042676
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	2,4536 mg/m³
Risk Characterization Ratio (RCR)	0,892209
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/	/tra

Contributing exposure scenario		
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial	
Operational conditions		
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 100 %	
Physical state	liquid	
Vapour pressure of the substance during use	100 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	240 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		
Local exhaust ventilation	Effectiveness: 90 %	
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %	
Avoid skin contact. Ensure minimization of manual phases		
Use suitable eye protection., Wear chemically resistant gloves in combination with 'basic' employee training.		
Exposure estimate and reference to		
Assessment method	EASY TRA v4.1, Workplace measurements	
	Worker - dermal, long-term - systemic	
Exposure estimate	0,0124 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,004964	
Assessment method	EASY TRA v4.1, Workplace measurements	
	Worker - dermal, long-term - local	
Exposure estimate	1,81 µg/cm <sup>3</sup>	

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Risk Characterization Ratio (RCR)	0,007663
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	2,4536 mg/m³
Risk Characterization Ratio (RCR)	0,892209
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 25 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Local exhaust ventilation	Effectiveness: 90 %
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Avoid skin contact. Ensure minimization of manual phases	
Use suitable eye protection., Wear chemically resistant gloves in combination with 'basic' employee training.	
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,3429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,137143
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - local
Exposure estimate	25 μg/cm <sup>3</sup>

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0 Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: Linalyl Acetate

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

Risk Characterization Ratio (RCR)	0,105843
	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - inhalation, long-term - systemic
Exposure estimate	1,2268 mg/m³
Risk Characterization Ratio (RCR)	0,446105
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see	
exposure estimates)	

Contributing exposure scenario PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use descriptors covered Use domain: industrial **Operational conditions** 

	Linalyl acetate	
Concentration of the substance	Content: >= 0 % - <= 100 %	
Physical state	liquid	
	100 Pa	
Vapour pressure of the substance during use	100 Pa	
during use	20 °C	
Process temperature	20 C	
Duration and Frequency of activity	60 min 5 days per week	
Duration and Frequency of activity		
Indoor/Outdoor	Indoor	
Risk Management Measures		
Local exhaust ventilation	Effectiveness: 95 %	
Wear chemically resistant gloves in		
combination with 'basic' employee	Effectiveness: 90 %	
training.		
Avoid skin contact. Ensure		
minimization of manual phases		
Use suitable eye protection., Wear		
chemically resistant gloves in		
combination with 'basic' employee		
training.		
Exposure estimate and reference to		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	1,3714 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,548571	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker	
	Worker dermal lang term local	

training.		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - systemic	
Exposure estimate	1,3714 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,548571	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker	
	Worker - dermal, long-term - local	
Exposure estimate	100 μg/cm <sup>3</sup>	
Risk Characterization Ratio (RCR)	0,42337	

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,4089 mg/m <sup>3</sup>	
Risk Characterization Ratio (RCR) 0,148702		
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra		

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 25 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	60 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Local exhaust ventilation	Effectiveness: 90 %
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Avoid skin contact. Ensure	
minimization of manual phases	
Use suitable eye protection., Wear chemically resistant gloves in combination with 'basic' employee training.	
Exposure estimate and reference to	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,1714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,068571
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - local
Exposure estimate	25 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,105843

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been	
	considered using a linear approach.	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,2045 mg/m <sup>3</sup>	
Risk Characterization Ratio (RCR)	0,074351	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see		
exposure estimates)	· ·	

Contributing exposure scenario	DDOC45, Llos a laboratory reagant
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
ose descriptors covered	Ose domain. industrial
Operational conditions	
	Linalyl acetate
Concentration of the substance	Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance	100 Pa
during use	
Process temperature	20 °C
	45 min 5 days manyook
Duration and Frequency of activity	15 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general or	
controlled ventilation (5 to 10 air	Effectiveness: 70 %
changes per hour)	
Wear chemically resistant gloves in	
combination with 'basic' employee	Effectiveness: 90 %
training.	
Avoid skin contact. Ensure	
minimization of manual phases	
Use suitable eye protection., Wear	
chemically resistant gloves in	
combination with 'basic' employee	
training.	
Exposure estimate and reference to	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,013714
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - local
Exposure estimate	10 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,042337

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker	
	Worker - inhalation, long-term - systemic	
Exposure estimate	1,2268 mg/m <sup>3</sup>	
Risk Characterization Ratio (RCR)	0,446105	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra		

\* \* \* \* \* \* \* \* \* \* \* \* \* \* \* \*

## 2. Short title of exposure scenario

Use in/as Formulation, (use in industrial settings) ERC2; PROC1, PROC3, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15

## Control of exposure and risk management measures

Contributing exposure scenario			
Use descriptors covered	AISE SPERC 2.1.a.v2: AISE SPERC 2.1.a.v2		
Operational conditions			
Annual amount used in the EU	230.000 kg		
Minimum emission days per year	250		
Emission factor air	0 %		
Emission factor water	0,01 %		
Emission factor soil	0 %		
Receive Surf. Water (Flow Rate).	18.000 m3/d		
Dilution factor river	10		
Dilution factor coast	100		
Risk Management Measures			
Wastewater treatment measures considered suitable are, e.g.		Precipitation, Coagulation, Must be eliminated from water by chemical flocculation.	
Type of STP		Municipal STP	
Assumed sewage treatment plant flow (m3/d)		2.000 m3/d	
Exposure estimate and reference to its source			
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment		
Risk Characterization Ratio (RCR)	0,04302		
	Risk from environmental exposure is driven by soil.		
Maximum amount of safe use	21.385,2 kg/d		

to Regulation (EC) No 1907/2006. Date / Revised: 29.08.2022

Date / Revised: 29.08.2022 Version: 1.0

Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

Risk from environmental exposure is driven by soil.

Contributing exposure scenario		
Use descriptors covered	AISE SPERC 2.1.b.v2: AISE SPERC 2.1.b.v2	
Operational conditions		
Annual amount used in the EU	92.000 kg	
Minimum emission days per year	250	
Emission factor air	0 %	
Emission factor water	0,1 %	
Emission factor soil	0 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures	•	
Wastewater treatment measures considered suitable are, e.g.		Precipitation, Coagulation, Must be eliminated from water by chemical flocculation.
Type of STP		Municipal STP
Assumed sewage treatment plant flow	(m3/d)	2.000 m3/d
Exposure estimate and reference to		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,17204	
	Risk from environmental exposure is driven by soil.	
	2.139	
Maximum amount of safe use kg/d		
Risk from environmental exposure is d	riven by soil.	

Contributing exposure scenario		
Use descriptors covered	AISE SPERC 2.1.c.v2: AISE SPERC 2.1.c.v2	
Operational conditions		
Annual amount used in the EU	72.000 kg	
Minimum emission days per year	250	
Emission factor air	0 %	

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Emission factor water	0,2 %		
Emission factor soil	0 %		
Receive Surf. Water (Flow Rate).	18.000 m3/d		
Dilution factor river	10		
Dilution factor coast	100		
Risk Management Measures			
Wastewater treatment measures considered suitable are, e.g.		Precipitation, Coagulation, Must be eliminated from water by chemical flocculation.	
Type of STP		Municipal STP	
Assumed sewage treatment plant flow (m3/d)		2.000 m3/d	
Exposure estimate and reference to its source			
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment		
Risk Characterization Ratio (RCR)	0,269273		
	Risk from environmental exposure is driven by soil.		
1.069,5			
Maximum amount of safe use	kg/d		
Risk from environmental exposure is driven by soil.			

Contributing exposure scenario		
Use descriptors covered	AISE SPERC 2.1.j.v2: AISE SPERC 2.1.j.v2	
Operational conditions		
Annual amount used in the EU	67.000 kg	
Minimum emission days per year	250	
Emission factor air	0 %	
Emission factor water	0,1 %	
Emission factor soil	0 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Wastewater treatment measures considered suitable are, e.g.		Nanofiltration (NR), Ultrafiltration (UF) or Reverse

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0 Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: Linalyl Acetate

(ID no. 30034993/SDS\_GEN\_FR/EN)

		Osmosis (OR), Coagulation, Must be eliminated from water
		by chemical flocculation.
Type of STP		Municipal STP
Assumed sewage treatment plant flow (m3/d)		2.000 m3/d
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETOC	CTRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,125294	
	Risk from environmental e	xposure is driven by soil.
	2.139	
Maximum amount of safe use	kg/d	
Risk from environmental exposure is driven by soil.		

Contributing exposure scenario		
Use descriptors covered	AISE SPERC 2.1.k.v2: A	AISE SPERC 2.1.k.v2
Operational conditions		
Annual amount used in the EU	36.000 kg	
Minimum emission days per year	250	
Emission factor air	0 %	
Emission factor water	0,2 %	
Emission factor soil	0 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Wastewater treatment measures considered suitable are, e.g.		Nanofiltration (NR), Ultrafiltration (UF) or Reverse Osmosis (OR), Coagulation, Must be eliminated from water by chemical flocculation.
Type of STP		Municipal STP
Assumed sewage treatment plant flow (m3/d)		2.000 m3/d
Exposure estimate and reference to		
Assessment method		OC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,134643	
		exposure is driven by soil.
Maximum amount of safe use	1.069,5 kg/d	

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

Risk from environmental exposure is driven by soil.

Contributing exposure scenario		
Use descriptors covered	AISE SPERC 2.1.I.v2: AIS	SE SPERC 2.1.l.v2
Operational conditions		
Annual amount used in the EU	36.000 kg	
Minimum emission days per year	250	
Emission factor air	0 %	
Emission factor water	0,4 %	
Emission factor soil	0 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Wastewater treatment measures considered suitable are, e.g.  Nanofilt Ultrafilti Osmosi Must be		Nanofiltration (NR), Ultrafiltration (UF) or Reverse Osmosis (OR), Coagulation, Must be eliminated from water by chemical flocculation.
Type of STP Municipal STP		
Assumed sewage treatment plant flow (m3/d) 2.000 m3/d		2.000 m3/d
Exposure estimate and reference to		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,269273	
	Risk from environmental exposure is driven by soil.	
Maximum amount of safe use	um amount of safe use 534,8 kg/d	
Risk from environmental exposure is di	riven by soil.	

Contributing exposure scenario	
Use descriptors covered	ERC2: Formulation into mixture
Operational conditions	
Annual amount used in the EU	102.000 kg
Minimum emission days per year	250

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0 Date previous version: not applicable Previous version: none Date / First version: 29.08.2022

Product: Linalyl Acetate

(ID no. 30034993/SDS\_GEN\_FR/EN)

Emission factor air	0 %		
Emission factor water	0 %		
Emission factor soil	0,01 %		
Receive Surf. Water (Flow Rate).	18.000 m3/d		
Dilution factor river	10		
Dilution factor coast	100		
Risk Management Measures	Risk Management Measures		
Type of STP		Municipal STP	
Assumed sewage treatment plant flow (m3/d)		2.000 m3/d	
Exposure estimate and reference to its source			
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment		
Risk Characterization Ratio (RCR)	0,01339		
	Risk from environmental exposure is driven by freshwater.		
	30.470,5		
Maximum amount of safe use	kg/d		
Risk from environmental exposure is driven by freshwater.			

Contributing exposure scenario		
Use descriptors covered	ERC2: Formulation into mi	xture
Operational conditions		
Annual amount used in the EU	11.000 kg	
Minimum emission days per year	250	
Emission factor air	0 %	
Emission factor water	2 %	
Emission factor soil	0 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Type of STP		Municipal STP
Assumed sewage treatment plant flow (m3/d)		2.000 m3/d
Exposure estimate and reference to its source		

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,411382
	Risk from environmental exposure is driven by soil.
	107
Maximum amount of safe use	kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.  Use domain: industrial
Operational conditions	
	Linalyl acetate
Concentration of the substance	Content: >= 0 % - <= 25 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	60 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general	
ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Avoid skin contact. Ensure minimization of manual phases	
Use suitable eye protection., Wear	
chemically resistant gloves in	
combination with 'basic' employee	
training.	
Exposure estimate and reference to	
	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
Exposure estimate	Worker - dermal, long-term - systemic 0,0009 mg/kg bw/day
Exposure estimate Risk Characterization Ratio (RCR)	0,0009 mg/kg bw/day 0,000343
MISK CHAIACIGHZAIIUH NAIIU (NCK)	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified
Assessment method	version. The concentration of the substance has been
	Toroiding The democratical of the substance has been

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

	considered using a linear approach.	
	Worker - dermal, long-term - local	
Exposure estimate	0,25 μg/cm <sup>3</sup>	
Risk Characterization Ratio (RCR)	0,001058	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,0029 mg/m <sup>3</sup>	
Risk Characterization Ratio (RCR)	0,001041	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)		

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 25 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Avoid skin contact. Ensure minimization of manual phases	
Use suitable eye protection., Wear chemically resistant gloves in combination with 'basic' employee training.	
Exposure estimate and reference to	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

	version, The concentration of the substance has been	
	considered using a linear approach.	
	Worker - dermal, long-term - systemic	
Exposure estimate	0,0171 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,006857	
	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified	
Assessment method	version, The concentration of the substance has been	
	considered using a linear approach.	
	Worker - dermal, long-term - local	
Exposure estimate	5 μg/cm <sup>3</sup>	
Risk Characterization Ratio (RCR)	0,021169	
	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified	
Assessment method	version, The concentration of the substance has been	
	considered using a linear approach.	
	Worker - inhalation, long-term - systemic	
Exposure estimate	1,1041 mg/m³	
Risk Characterization Ratio (RCR)	0,401494	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see		
exposure estimates)	·	

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 25 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Avoid skin contact. Ensure minimization of manual phases	
Use suitable eye protection., Wear chemically resistant gloves in	

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

combination with 'basic' employee training.	
Exposure estimate and reference to its source	
	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,3429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,137143
	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - dermal, long-term - local
Exposure estimate	50 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,211685
	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - inhalation, long-term - systemic
Exposure estimate	1,8402 mg/m³
Risk Characterization Ratio (RCR)	0,669157
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario		
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial	
Operational conditions		
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 10 %	
Physical state	liquid	
Vapour pressure of the substance during use	100 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	240 min 5 days per week	
Indoor/Outdoor	Indoor	
Risk Management Measures		
Provide a good standard of general or		
controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %	
Wear chemically resistant gloves in combination with 'basic' employee	Effectiveness: 90 %	

Date / Revised: 29.08.2022

Date previous version: not applicable Date / First version: 29.08.2022 Product: **Linalyl Acetate**  Version: 1.0 Previous version: none

(ID no. 30034993/SDS\_GEN\_FR/EN)

training.	
Avoid skin contact. Ensure	
minimization of manual phases	
Use suitable eye protection., Wear	
chemically resistant gloves in	
combination with 'basic' employee	
training.	
Exposure estimate and reference to	its source
	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,1371 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,054857
	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - dermal, long-term - local
Exposure estimate	10 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,042337
	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - inhalation, long-term - systemic
Exposure estimate	1,4721 mg/m³
Risk Characterization Ratio (RCR)	0,535325
Guidance to Downstream Users	
	tra Please note that a modified version has been used (see
exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 25 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	60 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Avoid skin contact. Ensure minimization of manual phases	
Use suitable eye protection., Wear chemically resistant gloves in combination with 'basic' employee training.	
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,3429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,137143
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - local
Exposure estimate	25 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,105843
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - systemic
Exposure estimate	1,4313 mg/m³
Risk Characterization Ratio (RCR)	0,520455
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/exposure estimates)	tra Please note that a modified version has been used (see

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 10 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Duration and Frequency of activity	60 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Avoid skin contact. Ensure minimization of manual phases	
Use suitable eye protection., Wear chemically resistant gloves in combination with 'basic' employee training.	
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,0686 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,027429
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - local
Exposure estimate	10 µg/cm³
Risk Characterization Ratio (RCR)	0,042337
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
Evacuum estimate	Worker - inhalation, long-term - systemic
Exposure estimate	0,5725 mg/m³
Risk Characterization Ratio (RCR)	0,208182
Guidance to Downstream Users	( D
For scaling see: http://www.ecetoc.org	/tra Please note that a modified version has been used (see

Contributing exposure scenario	
Use descriptors covered	PROC14: Tabletting, compression, extrusion, pelletisation, granulation Use domain: industrial
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 10 %

to Regulation (EC) No 1907/2006.

Version: 1.0 Previous version: none

Date / Revised: 29.08.2022 Date previous version: not applicable Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Avoid skin contact. Ensure minimization of manual phases	
Use suitable eye protection., Wear chemically resistant gloves in combination with 'basic' employee training.	
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,0343 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,013714
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - local
Exposure estimate	5 µg/cm³
Risk Characterization Ratio (RCR)	0,021169
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - systemic
Exposure estimate	1,2268 mg/m³
Risk Characterization Ratio (RCR)	0,446105
Guidance to Downstream Users	
	tra Please note that a modified version has been used (see
exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

	Linalyl acetate
Concentration of the substance	Content: >= 0 % - <= 25 %
Physical state	liquid
/apour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	15 min 5 days per week
ndoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general rentilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Vear chemically resistant gloves in combination with 'basic' employee raining.	Effectiveness: 90 %
Avoid skin contact. Ensure ninimization of manual phases	
Jse suitable eye protection., Wear chemically resistant gloves in combination with 'basic' employee raining.	
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate Risk Characterization Ratio (RCR)	0,0086 mg/kg bw/day 0,003429
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.  Worker - dermal, long-term - local
Exposure estimate	2,5 µg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,010584
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - systemic
Exposure estimate	0,7156 mg/m³ 0,260228
Risk Characterization Ratio (RCR)	

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

\* \* \* \* \* \* \* \* \* \* \* \* \* \* \* \*

#### 3. Short title of exposure scenario

Use in Cleaning Agents, (use in industrial settings) ERC4; PROC1, PROC2, PROC4, PROC7, PROC8b, PROC10, PROC13

# Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC4: Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
Operational conditions	

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.  Use domain: industrial
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 1 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Exposure estimate and reference to	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,0003 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000137
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.  Worker - dermal, long-term - local
Exposure estimate	0,1 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000423
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

	version, The concentration of the substance has been considered using a linear approach.	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,0008 mg/m³	
Risk Characterization Ratio (RCR)	0,000297	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see		
exposure estimates)		

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 1 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Exposure estimate and reference to	o its source
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,0137 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,005486
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - local
Exposure estimate	2 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,008467
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0818 mg/m³
Risk Characterization Ratio (RCR)	0,02974
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	g/tra Please note that a modified version has been used (see

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

#### exposure estimates)

Contributing exposure scenario	Contributing exposure scenario		
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial		
Operational conditions			
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 1 %		
Physical state	liquid		
Vapour pressure of the substance during use	100 Pa		
Process temperature	20 °C		
Duration and Frequency of activity	480 min 5 days per week		
Indoor/Outdoor	Indoor		
Risk Management Measures			
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %		
Exposure estimate and reference to	its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.		
	Worker - dermal, long-term - systemic		
Exposure estimate	0,0686 mg/kg bw/day		
Risk Characterization Ratio (RCR)  Assessment method	0,027429  EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.  Worker - dermal, long-term - local		
Exposure estimate	10 μg/cm <sup>3</sup>		
Risk Characterization Ratio (RCR)	0,042337		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.		
E	Worker - inhalation, long-term - systemic		
Exposure estimate	0,2863 mg/m³		
Risk Characterization Ratio (RCR)	0,104091		
Guidance to Downstream Users  For scaling see: http://www.ecetoc.org exposure estimates)	/tra Please note that a modified version has been used (see		

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

	Use domain: industrial
Operational conditions	
-	Linalyl acetate
Concentration of the substance	Content: >= 0 % - <= 1 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	60 min 5 days per week
Indoor/Outdoor	Outdoor
Exposure estimate and reference to	o its source
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,171429
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - local
Exposure estimate	20 μg/cm³
Risk Characterization Ratio (RCR)	0,084674
Assessment method	EASY TRA v4.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0526 mg/m³
Risk Characterization Ratio (RCR)	0,019128
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see	
exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 1 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Local exhaust ventilation	Effectiveness: 95 %
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,171429
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.  Worker - dermal, long-term - local
Exposure estimate	20 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,084674
Assessment method	EASY TRA v4.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,1061 mg/m³
Risk Characterization Ratio (RCR)	0,038573
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org exposure estimates)	/tra Please note that a modified version has been used (see

Contributing exposure scenario		
	PROC7: Industrial spraying	
Use descriptors covered	Use domain: industrial	
Operational conditions		
	Linalyl acetate	
Concentration of the substance	Content: >= 0 % - <= 1 %	
Physical state	liquid	
Vapour pressure of the substance	100 Pa	
during use		
Process temperature	20 °C	
1 100000 temperature		
Duration and Frequency of activity	480 min 5 days per week	
. , ,		
Indoor/Outdoor	Indoor	
Risk Management Measures		
Wear chemically resistant gloves in		
combination with 'basic' employee	Effectiveness: 90 %	
training.		
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified	

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,0429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,017143
	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - dermal, long-term - local
Exposure estimate	2 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,008467
Assessment method	EASY TRA v4.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,2581 mg/m³
Risk Characterization Ratio (RCR)	0,093847
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	g/tra Please note that a modified version has been used (see
exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 1 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Outdoor
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, Reduction factor for local exhaust ventilation (LEV) has been used for the calculation of dermal exposure estimates., The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,171429
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, Reduction factor for local exhaust ventilation (LEV) has been used for the calculation of dermal exposure estimates., The concentration of the substance

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

	has been considered using a linear approach.
	Worker - dermal, long-term - local
Exposure estimate	20 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,084674
Assessment method	EASY TRA v4.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0842 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,030605
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see	
exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	•
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 1 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	60 min 5 days per week
Indoor/Outdoor	Indoor
Exposure estimate and reference to	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,1371 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,054857
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - local
Exposure estimate	10 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,042337
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0818 mg/m³
Risk Characterization Ratio (RCR)	0,02974

Page: 49/129

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according

to Regulation (EC) No 1907/2006. Date / Revised: 29.08.2022

Version: 1.0 Previous version: none

Date previous version: not applicable Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

# Guidance to Downstream Users

For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)

Contributing exposure scenario	
	PROC10: Roller application or brushing
Use descriptors covered	Use domain: industrial
Operational conditions	
	Linalyl acetate
Concentration of the substance	Content: >= 0 % - <= 1 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Outdoor
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, Reduction factor for local exhaust ventilation (LEV) has been used for the calculation of dermal exposure estimates., The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,2743 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,109714
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, Reduction factor for local exhaust ventilation (LEV) has been used for the calculation of dermal exposure estimates., The concentration of the substance has been considered using a linear approach.  Worker - dermal, long-term - local
Exposure estimate	20 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,084674
Assessment method	EASY TRA v4.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,095 mg/m³
Risk Characterization Ratio (RCR)	0,034544
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.orgexposure estimates)	/tra Please note that a modified version has been used (see

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: industrial

Date / Revised: 29.08.2022
Date previous version: not applicable

Date / First version: 29.08.2022 Product: **Linalyl Acetate**  Version: 1.0 Previous version: none

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

Operational conditions	
	Linalyl acetate
Concentration of the substance	Content: >= 0 % - <= 1 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Local exhaust ventilation	Effectiveness: 90 %
Exposure estimate and reference to	o its source
	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,1371 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,054857
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - local
Exposure estimate	20 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,084674
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0818 mg/m³
Risk Characterization Ratio (RCR)	0,02974
Guidance to Downstream Users	
	g/tra Please note that a modified version has been used (see
exposure estimates)	

\*\*\*\*\*\*

#### 4. Short title of exposure scenario

Use as an intermediate, (use in industrial settings) ERC6a; PROC1, PROC2, PROC3, PROC8b, PROC9, PROC15

#### Control of exposure and risk management measures

# Contributing exposure scenario

to Regulation (EC) No 1907/2006.

Use descriptors covered

Version: 1.0 Previous version: none

Date / Revised: 29.08.2022 Date previous version: not applicable Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

	·
Use descriptors covered	ERC6a: Use of intermediate No assessment required - Industrial use as intermediate under strictly controlled conditions
Operational conditions	
Contributing exposure scenario	I DDOOM OL
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.  No assessment required - Industrial use as intermediate under strictly controlled conditions
Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions  No assessment required - Industrial use as intermediate under strictly controlled conditions
Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition  No assessment required - Industrial use as intermediate under strictly controlled conditions
Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities No assessment required - Industrial use as intermediate under strictly controlled conditions
Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing).  No assessment required - Industrial use as intermediate under strictly controlled conditions
Contributing exposure scenario	
5 p s s s s s s s s s s s s s s s s s s	PROC15: Use a laboratory reagent.
Use descriptors covered	No accessment required Industrial use as intermediate

No assessment required - Industrial use as intermediate

under strictly controlled conditions

Page: 52/129

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

\* \* \* \* \* \* \* \* \* \* \* \* \* \* \* \*

#### 5. Short title of exposure scenario

Use in Cleaning Agents, (use in professional settings) ERC8a, ERC8d; PROC1, PROC2, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13

## Control of exposure and risk management measures

Contributing exposure scenario		
Use descriptors covered	ERC8a: Widespread use of the control	of non-reactive processing aid article, indoor)
Operational conditions		
Annual amount used in the EU	510.000 kg	
Minimum emission days per year	365	
Emission factor air	100 %	
Emission factor water	100 %	
Emission factor soil	0 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Type of STP Municipal STP		Municipal STP
Assumed sewage treatment plant flow (m3/d) 2.000 m3/d		2.000 m3/d
Exposure estimate and reference to		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,130654	
	Risk from environmental exposure is driven by soil.	
Maximum amount of safe use	2,1 kg/d	
Risk from environmental exposure is driven by soil.		

Contributing exposure scenario	
Use descriptors covered	ERC8d: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

to Regulation (EC) No 1907/2006. Date / Revised: 29.08.2022

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Operational conditions		
Annual amount used in the EU	510.000 kg	
Minimum emission days per year	365	
Emission factor air	100 %	
Emission factor water	100 %	
Emission factor soil	20 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Type of STP Municipal STP		Municipal STP
		2.000 m3/d
Exposure estimate and reference to	its source	
Assessment method		
Risk Characterization Ratio (RCR)	0,130654	
	Risk from environmental exposure is driven by soil.	
	2,1	
Maximum amount of safe use	kg/d	
Risk from environmental exposure is driven by soil.		

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.  Use domain: professional
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 1 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Exposure estimate and reference to its source	

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0 Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: Linalyl Acetate

(ID no. 30034993/SDS\_GEN\_FR/EN)

	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,0003 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000137
	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - dermal, long-term - local
Exposure estimate	0,1 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000423
	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0008 mg/m³
Risk Characterization Ratio (RCR)	0,000297
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	g/tra Please note that a modified version has been used (see

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: professional
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 1 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

	Worker - dermal, long-term - systemic	
Exposure estimate	0,0137 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,005486	
,	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified	
Assessment method	version, The concentration of the substance has been	
	considered using a linear approach.	
	Worker - dermal, long-term - local	
Exposure estimate	2 μg/cm <sup>3</sup>	
Risk Characterization Ratio (RCR)	0,008467	
	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified	
Assessment method	version, The concentration of the substance has been	
	considered using a linear approach.	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,2863 mg/m <sup>3</sup>	
Risk Characterization Ratio (RCR)	0,104091	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see		
exposure estimates)		

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: professional
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 1 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	15 min 5 days per week
Indoor/Outdoor	Indoor
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,0686 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,027429
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - local
Exposure estimate	10 μg/cm <sup>3</sup>

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

Risk Characterization Ratio (RCR)	0,042337
Assessment method	EASY TRA v4.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0066 mg/m³
Risk Characterization Ratio (RCR)	0,002411
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see	
exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for
	exposure arises
	Use domain: professional
Operational conditions	
	Linalyl acetate
Concentration of the substance	Content: >= 0 % - <= 1 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Exposure estimate and reference to	
	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,0686 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,027429
	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - dermal, long-term - local
Exposure estimate	10 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,042337
Assessment method	EASY TRA v4.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,2913 mg/m³
Risk Characterization Ratio (RCR)	0,105925
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	g/tra Please note that a modified version has been used (see
exposure estimates)	

# Contributing exposure scenario

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: professional
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 1 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	60 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	•
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Exposure estimate and reference to	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,1371 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,054857
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - local
Exposure estimate	10 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,042337
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - systemic
Exposure estimate	0,2863 mg/m³
Risk Characterization Ratio (RCR)	0,104091
Guidance to Downstream Users For scaling see: http://www.ecetoc.org/exposure estimates)	tra Please note that a modified version has been used (see

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: professional

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Operational conditions	
	Linalyl acetate
Concentration of the substance	Content: >= 0 % - <= 1 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	60 min 5 days per week
Indoor/Outdoor	Indoor
Exposure estimate and reference to	its source
	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,1371 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,054857
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - local
Exposure estimate	10 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,042337
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - systemic
Exposure estimate	0,1636 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,059481
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/	tra Please note that a modified version has been used (see
exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: professional
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 1 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,2743 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,109714
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - local
Exposure estimate	20 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,084674
Assessment method	EASY TRA v4.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,2913 mg/m³
Risk Characterization Ratio (RCR)	0,105925
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario PROC10: Roller application or brushing Use descriptors covered Use domain: professional Operational conditions Linalyl acetate Concentration of the substance Content: >= 0 % - <= 1 % Physical state liquid Vapour pressure of the substance 100 Pa during use 20 °C Process temperature 480 min 5 days per week **Duration and Frequency of activity** Indoor/Outdoor Indoor Exposure estimate and reference to its source EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been Assessment method considered using a linear approach. Worker - dermal, long-term - systemic Exposure estimate 0,2743 mg/kg bw/day Risk Characterization Ratio (RCR) 0,109714 EASY TRA v4.1, ECETOC TRA v3.0, worker, modified Assessment method

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - dermal, long-term - local
Exposure estimate	20 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,084674
Assessment method	EASY TRA v4.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,141 mg/m³
Risk Characterization Ratio (RCR)	0,051269
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	g/tra Please note that a modified version has been used (see
exposure estimates)	

Contributing exposure scenario		
Use descriptors covered	PROC10: Roller application or brushing Use domain: professional	
Operational conditions		
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 1 %	
Physical state	liquid	
Vapour pressure of the substance during use	100 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Outdoor	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.	
	Worker - dermal, long-term - systemic	
Exposure estimate	0,2743 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,109714	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.  Worker - dermal, long-term - local	
Exposure estimate	20 μg/cm <sup>3</sup>	
Risk Characterization Ratio (RCR)	0.084674	
Assessment method	EASY TRA v4.1, Workplace measurements	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,095 mg/m³	
Risk Characterization Ratio (RCR)	0,034544	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see		
·		

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

### exposure estimates)

Contributing exposure scenario		
	PROC10: Roller application or brushing	
Use descriptors covered	Use domain: professional	
Operational conditions		
	Linalyl acetate	
Concentration of the substance	Content: >= 0 % - <= 1 %	
Physical state	liquid	
Vapour pressure of the substance during use	100 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	480 min 5 days per week	
Indoor/Outdoor	Outdoor	
Exposure estimate and reference to its source		
	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified	
Assessment method	version, The concentration of the substance has been	
	considered using a linear approach.	
	Worker - dermal, long-term - systemic	
Exposure estimate	0,2743 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,109714	
	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified	
Assessment method	version, The concentration of the substance has been	
	considered using a linear approach.	
	Worker - dermal, long-term - local	
Exposure estimate	20 μg/cm <sup>3</sup>	
Risk Characterization Ratio (RCR)	0,084674	
Assessment method	EASY TRA v4.1, Workplace measurements	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,1165 mg/m³	
Risk Characterization Ratio (RCR)	0,04237	
Guidance to Downstream Users		
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see		
exposure estimates)		

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
Operational conditions	
	Linalyl acetate
Concentration of the substance	Content: >= 0 % - <= 1 %
Physical state	liquid

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Vapour pressure of the substance during use	100 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	60 min 5 days per week	
Indoor/Outdoor	Indoor	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, Workplace measurements	
	Worker - dermal, long-term - systemic	
Exposure estimate	0,0044 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,001776	
Assessment method	EASY TRA v4.1, Workplace measurements	
	Worker - inhalation, long-term - systemic	
Exposure estimate	0,1613 mg/m³	
Risk Characterization Ratio (RCR)	0,058654	

Contributing exposure scenario	
	PROC11: Non industrial spraying
Use descriptors covered	Use domain: professional
Operational conditions	
	Linalyl acetate
Concentration of the substance	Content: >= 0 % - <= 1 %
Physical state	liquid
Vapour pressure of the substance	100 Pa
during use	
Process temperature	20 °C
- Trooper temperature	
Duration and Frequency of activity	60 min 5 days per week
Indoor/Outdoor	Outdoor
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, Workplace measurements
	Worker - dermal, long-term - systemic
Exposure estimate	0,0018 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000724
Assessment method	EASY TRA v4.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	0,0526 mg/m³
Risk Characterization Ratio (RCR)	0,019128

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
Operational conditions	

to Regulation (EC) No 1907/2006. Date / Revised: 29.08.2022

Version: 1.0 Previous version: none

Date previous version: not applicable Date / First version: 29.08.2022 Product: Linalyl Acetate

(ID no. 30034993/SDS\_GEN\_FR/EN)

Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 1 %
Physical state	liquid
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Wear chemically resistant gloves in combination with 'basic' employee training.	Effectiveness: 90 %
Exposure estimate and reference to	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,1071 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,042857
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
Exposure estimate	Worker - dermal, long-term - local
Exposure estimate  Risk Characterization Ratio (RCR)	5 µg/cm <sup>3</sup> 0,021169
Assessment method	EASY TRA v4.1, Workplace measurements
7.00000mont motilod	Worker - inhalation, long-term - systemic
Exposure estimate	0,2581 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,093847
Guidance to Downstream Users	1 -1
	tra Please note that a modified version has been used (see

Contributing exposure scenario		
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: professional	
Operational conditions		
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 1 %	
Physical state	liquid	
Vapour pressure of the substance during use	100 Pa	
Process temperature	20 °C	

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

Duration and Frequency of activity	60 min 5 days per week
Indoor/Outdoor	Indoor
Exposure estimate and reference to its source	
	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0,1371 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,054857
	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - dermal, long-term - local
Exposure estimate	20 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,084674
	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified
Assessment method	version, The concentration of the substance has been
	considered using a linear approach.
	Worker - inhalation, long-term - systemic
Exposure estimate	0,1636 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,059481
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org	/tra Please note that a modified version has been used (see
exposure estimates)	

#### ......

### 6. Short title of exposure scenario

Use in Cleaning Agents, (consumer use) ERC8a, ERC8d; PC31, PC35

# Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)
Operational conditions	
Annual amount used in the EU	510.000 kg
Minimum emission days per year	365
Emission factor air	100 %
Emission factor water	100 %

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Emission factor soil	0 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Type of STP	•	
Assumed sewage treatment plant flow (m3/d)		2.000 m3/d
Exposure estimate and reference to	its source	
Assessment method	EASY TRA v4.1, ECETOC	CTRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,130654	
	Risk from environmental exposure is driven by soil.	
	2,1	
Maximum amount of safe use	kg/d	
Risk from environmental exposure is o	Iriven by soil.	

Contributing exposure scenario			
Use descriptors covered		nd use of non-reactive processing aid r onto article, outdoor)	
Operational conditions			
Annual amount used in the EU	510.000 kg		
Minimum emission days per year	365		
Emission factor air	100 %		
Emission factor water	100 %		
Emission factor soil	20 %		
Receive Surf. Water (Flow Rate).	18.000 m3/d		
Dilution factor river	10		
Dilution factor coast	100		
Risk Management Measures			
Type of STP		Municipal STP	
Assumed sewage treatment plant flow (m3/d) 2.000 m3/d		2.000 m3/d	
Exposure estimate and reference to	o its source		
Assessment method	EASY TRA v4.1, E	EASY TRA v4.1, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,130654	0,130654	

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	2,1 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PC31: Polishes and Wax Blends. In accordance to the Article 14 (2a-f) of the REACh Regulation (EC) No 1907/2006, exposure estimation and risk characterisation needs not to be performed if the substance in a preparation is less than 0.1%.
Operational conditions	
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 0,75 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 0,3 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	365 uses per year
Room size	1 m3
Ventilation rate per hour	2
Temperature (Application)	21 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 0,01 g Relevant for dermal exposure estimates
Release area	20 cm <sup>2</sup>
	Release area is constant

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Release duration	0,3 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to its source	
A a a a a a m a m a th a d	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant
Assessment method	application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0003 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000271
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:
Assessment method	exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0027 mg/m³
Risk Characterization Ratio (RCR)	0,004041
	The exposure calculation is based on the mean
	concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
	Amount per use 0,01 g Relevant for dermal exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application
	Consumer - dermal, short-term - local
Exposure estimate	0,0001 µg/cm³
Risk Characterization Ratio (RCR)	0,000433
	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/h	ealthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Operational conditions	
	Linalyl acetate
Concentration of the substance	Content: >= 0 % - <= 0,22 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	365 uses per year
body weight	65 kg
Skin contact factor	80 %
Uptake fraction dermal	100 %
Leachable fraction	0,000007 %
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: migration, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0009 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000689
	The calculation is based on the internal chronic dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
Skin contact factor	80 %
Leachable fraction	0,000007 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: migration
	Consumer - dermal, short-term - local

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Exposure estimate	0,0001 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000017
	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,66 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 3 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 2 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	260 uses per year
Room size	2,5 m3
Ventilation rate per hour	2
Temperature (Application)	21 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 2,2 g Relevant for dermal exposure estimates
Release area	750 cm <sup>2</sup>
	Release area is constant
Release duration	2 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,1591 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,127299
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:
, accessification	exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0157 mg/m³

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Risk Characterization Ratio (RCR)	0,023021
	The exposure calculation is based on the mean
	concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,66 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
	Amount per use 2,2 g Relevant for dermal exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application
	Consumer - dermal, short-term - local
Exposure estimate	0,0675 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,285922
	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/h	ealthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,66 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 3 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 2 min Relevant for inhalative exposure estimates

to Regulation (EC) No 1907/2006.

Version: 1.0 Previous version: none

Date / Revised: 29.08.2022 Date previous version: not applicable Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Duration and Frequency of activity	120 uses per year
Room size	2,5 m3
Ventilation rate per hour	2
Temperature (Application)	21 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 2,2 g Relevant for dermal exposure estimates
Release area	750 cm <sup>2</sup>
	Release area is constant
Release duration	2 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant
Assessment method	application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0734 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,058753
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:
Assessment method	exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0157 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,023021
	The exposure calculation is based on the mean
	concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,66 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
	Amount per use 2,2 g Relevant for dermal exposure estimates

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application
	Consumer - dermal, short-term - local
Exposure estimate	0,0675 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,285922
The calculation is based on the external dose.	
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,66 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 24 h Relevant for inhalative exposure estimates
Duration and Frequency of activity	365 uses per year
body weight	65 kg
Release duration	86400 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model: exposure to vapour - constant rate
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0628 mg/m³
Risk Characterization Ratio (RCR)	0,092396
	The exposure calculation is based on the mean concentration on the day of exposure.
Guidance to Downstream Users	· · ·
For scaling see: http://www.rivm.nl/en/	healthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,66 %

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 24 h Relevant for inhalative exposure estimates
Duration and Frequency of activity	365 uses per year
body weight	65 kg
Release duration	43200 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:
Assessment method	exposure to vapour - constant rate
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0539 mg/m³
Risk Characterization Ratio (RCR)	0,079197
·	The exposure calculation is based on the mean
	concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/h	nealthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 0,75 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 0,3 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	104 uses per year
Room size	1 m3
Ventilation rate per hour	0,5
Temperature (Application)	21 °C
body weight	65 kg
Uptake fraction dermal	100 %

to Regulation (EC) No 1907/2006. Date / Revised: 29.08.2022

Version: 1.0 Previous version: none

Date previous version: not applicable
Date / First version: 29.08.2022
Product: Linalyl Acetate

(ID no. 30034993/SDS\_GEN\_FR/EN)

	Amount per use 0,01 g Relevant for dermal exposure
	estimates
Release area	20 cm <sup>2</sup>
	Release area is constant
Release duration	0,3 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant
Assessmentmethod	application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0001 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000077
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:
Assessmentmethod	exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0001 mg/m³
Risk Characterization Ratio (RCR)	0,000001
	The exposure calculation is based on the mean
	concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/	/healthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario		
	PC35: Washing and Cleaning Products (including solvent	
Use descriptors covered	based products).	
Operational conditions		
	Linalyl acetate	
Concentration of the substance	Content: >= 0 % - <= 0,22 %	
Vapour pressure of the substance during use	100 Pa	
Process temperature	20 °C	
body weight	65 kg	
	Amount per use 0,01 g Relevant for dermal exposure estimates	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application	
	Consumer - dermal, short-term - local	
Exposure estimate	0,0001 μg/cm <sup>3</sup>	
Risk Characterization Ratio (RCR)	0,000433	
	The calculation is based on the external dose.	
Guidance to Downstream Users		

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 240 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 20 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	104 uses per year
Room size	58 m3
Ventilation rate per hour	0,5
Temperature (Application)	21 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 19 g Relevant for dermal exposure estimates
Release area	100000 cm <sup>2</sup>
	Release area increases over time
Release duration	20 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,1832 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,146586
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:
7.00000mont motilou	exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,2692 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,39587
	The exposure calculation is based on the mean
Outdones to Description of the	concentration on the day of exposure.
Guidance to Downstream Users	

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
	Amount per use 19 g Relevant for dermal exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application
	Consumer - dermal, short-term - local
Exposure estimate	0,022 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,093141
	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/	healthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 0,75 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 0,3 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	4 uses per year
Room size	1 m3
Ventilation rate per hour	2

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Temperature (Application)	21 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 0,01 g Relevant for dermal exposure
	estimates
Release area	20 cm <sup>2</sup>
	Release area is constant
Release duration	0,3 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to it	ts source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant
Assessment method	application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0001 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,00003
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:
Assessment method	exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0001 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,00001
	The exposure calculation is based on the mean
	concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/he	ealthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	1
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
	Amount per use 0,01 g Relevant for dermal exposure estimates
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application
	Consumer - dermal, short-term - local

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Exposure estimate	0,0001 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000433
	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).	
Operational conditions		
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %	
Vapour pressure of the substance during use	100 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	Exposure duration: 25 min Relevant for inhalative exposure estimates	
Duration and Frequency of activity	Application duration: 20 min Relevant for inhalative exposure estimates	
Duration and Frequency of activity	4 uses per year	
Room size	10 m3	
Ventilation rate per hour	2	
Temperature (Application)	21 °C	
body weight	65 kg	
Uptake fraction dermal	100 %	
	Amount per use 19 g Relevant for dermal exposure estimates	
Release area	64000 cm <sup>2</sup>	
	Release area increases over time	
Release duration	20 min	
	Relevant for inhalative exposure estimates	
Exposure estimate and reference to		
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction	
	Consumer - dermal, long-term - systemic	
Exposure estimate	0,007 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,005638	
	The calculation is based on the internal chronic dose.	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:	
ASSESSITE III THE HIDU	exposure to vapour - evaporation	
	Consumer - inhalation, long-term - systemic	
Exposure estimate	0,0279 mg/m <sup>3</sup>	

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Risk Characterization Ratio (RCR)	0,040989
	The exposure calculation is based on the mean
	concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	1
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
	Amount per use 19 g Relevant for dermal exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application
	Consumer - dermal, short-term - local
Exposure estimate	0,022 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,093141
	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/h	nealthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,55 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 60 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	365 uses per year

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Room size	15 m3
Ventilation rate per hour	2,5
body weight	65 kg
Uptake fraction dermal	100 %
Spray duration	24,6 sec
Contact rate	46 mg/min
Release duration	0,41 min
	Relevant for dermal exposure estimates
Risk Management Measures	
Consumer Measures	Ensure spraying away from persons.
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: constant
Assessment method	application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0016 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001277
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:
Assessment method	Exposure to spray/dust
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0006 mg/m³
Risk Characterization Ratio (RCR)	0,000834
	The exposure calculation is based on the mean
	concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/	healthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
	Linalyl acetate
Concentration of the substance	Content: >= 0 % - <= 0,4 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
Contact rate	46 mg/min
Release duration	0,41 min
	Relevant for dermal exposure estimates
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: constant

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

	application rate
	Consumer - dermal, short-term - local
Exposure estimate	0,0001 µg/cm³
Risk Characterization Ratio (RCR)	0,000153
	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

	PC35: Washing and Cleaning Products (including solvent
Use descriptors covered	based products).
Operational conditions	
	Linalyl acetate
Concentration of the substance	Content: >= 0 % - <= 0,55 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 60 min
Duration and Frequency of activity	Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 10 min
Duration and Frequency of dottvity	Relevant for inhalative exposure estimates
Duration and Frequency of activity	365 uses per year
Room size	15 m3
Ventilation rate per hour	2,5
Temperature (Application)	21 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 0,16 g Relevant for dermal exposure estimates
Release area	17100 cm <sup>2</sup>
	Release area is constant
Release duration	10 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant
Assessment method	application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0135 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,010831
. ,	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:
Assessment method	exposure to vapour - evaporation

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0909 mg/m³
Risk Characterization Ratio (RCR)	0,133631
	The exposure calculation is based on the mean
	concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,55 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
	Amount per use 0,16 g Relevant for dermal exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application
	Consumer - dermal, short-term - local
Exposure estimate	0,0041 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,017329
	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/h	ealthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 25 min Relevant for inhalative exposure estimates

Date / Revised: 29.08.2022

Date previous version: not applicable Date / First version: 29.08.2022 Product: **Linalyl Acetate**  Version: 1.0 Previous version: none

(ID no. 30034993/SDS\_GEN\_FR/EN)

Duration and Frequency of activity	52 uses per year
Room size	10 m3
Ventilation rate per hour	2
body weight	65 kg
Uptake fraction dermal	100 %
Spray duration	90 sec
Contact rate	46 mg/min
Release duration	1,5 min
	Relevant for dermal exposure estimates
Risk Management Measures	
Consumer Measures	Ensure spraying away from persons.
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: constant
Assessment method	application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0003 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000266
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:
Assessment method	Exposure to spray/dust
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0029 mg/m³
Risk Characterization Ratio (RCR)	0,004324
	The exposure calculation is based on the mean
	concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/h	nealthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
Contact rate	46 mg/min
Release duration	1,5 min
	Relevant for dermal exposure estimates

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: constant application rate
	Consumer - dermal, short-term - local
Exposure estimate	0,0001 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000309
	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario			
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).		
Operational conditions			
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %		
Vapour pressure of the substance during use	100 Pa		
Process temperature	20 °C		
Duration and Frequency of activity	Exposure duration: 25 min Relevant for inhalative exposure estimates		
Duration and Frequency of activity	Application duration: 20 min Relevant for inhalative exposure estimates		
Duration and Frequency of activity	52 uses per year		
Room size	10 m3		
Ventilation rate per hour	2		
Temperature (Application)	21 °C		
body weight	65 kg		
Uptake fraction dermal	100 %		
	Amount per use 0,3 g Relevant for dermal exposure estimates		
Release area	64000 cm <sup>2</sup>		
	Release area is constant		
Release duration	20 min		
	Relevant for inhalative exposure estimates		
Exposure estimate and reference to	Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction		
	Consumer - dermal, long-term - systemic		
Exposure estimate	0,0014 mg/kg bw/day		
Risk Characterization Ratio (RCR)	0,001157		
	The calculation is based on the internal chronic dose.		

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0777 mg/m³
Risk Characterization Ratio (RCR)	0,11425
	The exposure calculation is based on the mean
	concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
	Amount per use 0,3 g Relevant for dermal exposure estimates
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application
	Consumer - dermal, short-term - local
Exposure estimate	0,0031 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,012996
	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/h	nealthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Duration and Frequency of activity	Exposure duration: 60 min Relevant for inhalative exposure estimates	
	26 uses per year	
Duration and Frequency of activity	20 d3c3 per year	
Room size	15 m3	
Ventilation rate per hour	2,5	
body weight	65 kg	
Uptake fraction dermal	100 %	
Spray duration	30 sec	
Contact rate	46 mg/min	
Release duration	0,5 min	
	Relevant for dermal exposure estimates	
Risk Management Measures		
Consumer Measures	Ensure spraying away from persons.	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: constant	
Assessment method	application rate, Uptake model: Uptake fraction	
	Consumer - dermal, long-term - systemic	
Exposure estimate	0,0001 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,000044	
	The calculation is based on the internal chronic dose.	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:	
Assessmentmethod	Exposure to spray/dust	
	Consumer - inhalation, long-term - systemic	
Exposure estimate	0,0003 mg/m³	
Risk Characterization Ratio (RCR)	0,000407	
	The exposure calculation is based on the mean	
	concentration on the day of exposure.	
Guidance to Downstream Users		
For scaling see: http://www.rivm.nl/en/h	nealthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
Contact rate	46 mg/min

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Release duration	0,5 min	
	Relevant for dermal exposure estimates	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: constant	
	application rate	
	Consumer - dermal, short-term - local	
Exposure estimate	0,0001 μg/cm <sup>3</sup>	
Risk Characterization Ratio (RCR)	0,000103	
	The calculation is based on the external dose.	
Guidance to Downstream Users		
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp		

Contributing exposure scenario		
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).	
Operational conditions		
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %	
Vapour pressure of the substance during use	100 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	26 uses per year	
body weight	65 kg	
Uptake fraction dermal	100 %	
	Amount per use 0,2 g Relevant for dermal exposure estimates	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction	
	Consumer - dermal, long-term - systemic	
Exposure estimate	0,0005 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,000386	
	The calculation is based on the internal chronic dose.	
Guidance to Downstream Users		
For scaling see: http://www.rivm.nl/en/h	nealthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

	Content: >= 0 % - <= 0,22 %	
Vapour pressure of the substance during use	100 Pa	
Process temperature	20 °C	
body weight	65 kg	
	Amount per use 0,2 g Relevant for dermal exposure estimates	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application	
	Consumer - dermal, short-term - local	
Exposure estimate	0,001 µg/cm <sup>3</sup>	
Risk Characterization Ratio (RCR)	0,004332	
	The calculation is based on the external dose.	
Guidance to Downstream Users		
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp		

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 0,75 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 0,3 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	< 1 uses per year
Room size	1 m3
Ventilation rate per hour	0,5
Temperature (Application)	21 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 0,01 g Relevant for dermal exposure estimates
Release area	20 cm <sup>2</sup>

Page: 89/129

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022

Date previous version: not applicable Date / First version: 29.08.2022 Product: **Linalyl Acetate**  Version: 1.0 Previous version: none

(ID no. 30034993/SDS\_GEN\_FR/EN)

	Release area is constant
Release duration	0,3 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant
Assessment method	application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0001 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000001
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:
Assessment method	exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0011 mg/m³
Risk Characterization Ratio (RCR)	0,001628
	The exposure calculation is based on the mean
	concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
	Amount per use 0,01 g Relevant for dermal exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application
	Consumer - dermal, short-term - local
Exposure estimate	0,0001 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000433
	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

	based products).
Operational conditions	
	Linalyl acetate
Concentration of the substance	Content: >= 0 % - <= 0,22 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 110 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 110 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	< 1 uses per year
Room size	58 m3
Ventilation rate per hour	0,5
Temperature (Application)	21 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 27 g Relevant for dermal exposure estimates
Release area	220000 cm <sup>2</sup>
	Release area increases over time
Release duration	110 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0013 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001001
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:
Assessment method	exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,1235 mg/m³
Risk Characterization Ratio (RCR)	0,181591
	The exposure calculation is based on the mean
	concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

	based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
	Amount per use 27 g Relevant for dermal exposure estimates
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application
	Consumer - dermal, short-term - local
Exposure estimate	0,0691 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,292421
	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).	
Operational conditions		
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %	
Vapour pressure of the substance during use	100 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	Exposure duration: 22 min Relevant for inhalative exposure estimates	
Duration and Frequency of activity	< 1 uses per year	
Room size	58 m3	
Ventilation rate per hour	0,5	
body weight	65 kg	
Uptake fraction dermal	100 %	
Spray duration	1320 sec	
Contact rate	5 mg/min	

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Release duration	22 min
	Relevant for dermal exposure estimates
Risk Management Measures	
Consumer Measures	Ensure spraying away from persons.
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0001 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,00004
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:
Assessment method	Exposure to spray/dust
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0117 mg/m³
Risk Characterization Ratio (RCR)	0,017185
	The exposure calculation is based on the mean
	concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario			
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).		
Operational conditions			
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %		
Vapour pressure of the substance during use	100 Pa		
Process temperature	20 °C		
body weight	65 kg		
Contact rate	5 mg/min		
Release duration	22 min		
	Relevant for dermal exposure estimates		
Exposure estimate and reference to	Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: constant application rate		
	Consumer - dermal, short-term - local		
Exposure estimate	0,0001 μg/cm <sup>3</sup>		
Risk Characterization Ratio (RCR)	0,000492		
	The calculation is based on the external dose.		
Guidance to Downstream Users			
For scaling see: http://www.rivm.nl/en/h	nealthanddisease/productsafety/ConsExpo.jsp		

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	14 uses per year
Duration and Frequency of activity	14 uses per year
body weight	8,69 kg
Uptake fraction dermal	100 %
Uptake fraction oral	100 %
	Amount ingested 0,384 mg Relevant for oral exposure estimates
Transfer coefficient	1,666667 cm <sup>2</sup> /s
Dislodgeable amount	0,0003 g/cm <sup>2</sup>
Contact time	3600 sec
Rubbed surface	22 m²
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: rubbing off, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0175 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,013983
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Oral model: direct intake, Uptake model: Uptake fraction
	Consumer - oral, long-term - systemic
Exposure estimate	0,0001 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000019
	The calculation is based on the internal chronic dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Operational conditions		
	Linalyl acetate	
Concentration of the substance	Content: >= 0 % - <= 0,22 %	
Vapour pressure of the substance	100 Pa	
during use		
Process temperature	20 °C	
body weight	8,69 kg	
Transfer coefficient	1,666667 cm <sup>2</sup> /s	
Dislodgeable amount	0,0003 g/cm <sup>2</sup>	
Contact time	3600 sec	
Rubbed surface	22 m²	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: rubbing	
Assessment method	off	
	Consumer - dermal, short-term - local	
Exposure estimate	0,0008 μg/cm <sup>3</sup>	
Risk Characterization Ratio (RCR)	0,003493	
	The calculation is based on the external dose.	
Guidance to Downstream Users		
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp		

Contributing exposure scenario	Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).	
Operational conditions		
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %	
Vapour pressure of the substance during use	100 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	10 uses per year	
body weight	65 kg	
Uptake fraction dermal	100 %	
	Amount per use 0,07 g Relevant for dermal exposure estimates	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction	
	Consumer - dermal, long-term - systemic	

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Exposure estimate	0,0001 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000052
	The calculation is based on the internal chronic dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
	Amount per use 0,07 g Relevant for dermal exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application
	Consumer - dermal, short-term - local
Exposure estimate	0,0007 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,003033
	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/h	nealthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
	Linalyl acetate
Concentration of the substance	Content: >= 0 % - <= 0,22 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 60 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 2 min Relevant for inhalative exposure estimates

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Duration and Frequency of activity	365 uses per year
Room size	20 m3
Ventilation rate per hour	0,6
Temperature (Application)	21 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 0,047 g Relevant for dermal exposure
	estimates
Release area	20000 cm <sup>2</sup>
	Release area increases over time
Release duration	2 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant
Assessmentmentou	application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0016 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,001273
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:
Assessment method	exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0115 mg/m³
Risk Characterization Ratio (RCR)	0,016973
	The exposure calculation is based on the mean
	concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/h	ealthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,22 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
	Amount per use 0,047 g Relevant for dermal exposure estimates

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application
	Consumer - dermal, short-term - local
Exposure estimate	0,0005 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,002036
	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,11 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 0,25 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	365 uses per year
Room size	1 m3
Ventilation rate per hour	2
body weight	65 kg
	Amount per use 0,27 µg Relevant for inhalative exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model: evaporation model - instantaneous release Consumer - inhalation, long-term - systemic
Exposure estimate	0,0001 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000001
	The exposure calculation is based on the mean concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/h	nealthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	

to Regulation (EC) No 1907/2006. Date / Revised: 29.08.2022

Version: 1.0 Previous version: none

Date previous version: not applicable
Date / First version: 29.08.2022
Product: Linalyl Acetate

(ID no. 30034993/SDS\_GEN\_FR/EN)

	Linalyl acetate
Concentration of the substance	Content: >= 0 % - <= 0,11 %
	100.7
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	104 uses per year
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 19 g Relevant for dermal exposure
	estimates
Exposure estimate and reference to	o its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0916 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,073293
	The calculation is based on the internal chronic dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/	/healthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
	Linalyl acetate
Concentration of the substance	Content: >= 0 % - <= 0,11 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
	Amount per use 19 g Relevant for dermal exposure
	estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant
Assessment method	application
	Consumer - dermal, short-term - local
Exposure estimate	0,011 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,046571
	The calculation is based on the external dose.

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

## Guidance to Downstream Users For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,11 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	365 uses per year
body weight	65 kg
Skin contact factor	80 %
Uptake fraction dermal	100 %
Leachable fraction	0,000003 %
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: migration, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0004 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000295
	The calculation is based on the internal chronic dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/h	ealthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,11 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Skin contact factor	80 %
Leachable fraction	0,000003 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: migration
	Consumer - dermal, short-term - local
Exposure estimate	0,0001 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000006
	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
· ·	PC35: Washing and Cleaning Products (including solvent
Use descriptors covered	based products).
Operational conditions	
	Linalyl acetate
Concentration of the substance	Content: >= 0 % - <= 0,11 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 0,75 min
	Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 0,3 min
	Relevant for inhalative exposure estimates
Duration and Frequency of activity	365 uses per year
Room size	1 m3
Ventilation rate per hour	2
Temperature (Application)	21 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 0,01 g Relevant for dermal exposure
	estimates
Release area	20 cm <sup>2</sup>
	Release area is constant
Release duration	0,3 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant
Magaagineni ineliioo	application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0002 mg/kg bw/day

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Risk Characterization Ratio (RCR)	0,000135
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:
	exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0014 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,002019
	The exposure calculation is based on the mean
	concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
	Linalyl acetate
Concentration of the substance	Content: >= 0 % - <= 0,11 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
	Amount per use 0,01 g Relevant for dermal exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant
Assessment method	application
	Consumer - dermal, short-term - local
Exposure estimate	0,0001 µg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000217
	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/	healthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,11 %
Vapour pressure of the substance during use	100 Pa

Page: 102/129

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Process temperature	20 °C	
Duration and Frequency of activity	104 uses per year	
body weight	65 kg	
Uptake fraction dermal	100 %	
	Amount per use 19 g Relevant for dermal exposure	
	estimates	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant	
Assessment method	application, Uptake model: Uptake fraction	
	Consumer - dermal, long-term - systemic	
Exposure estimate	0,0916 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,073293	
	The calculation is based on the internal chronic dose.	
Guidance to Downstream Users		
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp		

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,11 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
	Amount per use 19 g Relevant for dermal exposure estimates
Exposure estimate and reference to	o its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application
	Consumer - dermal, short-term - local
Exposure estimate	0,011 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,046571
	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en.	/healthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

	based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,11 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	365 uses per year
body weight	65 kg
Skin contact factor	80 %
Uptake fraction dermal	100 %
Leachable fraction	0,000003 %
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: migration, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0004 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000295
	The calculation is based on the internal chronic dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,11 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
Skin contact factor	80 %
Leachable fraction	0,000003 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: migration

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

	Consumer - dermal, short-term - local
Exposure estimate	0,0001 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,00006
	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	1
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,11 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 0,25 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	252 uses per year
Room size	1 m3
Ventilation rate per hour	2,5
body weight	65 kg
	Amount per use 0,27 µg Relevant for inhalative exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model: evaporation model - instantaneous release
Exposure estimate	Consumer - inhalation, long-term - systemic 0,0001 mg/m³
Risk Characterization Ratio (RCR)	0,00001
THE CHARACTER OF THE COLUMN	The exposure calculation is based on the mean concentration on the day of exposure.
Guidance to Downstream Users	· · · · · · · · · · · · · · · · · · ·
For scaling see: http://www.rivm.nl/en/h	nealthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,11 %

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	365 uses per year
body weight	65 kg
Uptake fraction oral	100 %
	Amount ingested 0,084 mg Relevant for oral exposure estimates
Exposure estimate and reference to	
•	EASY TRA v4.1, ConsExpo v4.1, Oral model: direct intake,
Assessment method	Uptake model: Uptake fraction
	Consumer - oral, long-term - systemic
Exposure estimate	0,0001 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000007
	The calculation is based on the internal chronic dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,11 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 0,75 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 0,3 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	35 uses per year
Room size	1 m3
Ventilation rate per hour	2,5
Temperature (Application)	21 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 0,01 g Relevant for dermal exposure

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

	estimates
Release area	20 cm <sup>2</sup>
	Release area is constant
Release duration	0,3 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant
	application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0001 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000013
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:
Assessment method	exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0009 mg/m³
Risk Characterization Ratio (RCR)	0,001344
	The exposure calculation is based on the mean
	concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,11 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
	Amount per use 0,01 g Relevant for dermal exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application
	Consumer - dermal, short-term - local
Exposure estimate	0,0001 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000217
	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/h	nealthanddisease/productsafety/ConsExpo.jsp

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,11 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 0,75 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 0,3 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	426 uses per year
Room size	1 m3
Ventilation rate per hour	2,5
Temperature (Application)	21 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 0,01 g Relevant for dermal exposure estimates
Release area	20 cm <sup>2</sup>
	Release area is constant
Release duration	0,3 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0002 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000158
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:
	exposure to vapour - evaporation  Consumer - inhalation, long-term - systemic
Exposure estimate	0,0001 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,00001
THOSE OFFICIALITY (TOTA)	The exposure calculation is based on the mean
	concentration on the day of exposure.
Guidance to Downstream Users	The state of the s
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	
i or scaning see. http://www.nvini.hi/en/	nearthanadisease/productsarety/Odnaczpo.jap

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,11 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
	Amount per use 0,01 g Relevant for dermal exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application
	Consumer - dermal, short-term - local
Exposure estimate	0,0001 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000217
	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario		
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).	
Operational conditions		
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,11 %	
Vapour pressure of the substance during use	100 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	Exposure duration: 60 min Relevant for inhalative exposure estimates	
Duration and Frequency of activity	Application duration: 16 min Relevant for inhalative exposure estimates	
Duration and Frequency of activity	426 uses per year	
Room size	15 m3	
Ventilation rate per hour	2,5	
Temperature (Application)	21 °C	
body weight	65 kg	

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Uptake fraction dermal	100 %
	Amount per use 8,6 g Relevant for dermal exposure
	estimates
Release area	1500 cm <sup>2</sup>
	Release area is constant
Release duration	16 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,1699 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,135889
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:
Assessment method	exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0005 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000727
	The exposure calculation is based on the mean
	concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/	healthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,11 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 60 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 16 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	426 uses per year
Room size	15 m3
Ventilation rate per hour	2,5
Temperature (Application)	21 °C
body weight	65 kg

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0 Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: Linalyl Acetate

(ID no. 30034993/SDS\_GEN\_FR/EN)

	Amount per use 8,6 g Relevant for dermal exposure
	estimates
Release area	1500 cm <sup>2</sup>
	Release area is constant
Release duration	16 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant
Assessment method	application
	Consumer - dermal, short-term - local
Exposure estimate	0,011 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,046571
	The calculation is based on the external dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:
Assessment method	exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0005 mg/m³
Risk Characterization Ratio (RCR)	0,000727
	The exposure calculation is based on the mean
	concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/	/healthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
osc acsoriptors covered	based products).
Operational conditions	
	Linalyl acetate
Concentration of the substance	Content: >= 0 % - <= 0,11 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	365 uses per year
body weight	65 kg
Uptake fraction oral	100 %
	Amount ingested 0,42 mg Relevant for oral exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Oral model: direct intake, Uptake model: Uptake fraction
	Consumer - oral, long-term - systemic

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Exposure estimate	0,0001 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000036
	The calculation is based on the internal chronic dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,11 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	128 uses per year
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 0,65 g Relevant for dermal exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0039 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,003086
	The calculation is based on the internal chronic dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/h	nealthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	l
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,11 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

body weight	65 kg
	Amount per use 0,65 g Relevant for dermal exposure
	estimates
Exposure estimate and reference to its source	
	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant
Assessment method	application
	Consumer - dermal, short-term - local
Exposure estimate	0,0017 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,00704
	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
	Linalyl acetate
Concentration of the substance	Content: >= 0 % - <= 0,11 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 10 min
Duration and Frequency of activity	Relevant for inhalative exposure estimates
Duration and Frequency of activity	128 uses per year
Room size	10 m3
Ventilation rate per hour	2
body weight	65 kg
Uptake fraction dermal	100 %
Spray duration	3 sec
Contact rate	46 mg/min
Release duration	0,05 min
	Relevant for dermal exposure estimates
Risk Management Measures	
Consumer Measures	Ensure spraying away from persons.
Exposure estimate and reference to	o its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: constant
	application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0001 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000011

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:
	Exposure to spray/dust
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0001 mg/m³
Risk Characterization Ratio (RCR)	0,000026
	The exposure calculation is based on the mean
	concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,11 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
Contact rate	46 mg/min
Release duration	0,05 min
	Relevant for dermal exposure estimates
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: constant application rate
	Consumer - dermal, short-term - local
Exposure estimate	0,0001 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,000005
·	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/	/healthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario		
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).	
Operational conditions		
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,11 %	
Vapour pressure of the substance during use	100 Pa	

Page: 114/129

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Process temperature	20 °C	
Duration and Frequency of activity	128 uses per year	
body weight	65 kg	
Uptake fraction dermal	100 %	
	Amount per use 2 g Relevant for dermal exposure	
	estimates	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant	
Assessment method	application, Uptake model: Uptake fraction	
	Consumer - dermal, long-term - systemic	
Exposure estimate	0,0119 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,009495	
	The calculation is based on the internal chronic dose.	
Guidance to Downstream Users		
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp		

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,11 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
	Amount per use 2 g Relevant for dermal exposure estimates
Exposure estimate and reference to it	ts source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application
	Consumer - dermal, short-term - local
Exposure estimate	0,0051 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,021661
	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent

Version: 1.0

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022

Date previous version: not applicable Date / First version: 29.08.2022 Product: **Linalyl Acetate**  Previous version: none

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

	based products). Other products of this category do either not exceed a concentration of 0.1% for this substance or exposure estimations are covered by the calculations made for this product category. In accordance to the Article 14 (2a-f) of the REACh Regulation (EC) No 1907/2006, exposure estimation and risk characterisation needs not to be performed if the substance in a preparation is less than 0.1%.
Operational conditions	
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C

\* \* \* \* \* \* \* \* \* \* \* \* \* \* \* \*

### 7. Short title of exposure scenario

Use in/as Air care products, (consumer use) ERC8a; PC3

# Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)
Operational conditions	
Annual amount used in the EU	510.000 kg
Minimum emission days per year	365
Emission factor air	100 %
Emission factor water	100 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	·
Type of STP	Municipal STP

Page: 116/129

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Baseletian (EQ) No. 1007/2006

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Assumed sewage treatment plant flow	(m3/d) 2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,130654
	Risk from environmental exposure is driven by soil.
	2,1
Maximum amount of safe use	kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PC3: Air care products.
Operational conditions	
	Linalyl acetate
Concentration of the substance	Content: >= 0 % - <= 3,4 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 480 min
Duration and Frequency of activity	Relevant for inhalative exposure estimates
Duration and Frequency of activity	150 uses per year
Room size	16 m3
Ventilation rate per hour	1
body weight	65 kg
Spray duration	28800 sec
Risk Management Measures	
Consumer Measures	Ensure spraying away from persons.
Exposure estimate and reference to it	ts source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:
Assessment method	Exposure to spray/dust
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0145 mg/m³
Risk Characterization Ratio (RCR)	0,021371
	The exposure calculation is based on the mean
	concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC3: Air care products.
Operational conditions	
Concentration of the substance	Linalyl acetate

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

	Content: >= 0 % - <= 0,17 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 240 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	90 uses per year
Room size	58 m3
Ventilation rate per hour	0,5
body weight	65 kg
Uptake fraction dermal	100 %
Spray duration	19,8 sec
Contact rate	269 mg/min
Release duration	0,33 min
	Relevant for dermal exposure estimates
Risk Management Measures	
Consumer Measures	Ensure spraying away from persons.
Exposure estimate and reference to	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,0006 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000458
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:
A33633ITCH ITCHOO	Exposure to spray/dust
	Consumer - inhalation, long-term - systemic
Exposure estimate	0,0007 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,001015
	The exposure calculation is based on the mean concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/h	ealthanddisease/productsafety/ConsExpo.jsp

Contributing exposure scenario		
Use descriptors covered	PC3: Air care products.	
Operational conditions		
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,17 %	
Vapour pressure of the substance during use	100 Pa	

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Process temperature	20 °C	
body weight	65 kg	
Contact rate	269 mg/min	
Release duration	0,33 min	
	Relevant for dermal exposure estimates	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: constant application rate	
	Consumer - dermal, short-term - local	
Exposure estimate	0,0001 μg/cm <sup>3</sup>	
Risk Characterization Ratio (RCR)	0,000037	
	The calculation is based on the external dose.	
Guidance to Downstream Users		
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp		

Contributing exposure scenario	
Use descriptors covered	PC3: Air care products.
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,17 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	90 uses per year
Duration and Frequency of activity	Exposure duration: 60 min Relevant for oral exposure estimates
Duration and Frequency of activity	90 uses per year
body weight	8,69 kg
Uptake fraction dermal	100 %
Uptake fraction oral	100 %
Transfer coefficient	1,666667 cm <sup>2</sup> /s
Dislodgeable amount	0,000082 g/cm <sup>2</sup>
Contact time	3600 sec
Rubbed surface	22 m <sup>2</sup>
Ingestion rate	0,001392 mg/min
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: rubbing off, Uptake model: Uptake fraction

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

	Consumer - dermal, long-term - systemic
Exposure estimate	0,0237 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,018986
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Oral model: constant rate, Uptake model: Uptake fraction
	Consumer - oral, long-term - systemic
Exposure estimate	0,0001 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,00002
	The calculation is based on the internal chronic dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario		
Use descriptors covered	PC3: Air care products.	
Operational conditions		
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,17 %	
Vapour pressure of the substance during use	100 Pa	
Process temperature	20 °C	
body weight	8,69 kg	
Transfer coefficient	1,666667 cm <sup>2</sup> /s	
Dislodgeable amount	0,000082 g/cm <sup>2</sup>	
Contact time	3600 sec	
Rubbed surface	22 m <sup>2</sup>	
Exposure estimate and reference to	its source	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: rubbing off	
	Consumer - dermal, short-term - local	
Exposure estimate	0,0002 μg/cm <sup>3</sup>	
Risk Characterization Ratio (RCR)	0,000738	
	The calculation is based on the external dose.	
Guidance to Downstream Users		
For scaling see: http://www.rivm.nl/en/h	ealthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC3: Air care products. Other products of this category do either not exceed a concentration of 0.1% for this substance or exposure estimations are covered by the calculations made for this product category. In accordance to the Article 14 (2a-f) of the REACh Regulation (EC) No 1907/2006, exposure estimation and risk characterisation needs not to be

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

	performed if the substance in a preparation is less than 0.1%.
Operational conditions	
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C

\* \* \* \* \* \* \* \* \* \* \* \* \* \* \* \*

### 8. Short title of exposure scenario

other consumer applications than fragrance, (consumer use) ERC8a, ERC8d; PC8

# Control of exposure and risk management measures

Contributing exposure scenario			
Use descriptors covered	ERC8a: Widespread us (no inclusion into or on	se of non-reactive processing aid to article, indoor)	
Operational conditions			
Annual amount used in the EU	510.000 kg		
Minimum emission days per year	365		
Emission factor air	100 %		
Emission factor water	100 %		
Emission factor soil	0 %		
Receive Surf. Water (Flow Rate).	18.000 m3/d		
Dilution factor river	10		
Dilution factor coast	100		
Risk Management Measures	-		
		Municipal STP	
Assumed sewage treatment plant flow (m3/d) 2.000 m3/d		2.000 m3/d	
Exposure estimate and reference to	its source		
Assessment method	EASY TRA v4.1, ECET	EASY TRA v4.1, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,130654		
	Risk from environmenta	al exposure is driven by soil.	
Maximum amount of safe use	2,1 kg/d		

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

Risk from environmental exposure is driven by soil.

Contributing exposure scenario		
Use descriptors covered	ERC8d: Widespread use of (no inclusion into or onto a	of non-reactive processing aid article, outdoor)
Operational conditions		
Annual amount used in the EU	510.000 kg	
Minimum emission days per year	365	
Emission factor air	100 %	
Emission factor water	100 %	
Emission factor soil	20 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Type of STP		Municipal STP
Assumed sewage treatment plant flow	(m3/d)	2.000 m3/d
Exposure estimate and reference to	its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,130654	
	Risk from environmental e	xposure is driven by soil.
	2,1	
Maximum amount of safe use	kg/d	
Risk from environmental exposure is d	riven by soil.	

Contributing exposure scenario	
Use descriptors covered	PC8: Biocidal Products.
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,78 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	54 uses per year

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none
Date / First version: 29.08.2022

Product: Linalyl Acetate

(ID no. 30034993/SDS\_GEN\_FR/EN)

Duration and Frequency of activity	Exposure duration: 180 min
	Relevant for oral exposure estimates
Duration and Frequency of activity	54 uses per year
body weight	65 kg
Uptake fraction dermal	100 %
Uptake fraction oral	100 %
	Amount per use 6 g Relevant for dermal exposure
	estimates
Ingestion rate	0,00133 mg/min
Exposure estimate and reference to	its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant
Assessment method	application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,1065 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,085216
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Oral model: constant
7.00000mont motilod	rate, Uptake model: Uptake fraction
	Consumer - oral, long-term - systemic
Exposure estimate	0,0001 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000021
	The calculation is based on the internal chronic dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC8: Biocidal Products.
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,78 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
body weight	65 kg
	Amount per use 6 g Relevant for dermal exposure estimates
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

	Consumer - dermal, short-term - local
Exposure estimate	0,0027 μg/cm <sup>3</sup>
Risk Characterization Ratio (RCR)	0,011322
	The calculation is based on the external dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC8: Biocidal Products.
Operational conditions	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,78 %
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C
Duration and Frequency of activity	54 uses per year
Duration and Frequency of activity	Exposure duration: 180 min Relevant for oral exposure estimates
Duration and Frequency of activity	54 uses per year
body weight	8,69 kg
Uptake fraction dermal	100 %
Uptake fraction oral	100 %
	Amount per use 1,5 g Relevant for dermal exposure estimates
Ingestion rate	0,00083 mg/min
Exposure estimate and reference to	o its source
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0,1992 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,159352
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Oral model: constant
ASSESSMENT METHOD	rate, Uptake model: Uptake fraction
	Consumer - oral, long-term - systemic
Exposure estimate	0,0001 mg/kg bw/day
Risk Characterization Ratio (RCR)	0,000099
	The calculation is based on the internal chronic dose.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/	/healthanddisease/productsafety/ConsExpo.jsp

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Contributing exposure scenario		
Use descriptors covered	PC8: Biocidal Products.	
Operational conditions		
	Linalyl acetate	
Concentration of the substance	Content: >= 0 % - <= 0,78 %	
Vapour pressure of the substance during use	100 Pa	
Process temperature	20 °C	
body weight	8,69 kg	
	Amount per use 1,5 g Relevant for dermal exposure estimates	
Exposure estimate and reference to	its source	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant	
Assessment method	application	
	Consumer - dermal, short-term - local	
Exposure estimate	0,0024 μg/cm <sup>3</sup>	
Risk Characterization Ratio (RCR)	0,01032	
	The calculation is based on the external dose.	
Guidance to Downstream Users		
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp		

Contributing exposure scenario		
Use descriptors covered	PC8: Biocidal Products.	
Operational conditions	-	
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,78 %	
Vapour pressure of the substance during use	100 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	Exposure duration: 240 min Relevant for inhalative exposure estimates	
Duration and Frequency of activity	90 uses per year	
Room size	58 m3	
Ventilation rate per hour	0,5	
body weight	65 kg	
Uptake fraction dermal	100 %	
Spray duration	19,8 sec	

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Contact rate	269 mg/min	
Release duration	0,33 min	
	Relevant for dermal exposure estimates	
Risk Management Measures		
Consumer Measures	Ensure spraying away from persons.	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction	
	Consumer - dermal, long-term - systemic	
Exposure estimate	0,0026 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,002101	
	The calculation is based on the internal chronic dose.	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:	
Assessment method	Exposure to spray/dust	
	Consumer - inhalation, long-term - systemic	
Exposure estimate	0,0032 mg/m <sup>3</sup>	
Risk Characterization Ratio (RCR)	0,004656	
	The exposure calculation is based on the mean	
	concentration on the day of exposure.	
Guidance to Downstream Users		
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp		

Contributing exposure scenario		
Use descriptors covered	PC8: Biocidal Products.	
Operational conditions		
	Linalyl acetate	
Concentration of the substance	Content: >= 0 % - <= 0,78 %	
Vapour pressure of the substance during use	100 Pa	
Process temperature	20 °C	
body weight	65 kg	
Contact rate	269 mg/min	
Release duration	0,33 min	
	Relevant for dermal exposure estimates	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: constant application rate	
	Consumer - dermal, short-term - local	
Exposure estimate	0,0001 µg/cm <sup>3</sup>	
Risk Characterization Ratio (RCR)	0,000168	
	The calculation is based on the external dose.	
Guidance to Downstream Users		
For scaling see: http://www.rivm.nl/en/	/healthanddisease/productsafety/ConsExpo.jsp	

Page: 126/129

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Contributing exposure scenario		
Use descriptors covered	PC8: Biocidal Products.	
Operational conditions		
Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,78 %	
Vapour pressure of the substance during use	100 Pa	
Process temperature	20 °C	
Duration and Frequency of activity	90 uses per year	
Duration and Frequency of activity	Exposure duration: 60 min Relevant for oral exposure estimates	
Duration and Frequency of activity	90 uses per year	
body weight	8,69 kg	
Uptake fraction dermal	100 %	
Uptake fraction oral	100 %	
Transfer coefficient	1,666667 cm <sup>2</sup> /s	
Dislodgeable amount	0,000082 g/cm <sup>2</sup>	
Contact time	3600 sec	
Rubbed surface	22 m <sup>2</sup>	
Ingestion rate	0,0064 mg/min	
Exposure estimate and reference to	its source	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: rubbing off, Uptake model: Uptake fraction	
	Consumer - dermal, long-term - systemic	
Exposure estimate	0,1089 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,087112	
	The calculation is based on the internal chronic dose.	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Oral model: constant	
<u> </u>	rate, Uptake model: Uptake fraction	
Even and una nation at a	Consumer - oral, long-term - systemic	
Exposure estimate	0,0001 mg/kg bw/day	
Risk Characterization Ratio (RCR)	0,000425	
Cuidones to Dougestresse Heart	The calculation is based on the internal chronic dose.	
Guidance to Downstream Users For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp		
roi scaling see: nttp://www.rivm.nl/en/r	ieaimanuuisease/productsaiety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC8: Biocidal Products.
Operational conditions	

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

Concentration of the substance	Linalyl acetate Content: >= 0 % - <= 0,78 %	
Vapour pressure of the substance during use	100 Pa	
Process temperature	20 °C	
body weight	8,69 kg	
Transfer coefficient	1,666667 cm <sup>2</sup> /s	
Dislodgeable amount	0,000082 g/cm <sup>2</sup>	
Contact time	3600 sec	
Rubbed surface	22 m²	
Exposure estimate and reference to its source		
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: rubbing off	
	Consumer - dermal, short-term - local	
Exposure estimate	0,0008 μg/cm <sup>3</sup>	
Risk Characterization Ratio (RCR)	0,003385	
	The calculation is based on the external dose.	
Guidance to Downstream Users		
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp		

Contributing exposure scenario	
Use descriptors covered	PC8: Biocidal Products. Other products of this category do either not exceed a concentration of 0.1% for this substance or exposure estimations are covered by the calculations made for this product category. In accordance to the Article 14 (2a-f) of the REACh Regulation (EC) No 1907/2006, exposure estimation and risk characterisation needs not to be performed if the substance in a preparation is less than 0.1%.
Operational conditions	
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C

\* \* \* \* \* \* \* \* \* \* \* \* \* \* \* \*

## 9. Short title of exposure scenario

Use in cosmetics, (consumer use) ERC8a; PC28, PC39

to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0
Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: **Linalyl Acetate** 

(ID no. 30034993/SDS\_GEN\_FR/EN)

Date of print 08.10.2025

## Control of exposure and risk management measures

Contributing exposure scenario		
Use descriptors covered	ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)	
Operational conditions		
Annual amount used in the EU	510.000 kg	
Minimum emission days per year	365	
Emission factor air	100 %	
Emission factor water	100 %	
Emission factor soil	0 %	
Receive Surf. Water (Flow Rate).	18.000 m3/d	
Dilution factor river	10	
Dilution factor coast	100	
Risk Management Measures		
Type of STP Municipal STP		
Assumed sewage treatment plant flow	w (m3/d) 2.000 m3/d	
Exposure estimate and reference to		
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment	
Risk Characterization Ratio (RCR)	0,130654	
	Risk from environmental exposure is driven by soil.	
Maximum amount of safe use	2,1 kg/d	
Risk from environmental exposure is driven by soil.		

Contributing exposure scenario	
Use descriptors covered	PC28: Perfumes, Fragrances. In accordance to the Article 14 (5b) of the REACh Regulation (EC) No 1907/2006, exposure estimation and risk characterisation needs not to be performed for end uses in cosmetic products within the scope of Directive EC 1223/2009.
Operational conditions	
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C

Page: 129/129

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 29.08.2022 Version: 1.0 Date previous version: not applicable Previous version: none

Date / First version: 29.08.2022 Product: Linalyl Acetate

(ID no. 30034993/SDS\_GEN\_FR/EN)

Contributing exposure scenario	
Use descriptors covered	PC39: Cosmetics, personal care products. In accordance to the Article 14 (5b) of the REACh Regulation (EC) No 1907/2006, exposure estimation and risk characterisation needs not to be performed for end uses in cosmetic products within the scope of Directive EC 1223/2009.
Operational conditions	
Vapour pressure of the substance during use	100 Pa
Process temperature	20 °C