

Safety data sheet

Page: 1/16

BASF Safety data sheet

Date / Revised: 31.10.2025

Product: **BUTYL ACRYLATE**

Version: 10.0

(30041258/SDS_GEN_VN/EN)

Date of print: 01.11.2025

1. Substance/preparation and manufacturer/supplier identification

Product name:
BUTYL ACRYLATE

Use: Monomer.

Uses advised against: All consumer uses are strongly advised against., Use of substance in adhesives (professional), Use of substance in coatings (professional), Use of substance in inks and toners (professional)

Recommended use: for industrial use only

Not recommended use: cosmetics, Pharmaceutical

Manufacturer/supplier:

BASF Vietnam Co. Ltd.

Level 23, Deutsches Haus, 33 Le Duan,

Sai Gon Ward, Ho Chi Minh City, Vietnam

Telephone: +84 28 3824 3833

Telefax number: +84 28 3824 3832

E-mail address: minh-triet.thieu@basf.com

Emergency information:

18001703 (Vietnam)

Telefax number: +84 28 3824 3832

International emergency number:

Telephone: +49 180 2273-112

2. Hazard identification

Classification of the substance and mixture:

Flammable liquids: Cat.3

Acute toxicity: Cat.4 (Inhalation - vapour)

Acute toxicity: Cat.5 (oral)

| Acute toxicity: Cat.5 (dermal)

BASF Safety data sheet
Date / Revised: 31.10.2025
Product: **BUTYL ACRYLATE**

Version: 10.0

(30041258/SDS_GEN_VN/EN)

Date of print: 01.11.2025

Skin irritation: Cat.2
Eye irritation: Cat.2A
Skin sensitization: Cat.1B
Specific target organ toxicity — single exposure: Cat.3 (irritating to respiratory system)
Hazardous to the aquatic environment - acute: Cat.2
Hazardous to the aquatic environment - chronic: Cat.3

Label elements and precautionary statement:

Pictogram:



Signal Word:

Warning

Hazard Statement:

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H303	May be harmful if swallowed.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.
H401	Toxic to aquatic life.
H313	May be harmful in contact with skin.

Precautionary Statements (Prevention):

P280	Wear protective gloves and eye protection or face protection.
P271	Use only outdoors or in a well-ventilated area.
P260	Do not breathe mist or vapour.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273	Avoid release to the environment.
P243	Take action to prevent static discharges.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P272	Contaminated work clothing should not be allowed out of the workplace.
P264	Wash contaminated body parts thoroughly after handling.
P242	Use non-sparking tools.
P240	Ground and bond container and receiving equipment.

Precautionary Statements (Response):

BASF Safety data sheet
Date / Revised: 31.10.2025
Product: **BUTYL ACRYLATE**

Version: 10.0

(30041258/SDS_GEN_VN/EN)

Date of print: 01.11.2025

P312	Call a POISON CENTER or physician if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P333 + P313	If skin irritation or rash occurs: Get medical attention.
P301 + P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P302 + P312	IF ON SKIN: Call a POISON CENTER or a doctor/physician if you feel unwell.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P332 + P313	If skin irritation occurs: Get medical attention.
P337 + P313	If eye irritation persists: Get medical attention.
P370 + P378	In case of fire: Use water spray, dry powder, foam or carbon dioxide for extinction.

Precautionary Statements (Storage):

P403 + P235	Store in a well-ventilated place. Keep cool.
P233	Keep container tightly closed.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

Other hazards which do not result in classification:

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition/information on ingredients

Chemical nature

Substance nature: Substance

n-butyl acrylate

CAS Number: 141-32-2

Hazardous ingredients

BASF Safety data sheet
Date / Revised: 31.10.2025
Product: **BUTYL ACRYLATE**

Version: 10.0

(30041258/SDS_GEN_VN/EN)

Date of print: 01.11.2025

n-butyl acrylate

Content (W/W): $\geq 99.5\%$ - $\leq 100\%$
CAS Number: 141-32-2

Flam. Liq.: Cat. 3
Acute Tox.: Cat. 4 (Inhalation - vapour)
Acute Tox.: Cat. 5 (oral)
Acute Tox.: Cat. 5 (dermal)
Skin Irrit.: Cat. 2
Eye Irrit.: Cat. 2A
Skin Sens.: Cat. 1B
STOT SE: Cat. 3 (irr. to respiratory syst.)
Aquatic Acute: Cat. 2
Aquatic Chronic: Cat. 3

4. First-Aid Measures

General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

Wash thoroughly with soap and water

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Note to physician:

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Hazards: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. (Further) symptoms and / or effects are not known so far

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Suitable extinguishing media:

dry powder, water spray, carbon dioxide, foam

Unsuitable extinguishing media for safety reasons:

water jet

BASF Safety data sheet
Date / Revised: 31.10.2025
Product: **BUTYL ACRYLATE**

Version: 10.0

(30041258/SDS_GEN_VN/EN)

Date of print: 01.11.2025

Additional information:

Use extinguishing measures to suit surroundings.

Specific hazards:

Risk of violent self-polymerization if overheated in a container. Cool endangered containers with water-spray.

The product is combustible. See SDS section 7 - Handling and storage.

Special protective equipment:

Wear a self-contained breathing apparatus. Special protective equipment for firefighters

Further information:

Extend fire extinguishing measures to the surroundings. Fight fire from maximum distance. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

Further information:

In case of a fire in the vicinity a restabilization system should be used if the temperature in the bulk storage-tank reaches 45°C. Evacuate area of all unnecessary personnel. In case of a fire in the vicinity evacuate all personnel in a greater area if the temperature in the bulk storage-tank reaches 60°C.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental Release Measures

Personal precautions:

Handle in accordance with good industrial hygiene and safety practice.

Avoid all sources of ignition: heat, sparks, open flame. Use antistatic tools.

Environmental precautions:

Discharge into the environment must be avoided.

Methods for cleaning up or taking up:

For large amounts: Pump off product.

Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations. Ensure adequate ventilation. Suppress gases/vapours/mists with water spray jet. Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Cleaning operations should be carried out only while wearing breathing apparatus. Pick up with suitable appliance and dispose of.

Additional information: High risk of slipping due to leakage/spillage of product.

Release of substance/product can cause fire or explosion. Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

7. Handling and Storage

Handling

The substance/ product may be handled only by appropriately trained personnel. Facility parts must be checked for polymer residues and cleaned on regular basis in order to avoid hazardous reactions.

Ensure thorough ventilation of stores and work areas. Encapsulation or exhaust ventilation required. When filling, transferring, or emptying of containers, adequate local exhaust ventilation is necessary. Vent waste air to atmosphere only through suitable separators. Check the condition of seals and connector screw threads.

The temperatures which must be avoided are to be considered. Protect against heat. Protect from direct sunlight. Protect contents from the effects of light. Do not open warm or swollen product containers. Remove persons to safety and alert fire brigade.

Ensure adequate inhibitor and dissolved oxygen level.

Avoid inhalation of dusts/mists/vapours. Avoid aerosol formation. Avoid all direct contact with the substance/product.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Substance/product can form explosive mixture with air. Ground all transfer equipment properly to prevent electrostatic discharge. It is recommended that all conductive parts of the machinery are grounded. Explosion-proof equipment is not necessary when loading and processing of the product takes place at a minimum of 5 °C below the flash point.

Heated containers should be cooled to prevent polymerization. If exposed to fire, keep containers cool by spraying with water. Emergency cooling must be provided for the eventuality of a fire in the vicinity.

Storage

Further information on storage conditions: Prior to storage ensure that the transfer equipment used and the intended storage containers do not contain other substances/products. Before transfer to stock the identity of the product must be proved to be without doubt. The entrance to storage rooms is to be granted only to appropriately trained personnel.

The stabilizer is only effective in the presence of oxygen. Maintain contact with atmosphere containing 5 - 21% oxygen. Never use tanks with inert-gas installation for storage.

Risk of polymerization. Protect against heat. Protect from direct sunlight. Avoid UV-light and other radiation with high energy. Protect against contamination.

In case of bulk storage, the storage-tanks should at least be equipped with two high temperature alert devices.

Even if the product is stored and handled as prescribed/indicated it should be used up within the indicated duration of storage.

Storage stability:

Storage temperature: < 35 °C

Storage duration: 12 Months

The stated storage temperature should be noted.

Avoid prolonged storage.

This product should be processed as soon as possible.

Ensure adequate inhibitor and dissolved oxygen level.

BASF Safety data sheet
Date / Revised: 31.10.2025
Product: **BUTYL ACRYLATE**

Version: 10.0

(30041258/SDS_GEN_VN/EN)

Date of print: 01.11.2025

Do not store with less than 10 % headspace above liquid.
Storage stability is based upon ambient temperatures and conditions described.
It is recommended to keep a safe distance of +2 degrees above the crystallization range.
The product is stabilized, the shelf life should be noted.
Storage temperature: 45 °C
A restabilization system should be used if the temperature in the bulk storage-tank reaches the indicated value.
Storage temperature: 60 °C
All personnel in a greater area should be evacuated if the temperature in the bulk storage-tank reaches the indicated value.

8. Exposure controls and personal protection

Components with occupational exposure limits

n-butyl acrylate, 141-32-2;
TWA value 2 ppm (ACGIHTLV)

Engineering Controls

Advice on system design:
Ensure adequate ventilation.

Personal protective equipment

Respiratory protection:

Suitable respiratory protection for lower concentrations or short-term effect: Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

butyl rubber (butyl) - 0.7 mm coating thickness

nitrile rubber (NBR) - 0.4 mm coating thickness

Manufacturer's directions for use should be observed because of great diversity of types.

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures:

Avoid contact with the skin, eyes and clothing. Avoid inhalation of vapour. Wearing of closed work clothing is required additionally to the stated personal protection equipment.

BASF Safety data sheet
Date / Revised: 31.10.2025
Product: **BUTYL ACRYLATE**

Version: 10.0

(30041258/SDS_GEN_VN/EN)

Date of print: 01.11.2025

9. Physical and Chemical Properties

Form:	liquid	
Colour:	colourless	
Odour:	acrylic-like	
Odour threshold:	not determined	
pH value:	not applicable	
Melting point:	-64.6 °C Literature data. The substance / product does not decompose.	
Boiling point:	147 °C (1,013 hPa)	
Flash point:	38 °C	(DIN 51755, closed cup)
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.	
Flammability (solid/gas):	Flammable liquid and vapour.	(derived from flash point)
Lower explosion limit:	For liquids not relevant for classification and labelling., The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Ignition temperature:	275 °C	(DIN 51794)
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Self ignition:	Based on its structural properties the product is not classified as self-igniting.	Test type: Spontaneous self-ignition at room-temperature.
Self heating ability:	not applicable, the product is a liquid	
SADT:	Not a substance/mixture liable to self-decomposition according to GHS.	
Explosion hazard:	Based on the chemical structure there is no indication of explosive properties.	
Fire promoting properties:	Based on its structural properties the product is not classified as oxidizing.	

BASF Safety data sheet
 Date / Revised: 31.10.2025
 Product: **BUTYL ACRYLATE**

Version: 10.0

(30041258/SDS_GEN_VN/EN)

Date of print: 01.11.2025

Vapour pressure:	5 hPa (22.2 °C)	
Density:	0.899 g/cm ³ (20 °C) 0.8689 g/cm ³ (50 °C) 0.8639 g/cm ³ (55 °C)	(calculated)
Relative density:	0.9 (20 °C)	
Relative vapour density (air):	4.41 (20 °C) Heavier than air.	(calculated)
Solubility in water:	1.7 g/l (20 °C)	
Solubility (qualitative) solvent(s):	organic solvents miscible	
Partitioning coefficient n-octanol/water (log Pow):	2.38 (25 °C)	(measured)
Adsorption/water - soil:	KOC: 88.4; log KOC: 1.95 Adsorption to solid soil phase is not expected.	(OECD Guideline 106)
Surface tension:	Based on chemical structure, surface activity is not to be expected.	
Viscosity, dynamic:	0.88 mPa.s (20 °C) 0.66 mPa.s (40 °C)	
Viscosity, kinematic:	(20 °C) not determined	
Molar mass:	128.17 g/mol	

Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular form. -

10. Stability and Reactivity

Conditions to avoid:

Avoid heat. Avoid oxygen content above the product of less than 5 %. Avoid UV-light and other radiation with high energy. Avoid direct sunlight. Avoid prolonged storage. Avoid inhibitor loss. Avoid excessive temperatures. Avoid all sources of ignition: heat, sparks, open flame. Avoid freezing. Avoid moisture.

BASF Safety data sheet
Date / Revised: 31.10.2025
Product: **BUTYL ACRYLATE**

Version: 10.0

(30041258/SDS_GEN_VN/EN)

Date of print: 01.11.2025

Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

Substances to avoid:

radical formers, free radical initiators, peroxides, mercaptans, nitro-compounds, perborates, azides, ether, ketones, aldehydes, amines, nitrates, nitrites, oxidizing agents, reducing agents, strong bases, alkaline reactive substances, acid anhydrides, acid chlorides, concentrated mineral acids, metal salts
Inert gas

Corrosion to metals: No corrosive effect on metal.

Hazardous reactions:

Explosion and fire hazard exists under confined conditions. Ignitable air mixtures can form when the product is heated above the flash point and/or when sprayed or atomized. Formation of explosive gas/air mixtures.

Polymerization coupled with heat formation.

Risk of spontaneous polymerization by oxygen depletion of the liquid phase. Risk of spontaneous polymerization when heated or in the presence of UV radiation. Risk of spontaneous and violent self-polymerization if inhibitor is lost or product is exposed to excessive heat. Polymerization produces gases which may burst closed or confined containers. Reactions may cause ignition.

Risk of spontaneous polymerization in the presence of starters for radical chain reactions (e.g. peroxides). Reacts with nitric acid. Risk of spontaneous polymerization in the presence of oxidizing agents.

Hazardous reactions in presence of mentioned substances to avoid.

The product is stabilized against spontaneous polymerization prior to despatch. The product is stable if stored and handled as prescribed/indicated.

Hazardous decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Chemical stability:

The product is stable if stored and handled as prescribed/indicated.

Reactivity:

No hazardous reactions if stored and handled as prescribed/indicated.

11. Toxicological Information

Routes of exposure

Acute oral toxicity

Experimental/calculated data:

LD50rat (oral): 3,150 mg/kg (BASF-Test)

Acute inhalation toxicity

LC50 rat (by inhalation): 10.3 mg/l 4 h (OECD Guideline 403)

The vapour was tested.

Acute dermal toxicity

LD50 rabbit (dermal): 2,000 - 3,024 mg/kg (other)

Assessment of acute toxicity

Of moderate toxicity after short-term inhalation. Of low toxicity after single ingestion. Of low toxicity after short-term skin contact.

Symptoms

Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Irritation

Assessment of irritating effects:

Eye contact causes irritation. Skin contact causes irritation.

Experimental/calculated data:

Skin corrosion/irritation rabbit: Irritant. (BASF-Test)

Serious eye damage/irritation rabbit: Irritant. (other)

Respiratory/Skin sensitization

Assessment of sensitization:

Sensitization after skin contact possible.

Experimental/calculated data:

Mouse Local Lymph Node Assay (LLNA) mouse: skin sensitizing (OECD Guideline 429)

Germ cell mutagenicity

Assessment of mutagenicity:

The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture. The substance was not mutagenic in a test with mammals. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Carcinogenicity

Assessment of carcinogenicity:

In long-term animal studies in which the substance was given by inhalation, a carcinogenic effect was not observed. The substance showed no carcinogenic activity in animals after chronic administration to the skin. IARC Group 3 (not classifiable as to human carcinogenicity).

Reproductive toxicity

Assessment of reproduction toxicity:

The results of animal studies gave no indication of a fertility impairing effect.

Developmental toxicity

Assessment of teratogenicity:

No indications of a developmental toxic / teratogenic effect were seen in animal studies.

Specific target organ toxicity (single exposure)

Causes temporary irritation of the respiratory tract.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

After repeated exposure the prominent effect is local irritation. The substance may cause damage to the olfactory epithelium after repeated inhalation.

Aspiration hazard

not applicable

12. Ecological Information

Ecotoxicity

Toxicity to fish:

LC50 (96 h) 2.1 mg/l, *Cyprinodon variegatus* (OECD Guideline 203, Flow through.)

The statement of the toxic effect relates to the analytically determined concentration.

Aquatic invertebrates:

EC50 (48 h) 8.2 mg/l, *Daphnia magna* (OECD Guideline 202, part 1, Flow through.)

The statement of the toxic effect relates to the analytically determined concentration.

Aquatic plants:

EC50 (96 h) 2.65 mg/l, *Selenastrum capricornutum* (OECD Guideline 201, static)

The statement of the toxic effect relates to the analytically determined concentration.

Microorganisms/Effect on activated sludge:

EC0 (3 d) > 150 mg/l, activated sludge, industrial (other, aerobic)

Nominal concentration.

Chronic toxicity to fish:

No data available.

Chronic toxicity to aquatic invertebrates:

No observed effect concentration (21 d), 0.136 mg/l, *Daphnia magna* (OECD Guideline 211, semistatic)

The statement of the toxic effect relates to the analytically determined concentration.

Assessment of terrestrial toxicity:

No effects at the highest test concentration.

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Soil living organisms:

EC50 (28 d) > 1,000 mg/kg, soil dwelling microorganisms (OECD Guideline 217)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The details of the toxic effect relate to the nominal concentration.

Terrestrial plants:

No data available.

Other terrestrial non-mammals:
No data available.

Mobility

Assessment transport between environmental compartments:
The substance will not evaporate into the atmosphere from the water surface.
Adsorption to solid soil phase is not expected.

Persistence and degradability

Elimination information:
80 - 90 % TIC of the ThIC (28 d) (ISO 14593) (aerobic, activated sludge, domestic)

Assessment of stability in water:
In contact with water the substance will hydrolyse slowly.

Information on Stability in Water (Hydrolysis):
 $t_{1/2}$ 1,100 d (25 °C, pH value 7), (OECD Guideline 111, pH 7)
In contact with water the substance will hydrolyse slowly.

Bioaccumulation potential

Assessment bioaccumulation potential:
Accumulation in organisms is not to be expected.

Bioaccumulation potential:
Bioconcentration factor: 17.3 (calculated)
Accumulation in organisms is not to be expected.

Additional information

Other ecotoxicological advice:
Do not release untreated into natural waters. Acutely toxic for aquatic organisms.

13. Disposal Considerations

Information on disposal regulations: Must comply with regulations on hazardous waste such as:

- Decree No. 08/2022/ND-CP of the Government: detailing a number of articles of the Law on Environmental Protection.

- Circular No. 02/2022/TT-BTNMT of the Ministry of Natural Resources and Environment: detailing a number of articles of the Law on Environmental Protection.

Must be sent to a suitable incineration plant, observing local regulations.

Contaminated packaging:
Uncleaned empties should be disposed of in the same manner as the contents.

BASF Safety data sheet
Date / Revised: 31.10.2025
Product: **BUTYL ACRYLATE**

Version: 10.0

(30041258/SDS_GEN_VN/EN)

Date of print: 01.11.2025

14. Transport Information

Domestic transport:

UN number or ID number: UN 2348
UN proper shipping name: BUTYL ACRYLATES, STABILIZED
Transport hazard class(es): 3
Packing group: III
Environmental hazards: no

Special precautions for user: None known

Sea transport

IMDG

UN number or ID number: UN 2348
UN proper shipping name: BUTYL ACRYLATES, STABILIZED
Transport hazard class(es): 3
Packing group: III
Environmental hazards: no

Marine pollutant: NO
Special precautions for user: EmS: F-E; S-D

Air transport

IATA/ICAO

UN number or ID number: UN 2348
UN proper shipping name: BUTYL ACRYLATES, STABILIZED
Transport hazard class(es): 3
Packing group: III
Environmental hazards: No Mark as dangerous for the environment is needed
Special precautions for user: None known

Maritime transport in bulk according to IMO instruments

Regulation: IBC-Code

Product name: Butyl acrylate (all isomers)
Pollution category: Y
Ship Type: 3

15. Regulatory Information

Other regulations

Legal information on safety, health and environment for chemicals:

Law on Chemicals No. 06/2007/QH12

Chemical Safety Sheets (SDS) are compiled in accordance with international regulations on chemical classification and labelling (GHS) as well as relevant applicable legal regulations:

- QCVN 05A:2020/BCT National Technical Regulation on safety in production, trading, use, preservation and transportation of hazardous chemicals.
- Amendment 1:2024 QCVN 05A:2020/BCT National technical regulation on safety in production, trading, use, preservation and transportation of hazardous chemicals.
- Decree No. 113/2017/ND-CP dated 09/10/2017 of the Government detailing and guiding the implementation of a number of articles of the Law on Chemicals;
- Circular No. 32/2017/TT-BCT dated 28/12/2017 of the Ministry of Industry and Trade specifying and guiding the implementation of a number of articles of the Law on Chemicals and Decree No. 113/2017/ND-CP dated 09/10/2017 of the Government detailing and guiding the implementation of a number of articles of the Law on Chemicals;
- Decree No. 82/2022/ND-CP dated October 18, 2022 of the Government amending and supplementing a number of articles of the Government's Decree No. 113/2017/ND-CP dated October 09, 2017 detailing and guiding the implementation of a number of articles of the Law on Chemicals
- Circular No. 17/2022/TT-BCT dated October 27, 2022 of the Ministry of Industry and Trade amending and supplementing a number of articles of Circular No. 32/2017/TT-BCT dated December 28, 2017 of the Minister of Industry and Trade specifying and guiding the implementation of a number of articles of the Law on Chemicals and the Government's Decree No. 113/2017/ND-CP dated October 09, 2017 detailing and guiding the exam a number of articles of the Law on Chemicals
- Decree No. 161/2024 ND-CP dated December 18, 2024 of the Government regulating the list of dangerous goods, transportation of dangerous goods and the order and procedures for issuance of licenses and certificates of completion of training programs for drivers or escorts transporting dangerous goods on roads;
- Decree 34/2024/ND-CP dated 31/03/2024 regulating the list of dangerous goods, transporting dangerous goods by road motor vehicles and inland waterway vehicles
- Circular No. 37/2020/TT-BCT dated 30/11/2020 of the Ministry of Industry and Trade stipulating the list of dangerous goods that must be packed in the process of transporting and transporting dangerous goods by road, railway and inland waterway motor vehicles.
- Decree No. 71/2019/ND-CP dated August 30, 2019 of the Government stipulating the sanctioning of administrative violations in the field of chemicals and industrial explosives.

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

16. Other Information

Safe Handling and Storage aspects are covered in a brochure which is available on request.

BASF Safety data sheet
Date / Revised: 31.10.2025
Product: **BUTYL ACRYLATE**

Version: 10.0

(30041258/SDS_GEN_VN/EN)

Date of print: 01.11.2025

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.