

Safety Data Sheet Styrofan® D 623

Revision date : 2018/10/15 Page: 1/9

Version: 2.0 (30743868/SDS_GEN_MX/EN)

1. Identification

Product identifier used on the label

Styrofan® D 623

Recommended use of the chemical and restriction on use

Recommended use*: Raw material, for industrial use only

Recommended use*: Raw material

Suitable for use in industrial sector: chemical industry

Details of the supplier of the safety data sheet

Company:

BASF Mexicana S.A. de C.V. Av. Insurgentes Sur 975 Col. CD. De Los Deportes, C.P. 03710 Ciudad de México MÉXICO

Telephone: +52 55 5325 2600

Emergency telephone number

SETIQ: 1800-00-214-(Rep. Mexicana) or 55-59-15-88 (CDMX)

Telephone: +1-800-849-5204 or +1-833-229-1000

Other means of identification

Chemical family: Polymer, dispersion

2. Hazards Identification

According to Regulation NOM-018-STPS-2015

Classification of the product

No need for classification according to GHS criteria for this product.

Label elements

^{*} The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Styrofan® D 623

Revision date: 2018/10/15 Page: 2/9
Version: 2.0 (30743868/SDS GEN MX/EN)

Version: 2.0 (30/43868/5D5_GEN_WX/EN_x

The product does not require a hazard warning label in accordance with GHS criteria.

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered. If the product adheres to skin, irritation may occur when it dries.

Labeling of special preparations (GHS):

This product is capable of releasing formaldehyde into the air. May cause cancer.

3. Composition / Information on Ingredients

According to Regulation NOM-018-STPS-2015

CAS NumberWeight %Chemical name50-00-00.0 - < 0.05%</td>Formaldehyde

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

If on skin:

Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

If in eyes:

Flush with copious amounts of water for at least 15 minutes. If irritation develops, seek medical attention.

If swallowed:

Immediately rinse mouth and then drink plenty of water, do not induce vomiting, seek medical attention. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions.

Most important symptoms and effects, both acute and delayed

Symptoms: No significant symptoms are expected due to the non-classification of the product. Hazards: No hazards anticipated.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Symptomatic treatment (decontamination, vital functions).

Styrofan® D 623

Revision date: 2018/10/15 Page: 3/9
Version: 2.0 (30743868/SDS GEN MX/EN)

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media: water spray, foam, dry powder

Special hazards arising from the substance or mixture

Hazards during fire-fighting: No particular hazards known.

Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Product itself is non-combustible; fire extinguishing method of surrounding areas must be considered.

6. Accidental release measures

Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Avoid contact with skin and eyes.

Environmental precautions

Do not release untreated into natural waters.

Methods and material for containment and cleaning up

Spills should be contained, solidified, and placed in suitable containers for disposal.

For small amounts: Pick up with absorbent material (e.g. sand, sawdust, general-purpose binder).

Dispose of absorbed material in accordance with regulations.

For large amounts: Pump off product.

7. Handling and Storage

Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. No special measures necessary provided product is used correctly. Ensure adequate ventilation.

Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Store protected against freezing.

Protect from temperatures below: 5 °C Protect from temperatures above: 60 °C

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Styrofan® D 623

Revision date : 2018/10/15 Page: 4/9
Version: 2.0 (30743868/SDS_GEN_MX/EN)

The release and quantity of the stated substance is dependent on the processing conditions.

Formaldehyde Exposure CLV 0.3 ppm ;

limits

Advice on system design:

Ensure adequate ventilation.

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.

General safety and hygiene measures:

Hands and/or face should be washed before breaks and at the end of the shift. Avoid contact with skin and eyes.

9. Physical and Chemical Properties

Form: liquid, dispersion
Odour: faintly aromatic
Odour threshold: not determined

Colour: white

pH value: 7.8 - 10.0 (DIN ISO 976)

Information on: Water

Melting point: 0 °C

Information on: Water

Boiling point: 100 °C

Flash point: > 300 °F

Flammability: not flammable

Lower explosion limit: For liquids not relevant for

classification and labelling.

(Unspecified)

Upper explosion limit: For liquids not relevant for

classification and labelling.

Autoignition: not applicable

Information on: Water

Vapour pressure: 23.4 hPa (20 °C)

Literature data.

Density: approx. 1.02 g/cm3 (ISO 2811-1)

(20 °C)

Relative density:
Vapour density:

Partitioning coefficient n
No data available.

not applicable

octanol/water (log Pow):

Self-ignition not self-igniting

temperature:

Styrofan® D 623

Revision date : 2018/10/15 Page: 5/9
Version: 2.0 (30743868/SDS_GEN_MX/EN)

Viscosity, dynamic: 35 - 150 mPa.s (DIN EN ISO 3219)

(23°C)

Solids content: 50 - 52 % (DIN EN ISO 3251)

Solubility in water: (15 °C)

partly soluble

Miscibility with water: miscible

Other Information: Range of particle size: $< 0.1 \mu m - 10 \mu m$

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

Corrosive effects to metal are not anticipated.

Oxidizing properties: not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions. After long storage, slight quantities of carbon monoxide may be formed.

The product is chemically stable.

Conditions to avoid

Avoid extreme heat.

Incompatible materials

metal salts

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: carbon dioxide, carbon monoxide, hydrocarbons

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Oral

Type of value: LD50

Species: rat

Styrofan® D 623

Revision date: 2018/10/15 Page: 6/9
Version: 2.0 (30743868/SDS GEN MX/EN)

Value: > 2,000 - 10,000 mg/kg

Assessment other acute effects

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Irritation / corrosion

Assessment of irritating effects: If the product adheres to skin, irritation may occur when it dries. Not irritating to the eyes. Not irritating to the skin. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

<u>Skin</u>

Species: rabbit Result: non-irritant

Method: OECD Guideline 404

Eye

Species: rabbit Result: non-irritant

Method: OECD Guideline 405

Sensitization

Assessment of sensitization: Skin sensitizing effects were not observed in animal studies. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aspiration Hazard not applicable

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: No adverse effects were observed after repeated inhalative exposure in animal studies. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Genetic toxicity

Assessment of mutagenicity: The substance was not mutagenic in bacteria. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Carcinogenicity

Assessment of carcinogenicity: None of the components in this product at concentrations greater than 0.1% are listed by IARC; NTP, OSHA or ACGIH as a carcinogen.

Information on: Formaldehyde

Assessment of carcinogenicity: NTP listed carcinogen The International Agency for Research on Cancer (IARC) has classified formaldehyde as a Group 1 (known) human carcinogen based on epidemiological evidence linking formaldehyde exposure to occurrence of nasopharyngeal cancer and leukemia. Current regulatory information is provided in this MSDS. No adverse health effects are anticipated if recommended personal protective equipment and industrial hygiene practices are used.

Reproductive toxicity

Styrofan® D 623

Revision date: 2018/10/15 Page: 7/9
Version: 2.0 (30743868/SDS GEN MX/EN)

Assessment of reproduction toxicity: Not expected to cause reproductive toxicity (based on composition).

Teratogenicity

Assessment of teratogenicity: The data available for an assessment of the effect of the substance on developmental toxicity are not sufficient for a proper evaluation.

Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The statement was derived from products of similar composition.

Symptoms of Exposure

No significant symptoms are expected due to the non-classification of the product.

12. Ecological Information

Toxicity

Toxicity to fish

LC50 (96 h) > 100 mg/l, Brachydanio rerio (OECD Guideline 203, static)

Aquatic invertebrates

EC50 (48 h) > 100 mg/l, Daphnia magna (OECD Guideline 202, part 1, static)

Aquatic plants

EC50 (72 h) > 100 mg/l, Scenedesmus subspicatus (OECD Guideline 201) Nominal concentration.

Microorganisms/Effect on activated sludge

Toxicity to microorganisms

DIN EN ISO 8192-OECD 209-88/302/EEC,P. C activated sludge, domestic/EC20 (0.5 h): > 100 mg/l

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Persistence and degradability

Assessment biodegradation and elimination (H2O)

The product can be virtually eliminated from water by abiotic processes e.g. adsorption onto activated sludge.

Elimination information

Not readily biodegradable.

Bioaccumulative potential

Bioaccumulation potential

Based on its structural properties, the polymer is not biologically available. Accumulation in organisms is not to be expected.

Mobility in soil

Styrofan® D 623

Revision date : 2018/10/15 Page: 8/9
Version: 2.0 (30743868/SDS_GEN_MX/EN)

Assessment transport between environmental compartments

No data available.

Additional information

Adsorbable organically-bound halogen (AOX):

No data available.

Other ecotoxicological advice:

Do not release untreated into natural waters. At the present state of knowledge, no negative ecological effects are expected.

Ecological data are determined by analogy.

13. Disposal considerations

Waste disposal of substance:

Must be sent to a suitable incineration plant, observing local regulations. Incinerate or dispose of in a licensed facility. Do not discharge into drains/surface waters/groundwater.

Container disposal:

Dispose of in a licensed facility. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

14. Transport Information

Land transport

TDG

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Not applicable

NFPA Hazard codes:

Health: 1 Fire: 0 Reactivity: 0 Special:

Safety Data Sheet Styrofan® D 623

Revision date: 2018/10/15 Page: 9/9
Version: 2.0 (30743868/SDS GEN MX/EN)

16. Other Information

SDS Prepared by:

BASF NA Product Regulations SDS Prepared on: 2018/10/15

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Styrofan® D 623 is a registered trademark of BASF Mexicana or BASF SE

This information is considered accurate but is not exhaustive and shall only be used as a guideline based on current knowledge of the chemical substance or mixture. Safety precautions suitable for the product must be applied.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. **END OF DATA SHEET**