

# Tinuvin® 329

**Product Description** 

Tinuvin 329 is a UV absorber of the hydroxyphenyl-benzotriazole class used as a light stabilizer for plastics and other organic substrates.

Key Features & Benefits

- Hydroxyphenyl-benzotriazole UVA with excellent spectral coverage in the UV region
- Good photopermanence
- Improves exterior durability of ambient and low temperature cured coatings

**Chemical Structure** 

2phenol, 2-(2H-benzotriazol-2-yl)-4-(1,1,3,3,-tetramethylbutyl)

#### **Properties**

**Typical Properties** 

| Appearance             |       | slightly yellow powder |
|------------------------|-------|------------------------|
| CAS No:                |       | 3147 – 75 – 9          |
| Molecular weight       | g/mol | 329                    |
| Melting range          | °C    | 103 – 105              |
| Flash point            | °C    | > 150                  |
| Density at 20°C        | g/ml  | 1.18                   |
| Vapor pressure at 25°C | Pa    | 1 E-5                  |

Solubility at 20°C (g/100 g solution):


| acetone       | 9      |
|---------------|--------|
| benzene       | 32     |
| chloroform    | 37     |
| cyclohexane   | 15     |
| ethyl acetate | 15     |
| n-hexane      | 6      |
| methanol      | 0.6    |
| water         | < 0.01 |

Volatility (TGA, air at 20°C/min)

| Temperature at 1.0% weight loss | °C | 180 |
|---------------------------------|----|-----|
| Temperature at 2.0% weight loss | °C | 200 |
| Temperature at 5.0% weight loss | °C | 220 |

These typical values should not be interpreted as specifications.

# Absorbance Spectrum (in 10 mg/l chloroform)



Tinuvin 329 exhibits strong absorbance in the 300 – 400 nm region and minimal absorbance in the visible region (> 400 nm) of the spectrum. The absorption maxima are at 301 nm and 343 nm ( $\epsilon$  = 15910 l/mol·cm) in chloroform solution.

## **Applications**

Tinuvin 329 is an effective light stabilizer for a variety of plastics, adhesives and other organic substrates. It protects polymers from UV energy, helping to preserve the original appearance and physical integrity of molded articles, films, sheets and fibers from outdoor weathering.

#### **Processing**

Tinuvin 329 can be used alone or in combination with other additives such as hindered amine light stabilizers (HALS), antioxidants (hindered phenols, phosphites, thiosynergists, hydroxylamines) and other functional stabilizers and additives.

The use of Tinuvin 329 in combination with HALS is particularly noteworthy in that a synergistic performance is often observed.

The amount of Tinuvin 329 required for optimum performance should be determined in laboratory trials covering a concentration range.

# **Recommend Concentrations**

Typical use levels range between 1.0 and 3.0%, depending on the substrate and performance requirements of the final applications.

### Safety

#### General

The usual safety precautions when handling chemicals must be observed. These include the measure described in Federal, State and Local health and safety regulations, thorough ventilation of the workplace, good skin care, and wearing of protective goggles.

#### Safety Data Sheet

All safety information is provided in the Safety Data Sheet for Tinuvin 329.

#### **Storage**

Please refer to the "Handling and Storage of Polymer Dispersions" brochure.

### **Important**

WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, THEY ARE PROVIDED FOR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, BASF RECOMMENDS THAT THE READER MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR A PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESCRIPTIONS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF BASE'S TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTIONS, DESIGNS, DATA OR INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT THE READER'S RISK.

Tinuvin is a registered trademark of BASF Group.

© BASF Corporation, 2022



BASF Corporation is fully committed to the Responsible Care® initiative in the USA, Canada, and Mexico.
For more information on Responsible Care® go to:
U.S.: www.basf.us/responsiblecare\_usa
Canada: www.basf.us/responsiblecare\_canada
México: www.basf.us/responsiblecare\_mexico

#### **BASF Corporation**

Dispersions and Resins 11501 Steele Creek Road Charlotte, North Carolina 28273 Phone: (800) 251 – 0612 Email: CustCare-Charlotte@basf.com www.basf.us/dpsolutions

October 2022 Rev 4 page 3 of 3