

# Safety data sheet

Page: 1/167

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

## Ammonium chloride RWS food grade

UFI: 9M2Q-30MK-R00E-J01E

The substance/mixture contains nanoforms.

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: food additive(s)

Recommended use: Raw material, auxiliary, inorganic salts, flavours

For the detailed identified uses of the product see appendix of the safety data sheet.

### 1.3. Details of the supplier of the safety data sheet

Company:

BASF SE  
67056 Ludwigshafen  
GERMANY

Contact address:

BASF Hellas S.A.  
Sindos Industrial Area  
57022 Sindos  
GREECE

Telephone: +30 2310 797-195

E-mail address: gr-psr-hellas@basf.com

### 1.4. Emergency telephone number

Greek Poison Information Centre

0030 210 7793777 (24 hours / 7 days)

International emergency number:

Telephone: +49 180 2273-112

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

## SECTION 2: Hazards Identification

### 2.1. Classification of the substance or mixture

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

According to Regulation (EC) No 1272/2008 [CLP]

Acute Tox. 4 (oral)

H302 Harmful if swallowed.

Eye Irrit. 2

H319 Causes serious eye irritation.

For the classifications not written out in full in this section the full text can be found in section 16.

### 2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

Pictogram:



Signal Word:

Warning

Hazard Statement:

H319

Causes serious eye irritation.

H302

Harmful if swallowed.

Precautionary Statements (Prevention):

P280

Wear eye and face protection.

P270

Do not eat, drink or smoke when using this product.

P264

Wash contaminated skin thoroughly with plenty of water and soap after handling.

Precautionary Statements (Response):

P301 + P312

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P330

Rinse mouth.

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313

If eye irritation persists: Get medical attention.

Precautionary Statements (Disposal):

P501

Dispose of contents and container to hazardous or special waste collection point.

Hazard determining component(s) for labelling: ammonium chloride

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

## 2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

No specific dangers known, if the regulations/notes for storage and handling are considered.

The product does not contain a substance above legal limits fulfilling the PBT

(persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

## SECTION 3: Composition/Information on Ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Chemical nature

ammonium chloride

Contains:formulation auxiliary, anticaking agent

Regulatory relevant ingredients

ammonium chloride

Content (W/W):  $\geq 75\%$  -  $\leq 100\%$  Acute Tox. 4 (oral)

% Eye Irrit. 2

CAS Number: 12125-02-9 H319, H302

EC-Number: 235-186-4

REACH registration number: 01-2119487950-27, 01-2119489385-24

INDEX-Number: 017-014-00-8

Pentacalcium hydroxide tris(orthophosphate)

Content (W/W):  $\geq 0\%$  -  $\leq 0,7\%$

CAS Number: 12167-74-7

EC-Number: 235-330-6

Particle characteristics of nanoform:

Particle size distribution: 9,94  $\mu\text{m}$  (D90, Volumetric Distribution)

4,77  $\mu\text{m}$  (D50, Volumetric Distribution)

2,06  $\mu\text{m}$  (D10, Volumetric Distribution)

Specific Surface Area:  $> 60\text{ m}^2/\text{cm}^3$  (VSSA)

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

---

## SECTION 4: First-Aid Measures

### 4.1. Description of first aid measures

Remove contaminated clothing.

If inhaled:

After inhalation of decomposition products: Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

Wash thoroughly with soap and water

On contact with eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

## SECTION 5: Fire-Fighting Measures

### 5.1. Extinguishing media

Suitable extinguishing media:  
water spray

Unsuitable extinguishing media for safety reasons:  
water jet

### 5.2. Special hazards arising from the substance or mixture

Endangering substances: ammonia, anhydrous, hydrogen chloride

Advice: The substances/groups of substances mentioned can be released if the product is involved in a fire.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

### 5.3. Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

Product itself is non-combustible; fire extinguishing method of surrounding areas must be considered. In case of fire and/or explosion do not breathe fumes. Large quantities of extinguishing water containing dissolved product should be contained. Contaminated extinguishing water must be disposed of in accordance with official regulations.

---

## SECTION 6: Accidental Release Measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective clothing.

### 6.2. Environmental precautions

Do not empty into drains.

### 6.3. Methods and material for containment and cleaning up

For residues: Pick up in dry form. Dispose of absorbed material in accordance with regulations.

### 6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

---

## SECTION 7: Handling and Storage

### 7.1. Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

No special precautions necessary.

### 7.2. Conditions for safe storage, including any incompatibilities

Segregate from alkalies and alkalizing substances. Segregate from nitrites. Segregate from oxidants. Do not store with: Sodium nitrate

Suitable materials for containers: Polyester resin, glass reinforced (Palatal A410), High density polyethylene (HDPE), Low density polyethylene (LDPE), Stainless steel 1.4571, rubberized, enamelled, Paper/Fibreboard

Further information on storage conditions: Protect against moisture.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

### 7.3. Specific end use(s)

See exposure scenario(s) in the attachment to this safety data sheet.

---

## SECTION 8: Exposure Controls/Personal Protection

### 8.1. Control parameters

Components with occupational exposure limits

12125-02-9: ammonium chloride

TWA value 10 mg/m<sup>3</sup> (OEL (GR)), fumes/smoke

STEL value 20 mg/m<sup>3</sup> (OEL (GR)), fumes/smoke

Ceiling limit value/factor: 15 min

#### Components with PNEC

12125-02-9: ammonium chloride

freshwater: 0,25 mg/l

marine water: 0,025 mg/l

intermittent release: 0,43 mg/l

sediment (freshwater):

No hazard identified.

sediment (marine water):

No hazard identified.

soil: 50,7 mg/kg

STP:

No hazard identified.

#### Components with DNEL

12125-02-9: ammonium chloride

worker: Long-term exposure- systemic effects, Inhalation: 43,97 mg/m<sup>3</sup>

worker: Long-term exposure- systemic effects, dermal: 128,9 mg/kg

consumer: Long-term exposure- systemic effects, Inhalation: 9,4 mg/m<sup>3</sup>

consumer: Long-term exposure- systemic effects, dermal: 55,2 mg/kg

consumer: Long-term exposure- systemic effects, oral: 55,2 mg/kg

### 8.2. Exposure controls

#### Personal protective equipment

Respiratory protection:

Breathing protection if dusts are formed. Particle filter with low efficiency for solid particles (e.g. EN 143 or 149, Type P1 or FFP1)

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

chloroprene rubber (CR) - 0.5 mm coating thickness

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

butyl rubber (butyl) - 0.7 mm coating thickness

nitrile rubber (NBR) - 0.4 mm coating thickness

fluoroelastomer (FKM) - 0.7 mm coating thickness

polyvinylchloride (PVC) - 0.7 mm coating thickness

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

#### General safety and hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Avoid inhalation of dusts. When using, do not eat, drink or smoke. Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

|                    |                                       |
|--------------------|---------------------------------------|
| State of matter:   | solid                                 |
| Form:              | crystalline, powder                   |
| Colour:            | white                                 |
| Odour:             | almost odourless                      |
| Odour threshold:   |                                       |
|                    | not applicable, odour not perceivable |
| Melting point:     | 338 °C                                |
|                    | Literature data.                      |
|                    | The substance / product               |
|                    | decomposes.                           |
| Boiling point:     | (1.013,25 hPa)                        |
|                    | The substance / product               |
|                    | decomposes therefore not              |
|                    | determined.                           |
| Sublimation point: | 338 °C                                |
|                    | The substance / product               |
|                    | decomposes.                           |
| Flammability:      | not flammable                         |

(Regulation 440/2008/EC,  
A.10)

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|   |   |  |
|---|---|--|
| Lower explosion limit:                              | For solids not relevant for classification and labelling.                   |  |
| Upper explosion limit:                              | For solids not relevant for classification and labelling.                   |  |
| Flash point:  | not applicable, the product is a solid                                      |  |
| Auto-ignition temperature:                          | The substance / product decomposes therefore not determined.                |  |
| Self-ignition temperature:                          |   | Test type: Self-ignition at high temperatures. |
| Thermal decomposition:                              | not self-igniting   |  |
| SADT:   | To avoid thermal decomposition, do not overheat.                            |  |
| pH value:   | 5,0 - 5,5<br>(1,0 - 10,0 %(m), 25 °C)                                       |  |
| Viscosity, dynamic:                                 | not applicable, the product is a solid                                      |  |
| Solubility in water:                                |   | (OECD Guideline 105)                           |
|   | 296 - 298 g/l<br>(20 °C, pH 5,4)  |  |
| Partitioning coefficient n-octanol/water (log Kow): | The value has not been determined because the substance is inorganic.       |  |
| Vapour pressure:                                    | 66 mbar<br>(250 °C)   |  |
| Density:  | Literature data.<br>1,5274 g/cm <sup>3</sup><br>(20 °C)<br>Literature data. |  |
| <u>Particle characteristics</u>                     |   |  |
| Particle size distribution:                         | 100 - 125 µm  | (D50, Volumetric Distribution, measured)       |
| Particle Shape:                                     | fine particles - spheres  |  |

## 9.2. Other information

### Information with regard to physical hazard classes

#### Explosives

Explosion hazard: not explosive (Regulation 440/2008/EC, A.14)

Impact sensitivity: Based on the chemical structure there is no shock-sensitivity.



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

#### Oxidizing properties

Fire promoting properties: not fire-propagating

(Regulation 440/2008/EC,  
A.17)

#### Pyrophoric properties

Self-ignition temperature:

Test type: Spontaneous self-ignition at room-temperature.

not self-igniting

#### Self-heating substances and mixtures

Self heating ability: It is not a substance capable of spontaneous heating.

#### **Other safety characteristics**

Bulk density: 600 - 900 kg/m<sup>3</sup>

(DIN ISO 697)

pK<sub>A</sub>:

not applicable

*Information on: ammonia, anhydrous*

pK<sub>A</sub>:

*Study scientifically not justified., The substance does not dissociate.*

-----  
Hygroscopy:

hygroscopic

:

Study scientifically not justified.

Surface tension:

Based on chemical structure, surface activity is not to be expected.

Evaporation rate:

The product is a non-volatile solid.

## **SECTION 10: Stability and Reactivity**

### **10.1. Reactivity**

No hazardous reactions if stored and handled as prescribed/indicated.

### **10.2. Chemical stability**

The product is chemically stable.

### **10.3. Possibility of hazardous reactions**

Violent reaction under influence of oxidizing agents. Incompatible with bases. Reacts with nitrites. The product is stable if stored and handled as prescribed/indicated.

### **10.4. Conditions to avoid**

Avoid heat. Avoid moisture. See SDS section 7 - Handling and storage.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

## 10.5. Incompatible materials

Substances to avoid:

nitrites, nitrates, oxidizing agents

## 10.6. Hazardous decomposition products

Hazardous decomposition products:

hydrogen chloride, ammonia, anhydrous

# SECTION 11: Toxicological Information

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Acute toxicity

Assessment of acute toxicity:

Of moderate toxicity after single ingestion. Virtually nontoxic after a single skin contact.

Experimental/calculated data:

LD50 rat (oral): 1.410 mg/kg (BASF-Test)

(by inhalation): No data available.

LD50 rat (dermal): > 2.000 mg/kg (Directive 92/69/EEC, B.3)

No mortality was observed.

### Irritation

Assessment of irritating effects:

Not irritating to the skin. Eye contact causes irritation.

Experimental/calculated data:

Skin corrosion/irritation

rabbit: non-irritant (Draize test)

Serious eye damage/irritation

rabbit: Irritant. (BASF-Test)

### Respiratory/Skin sensitization

Assessment of sensitization:

Skin sensitizing effects were not observed in animal studies.

Experimental/calculated data:

Guinea pig maximization test guinea pig: Non-sensitizing. (similar to OECD guideline 406)

### Germ cell mutagenicity

Assessment of mutagenicity:

In the majority of studies performed with microorganisms and in mammalian cell culture, a mutagenic effect was not found. A mutagenic effect was also not observed in in vivo tests.

### Carcinogenicity

Assessment of carcinogenicity:

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

In long-term studies in rats in which the substance was given by feed, a carcinogenic effect was not observed.

#### Reproductive toxicity

Assessment of reproduction toxicity:  
Study scientifically not justified.

#### Developmental toxicity

Assessment of teratogenicity:  
No indications of a developmental toxic / teratogenic effect were seen in animal studies.

#### Specific target organ toxicity (single exposure)

Assessment of STOT single:  
Apart from effects causing lethality, no specific target organ toxicity was observed in experimental studies.

#### Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:  
Repeated oral uptake of the substance did not cause substance-related effects.

#### Aspiration hazard

not applicable

#### Interactive effects

No data available.

## **11.2. Information on other hazards**

#### Endocrine disrupting properties

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

---

## **SECTION 12: Ecological Information**

### **12.1. Toxicity**

Assessment of aquatic toxicity:  
Harmful to aquatic life.

Acutely harmful for aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Toxicity to fish:

LC50 (96 h) 42,91 mg/l Ammonium chloride, *Oncorhynchus mykiss* (other, other)

Aquatic invertebrates:

EC50 (48 h) 136,6 mg/l, *Daphnia magna* (other, static)

Aquatic plants:

EC50 (5 d) 1.300 mg/l (growth rate), *Chlorella vulgaris* (other, static)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

EC50 (18 d) 2.700 mg/l (biomass), *Chlorella vulgaris* (other, static)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Microorganisms/Effect on activated sludge:

EC20 (0,5 h) approx. 850 mg/l, activated sludge, domestic (OECD Guideline 209, aquatic)

Chronic toxicity to fish:

EC10 (30 d) 4,28 mg/l ammonium chloride, *Lepomis macrochirus* (other, Flow through.)

Chronic toxicity to aquatic invertebrates:

EC10 (70 d) 2,52 mg/l ammonium chloride, aquatic crustacea (other, semistatic)

Assessment of terrestrial toxicity:

Toxic effects have been observed in studies with soil living organisms.

Soil living organisms:

LC50 (14 d) 163 mg/kg, *Eisenia foetida* (other, artificial soil)

Terrestrial plants:

No observed effect concentration (84 d) 626 mg/l

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Other terrestrial non-mammals:

Study scientifically not justified.

## 12.2. Persistence and degradability

Assessment biodegradation and elimination (H<sub>2</sub>O):

Inorganic product which cannot be eliminated from water by biological purification processes. Can be oxidized to nitrate, or be reduced to nitrogen, by microorganisms.

Elimination information:

not applicable

Assessment of stability in water:

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

According to structural properties, hydrolysis is not expected/probable.  
Study scientifically not justified.

Information on Stability in Water (Hydrolysis):  
Study scientifically not justified.

### **12.3. Bioaccumulative potential**

Assessment bioaccumulation potential:  
Accumulation in organisms is not to be expected.

Bioaccumulation potential:  
Accumulation in organisms is not to be expected.

### **12.4. Mobility in soil**

Assessment transport between environmental compartments:  
Volatility: The substance will not evaporate into the atmosphere from the water surface. Study scientifically not justified.  
Adsorption in soil: Adsorption to solid soil phase is possible.

### **12.5. Results of PBT and vPvB assessment**

The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative).

### **12.6. Endocrine disrupting properties**

The product does not contain a substance that is considered to have endocrine disrupting properties according to EU REACH Article 57(f).

### **12.7. Other adverse effects**

#### Results of PMT and vPvM assessment

PMT assessment does not apply. vPvM assessment does not apply.

#### Additional information

Add. remarks environm. fate & pathway:  
The product has not been tested. The statements on environmental fate and pathway have been derived from the properties of the individual components.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

## SECTION 13: Disposal Considerations

### 13.1. Waste treatment methods

Contact manufacturer regarding recycling.

Contact waste centre regarding recycling.

Contaminated packaging:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

## SECTION 14: Transport Information

### Land transport

ADR

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable

UN proper shipping name: Not applicable

Transport hazard class(es): Not applicable

Packing group: Not applicable

Environmental hazards: Not applicable

Special precautions for user: None known

RID

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable

UN proper shipping name: Not applicable

Transport hazard class(es): Not applicable

Packing group: Not applicable

Environmental hazards: Not applicable

Special precautions for user: None known

### Inland waterway transport

ADN

Not classified as a dangerous good under transport regulations

UN number or ID number: Not applicable

UN proper shipping name: Not applicable

Transport hazard class(es): Not applicable

Packing group: Not applicable

Environmental hazards: Not applicable

Special precautions for user: None known

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

#### Transport in inland waterway vessel

Not evaluated

#### Sea transport

##### IMDG

|                              |  |
|------------------------------|--|
|                              | Not classified as a dangerous good under transport regulations |
| UN number or ID number:      | Not applicable   |
| UN proper shipping name:     | Not applicable   |
| Transport hazard class(es):  | Not applicable   |
| Packing group:               | Not applicable   |
| Environmental hazards:       | Not applicable   |
| Special precautions for user | None known   |

#### Air transport

##### IATA/ICAO

|                              |  |
|------------------------------|--|
|                              | Not classified as a dangerous good under transport regulations |
| UN number or ID number:      | Not applicable   |
| UN proper shipping name:     | Not applicable   |
| Transport hazard class(es):  | Not applicable   |
| Packing group:               | Not applicable   |
| Environmental hazards:       | Not applicable   |
| Special precautions for user | None known   |

#### **14.1. UN number or ID number**

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

#### **14.2. UN proper shipping name**

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

#### **14.3. Transport hazard class(es)**

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

#### **14.4. Packing group**

See corresponding entries for "Packing group" for the respective regulations in the tables above.

#### **14.5. Environmental hazards**

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

#### **14.6. Special precautions for user**

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

#### **14.7. Maritime transport in bulk according to IMO instruments**

Maritime transport in bulk is not intended.

#### **Further information**

Specific national features of transport regulations must be observed. They are to be found in the shipping documents.

---

### **SECTION 15: Regulatory Information**

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

##### Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 75

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):

Listed in above regulation: no

Classification applies for standard conditions of temperature and pressure.

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

#### **15.2. Chemical Safety Assessment**

Chemical Safety Assessment performed

---

### **SECTION 16: Other Information**

Assessment of the hazard classes according to UN GHS criteria (most recent version)

Acute Tox. 4 (oral)

Aquatic Acute 3

Eye Irrit. 2A

chemical industry

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

Acute Tox.

Acute toxicity

Eye Irrit.

Eye irritation

H319

Causes serious eye irritation.

H302

Harmful if swallowed.

#### Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.  
ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

## Annex: Exposure Scenarios

### Index

1. Manufacture of substance, Distribution of substance, Industrial applications  
IS; IS; ERC1; PROC1, PROC2, PROC3, PROC4, PROC8b, PROC9, PROC15
2. Formulation & (re)packing of substances and mixtures, Industrial applications  
IS; IS; ERC2; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC13, PROC14, PROC15, PROC19, PROC26
3. Formulation & (re)packing of substances and mixtures, (solid preparations), Industrial applications  
IS; IS; ERC3; PROC2, PROC3, PROC4, PROC5, PROC6, PROC8b, PROC9, PROC13, PROC14, PROC15, PROC19, PROC26
4. Use as a Process chemical, Use in Metallurgy, Use for Electroplating, Use in Textile finishing, Use in Biotechnology, Use in leather tanning, finishing, impregnation, Industrial applications  
IS; SU5, SU9, SU14, SU15, SU24; ERC4; PROC2, PROC3, PROC4, PROC5, PROC6, PROC8b, PROC9, PROC10, PROC13, PROC15, PROC22, PROC23, PROC24, PROC25, PROC26
5. Production of pharmaceutical products, Use in Personal care products, Use in/as Flavouring agent(s), Use in cosmetics, Industrial applications  
IS; SU4, SU20; ERC4; PROC5, PROC14
6. Use in Batteries, Production, (solid preparations), Industrial applications  
IS; SU6b, SU8, SU16; ERC5; PROC2, PROC3, PROC4, PROC5, PROC6, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15, PROC19, PROC21, PROC26
7. Use as an intermediate, Production of Fertilizers, Formulation of catalysts, Industrial applications  
IS; SU1, SU8; ERC6a; PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC13, PROC14, PROC15, PROC26
8. Use as Reactive process agent, Use in Metallurgy, Use in Metal surface treatment, Use in Textile finishing, Use in leather tanning, finishing, impregnation, Use in Biotechnology, Industrial applications  
IS; SU5, SU9, SU14, SU15, SU24; ERC6b; PROC2, PROC3, PROC4, PROC5, PROC6, PROC8b, PROC9, PROC10, PROC13, PROC15, PROC22, PROC23, PROC25, PROC26
9. Use as Cross-linking agent, Production of woodbased materials (panels, bricks, etc), Production of bonded fibers or fiber mats  
IS; SU6a; ERC6d; PROC6, PROC14
10. Use as a Process chemical, Professional applications, (indoor use)  
PW; SU1, SU8; ERC8a; PROC2, PROC3, PROC4, PROC5, PROC8b, PROC9, PROC13, PROC14, PROC15, PROC19, PROC26
11. Use as Reactive process agent, Use in/as Fertilizers, Use in Metallurgy, Use in Metal surface treatment, Use in Textile finishing, Use in Biotechnology, Professional applications, (indoor use)  
PW; SU5, SU14, SU15; ERC8b; PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC11, PROC13, PROC14, PROC15, PROC19, PROC23, PROC26

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

**12.** Use as a Process chemical, Professional applications, (outdoor use)

PW; SU1, SU8, SU10; ERC8d; PROC2, PROC3, PROC4, PROC5, PROC8b, PROC9, PROC13, PROC14, PROC15, PROC19, PROC26

**13.** Use as Reactive process agent, Use in/as Fertilizers, Use in Metallurgy, Use in Metal surface treatment, Use in Textile finishing, Use in Biotechnology, Use in leather tanning, finishing, impregnation, Professional applications, (outdoor use)

PW; SU5, SU10, SU14, SU15; ERC8e; PROC2, PROC3, PROC4, PROC5, PROC6, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC14, PROC19, PROC26

**14.** Use in Wood articles, Service life of articles, Consumer applications

C; C; ERC10a, ERC11a; AC11

**15.** Use in Biotechnology, Industrial applications

ERC6a, ERC6b; PROC4, PROC9

**16.** Use in Cleaning Agents, Use in/as Laundry agents, Consumer applications

C; C; ERC8a, ERC8d; PC35, PC39

**17.** Use in Metal surface treatment, Consumer applications

C; C; ERC8b, ERC8e; PC14, PC38

**18.** Use in/as Fertilizers, Consumer applications

C; C; ERC8b, ERC8e; PC12, PC27

**19.** Use in Adhesives, Use in Surface treatment products, Wood treatment, Use in Wood articles, Consumer applications

C; C; ERC8c, ERC8f; PC1

**20.** Use in Batteries, Consumer applications

C; C; ERC9a, ERC9b; PC42

**21.** Use in Batteries, Service life of articles, Consumer applications

C; C; ERC10a, ERC11a, ERC12a; AC3

**22.** Use in pharmaceuticals, Use as Additive, Dietary intake, Use in cosmetics, Use in/as Flavouring agent(s), Consumer applications

C; C; ERC8a, ERC8b, ERC8e; PC20, PC29, PC39

\*\*\*\*\*

## 1. Short title of exposure scenario

Manufacture of substance, Distribution of substance, Industrial applications

IS; IS; ERC1; PROC1, PROC2, PROC3, PROC4, PROC8b, PROC9, PROC15

## Control of exposure and risk management measures

|                                       |                                    |
|---------------------------------------|------------------------------------|
| <b>Contributing exposure scenario</b> |                                    |
| <b>Use descriptors covered</b>        | ERC1: Manufacture of the substance |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
|  | As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
|--|---|

### **Operational conditions**

| <b>Contributing exposure scenario</b>  |  |
|--|--|
| <b>Use descriptors covered</b>   | PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.<br>Use domain: industrial |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$  |
| Physical state   | Solid, medium dustiness  |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | 480 min 5 days per week  |
| Indoor/Outdoor   | Indoor   |
| <b>Risk Management Measures</b>  |  |
| Use suitable eye protection.   |  |
| <b>Exposure estimate and reference to its source</b>                               |  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - dermal, long-term - systemic  |
| Exposure estimate  | 0,0343 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,000266   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - inhalation, long-term - systemic  |
| Exposure estimate  | 0,01 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,000227   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |  |

| <b>Contributing exposure scenario</b> |   |
|---------------------------------------|---|
| <b>Use descriptors covered</b>        | PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions<br>Use domain: industrial |
| <b>Operational conditions</b>         |   |
| Concentration of the substance        | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$   |
| Physical state                        | Solid, medium dustiness   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Vapour pressure of the substance during use  | 130 Pa                                    |
| Process temperature  | 20 °C                                     |
| Duration and Frequency of activity   | 480 min 5 days per week                   |
| Indoor/Outdoor   | Indoor                                    |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 1,3714 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,010639                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 0,5 mg/m <sup>3</sup>                     |
| Risk Characterization Ratio (RCR)  | 0,011371                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition<br>Use domain: industrial |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state                                       | Solid, medium dustiness   |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | 480 min 5 days per week   |
| Indoor/Outdoor                                       | Indoor  |
| <b>Risk Management Measures</b>                      |   |
| Use suitable eye protection.                         |   |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate                                    | 0,6857 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)                    | 0,00532   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |                     |
|--|---------------------|
| Exposure estimate  | 1 mg/m <sup>3</sup> |
| Risk Characterization Ratio (RCR)  | 0,022743            |
| <b>Guidance to Downstream Users</b>  |                     |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |                     |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>  |  |
| <b>Use descriptors covered</b>   | PROC4: Chemical production where opportunity for exposure arises<br>Use domain: industrial |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %  |
| Physical state   | Solid, medium dustiness  |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | 480 min 5 days per week  |
| Indoor/Outdoor   | Indoor   |
| <b>Risk Management Measures</b>  |  |
| Use suitable eye protection.   |  |
| <b>Exposure estimate and reference to its source</b>                               |  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - dermal, long-term - systemic  |
| Exposure estimate  | 6,8571 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,053197   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - inhalation, long-term - systemic  |
| Exposure estimate  | 5 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,113714   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |  |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities<br>Use domain: industrial |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state                              | Solid, medium dustiness   |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Duration and Frequency of activity   | 480 min 5 days per week                   |
| Indoor/Outdoor   | Indoor                                    |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 13,7143 mg/kg bw/day                      |
| Risk Characterization Ratio (RCR)  | 0,106395                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 1 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,022743                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing).<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 6,8571 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,053197  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 5 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,113714  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC15: Use a laboratory reagent.<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %             |
| Physical state   | Solid, medium dustiness                                     |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week                                     |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                      |
|  | Worker - dermal, long-term - systemic                       |
| Exposure estimate  | 0,3429 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,00266   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                      |
|  | Worker - inhalation, long-term - systemic                   |
| Exposure estimate  | 0,5 mg/m <sup>3</sup>                                       |
| Risk Characterization Ratio (RCR)  | 0,011371  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

\*\*\*\*\*

## 2. Short title of exposure scenario

Formulation & (re)packing of substances and mixtures, Industrial applications

IS; IS; ERC2; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC13, PROC14, PROC15, PROC19, PROC26

## Control of exposure and risk management measures

|                                       |   |
|---------------------------------------|---|
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | ERC2: Formulation into mixture<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
| <b>Operational conditions</b>         |   |
| <b>Contributing exposure scenario</b> |   |



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| <b>Use descriptors covered</b>   | PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.<br>Use domain: industrial |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$  |
| Physical state   | Solid, medium dustiness  |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | 480 min 5 days per week  |
| Indoor/Outdoor   | Indoor   |
| <b>Risk Management Measures</b>  |  |
| Use suitable eye protection.   |  |
| <b>Exposure estimate and reference to its source</b>                               |  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - dermal, long-term - systemic  |
| Exposure estimate  | 0,0343 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,000266   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - inhalation, long-term - systemic  |
| Exposure estimate  | 0,01 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,000227   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |  |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions<br>Use domain: industrial |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$   |
| Physical state                              | Solid, medium dustiness   |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |
| Duration and Frequency of activity          | 480 min 5 days per week   |
| Indoor/Outdoor                              | Indoor  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 1,3714 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,010639                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 0,5 mg/m <sup>3</sup>                     |
| Risk Characterization Ratio (RCR)  | 0,011371                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 0,6857 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,00532   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 1 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,022743  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|                                       |  |
|---------------------------------------|--|
| <b>Contributing exposure scenario</b> |  |
| <b>Use descriptors covered</b>        | PROC4: Chemical production where opportunity for |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
|  | exposure arises<br>Use domain: industrial               |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$ |
| Physical state   | Solid, medium dustiness                                 |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week                                 |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - dermal, long-term - systemic                   |
| Exposure estimate  | 6,8571 mg/kg bw/day                                     |
| Risk Characterization Ratio (RCR)  | 0,053197  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - inhalation, long-term - systemic               |
| Exposure estimate  | 5 mg/m <sup>3</sup>                                     |
| Risk Characterization Ratio (RCR)  | 0,113714  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>                |  |
| <b>Use descriptors covered</b>                       | PROC5: Mixing or blending in batch processes<br>Use domain: industrial |
| <b>Operational conditions</b>                        |  |
| Concentration of the substance                       | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$                |
| Physical state                                       | Solid, medium dustiness  |
| Vapour pressure of the substance during use          | 130 Pa   |
| Process temperature                                  | 20 °C  |
| Duration and Frequency of activity                   | 480 min 5 days per week  |
| Indoor/Outdoor                                       | Indoor   |
| <b>Risk Management Measures</b>                      |  |
| Use suitable eye protection.                         |  |
| <b>Exposure estimate and reference to its source</b> |  |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker                                 |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 13,7143 mg/kg bw/day                      |
| Risk Characterization Ratio (RCR)  | 0,106395                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 5 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,113714                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 13,7143 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,106395  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 5 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,113714  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|                                       |   |
|---------------------------------------|---|
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities<br>Use domain: industrial |
| <b>Operational conditions</b>         |   |
| Concentration of the substance        | ammonium chloride<br>Content: >= 0 % - <= 100 %   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Physical state   | Solid, medium dustiness                   |
| Vapour pressure of the substance during use  | 130 Pa                                    |
| Process temperature  | 20 °C                                     |
| Duration and Frequency of activity   | 480 min 5 days per week                   |
| Indoor/Outdoor   | Indoor                                    |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 13,7143 mg/kg bw/day                      |
| Risk Characterization Ratio (RCR)  | 0,106395                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 1 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,022743                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing).<br>Use domain: industrial |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state                                       | Solid, medium dustiness   |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | 480 min 5 days per week   |
| Indoor/Outdoor                                       | Indoor  |
| <b>Risk Management Measures</b>                      |   |
| Use suitable eye protection.                         |   |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate                                    | 6,8571 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)                    | 0,053197  |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |                     |
|--|---------------------|
| Exposure estimate  | 5 mg/m <sup>3</sup> |
| Risk Characterization Ratio (RCR)  | 0,113714            |
| <b>Guidance to Downstream Users</b>  |                     |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |                     |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC13: Treatment of articles by dipping and pouring.<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %                                 |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 13,7143 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,106395  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic                                       |
| Exposure estimate  | 1 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,022743  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PROC14: Tableting, compression, extrusion, pelletisation, granulation<br>Use domain: industrial |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state                              | Solid, medium dustiness   |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Duration and Frequency of activity   | 480 min 5 days per week                   |
| Indoor/Outdoor   | Indoor                                    |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 3,4286 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,026599                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 1 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,022743                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC15: Use a laboratory reagent.<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %             |
| Physical state   | Solid, medium dustiness                                     |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week                                     |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                      |
|  | Worker - dermal, long-term - systemic                       |
| Exposure estimate  | 0,3429 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,00266   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                      |
|  | Worker - inhalation, long-term - systemic                   |
| Exposure estimate  | 0,5 mg/m <sup>3</sup>                                       |
| Risk Characterization Ratio (RCR)  | 0,011371  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|                                       |  |
|---------------------------------------|--|
| <b>Contributing exposure scenario</b> |  |
| <b>Use descriptors covered</b>        | PROC19: Manual activities involving hand contact |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
|  | Use domain: industrial                                  |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$ |
| Physical state   | Solid, medium dustiness                                 |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week                                 |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable chemically resistant gloves.  | Effectiveness: 80 %                                     |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - dermal, long-term - systemic                   |
| Exposure estimate  | 28,2857 mg/kg bw/day                                    |
| Risk Characterization Ratio (RCR)  | 0,219439  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - inhalation, long-term - systemic               |
| Exposure estimate  | 5 mg/m <sup>3</sup>                                     |
| Risk Characterization Ratio (RCR)  | 0,113714  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>   |   |
| <b>Use descriptors covered</b>  | PROC26: Handling of solid inorganic substances at ambient temperature<br>Use domain: industrial |
| <b>Operational conditions</b>   |   |
| Physical state  | Solid, medium dustiness   |
| Vapour pressure of the substance during use   | 130 Pa  |
| Process temperature   | 20 °C   |
| <b>Risk Management Measures</b>   |   |
| Use suitable eye protection.  |   |
| <b>Exposure estimate and reference to its source</b>  |   |
| Assessment method   | Qualitative assessment  |
| <b>Additional good practice advice</b>  |   |
| There is no corresponding TRA entry concerning PROC 26 and thus, calculation of PROC 26 with TRA is not possible. To approximately map the activities described by PROC 26, PROC 5, 8b and 9 were used. PROC 8b and 9 were used to address the transfer, packaging, unpacking, and weighing |   |



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

while PROC 5 addresses mixing and blending activities

There is no corresponding TRA entry concerning PROC 26 and thus, calculation of PROC 26 with TRA is not possible. To approximately map the activities described by PROC 26, PROC 5, 8b and 9 were used. PROC 8b and 9 were used to address the transfer, packaging, unpacking, and weighing while PROC 5 addresses mixing and blending activities

\*\*\*\*\*

### 3. Short title of exposure scenario

Formulation & (re)packing of substances and mixtures, (solid preparations), Industrial applications IS; IS; ERC3; PROC2, PROC3, PROC4, PROC5, PROC6, PROC8b, PROC9, PROC13, PROC14, PROC15, PROC19, PROC26

### Control of exposure and risk management measures

| Contributing exposure scenario                |   |
|---|---|
| Use descriptors covered                       | ERC3: Formulation into solid matrix<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.                |
| Operational conditions                        |   |
| Contributing exposure scenario                |   |
| Use descriptors covered                       | PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions<br>Use domain: industrial |
| Operational conditions                        |   |
| Concentration of the substance                | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$   |
| Physical state                                | Solid, medium dustiness   |
| Vapour pressure of the substance during use   | 130 Pa  |
| Process temperature                           | 20 °C   |
| Duration and Frequency of activity            | 480 min 5 days per week   |
| Indoor/Outdoor                                | Indoor  |
| Risk Management Measures                      |   |
| Use suitable eye protection.                  |   |
| Exposure estimate and reference to its source |   |
| Assessment method                             | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|   | Worker - dermal, long-term - systemic   |
| Exposure estimate                             | 1,3714 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)             | 0,010639  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 0,5 mg/m <sup>3</sup>                     |
| Risk Characterization Ratio (RCR)  | 0,011371                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 0,6857 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,00532   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 1 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,022743  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|                                       |  |
|---------------------------------------|--|
| <b>Contributing exposure scenario</b> |  |
| <b>Use descriptors covered</b>        | PROC4: Chemical production where opportunity for exposure arises<br>Use domain: industrial |
| <b>Operational conditions</b>         |  |
| Concentration of the substance        | ammonium chloride<br>Content: >= 0 % - <= 100 %  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Physical state   | Solid, medium dustiness                   |
| Vapour pressure of the substance during use  | 130 Pa                                    |
| Process temperature  | 20 °C                                     |
| Duration and Frequency of activity   | 480 min 5 days per week                   |
| Indoor/Outdoor   | Indoor                                    |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 6,8571 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,053197                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 5 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,113714                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>                |  |
| <b>Use descriptors covered</b>                       | PROC5: Mixing or blending in batch processes<br>Use domain: industrial |
| <b>Operational conditions</b>                        |  |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 100 %                        |
| Physical state                                       | Solid, medium dustiness  |
| Vapour pressure of the substance during use          | 130 Pa   |
| Process temperature                                  | 20 °C  |
| Duration and Frequency of activity                   | 480 min 5 days per week  |
| Indoor/Outdoor                                       | Indoor   |
| <b>Risk Management Measures</b>                      |  |
| Use suitable eye protection.                         |  |
| <b>Exposure estimate and reference to its source</b> |  |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker                                 |
|  | Worker - dermal, long-term - systemic                                  |
| Exposure estimate                                    | 13,7143 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)                    | 0,106395   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker                                 |
|  | Worker - inhalation, long-term - systemic                              |
| Exposure estimate                                    | 5 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)                    | 0,113714   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

### **Guidance to Downstream Users**

For scaling see: <http://www.ecetoc.org/tra>

### **Contributing exposure scenario**

|                                |   |
|--------------------------------|---|
| <b>Use descriptors covered</b> | PROC6: Calendering operations<br>Use domain: industrial |
|--------------------------------|---|

### **Operational conditions**

|                                |   |
|--------------------------------|---|
| Concentration of the substance | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$ |
|--------------------------------|---|

|                |                         |
|----------------|-------------------------|
| Physical state | Solid, medium dustiness |
|----------------|-------------------------|

|   |        |
|---|--------|
| Vapour pressure of the substance during use | 130 Pa |
|---|--------|

|                     |       |
|---------------------|-------|
| Process temperature | 20 °C |
|---------------------|-------|

|                                    |                         |
|------------------------------------|-------------------------|
| Duration and Frequency of activity | 480 min 5 days per week |
|------------------------------------|-------------------------|

|                |        |
|----------------|--------|
| Indoor/Outdoor | Indoor |
|----------------|--------|

### **Risk Management Measures**

|                              |  |
|------------------------------|--|
| Use suitable eye protection. |  |
|------------------------------|--|

### **Exposure estimate and reference to its source**

|                   |  |
|-------------------|--|
| Assessment method | EASY TRA v4.2, ECETOC TRA v3.0, Worker |
|-------------------|--|

|  |                                       |
|--|---------------------------------------|
|  | Worker - dermal, long-term - systemic |
|--|---------------------------------------|

|                   |                      |
|-------------------|----------------------|
| Exposure estimate | 27,4286 mg/kg bw/day |
|-------------------|----------------------|

|                                   |         |
|-----------------------------------|---------|
| Risk Characterization Ratio (RCR) | 0,21279 |
|-----------------------------------|---------|

|                   |  |
|-------------------|--|
| Assessment method | EASY TRA v4.2, ECETOC TRA v3.0, Worker |
|-------------------|--|

|  |   |
|--|---|
|  | Worker - inhalation, long-term - systemic |
|--|---|

|                   |                     |
|-------------------|---------------------|
| Exposure estimate | 5 mg/m <sup>3</sup> |
|-------------------|---------------------|

|                                   |          |
|-----------------------------------|----------|
| Risk Characterization Ratio (RCR) | 0,113714 |
|-----------------------------------|----------|

### **Guidance to Downstream Users**

For scaling see: <http://www.ecetoc.org/tra>

### **Contributing exposure scenario**

|                                |   |
|--------------------------------|---|
| <b>Use descriptors covered</b> | PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities<br>Use domain: industrial |
|--------------------------------|---|

### **Operational conditions**

|                                |   |
|--------------------------------|---|
| Concentration of the substance | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$ |
|--------------------------------|---|

|                |                         |
|----------------|-------------------------|
| Physical state | Solid, medium dustiness |
|----------------|-------------------------|

|   |        |
|---|--------|
| Vapour pressure of the substance during use | 130 Pa |
|---|--------|

|                     |       |
|---------------------|-------|
| Process temperature | 20 °C |
|---------------------|-------|

|                                    |                         |
|------------------------------------|-------------------------|
| Duration and Frequency of activity | 480 min 5 days per week |
|------------------------------------|-------------------------|

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Indoor/Outdoor   | Indoor                                    |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 13,7143 mg/kg bw/day                      |
| Risk Characterization Ratio (RCR)  | 0,106395                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 1 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,022743                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing).<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 6,8571 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,053197  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 5 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,113714  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|                                       |   |
|---------------------------------------|---|
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | PROC13: Treatment of articles by dipping and pouring.<br>Use domain: industrial |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$ |
| Physical state   | Solid, medium dustiness                                 |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week                                 |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - dermal, long-term - systemic                   |
| Exposure estimate  | 13,7143 mg/kg bw/day                                    |
| Risk Characterization Ratio (RCR)  | 0,106395  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - inhalation, long-term - systemic               |
| Exposure estimate  | 1 mg/m <sup>3</sup>                                     |
| Risk Characterization Ratio (RCR)  | 0,022743  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PROC14: Tableting, compression, extrusion, pelletisation, granulation<br>Use domain: industrial |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$   |
| Physical state                                       | Solid, medium dustiness   |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | 480 min 5 days per week   |
| Indoor/Outdoor                                       | Indoor  |
| <b>Risk Management Measures</b>                      |   |
| Use suitable eye protection.                         |   |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Exposure estimate  | 3,4286 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,026599                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 1 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,022743                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC15: Use a laboratory reagent.<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %             |
| Physical state   | Solid, medium dustiness                                     |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week                                     |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                      |
|  | Worker - dermal, long-term - systemic                       |
| Exposure estimate  | 0,3429 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,00266   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                      |
|  | Worker - inhalation, long-term - systemic                   |
| Exposure estimate  | 0,5 mg/m <sup>3</sup>                                       |
| Risk Characterization Ratio (RCR)  | 0,011371  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|                                       |  |
|---------------------------------------|--|
| <b>Contributing exposure scenario</b> |  |
| <b>Use descriptors covered</b>        | PROC19: Manual activities involving hand contact<br>Use domain: industrial |
| <b>Operational conditions</b>         |  |
| Concentration of the substance        | ammonium chloride<br>Content: >= 0 % - <= 100 %                            |
| Physical state                        | Solid, medium dustiness  |
| Vapour pressure of the substance      | 130 Pa   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| during use   |   |
| Process temperature  | 20 °C                                     |
| Duration and Frequency of activity   | 480 min 5 days per week                   |
| Indoor/Outdoor   | Indoor                                    |
| <b>Risk Management Measures</b>  |   |
| Use suitable chemically resistant gloves.  | Effectiveness: 80 %                       |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 28,2857 mg/kg bw/day                      |
| Risk Characterization Ratio (RCR)  | 0,219439                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 5 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,113714                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>   |   |
| <b>Use descriptors covered</b>  | PROC26: Handling of solid inorganic substances at ambient temperature<br>Use domain: industrial |
| <b>Operational conditions</b>   |   |
| Physical state  | Solid, medium dustiness   |
| Vapour pressure of the substance during use   | 130 Pa  |
| Process temperature   | 20 °C   |
| <b>Risk Management Measures</b>   |   |
| Use suitable eye protection.  |   |
| <b>Exposure estimate and reference to its source</b>  |   |
| Assessment method   | Qualitative assessment  |
| <b>Additional good practice advice</b>  |   |
| There is no corresponding TRA entry concerning PROC 26 and thus, calculation of PROC 26 with TRA is not possible. To approximately map the activities described by PROC 26, PROC 5, 8b and 9 were used. PROC 8b and 9 were used to address the transfer, packaging, unpacking, and weighing while PROC 5 addresses mixing and blending activities |   |
| There is no corresponding TRA entry concerning PROC 26 and thus, calculation of PROC 26 with TRA is not possible. To approximately map the activities described by PROC 26, PROC 5, 8b and 9 were used. PROC 8b and 9 were used to address the transfer, packaging, unpacking, and weighing while PROC 5 addresses mixing and blending activities |   |

\*\*\*\*\*



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

#### 4. Short title of exposure scenario

Use as a Process chemical, Use in Metallurgy, Use for Electroplating, Use in Textile finishing, Use in Biotechnology, Use in leather tanning, finishing, impregnation, Industrial applications  
IS; SU5, SU9, SU14, SU15, SU24; ERC4; PROC2, PROC3, PROC4, PROC5, PROC6, PROC8b, PROC9, PROC10, PROC13, PROC15, PROC22, PROC23, PROC24, PROC25, PROC26

#### Control of exposure and risk management measures

| Contributing exposure scenario   |  |
|--|--|
| Use descriptors covered  | ERC4: Use of non-reactive processing aid at industrial site (no inclusion into or onto article)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
| Operational conditions   |  |
| Contributing exposure scenario   |  |
| Use descriptors covered  | PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions<br>Use domain: industrial  |
| Operational conditions   |  |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$  |
| Physical state   | Solid, medium dustiness  |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | 480 min 5 days per week  |
| Indoor/Outdoor   | Indoor   |
| Risk Management Measures   |  |
| Use suitable eye protection.   |  |
| Exposure estimate and reference to its source                                      |  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - dermal, long-term - systemic  |
| Exposure estimate  | 1,3714 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,010639   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - inhalation, long-term - systemic  |
| Exposure estimate  | 0,5 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,011371   |
| Guidance to Downstream Users   |  |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

| <b>Contributing exposure scenario</b>  |   |
|--|---|
| <b>Use descriptors covered</b>   | PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$   |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 0,6857 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,00532   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 1 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,022743  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

| <b>Contributing exposure scenario</b>       |  |
|---|--|
| <b>Use descriptors covered</b>              | PROC4: Chemical production where opportunity for exposure arises<br>Use domain: industrial |
| <b>Operational conditions</b>               |  |
| Concentration of the substance              | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$                                    |
| Physical state                              | Solid, medium dustiness  |
| Vapour pressure of the substance during use | 130 Pa   |
| Process temperature                         | 20 °C  |
| Duration and Frequency of activity          | 480 min 5 days per week  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Indoor/Outdoor   | Indoor                                    |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 6,8571 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,053197                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 5 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,113714                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>  |  |
| <b>Use descriptors covered</b>   | PROC5: Mixing or blending in batch processes<br>Use domain: industrial |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %                        |
| Physical state   | Solid, medium dustiness  |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | 480 min 5 days per week  |
| Indoor/Outdoor   | Indoor   |
| <b>Risk Management Measures</b>  |  |
| Use suitable eye protection.   |  |
| <b>Exposure estimate and reference to its source</b>                               |  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                                 |
|  | Worker - dermal, long-term - systemic                                  |
| Exposure estimate  | 13,7143 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,106395   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                                 |
|  | Worker - inhalation, long-term - systemic                              |
| Exposure estimate  | 5 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,113714   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |  |

|                                       |   |
|---------------------------------------|---|
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | PROC6: Calendering operations<br>Use domain: industrial |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$ |
| Physical state   | Solid, medium dustiness                                 |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week                                 |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - dermal, long-term - systemic                   |
| Exposure estimate  | 27,4286 mg/kg bw/day                                    |
| Risk Characterization Ratio (RCR)  | 0,21279   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - inhalation, long-term - systemic               |
| Exposure estimate  | 5 mg/m <sup>3</sup>                                     |
| Risk Characterization Ratio (RCR)  | 0,113714  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities<br>Use domain: industrial |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$   |
| Physical state                                       | Solid, medium dustiness   |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | 480 min 5 days per week   |
| Indoor/Outdoor                                       | Indoor  |
| <b>Risk Management Measures</b>                      |   |
| Use suitable eye protection.                         |   |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Exposure estimate  | 13,7143 mg/kg bw/day                      |
| Risk Characterization Ratio (RCR)  | 0,106395                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 1 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,022743                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing).<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 6,8571 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,053197  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 5 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,113714  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|                                       |  |
|---------------------------------------|--|
| <b>Contributing exposure scenario</b> |  |
| <b>Use descriptors covered</b>        | PROC10: Roller application or brushing<br>Use domain: industrial |
| <b>Operational conditions</b>         |  |
| Concentration of the substance        | ammonium chloride<br>Content: >= 0 % - <= 100 %                  |
| Physical state                        | Solid, medium dustiness  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Vapour pressure of the substance during use  | 130 Pa                                    |
| Process temperature  | 20 °C                                     |
| Duration and Frequency of activity   | 480 min 5 days per week                   |
| Indoor/Outdoor   | Indoor                                    |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 27,4286 mg/kg bw/day                      |
| Risk Characterization Ratio (RCR)  | 0,21279                                   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 5 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,113714                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PROC13: Treatment of articles by dipping and pouring.<br>Use domain: industrial |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 100 %                                 |
| Physical state                                       | Solid, medium dustiness   |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | 480 min 5 days per week   |
| Indoor/Outdoor                                       | Indoor  |
| <b>Risk Management Measures</b>                      |   |
| Use suitable eye protection.                         |   |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate                                    | 13,7143 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)                    | 0,106395  |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic                                       |
| Exposure estimate                                    | 1 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)                    | 0,022743  |
| <b>Guidance to Downstream Users</b>                  |   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

For scaling see: <http://www.ecetoc.org/tra>

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC15: Use a laboratory reagent.<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$     |
| Physical state   | Solid, medium dustiness                                     |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week                                     |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                      |
|  | Worker - dermal, long-term - systemic                       |
| Exposure estimate  | 0,3429 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,00266   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                      |
|  | Worker - inhalation, long-term - systemic                   |
| Exposure estimate  | 0,5 mg/m <sup>3</sup>                                       |
| Risk Characterization Ratio (RCR)  | 0,011371  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|   |  |
|---|--|
| <b>Contributing exposure scenario</b>       |  |
| <b>Use descriptors covered</b>              | PROC22: Manufacturing and processing of minerals and/or metals at substantially elevated temperature<br>Use domain: industrial |
| <b>Operational conditions</b>               |  |
| Concentration of the substance              | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$  |
| Physical state                              | Solid, low dustiness   |
| Vapour pressure of the substance during use | 130 Pa   |
| Process temperature                         | 20 °C  |
| Duration and Frequency of activity          | 480 min 5 days per week  |
| Indoor/Outdoor                              | Indoor   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 2,8286 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,021944                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 1 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,022743                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC23: Open processing and transfer operations at substantially elevated temperature<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state   | Solid, low dustiness  |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 1,4143 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,010972  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 1 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,022743  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|                                       |   |
|---------------------------------------|---|
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | PROC24: High (mechanical) energy work-up of substances bound in /on materials and/or articles<br>Use domain: industrial |



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$ |
| Physical state   | Solid, low dustiness                                    |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week                                 |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - dermal, long-term - systemic                   |
| Exposure estimate  | 2,8286 mg/kg bw/day                                     |
| Risk Characterization Ratio (RCR)  | 0,021944  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - inhalation, long-term - systemic               |
| Exposure estimate  | 1 mg/m <sup>3</sup>                                     |
| Risk Characterization Ratio (RCR)  | 0,022743  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PROC25: Other hot work operations with metals<br>Use domain: industrial |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$                 |
| Physical state                                       | Solid, low dustiness  |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | 480 min 5 days per week   |
| Indoor/Outdoor                                       | Indoor  |
| <b>Risk Management Measures</b>                      |   |
| Use suitable eye protection.                         |   |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker                                  |
|  | Worker - dermal, long-term - systemic                                   |
| Exposure estimate                                    | 0,2829 mg/kg bw/day   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Risk Characterization Ratio (RCR)  | 0,002194                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 5 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,113714                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>   |   |
| <b>Use descriptors covered</b>  | PROC26: Handling of solid inorganic substances at ambient temperature<br>Use domain: industrial |
| <b>Operational conditions</b>   |   |
| Physical state  | Solid, medium dustiness   |
| Vapour pressure of the substance during use   | 130 Pa  |
| Process temperature   | 20 °C   |
| <b>Risk Management Measures</b>   |   |
| Use suitable eye protection.  |   |
| <b>Exposure estimate and reference to its source</b>  |   |
| Assessment method   | Qualitative assessment  |
| <b>Additional good practice advice</b>  |   |
| There is no corresponding TRA entry concerning PROC 26 and thus, calculation of PROC 26 with TRA is not possible. To approximately map the activities described by PROC 26, PROC 5, 8b and 9 were used. PROC 8b and 9 were used to address the transfer, packaging, unpacking, and weighing while PROC 5 addresses mixing and blending activities |   |
| There is no corresponding TRA entry concerning PROC 26 and thus, calculation of PROC 26 with TRA is not possible. To approximately map the activities described by PROC 26, PROC 5, 8b and 9 were used. PROC 8b and 9 were used to address the transfer, packaging, unpacking, and weighing while PROC 5 addresses mixing and blending activities |   |

\*\*\*\*\*

## 5. Short title of exposure scenario

Production of pharmaceutical products, Use in Personal care products, Use in/as Flavouring agent(s), Use in cosmetics, Industrial applications  
IS; SU4, SU20; ERC4; PROC5, PROC14

## Control of exposure and risk management measures

|                                       |  |
|---------------------------------------|--|
| <b>Contributing exposure scenario</b> |  |
| <b>Use descriptors covered</b>        | ERC4: Use of non-reactive processing aid at industrial site (no inclusion into or onto article)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| <b>Operational conditions</b>  |  |
| <b>Contributing exposure scenario</b>  |  |
| <b>Use descriptors covered</b>   | PROC5: Mixing or blending in batch processes<br>Use domain: industrial |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$                |
| Physical state   | Solid, medium dustiness  |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | 480 min 5 days per week  |
| Indoor/Outdoor   | Indoor   |
| <b>Risk Management Measures</b>  |  |
| Use suitable eye protection.   |  |
| <b>Exposure estimate and reference to its source</b>                               |  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                                 |
|  | Worker - dermal, long-term - systemic                                  |
| Exposure estimate  | 13,7143 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,106395   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                                 |
|  | Worker - inhalation, long-term - systemic                              |
| Exposure estimate  | 5 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,113714   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |  |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PROC14: Tableting, compression, extrusion, pelletisation, granulation<br>Use domain: industrial |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$   |
| Physical state                              | Solid, medium dustiness   |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |
| Duration and Frequency of activity          | 480 min 5 days per week   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Indoor/Outdoor   | Indoor                                    |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 3,4286 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,026599                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 1 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,022743                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

\*\*\*\*\*

## 6. Short title of exposure scenario

Use in Batteries, Production, (solid preparations), Industrial applications

IS; SU6b, SU8, SU16; ERC5; PROC2, PROC3, PROC4, PROC5, PROC6, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15, PROC19, PROC21, PROC26

## Control of exposure and risk management measures

|   |  |
|---|--|
| <b>Contributing exposure scenario</b>       |  |
| <b>Use descriptors covered</b>              | ERC5: Use at industrial site leading to inclusion into/onto article<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
| <b>Operational conditions</b>               |  |
| <b>Contributing exposure scenario</b>       |  |
| <b>Use descriptors covered</b>              | PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions<br>Use domain: industrial                  |
| <b>Operational conditions</b>               |  |
| Concentration of the substance              | ammonium chloride<br>Content: >= 0 % - <= 100 %  |
| Physical state                              | Solid, medium dustiness  |
| Vapour pressure of the substance during use | 130 Pa   |
| Process temperature                         | 20 °C  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Duration and Frequency of activity   | 480 min 5 days per week                   |
| Indoor/Outdoor   | Indoor                                    |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 1,3714 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,010639                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 0,5 mg/m <sup>3</sup>                     |
| Risk Characterization Ratio (RCR)  | 0,011371                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 0,6857 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,00532   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 1 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,022743  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

| <b>Contributing exposure scenario</b>  |  |
|--|--|
| <b>Use descriptors covered</b>   | PROC4: Chemical production where opportunity for exposure arises<br>Use domain: industrial |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$                                    |
| Physical state   | Solid, medium dustiness  |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | 480 min 5 days per week  |
| Indoor/Outdoor   | Indoor   |
| <b>Risk Management Measures</b>  |  |
| Use suitable eye protection.   |  |
| <b>Exposure estimate and reference to its source</b>                               |  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - dermal, long-term - systemic  |
| Exposure estimate  | 6,8571 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,053197   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - inhalation, long-term - systemic  |
| Exposure estimate  | 5 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,113714   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |  |

| <b>Contributing exposure scenario</b>       |  |
|---|--|
| <b>Use descriptors covered</b>              | PROC5: Mixing or blending in batch processes<br>Use domain: industrial |
| <b>Operational conditions</b>               |  |
| Concentration of the substance              | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$                |
| Physical state                              | Solid, medium dustiness  |
| Vapour pressure of the substance during use | 130 Pa   |
| Process temperature                         | 20 °C  |
| Duration and Frequency of activity          | 480 min 5 days per week  |
| Indoor/Outdoor                              | Indoor   |
| <b>Risk Management Measures</b>             |  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 13,7143 mg/kg bw/day                      |
| Risk Characterization Ratio (RCR)  | 0,106395                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 5 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,113714                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC6: Calendering operations<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %         |
| Physical state   | Solid, medium dustiness                                 |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week                                 |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - dermal, long-term - systemic                   |
| Exposure estimate  | 27,4286 mg/kg bw/day                                    |
| Risk Characterization Ratio (RCR)  | 0,21279   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - inhalation, long-term - systemic               |
| Exposure estimate  | 5 mg/m <sup>3</sup>                                     |
| Risk Characterization Ratio (RCR)  | 0,113714  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|                                       |   |
|---------------------------------------|---|
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities<br>Use domain: industrial |
| <b>Operational conditions</b>         |   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$ |
| Physical state   | Solid, medium dustiness                                 |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week                                 |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - dermal, long-term - systemic                   |
| Exposure estimate  | 13,7143 mg/kg bw/day                                    |
| Risk Characterization Ratio (RCR)  | 0,106395  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - inhalation, long-term - systemic               |
| Exposure estimate  | 1 mg/m <sup>3</sup>                                     |
| Risk Characterization Ratio (RCR)  | 0,022743  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing).<br>Use domain: industrial |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$   |
| Physical state                                       | Solid, medium dustiness   |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | 480 min 5 days per week   |
| Indoor/Outdoor                                       | Indoor  |
| <b>Risk Management Measures</b>                      |   |
| Use suitable eye protection.                         |   |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate                                    | 6,8571 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)                    | 0,053197  |



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 5 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,113714                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>  |  |
| <b>Use descriptors covered</b>   | PROC10: Roller application or brushing<br>Use domain: industrial |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %                  |
| Physical state   | Solid, medium dustiness  |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | 480 min 5 days per week  |
| Indoor/Outdoor   | Indoor   |
| <b>Risk Management Measures</b>  |  |
| Use suitable eye protection.   |  |
| <b>Exposure estimate and reference to its source</b>                               |  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                           |
|  | Worker - dermal, long-term - systemic                            |
| Exposure estimate  | 27,4286 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,21279  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                           |
|  | Worker - inhalation, long-term - systemic                        |
| Exposure estimate  | 5 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,113714   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |  |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PROC13: Treatment of articles by dipping and pouring.<br>Use domain: industrial |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: >= 0 % - <= 100 %                                 |
| Physical state                              | Solid, medium dustiness   |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Duration and Frequency of activity   | 480 min 5 days per week                   |
| Indoor/Outdoor   | Indoor                                    |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 13,7143 mg/kg bw/day                      |
| Risk Characterization Ratio (RCR)  | 0,106395                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 1 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,022743                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| Use descriptors covered  | PROC14: Tableting, compression, extrusion, pelletisation, granulation<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 3,4286 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,026599  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 1 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,022743  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC15: Use a laboratory reagent.<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$     |
| Physical state   | Solid, medium dustiness                                     |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week                                     |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                      |
|  | Worker - dermal, long-term - systemic                       |
| Exposure estimate  | 0,3429 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,00266   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                      |
|  | Worker - inhalation, long-term - systemic                   |
| Exposure estimate  | 0,5 mg/m <sup>3</sup>                                       |
| Risk Characterization Ratio (RCR)  | 0,011371  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|   |  |
|---|--|
| <b>Contributing exposure scenario</b>       |  |
| <b>Use descriptors covered</b>              | PROC19: Manual activities involving hand contact<br>Use domain: industrial |
| <b>Operational conditions</b>               |  |
| Concentration of the substance              | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$                    |
| Physical state                              | Solid, medium dustiness  |
| Vapour pressure of the substance during use | 130 Pa   |
| Process temperature                         | 20 °C  |
| Duration and Frequency of activity          | 480 min 5 days per week  |
| Indoor/Outdoor                              | Indoor   |
| <b>Risk Management Measures</b>             |  |
| Use suitable chemically resistant gloves.   | Effectiveness: 80 %  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 28,2857 mg/kg bw/day                      |
| Risk Characterization Ratio (RCR)  | 0,219439                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 5 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,113714                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>  |  |
| <b>Use descriptors covered</b>   | PROC21: Low energy manipulation and handling of substances bound in/on materials or articles<br>Use domain: industrial |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %  |
| Physical state   | Solid, medium dustiness  |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | 480 min 5 days per week  |
| Indoor/Outdoor   | Indoor   |
| <b>Risk Management Measures</b>  |  |
| Use suitable eye protection.   |  |
| <b>Exposure estimate and reference to its source</b>                               |  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - dermal, long-term - systemic  |
| Exposure estimate  | 2,8286 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,021944   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - inhalation, long-term - systemic  |
| Exposure estimate  | 3 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,068228   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |  |

|                                       |   |
|---------------------------------------|---|
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | PROC26: Handling of solid inorganic substances at ambient temperature<br>Use domain: industrial |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|   |                         |
|---|-------------------------|
| <b>Operational conditions</b>   |                         |
| Physical state  | Solid, medium dustiness |
| Vapour pressure of the substance during use   | 130 Pa                  |
| Process temperature   | 20 °C                   |
| <b>Risk Management Measures</b>   |                         |
| Use suitable eye protection.  |                         |
| <b>Exposure estimate and reference to its source</b>  |                         |
| Assessment method   | Qualitative assessment  |
| <b>Additional good practice advice</b>  |                         |
| There is no corresponding TRA entry concerning PROC 26 and thus, calculation of PROC 26 with TRA is not possible. To approximately map the activities described by PROC 26, PROC 5, 8b and 9 were used. PROC 8b and 9 were used to address the transfer, packaging, unpacking, and weighing while PROC 5 addresses mixing and blending activities |                         |
| There is no corresponding TRA entry concerning PROC 26 and thus, calculation of PROC 26 with TRA is not possible. To approximately map the activities described by PROC 26, PROC 5, 8b and 9 were used. PROC 8b and 9 were used to address the transfer, packaging, unpacking, and weighing while PROC 5 addresses mixing and blending activities |                         |

\*\*\*\*\*

## 7. Short title of exposure scenario

Use as an intermediate, Production of Fertilizers, Formulation of catalysts, Industrial applications IS; SU1, SU8; ERC6a; PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC13, PROC14, PROC15, PROC26

## Control of exposure and risk management measures

|                                       |   |
|---------------------------------------|---|
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | ERC6a: Use of intermediate<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.                         |
| <b>Operational conditions</b>         |   |
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions<br>Use domain: industrial |
| <b>Operational conditions</b>         |   |
| Concentration of the substance        | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state                        | Solid, medium dustiness   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Vapour pressure of the substance during use  | 130 Pa                                    |
| Process temperature  | 20 °C                                     |
| Duration and Frequency of activity   | 480 min 5 days per week                   |
| Indoor/Outdoor   | Indoor                                    |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 1,3714 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,010639                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 0,5 mg/m <sup>3</sup>                     |
| Risk Characterization Ratio (RCR)  | 0,011371                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition<br>Use domain: industrial |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state                                       | Solid, medium dustiness   |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | 480 min 5 days per week   |
| Indoor/Outdoor                                       | Indoor  |
| <b>Risk Management Measures</b>                      |   |
| Use suitable eye protection.                         |   |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate                                    | 0,6857 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)                    | 0,00532   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |                     |
|--|---------------------|
| Exposure estimate  | 1 mg/m <sup>3</sup> |
| Risk Characterization Ratio (RCR)  | 0,022743            |
| <b>Guidance to Downstream Users</b>  |                     |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |                     |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>  |  |
| <b>Use descriptors covered</b>   | PROC4: Chemical production where opportunity for exposure arises<br>Use domain: industrial |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %  |
| Physical state   | Solid, medium dustiness  |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | 480 min 5 days per week  |
| Indoor/Outdoor   | Indoor   |
| <b>Risk Management Measures</b>  |  |
| Use suitable eye protection.   |  |
| <b>Exposure estimate and reference to its source</b>                               |  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - dermal, long-term - systemic  |
| Exposure estimate  | 6,8571 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,053197   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - inhalation, long-term - systemic  |
| Exposure estimate  | 5 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,113714   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |  |

|   |  |
|---|--|
| <b>Contributing exposure scenario</b>       |  |
| <b>Use descriptors covered</b>              | PROC5: Mixing or blending in batch processes<br>Use domain: industrial |
| <b>Operational conditions</b>               |  |
| Concentration of the substance              | ammonium chloride<br>Content: >= 0 % - <= 100 %                        |
| Physical state                              | Solid, medium dustiness  |
| Vapour pressure of the substance during use | 130 Pa   |
| Process temperature                         | 20 °C  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Duration and Frequency of activity   | 480 min 5 days per week                   |
| Indoor/Outdoor   | Indoor                                    |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 13,7143 mg/kg bw/day                      |
| Risk Characterization Ratio (RCR)  | 0,106395                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 5 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,113714                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 13,7143 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,106395  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 5 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,113714  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|                                       |
|---------------------------------------|
| <b>Contributing exposure scenario</b> |
|---------------------------------------|



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| <b>Use descriptors covered</b>   | PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$   |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 13,7143 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,106395  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 1 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,022743  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing).<br>Use domain: industrial |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$   |
| Physical state                              | Solid, medium dustiness   |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |
| Duration and Frequency of activity          | 480 min 5 days per week   |
| Indoor/Outdoor                              | Indoor  |
| <b>Risk Management Measures</b>             |   |
| Use suitable eye protection.                |   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

| <b>Exposure estimate and reference to its source</b>                               |   |
|--|---|
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 6,8571 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,053197                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 5 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,113714                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

| <b>Contributing exposure scenario</b>  |   |
|--|---|
| <b>Use descriptors covered</b>   | PROC13: Treatment of articles by dipping and pouring.<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %                                 |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 13,7143 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,106395  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic                                       |
| Exposure estimate  | 1 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,022743  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

| <b>Contributing exposure scenario</b> |   |
|---------------------------------------|---|
| <b>Use descriptors covered</b>        | PROC14: Tableting, compression, extrusion, pelletisation, granulation<br>Use domain: industrial |
| <b>Operational conditions</b>         |   |
| Concentration of the substance        | ammonium chloride   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
|  | Content: $\geq 0\%$ - $\leq 100\%$        |
| Physical state   | Solid, medium dustiness                   |
| Vapour pressure of the substance during use  | 130 Pa                                    |
| Process temperature  | 20 °C                                     |
| Duration and Frequency of activity   | 480 min 5 days per week                   |
| Indoor/Outdoor   | Indoor                                    |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 3,4286 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,026599                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 1 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,022743                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PROC15: Use a laboratory reagent.<br>Use domain: industrial |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$     |
| Physical state                                       | Solid, medium dustiness                                     |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | 480 min 5 days per week                                     |
| Indoor/Outdoor                                       | Indoor  |
| <b>Risk Management Measures</b>                      |   |
| Use suitable eye protection.                         |   |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker                      |
|  | Worker - dermal, long-term - systemic                       |
| Exposure estimate                                    | 0,3429 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)                    | 0,00266   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker                      |
|  | Worker - inhalation, long-term - systemic                   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |                       |
|--|-----------------------|
| Exposure estimate  | 0,5 mg/m <sup>3</sup> |
| Risk Characterization Ratio (RCR)  | 0,011371              |
| <b>Guidance to Downstream Users</b>  |                       |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |                       |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>   |   |
| <b>Use descriptors covered</b>  | PROC26: Handling of solid inorganic substances at ambient temperature<br>Use domain: industrial |
| <b>Operational conditions</b>   |   |
| Physical state  | Solid, medium dustiness   |
| Vapour pressure of the substance during use   | 130 Pa  |
| Process temperature   | 20 °C   |
| <b>Risk Management Measures</b>   |   |
| Use suitable eye protection.  |   |
| <b>Exposure estimate and reference to its source</b>  |   |
| Assessment method   | Qualitative assessment  |
| <b>Additional good practice advice</b>  |   |
| There is no corresponding TRA entry concerning PROC 26 and thus, calculation of PROC 26 with TRA is not possible. To approximately map the activities described by PROC 26, PROC 5, 8b and 9 were used. PROC 8b and 9 were used to address the transfer, packaging, unpacking, and weighing while PROC 5 addresses mixing and blending activities |   |
| There is no corresponding TRA entry concerning PROC 26 and thus, calculation of PROC 26 with TRA is not possible. To approximately map the activities described by PROC 26, PROC 5, 8b and 9 were used. PROC 8b and 9 were used to address the transfer, packaging, unpacking, and weighing while PROC 5 addresses mixing and blending activities |   |

\*\*\*\*\*

## 8. Short title of exposure scenario

Use as Reactive process agent, Use in Metallurgy, Use in Metal surface treatment, Use in Textile finishing, Use in leather tanning, finishing, impregnation, Use in Biotechnology, Industrial applications IS; SU5, SU9, SU14, SU15, SU24; ERC6b; PROC2, PROC3, PROC4, PROC5, PROC6, PROC8b, PROC9, PROC10, PROC13, PROC15, PROC22, PROC23, PROC25, PROC26

## Control of exposure and risk management measures

|                                       |   |
|---------------------------------------|---|
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | ERC6b: Use of reactive processing aid at industrial site (no inclusion into or onto article)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
| <b>Operational conditions</b>         |   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

| <b>Contributing exposure scenario</b>  |   |
|--|---|
| <b>Use descriptors covered</b>   | PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$   |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 1,3714 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,010639  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 0,5 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,011371  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

| <b>Contributing exposure scenario</b>       |   |
|---|---|
| <b>Use descriptors covered</b>              | PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition<br>Use domain: industrial |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$   |
| Physical state                              | Solid, medium dustiness   |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Duration and Frequency of activity   | 480 min 5 days per week                   |
| Indoor/Outdoor   | Indoor                                    |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 0,6857 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,00532                                   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 1 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,022743                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>  |  |
| <b>Use descriptors covered</b>   | PROC4: Chemical production where opportunity for exposure arises<br>Use domain: industrial |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %  |
| Physical state   | Solid, medium dustiness  |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | 480 min 5 days per week  |
| Indoor/Outdoor   | Indoor   |
| <b>Risk Management Measures</b>  |  |
| Use suitable eye protection.   |  |
| <b>Exposure estimate and reference to its source</b>                               |  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - dermal, long-term - systemic  |
| Exposure estimate  | 6,8571 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,053197   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - inhalation, long-term - systemic  |
| Exposure estimate  | 5 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,113714   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |  |

**Contributing exposure scenario**

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| <b>Use descriptors covered</b>   | PROC5: Mixing or blending in batch processes<br>Use domain: industrial |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$                |
| Physical state   | Solid, medium dustiness  |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | 480 min 5 days per week  |
| Indoor/Outdoor   | Indoor   |
| <b>Risk Management Measures</b>  |  |
| Use suitable eye protection.   |  |
| <b>Exposure estimate and reference to its source</b>                               |  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                                 |
|  | Worker - dermal, long-term - systemic                                  |
| Exposure estimate  | 13,7143 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,106395   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                                 |
|  | Worker - inhalation, long-term - systemic                              |
| Exposure estimate  | 5 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,113714   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |  |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PROC6: Calendering operations<br>Use domain: industrial |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$ |
| Physical state                                       | Solid, medium dustiness                                 |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | 480 min 5 days per week                                 |
| Indoor/Outdoor                                       | Indoor  |
| <b>Risk Management Measures</b>                      |   |
| Use suitable eye protection.                         |   |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 27,4286 mg/kg bw/day                      |
| Risk Characterization Ratio (RCR)  | 0,21279                                   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 5 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,113714                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 13,7143 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,106395  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 1 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,022743  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|                                       |   |
|---------------------------------------|---|
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing).<br>Use domain: industrial |
| <b>Operational conditions</b>         |   |
| Concentration of the substance        | ammonium chloride<br>Content: >= 0 % - <= 100 %   |



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Physical state   | Solid, medium dustiness                   |
| Vapour pressure of the substance during use  | 130 Pa                                    |
| Process temperature  | 20 °C                                     |
| Duration and Frequency of activity   | 480 min 5 days per week                   |
| Indoor/Outdoor   | Indoor                                    |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 6,8571 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,053197                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 5 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,113714                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>                |  |
| <b>Use descriptors covered</b>                       | PROC10: Roller application or brushing<br>Use domain: industrial |
| <b>Operational conditions</b>                        |  |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 100 %                  |
| Physical state                                       | Solid, medium dustiness  |
| Vapour pressure of the substance during use          | 130 Pa   |
| Process temperature                                  | 20 °C  |
| Duration and Frequency of activity                   | 480 min 5 days per week  |
| Indoor/Outdoor                                       | Indoor   |
| <b>Risk Management Measures</b>                      |  |
| Use suitable eye protection.                         |  |
| <b>Exposure estimate and reference to its source</b> |  |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker                           |
|  | Worker - dermal, long-term - systemic                            |
| Exposure estimate                                    | 27,4286 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)                    | 0,21279  |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker                           |
|  | Worker - inhalation, long-term - systemic                        |
| Exposure estimate                                    | 5 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)                    | 0,113714   |
| <b>Guidance to Downstream Users</b>                  |  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

For scaling see: <http://www.ecetoc.org/tra>

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC13: Treatment of articles by dipping and pouring.<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$                         |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 13,7143 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,106395  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic                                       |
| Exposure estimate  | 1 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,022743  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PROC15: Use a laboratory reagent.<br>Use domain: industrial |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$     |
| Physical state                              | Solid, medium dustiness                                     |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |
| Duration and Frequency of activity          | 480 min 5 days per week                                     |
| Indoor/Outdoor                              | Indoor  |
| <b>Risk Management Measures</b>             |   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 0,3429 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,00266                                   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 0,5 mg/m <sup>3</sup>                     |
| Risk Characterization Ratio (RCR)  | 0,011371                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>  |  |
| <b>Use descriptors covered</b>   | PROC22: Manufacturing and processing of minerals and/or metals at substantially elevated temperature<br>Use domain: industrial |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %  |
| Physical state   | Solid, low dustiness   |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | 480 min 5 days per week  |
| Indoor/Outdoor   | Indoor   |
| <b>Risk Management Measures</b>  |  |
| Use suitable eye protection.   |  |
| <b>Exposure estimate and reference to its source</b>                               |  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - dermal, long-term - systemic  |
| Exposure estimate  | 2,8286 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,021944   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - inhalation, long-term - systemic  |
| Exposure estimate  | 1 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,022743   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |  |

|                                       |   |
|---------------------------------------|---|
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | PROC23: Open processing and transfer operations at substantially elevated temperature<br>Use domain: industrial |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

| <b>Operational conditions</b>  |   |
|--|---|
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$ |
| Physical state   | Solid, low dustiness                                    |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week                                 |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - dermal, long-term - systemic                   |
| Exposure estimate  | 1,4143 mg/kg bw/day                                     |
| Risk Characterization Ratio (RCR)  | 0,010972  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - inhalation, long-term - systemic               |
| Exposure estimate  | 1 mg/m <sup>3</sup>                                     |
| Risk Characterization Ratio (RCR)  | 0,022743  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

| <b>Contributing exposure scenario</b>                |   |
|--|---|
| <b>Use descriptors covered</b>                       | PROC25: Other hot work operations with metals<br>Use domain: industrial |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$                 |
| Physical state                                       | Solid, low dustiness  |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | 480 min 5 days per week   |
| Indoor/Outdoor                                       | Indoor  |
| <b>Risk Management Measures</b>                      |   |
| Use suitable eye protection.                         |   |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker                                  |
|  | Worker - dermal, long-term - systemic                                   |
| Exposure estimate                                    | 0,2829 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)                    | 0,002194  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 5 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,113714                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>   |   |
| <b>Use descriptors covered</b>  | PROC26: Handling of solid inorganic substances at ambient temperature<br>Use domain: industrial |
| <b>Operational conditions</b>   |   |
| Physical state  | Solid, medium dustiness   |
| Vapour pressure of the substance during use   | 130 Pa  |
| Process temperature   | 20 °C   |
| <b>Risk Management Measures</b>   |   |
| Use suitable eye protection.  |   |
| <b>Exposure estimate and reference to its source</b>  |   |
| Assessment method   | Qualitative assessment  |
| <b>Additional good practice advice</b>  |   |
| There is no corresponding TRA entry concerning PROC 26 and thus, calculation of PROC 26 with TRA is not possible. To approximately map the activities described by PROC 26, PROC 5, 8b and 9 were used. PROC 8b and 9 were used to address the transfer, packaging, unpacking, and weighing while PROC 5 addresses mixing and blending activities |   |
| There is no corresponding TRA entry concerning PROC 26 and thus, calculation of PROC 26 with TRA is not possible. To approximately map the activities described by PROC 26, PROC 5, 8b and 9 were used. PROC 8b and 9 were used to address the transfer, packaging, unpacking, and weighing while PROC 5 addresses mixing and blending activities |   |

\*\*\*\*\*

## 9. Short title of exposure scenario

Use as Cross-linking agent, Production of woodbased materials (panels, bricks, etc), Production of bonded fibers or fiber mats

IS; SU6a; ERC6d; PROC6, PROC14

## Control of exposure and risk management measures

|                                       |  |
|---------------------------------------|--|
| <b>Contributing exposure scenario</b> |  |
| <b>Use descriptors covered</b>        | ERC6d: Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| <b>Operational conditions</b>  |   |
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC6: Calendering operations<br>Use domain: industrial |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$ |
| Physical state   | Solid, medium dustiness                                 |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week                                 |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - dermal, long-term - systemic                   |
| Exposure estimate  | 27,4286 mg/kg bw/day                                    |
| Risk Characterization Ratio (RCR)  | 0,21279   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - inhalation, long-term - systemic               |
| Exposure estimate  | 5 mg/m <sup>3</sup>                                     |
| Risk Characterization Ratio (RCR)  | 0,113714  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PROC14: Tableting, compression, extrusion, pelletisation, granulation<br>Use domain: industrial |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$   |
| Physical state                              | Solid, medium dustiness   |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |
| Duration and Frequency of activity          | 480 min 5 days per week   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Indoor/Outdoor   | Indoor                                    |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 3,4286 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,026599                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 1 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,022743                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

\*\*\*\*\*

## 10. Short title of exposure scenario

Use as a Process chemical, Professional applications, (indoor use)

PW; SU1, SU8; ERC8a; PROC2, PROC3, PROC4, PROC5, PROC8b, PROC9, PROC13, PROC14, PROC15, PROC19, PROC26

## Control of exposure and risk management measures

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
| <b>Operational conditions</b>               |   |
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions<br>Use domain: professional   |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state                              | Solid, medium dustiness   |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Duration and Frequency of activity   | 480 min 5 days per week                   |
| Indoor/Outdoor   | Indoor                                    |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 1,3714 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,010639                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 1 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,022743                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition<br>Use domain: professional |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 0,6857 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,00532   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 1 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,022743  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>  |  |
| <b>Use descriptors covered</b>   | PROC4: Chemical production where opportunity for exposure arises<br>Use domain: professional |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$                                      |
| Physical state   | Solid, medium dustiness  |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | 480 min 5 days per week  |
| Indoor/Outdoor   | Indoor   |
| <b>Risk Management Measures</b>  |  |
| Use suitable eye protection.   |  |
| <b>Exposure estimate and reference to its source</b>                               |  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - dermal, long-term - systemic  |
| Exposure estimate  | 6,8571 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,053197   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - inhalation, long-term - systemic  |
| Exposure estimate  | 5 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,113714   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |  |

|   |  |
|---|--|
| <b>Contributing exposure scenario</b>       |  |
| <b>Use descriptors covered</b>              | PROC5: Mixing or blending in batch processes<br>Use domain: professional |
| <b>Operational conditions</b>               |  |
| Concentration of the substance              | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$                  |
| Physical state                              | Solid, medium dustiness  |
| Vapour pressure of the substance during use | 130 Pa   |
| Process temperature                         | 20 °C  |
| Duration and Frequency of activity          | 480 min 5 days per week  |
| Indoor/Outdoor                              | Indoor   |
| <b>Risk Management Measures</b>             |  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 13,7143 mg/kg bw/day                      |
| Risk Characterization Ratio (RCR)  | 0,106395                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 5 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,113714                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities<br>Use domain: professional |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 13,7143 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,106395  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 5 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,113714  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|                                       |   |
|---------------------------------------|---|
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing).<br>Use domain: professional |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$ |
| Physical state   | Solid, medium dustiness                                 |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week                                 |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - dermal, long-term - systemic                   |
| Exposure estimate  | 6,8571 mg/kg bw/day                                     |
| Risk Characterization Ratio (RCR)  | 0,053197  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - inhalation, long-term - systemic               |
| Exposure estimate  | 5 mg/m <sup>3</sup>                                     |
| Risk Characterization Ratio (RCR)  | 0,113714  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PROC13: Treatment of articles by dipping and pouring.<br>Use domain: professional |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$                           |
| Physical state                                       | Solid, medium dustiness   |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | 480 min 5 days per week   |
| Indoor/Outdoor                                       | Indoor  |
| <b>Risk Management Measures</b>                      |   |
| Use suitable eye protection.                         |   |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate                                    | 13,7143 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)                    | 0,106395  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 5 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,113714                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC14: Tableting, compression, extrusion, pelletisation, granulation<br>Use domain: professional |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 3,4286 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,026599  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 5 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,113714  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PROC15: Use a laboratory reagent.<br>Use domain: professional |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: >= 0 % - <= 100 %               |
| Physical state                              | Solid, medium dustiness                                       |
| Vapour pressure of the substance during use | 130 Pa  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Process temperature  | 20 °C                                     |
| Duration and Frequency of activity   | 480 min 5 days per week                   |
| Indoor/Outdoor   | Indoor                                    |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 0,3429 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,00266                                   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 0,5 mg/m <sup>3</sup>                     |
| Risk Characterization Ratio (RCR)  | 0,011371                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>                |  |
| <b>Use descriptors covered</b>                       | PROC19: Manual activities involving hand contact<br>Use domain: professional |
| <b>Operational conditions</b>                        |  |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 100 %                              |
| Physical state                                       | Solid, medium dustiness  |
| Vapour pressure of the substance during use          | 130 Pa   |
| Process temperature                                  | 20 °C  |
| Duration and Frequency of activity                   | 480 min 5 days per week  |
| Indoor/Outdoor                                       | Indoor   |
| <b>Risk Management Measures</b>                      |  |
| Use suitable chemically resistant gloves.            | Effectiveness: 80 %  |
| Use suitable eye protection.                         |  |
| <b>Exposure estimate and reference to its source</b> |  |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker                                       |
|  | Worker - dermal, long-term - systemic  |
| Exposure estimate                                    | 28,2857 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)                    | 0,219439   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker                                       |
|  | Worker - inhalation, long-term - systemic                                    |
| Exposure estimate                                    | 5 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)                    | 0,113714   |
| <b>Guidance to Downstream Users</b>                  |  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

For scaling see: <http://www.ecetoc.org/tra>

| <b>Contributing exposure scenario</b>   |   |
|---|---|
| <b>Use descriptors covered</b>  | PROC26: Handling of solid inorganic substances at ambient temperature<br>Use domain: professional |
| <b>Operational conditions</b>   |   |
| Physical state  | Solid, medium dustiness   |
| Vapour pressure of the substance during use   | 130 Pa  |
| Process temperature   | 20 °C   |
| <b>Risk Management Measures</b>   |   |
| Use suitable eye protection.  |   |
| <b>Exposure estimate and reference to its source</b>  |   |
| Assessment method   | Qualitative assessment  |
| <b>Additional good practice advice</b>  |   |
| There is no corresponding TRA entry concerning PROC 26 and thus, calculation of PROC 26 with TRA is not possible. To approximately map the activities described by PROC 26, PROC 5, 8b and 9 were used. PROC 8b and 9 were used to address the transfer, packaging, unpacking, and weighing while PROC 5 addresses mixing and blending activities |   |
| There is no corresponding TRA entry concerning PROC 26 and thus, calculation of PROC 26 with TRA is not possible. To approximately map the activities described by PROC 26, PROC 5, 8b and 9 were used. PROC 8b and 9 were used to address the transfer, packaging, unpacking, and weighing while PROC 5 addresses mixing and blending activities |   |

\*\*\*\*\*

## 11. Short title of exposure scenario

Use as Reactive process agent, Use in/as Fertilizers, Use in Metallurgy, Use in Metal surface treatment, Use in Textile finishing, Use in Biotechnology, Professional applications, (indoor use)  
PW; SU5, SU14, SU15; ERC8b; PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC11, PROC13, PROC14, PROC15, PROC19, PROC23, PROC26

## Control of exposure and risk management measures

| <b>Contributing exposure scenario</b> |   |
|---------------------------------------|---|
| <b>Use descriptors covered</b>        | ERC8b: Widespread use of reactive processing aid (no inclusion into or onto article, indoor)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
| <b>Operational conditions</b>         |   |
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | PROC2: Chemical production or refinery in closed  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
|  | continuous process with occasional controlled exposure or processes with equivalent containment conditions<br>Use domain: professional |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$  |
| Physical state   | Solid, medium dustiness  |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | 480 min 5 days per week  |
| Indoor/Outdoor   | Indoor   |
| <b>Risk Management Measures</b>  |  |
| Use suitable eye protection.   |  |
| <b>Exposure estimate and reference to its source</b>                               |  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - dermal, long-term - systemic  |
| Exposure estimate  | 1,3714 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,010639   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - inhalation, long-term - systemic  |
| Exposure estimate  | 1 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,022743   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |  |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition<br>Use domain: professional |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$   |
| Physical state                              | Solid, medium dustiness   |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |
| Duration and Frequency of activity          | 480 min 5 days per week   |
| Indoor/Outdoor                              | Indoor  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 0,6857 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,00532                                   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 1 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,022743                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>  |  |
| <b>Use descriptors covered</b>   | PROC4: Chemical production where opportunity for exposure arises<br>Use domain: professional |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %  |
| Physical state   | Solid, medium dustiness  |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | 480 min 5 days per week  |
| Indoor/Outdoor   | Indoor   |
| <b>Risk Management Measures</b>  |  |
| Use suitable eye protection.   |  |
| <b>Exposure estimate and reference to its source</b>                               |  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - dermal, long-term - systemic  |
| Exposure estimate  | 6,8571 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,053197   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - inhalation, long-term - systemic  |
| Exposure estimate  | 5 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,113714   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |  |

|                                       |  |
|---------------------------------------|--|
| <b>Contributing exposure scenario</b> |  |
| <b>Use descriptors covered</b>        | PROC5: Mixing or blending in batch processes<br>Use domain: professional |



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$ |
| Physical state   | Solid, medium dustiness                                 |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week                                 |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - dermal, long-term - systemic                   |
| Exposure estimate  | 13,7143 mg/kg bw/day                                    |
| Risk Characterization Ratio (RCR)  | 0,106395  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - inhalation, long-term - systemic               |
| Exposure estimate  | 5 mg/m <sup>3</sup>                                     |
| Risk Characterization Ratio (RCR)  | 0,113714  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PROC6: Calendering operations<br>Use domain: professional |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$   |
| Physical state                                       | Solid, medium dustiness                                   |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | 480 min 5 days per week                                   |
| Indoor/Outdoor                                       | Indoor  |
| <b>Risk Management Measures</b>                      |   |
| Use suitable eye protection.                         |   |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker                    |
|  | Worker - dermal, long-term - systemic                     |
| Exposure estimate                                    | 27,4286 mg/kg bw/day                                      |
| Risk Characterization Ratio (RCR)                    | 0,21279   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 5 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,113714                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities<br>Use domain: professional |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 13,7143 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,106395  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 10 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,227428  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|                                       |   |
|---------------------------------------|---|
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities<br>Use domain: professional |
| <b>Operational conditions</b>         |   |
| Concentration of the substance        | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state                        | Solid, medium dustiness   |
| Vapour pressure of the substance      | 130 Pa  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| during use   |   |
| Process temperature  | 20 °C                                     |
| Duration and Frequency of activity   | 480 min 5 days per week                   |
| Indoor/Outdoor   | Indoor                                    |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 13,7143 mg/kg bw/day                      |
| Risk Characterization Ratio (RCR)  | 0,106395                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 5 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,113714                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing).<br>Use domain: professional |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state                                       | Solid, medium dustiness   |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | 480 min 5 days per week   |
| Indoor/Outdoor                                       | Indoor  |
| <b>Risk Management Measures</b>                      |   |
| Use suitable eye protection.                         |   |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate                                    | 6,8571 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)                    | 0,053197  |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate                                    | 5 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)                    | 0,113714  |
| <b>Guidance to Downstream Users</b>                  |   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

For scaling see: <http://www.ecetoc.org/tra>

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC11: Non industrial spraying<br>Use domain: professional |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $< 1\%$          |
| Physical state   | liquid  |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week                                     |
| Indoor/Outdoor   | Indoor  |
|  | Any sized room  |
| Application rate   | $> 3$ l/min   |
| <b>Risk Management Measures</b>  |   |
| Ensure that the task is carried out only downward.                                 |   |
| Surface spraying with no or low compressed air use.                                |   |
| Ensure doors and windows are opened (general ventilation).                         |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                      |
|  | Worker - dermal, long-term - systemic                       |
| Exposure estimate  | 10,7143 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,083121  |
| Assessment method  | EASY TRA v4.2, Advanced REACH Tool v1.5                     |
|  | Worker - inhalation, long-term - systemic                   |
| Exposure estimate  | 12 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,272913  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|                                       |   |
|---------------------------------------|---|
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | PROC11: Non industrial spraying<br>Use domain: professional |
| <b>Operational conditions</b>         |   |
| Concentration of the substance        | ammonium chloride<br>Content: $\geq 0\%$ - $< 1\%$          |
| Physical state                        | liquid  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|   |   |
|---|---|
| Vapour pressure of the substance during use   | 130 Pa                                    |
| Process temperature   | 20 °C                                     |
| Duration and Frequency of activity  | 480 min 5 days per week                   |
| Indoor/Outdoor  | Indoor                                    |
|   | Any sized room                            |
| Application rate  | > 3 l/min                                 |
| <b>Risk Management Measures</b>   |   |
| Ensure that the task is carried out only downward.  |   |
| Ensure doors and windows are opened (general ventilation).  |   |
| Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m). |   |
| Ensure that the worker is in a personal enclosure   |   |
| Use suitable eye protection.  |   |
| <b>Exposure estimate and reference to its source</b>  |   |
| Assessment method   | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|   | Worker - dermal, long-term - systemic     |
| Exposure estimate   | 10,7143 mg/kg bw/day                      |
| Risk Characterization Ratio (RCR)   | 0,083121                                  |
| Assessment method   | EASY TRA v4.2, Advanced REACH Tool v1.5   |
|   | Worker - inhalation, long-term - systemic |
| Exposure estimate   | 21 mg/m <sup>3</sup>                      |
| Risk Characterization Ratio (RCR)   | 0,477598                                  |
| <b>Guidance to Downstream Users</b>   |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>  |   |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PROC13: Treatment of articles by dipping and pouring.<br>Use domain: professional |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: >= 0 % - <= 100 %                                   |
| Physical state                              | Solid, medium dustiness   |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |
| Duration and Frequency of activity          | 480 min 5 days per week   |
| Indoor/Outdoor                              | Indoor  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 13,7143 mg/kg bw/day                      |
| Risk Characterization Ratio (RCR)  | 0,106395                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 5 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,113714                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC14: Tableting, compression, extrusion, pelletisation, granulation<br>Use domain: professional |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 3,4286 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,026599  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 5 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,113714  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|                                       |   |
|---------------------------------------|---|
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | PROC15: Use a laboratory reagent.<br>Use domain: professional |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$ |
| Physical state   | Solid, medium dustiness                                 |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week                                 |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - dermal, long-term - systemic                   |
| Exposure estimate  | 0,3429 mg/kg bw/day                                     |
| Risk Characterization Ratio (RCR)  | 0,00266   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - inhalation, long-term - systemic               |
| Exposure estimate  | 0,5 mg/m <sup>3</sup>                                   |
| Risk Characterization Ratio (RCR)  | 0,011371  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>                |  |
| <b>Use descriptors covered</b>                       | PROC19: Manual activities involving hand contact<br>Use domain: professional |
| <b>Operational conditions</b>                        |  |
| Concentration of the substance                       | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$                      |
| Physical state                                       | Solid, medium dustiness  |
| Vapour pressure of the substance during use          | 130 Pa   |
| Process temperature                                  | 20 °C  |
| Duration and Frequency of activity                   | 480 min 5 days per week  |
| Indoor/Outdoor                                       | Indoor   |
| <b>Risk Management Measures</b>                      |  |
| Use suitable chemically resistant gloves.            | Effectiveness: 80 %  |
| Use suitable eye protection.                         |  |
| <b>Exposure estimate and reference to its source</b> |  |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker                                       |
|  | Worker - dermal, long-term - systemic  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Exposure estimate  | 28,2857 mg/kg bw/day                      |
| Risk Characterization Ratio (RCR)  | 0,219439                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 5 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,113714                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC23: Open processing and transfer operations at substantially elevated temperature<br>Use domain: professional |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state   | Solid, low dustiness  |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 1,4143 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,010972  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 3 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,068228  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PROC26: Handling of solid inorganic substances at ambient temperature<br>Use domain: professional |
| <b>Operational conditions</b>               |   |
| Physical state                              | Solid, medium dustiness   |
| Vapour pressure of the substance during use | 130 Pa  |



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|   |                        |
|---|------------------------|
| Process temperature   | 20 °C                  |
| <b>Risk Management Measures</b>   |                        |
| Use suitable eye protection.  |                        |
| <b>Exposure estimate and reference to its source</b>  |                        |
| Assessment method   | Qualitative assessment |
| <b>Additional good practice advice</b>  |                        |
| There is no corresponding TRA entry concerning PROC 26 and thus, calculation of PROC 26 with TRA is not possible. To approximately map the activities described by PROC 26, PROC 5, 8b and 9 were used. PROC 8b and 9 were used to address the transfer, packaging, unpacking, and weighing while PROC 5 addresses mixing and blending activities |                        |
| There is no corresponding TRA entry concerning PROC 26 and thus, calculation of PROC 26 with TRA is not possible. To approximately map the activities described by PROC 26, PROC 5, 8b and 9 were used. PROC 8b and 9 were used to address the transfer, packaging, unpacking, and weighing while PROC 5 addresses mixing and blending activities |                        |

\*\*\*\*\*

## 12. Short title of exposure scenario

Use as a Process chemical, Professional applications, (outdoor use)

PW; SU1, SU8, SU10; ERC8d; PROC2, PROC3, PROC4, PROC5, PROC8b, PROC9, PROC13, PROC14, PROC15, PROC19, PROC26

## Control of exposure and risk management measures

|   |  |
|---|--|
| <b>Contributing exposure scenario</b>       |  |
| <b>Use descriptors covered</b>              | ERC8d: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
| <b>Operational conditions</b>               |  |
| <b>Contributing exposure scenario</b>       |  |
| <b>Use descriptors covered</b>              | PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions<br>Use domain: professional  |
| <b>Operational conditions</b>               |  |
| Concentration of the substance              | ammonium chloride<br>Content: >= 0 % - <= 100 %  |
| Physical state                              | Solid, medium dustiness  |
| Vapour pressure of the substance during use | 130 Pa   |
| Process temperature                         | 20 °C  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Duration and Frequency of activity   | 480 min 5 days per week                   |
| Indoor/Outdoor   | Outdoor                                   |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 1,3714 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,010639                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 0,7 mg/m <sup>3</sup>                     |
| Risk Characterization Ratio (RCR)  | 0,01592                                   |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition<br>Use domain: professional |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state                                       | Solid, medium dustiness   |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | 480 min 5 days per week   |
| Indoor/Outdoor                                       | Outdoor   |
| <b>Risk Management Measures</b>                      |   |
| Use suitable eye protection.                         |   |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate                                    | 0,6857 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)                    | 0,00532   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate                                    | 0,7 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)                    | 0,01592   |
| <b>Guidance to Downstream Users</b>                  |   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

For scaling see: <http://www.ecetoc.org/tra>

| <b>Contributing exposure scenario</b>  |  |
|--|--|
| <b>Use descriptors covered</b>   | PROC4: Chemical production where opportunity for exposure arises<br>Use domain: professional |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$                                      |
| Physical state   | Solid, medium dustiness  |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | 480 min 5 days per week  |
| Indoor/Outdoor   | Outdoor  |
| <b>Risk Management Measures</b>  |  |
| Use suitable eye protection.   |  |
| <b>Exposure estimate and reference to its source</b>                               |  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - dermal, long-term - systemic  |
| Exposure estimate  | 6,8571 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,053197   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - inhalation, long-term - systemic  |
| Exposure estimate  | 3,5 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,0796   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |  |

| <b>Contributing exposure scenario</b>       |  |
|---|--|
| <b>Use descriptors covered</b>              | PROC5: Mixing or blending in batch processes<br>Use domain: professional |
| <b>Operational conditions</b>               |  |
| Concentration of the substance              | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$                  |
| Physical state                              | Solid, medium dustiness  |
| Vapour pressure of the substance during use | 130 Pa   |
| Process temperature                         | 20 °C  |
| Duration and Frequency of activity          | 480 min 5 days per week  |
| Indoor/Outdoor                              | Outdoor  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 13,7143 mg/kg bw/day                      |
| Risk Characterization Ratio (RCR)  | 0,106395                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 3,5 mg/m <sup>3</sup>                     |
| Risk Characterization Ratio (RCR)  | 0,0796                                    |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities<br>Use domain: professional |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Outdoor   |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 13,7143 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,106395  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 3,5 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,0796  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|                                       |   |
|---------------------------------------|---|
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing).<br>Use domain: professional |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$ |
| Physical state   | Solid, medium dustiness                                 |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week                                 |
| Indoor/Outdoor   | Outdoor   |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - dermal, long-term - systemic                   |
| Exposure estimate  | 6,8571 mg/kg bw/day                                     |
| Risk Characterization Ratio (RCR)  | 0,053197  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - inhalation, long-term - systemic               |
| Exposure estimate  | 3,5 mg/m <sup>3</sup>                                   |
| Risk Characterization Ratio (RCR)  | 0,0796  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PROC13: Treatment of articles by dipping and pouring.<br>Use domain: professional |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$                           |
| Physical state                                       | Solid, medium dustiness   |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | 480 min 5 days per week   |
| Indoor/Outdoor                                       | Outdoor   |
| <b>Risk Management Measures</b>                      |   |
| Use suitable eye protection.                         |   |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate                                    | 13,7143 mg/kg bw/day  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Risk Characterization Ratio (RCR)  | 0,106395                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 3,5 mg/m <sup>3</sup>                     |
| Risk Characterization Ratio (RCR)  | 0,0796                                    |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC14: Tableting, compression, extrusion, pelletisation, granulation<br>Use domain: professional |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Outdoor   |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 3,4286 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,026599  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 3,5 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,0796  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|                                       |   |
|---------------------------------------|---|
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | PROC15: Use a laboratory reagent.<br>Use domain: professional |
| <b>Operational conditions</b>         |   |
| Concentration of the substance        | ammonium chloride<br>Content: >= 0 % - <= 100 %               |
| Physical state                        | Solid, medium dustiness                                       |
| Vapour pressure of the substance      | 130 Pa  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| during use   |   |
| Process temperature  | 20 °C                                     |
| Duration and Frequency of activity   | 480 min 5 days per week                   |
| Indoor/Outdoor   | Outdoor                                   |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 0,3429 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,00266                                   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 0,35 mg/m <sup>3</sup>                    |
| Risk Characterization Ratio (RCR)  | 0,00796                                   |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>                |  |
| <b>Use descriptors covered</b>                       | PROC19: Manual activities involving hand contact<br>Use domain: professional |
| <b>Operational conditions</b>                        |  |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 100 %                              |
| Physical state                                       | Solid, medium dustiness  |
| Vapour pressure of the substance during use          | 130 Pa   |
| Process temperature                                  | 20 °C  |
| Duration and Frequency of activity                   | 480 min 5 days per week  |
| Indoor/Outdoor                                       | Outdoor  |
| <b>Risk Management Measures</b>                      |  |
| Use suitable chemically resistant gloves.            | Effectiveness: 80 %  |
| Use suitable eye protection.                         |  |
| <b>Exposure estimate and reference to its source</b> |  |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker                                       |
|  | Worker - dermal, long-term - systemic  |
| Exposure estimate                                    | 28,2857 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)                    | 0,219439   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker                                       |
|  | Worker - inhalation, long-term - systemic                                    |
| Exposure estimate                                    | 3,5 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)                    | 0,0796   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

### **Guidance to Downstream Users**

For scaling see: <http://www.ecetoc.org/tra>

### **Contributing exposure scenario**

|                                |   |
|--------------------------------|---|
| <b>Use descriptors covered</b> | PROC26: Handling of solid inorganic substances at ambient temperature<br>Use domain: professional |
|--------------------------------|---|

### **Operational conditions**

|   |                         |
|---|-------------------------|
| Physical state                              | Solid, medium dustiness |
| Vapour pressure of the substance during use | 130 Pa                  |
| Process temperature                         | 20 °C                   |

### **Risk Management Measures**

|                              |  |
|------------------------------|--|
| Use suitable eye protection. |  |
|------------------------------|--|

### **Exposure estimate and reference to its source**

|                   |                        |
|-------------------|------------------------|
| Assessment method | Qualitative assessment |
|-------------------|------------------------|

### **Additional good practice advice**

There is no corresponding TRA entry concerning PROC 26 and thus, calculation of PROC 26 with TRA is not possible. To approximately map the activities described by PROC 26, PROC 5, 8b and 9 were used. PROC 8b and 9 were used to address the transfer, packaging, unpacking, and weighing while PROC 5 addresses mixing and blending activities

There is no corresponding TRA entry concerning PROC 26 and thus, calculation of PROC 26 with TRA is not possible. To approximately map the activities described by PROC 26, PROC 5, 8b and 9 were used. PROC 8b and 9 were used to address the transfer, packaging, unpacking, and weighing while PROC 5 addresses mixing and blending activities

\*\*\*\*\*

### **13. Short title of exposure scenario**

Use as Reactive process agent, Use in/as Fertilizers, Use in Metallurgy, Use in Metal surface treatment, Use in Textile finishing, Use in Biotechnology, Use in leather tanning, finishing, impregnation, Professional applications, (outdoor use)

PW; SU5, SU10, SU14, SU15; ERC8e; PROC2, PROC3, PROC4, PROC5, PROC6, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC14, PROC19, PROC26

### **Control of exposure and risk management measures**

### **Contributing exposure scenario**

|                                |  |
|--------------------------------|--|
| <b>Use descriptors covered</b> | ERC8e: Widespread use of reactive processing aid (no inclusion into or onto article, outdoor)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
|--------------------------------|--|

### **Operational conditions**



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

| <b>Contributing exposure scenario</b>  |   |
|--|---|
| <b>Use descriptors covered</b>   | PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions<br>Use domain: professional |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$   |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Outdoor   |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 1,3714 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,010639  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 0,7 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,01592   |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

| <b>Contributing exposure scenario</b>       |   |
|---|---|
| <b>Use descriptors covered</b>              | PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition<br>Use domain: professional |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$   |
| Physical state                              | Solid, medium dustiness   |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |
| Duration and Frequency of activity          | 480 min 5 days per week   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Indoor/Outdoor   | Outdoor                                   |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 0,6857 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,00532                                   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 0,7 mg/m <sup>3</sup>                     |
| Risk Characterization Ratio (RCR)  | 0,01592                                   |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>  |  |
| <b>Use descriptors covered</b>   | PROC4: Chemical production where opportunity for exposure arises<br>Use domain: professional |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %  |
| Physical state   | Solid, medium dustiness  |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | 480 min 5 days per week  |
| Indoor/Outdoor   | Outdoor  |
| <b>Risk Management Measures</b>  |  |
| Use suitable eye protection.   |  |
| <b>Exposure estimate and reference to its source</b>                               |  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - dermal, long-term - systemic  |
| Exposure estimate  | 6,8571 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,053197   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker   |
|  | Worker - inhalation, long-term - systemic  |
| Exposure estimate  | 3,5 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,0796   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |  |

|                                       |  |
|---------------------------------------|--|
| <b>Contributing exposure scenario</b> |  |
| <b>Use descriptors covered</b>        | PROC5: Mixing or blending in batch processes |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
|  | Use domain: professional                                |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$ |
| Physical state   | Solid, medium dustiness                                 |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week                                 |
| Indoor/Outdoor   | Outdoor   |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - dermal, long-term - systemic                   |
| Exposure estimate  | 13,7143 mg/kg bw/day                                    |
| Risk Characterization Ratio (RCR)  | 0,106395  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - inhalation, long-term - systemic               |
| Exposure estimate  | 3,5 mg/m <sup>3</sup>                                   |
| Risk Characterization Ratio (RCR)  | 0,0796  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PROC6: Calendering operations<br>Use domain: professional |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$   |
| Physical state                                       | Solid, medium dustiness                                   |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | 480 min 5 days per week                                   |
| Indoor/Outdoor                                       | Outdoor   |
| <b>Risk Management Measures</b>                      |   |
| Use suitable eye protection.                         |   |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker                    |
|  | Worker - dermal, long-term - systemic                     |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Exposure estimate  | 27,4286 mg/kg bw/day                      |
| Risk Characterization Ratio (RCR)  | 0,21279                                   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 3,5 mg/m <sup>3</sup>                     |
| Risk Characterization Ratio (RCR)  | 0,0796                                    |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities<br>Use domain: professional |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Outdoor   |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 13,7143 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,106395  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 3,5 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,0796  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|                                       |   |
|---------------------------------------|---|
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing).<br>Use domain: professional |
| <b>Operational conditions</b>         |   |
| Concentration of the substance        | ammonium chloride<br>Content: >= 0 % - <= 100 %   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Physical state   | Solid, medium dustiness                   |
| Vapour pressure of the substance during use  | 130 Pa                                    |
| Process temperature  | 20 °C                                     |
| Duration and Frequency of activity   | 480 min 5 days per week                   |
| Indoor/Outdoor   | Outdoor                                   |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 6,8571 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,053197                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 3,5 mg/m <sup>3</sup>                     |
| Risk Characterization Ratio (RCR)  | 0,0796                                    |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>                |  |
| <b>Use descriptors covered</b>                       | PROC10: Roller application or brushing<br>Use domain: professional |
| <b>Operational conditions</b>                        |  |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 100 %                    |
| Physical state                                       | Solid, medium dustiness  |
| Vapour pressure of the substance during use          | 130 Pa   |
| Process temperature                                  | 20 °C  |
| Duration and Frequency of activity                   | 480 min 5 days per week  |
| Indoor/Outdoor                                       | Outdoor  |
| <b>Risk Management Measures</b>                      |  |
| Use suitable eye protection.                         |  |
| <b>Exposure estimate and reference to its source</b> |  |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker                             |
|  | Worker - dermal, long-term - systemic                              |
| Exposure estimate                                    | 27,4286 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)                    | 0,21279  |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker                             |
|  | Worker - inhalation, long-term - systemic                          |
| Exposure estimate                                    | 3,5 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)                    | 0,0796   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

### **Guidance to Downstream Users**

For scaling see: <http://www.ecetoc.org/tra>

### **Contributing exposure scenario**

|                                |   |
|--------------------------------|---|
| <b>Use descriptors covered</b> | PROC11: Non industrial spraying<br>Use domain: professional |
|--------------------------------|---|

### **Operational conditions**

|   |  |
|---|--|
| Concentration of the substance              | ammonium chloride<br>Content: $\geq 0\%$ - $< 1\%$ |
| Physical state                              | liquid   |
| Vapour pressure of the substance during use | 130 Pa   |
| Process temperature                         | 20 °C  |
| Duration and Frequency of activity          | 480 min 5 days per week                            |
| Indoor/Outdoor                              | Outdoor  |
| Application rate                            | $> 3$ l/min  |

### **Risk Management Measures**

|   |  |
|---|--|
| Ensure that the task is carried out only downward.  |  |
| Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m). |  |
| Ensure that the worker is in a personal enclosure   |  |
| Use suitable eye protection.  |  |

### **Exposure estimate and reference to its source**

|                                   |   |
|-----------------------------------|---|
| Assessment method                 | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|                                   | Worker - dermal, long-term - systemic     |
| Exposure estimate                 | 10,7143 mg/kg bw/day                      |
| Risk Characterization Ratio (RCR) | 0,083121                                  |
| Assessment method                 | EASY TRA v4.2, Advanced REACH Tool v1.5   |
|                                   | Worker - inhalation, long-term - systemic |
| Exposure estimate                 | 0,26 mg/m <sup>3</sup>                    |
| Risk Characterization Ratio (RCR) | 0,005913                                  |

### **Guidance to Downstream Users**

For scaling see: <http://www.ecetoc.org/tra>

### **Contributing exposure scenario**

|                                |   |
|--------------------------------|---|
| <b>Use descriptors covered</b> | PROC11: Non industrial spraying<br>Use domain: professional |
|--------------------------------|---|

### **Operational conditions**

|                                |  |
|--------------------------------|--|
| Concentration of the substance | ammonium chloride<br>Content: $\geq 0\%$ - $< 1\%$ |
|--------------------------------|--|

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Physical state   | liquid                                    |
| Vapour pressure of the substance during use  | 130 Pa                                    |
| Process temperature  | 20 °C                                     |
| Duration and Frequency of activity   | 480 min 5 days per week                   |
| Indoor/Outdoor   | Outdoor                                   |
| Application rate   | > 3 l/min                                 |
| <b>Risk Management Measures</b>  |   |
| Ensure that the task is carried out only downward.                                 |   |
| Surface spraying with no or low compressed air use.                                |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 10,7143 mg/kg bw/day                      |
| Risk Characterization Ratio (RCR)  | 0,083121                                  |
| Assessment method  | EASY TRA v4.2, Advanced REACH Tool v1.5   |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 3,2 mg/m <sup>3</sup>                     |
| Risk Characterization Ratio (RCR)  | 0,072777                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PROC13: Treatment of articles by dipping and pouring.<br>Use domain: professional |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 100 %                                   |
| Physical state                                       | Solid, medium dustiness   |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | 480 min 5 days per week   |
| Indoor/Outdoor                                       | Outdoor   |
| <b>Risk Management Measures</b>                      |   |
| Use suitable eye protection.                         |   |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Exposure estimate  | 13,7143 mg/kg bw/day                      |
| Risk Characterization Ratio (RCR)  | 0,106395                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 3,5 mg/m <sup>3</sup>                     |
| Risk Characterization Ratio (RCR)  | 0,0796                                    |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>  |   |
| <b>Use descriptors covered</b>   | PROC14: Tableting, compression, extrusion, pelletisation, granulation<br>Use domain: professional |
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %   |
| Physical state   | Solid, medium dustiness   |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week   |
| Indoor/Outdoor   | Outdoor   |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |
| Exposure estimate  | 3,4286 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,026599  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - inhalation, long-term - systemic   |
| Exposure estimate  | 3,5 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,0796  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|                                       |  |
|---------------------------------------|--|
| <b>Contributing exposure scenario</b> |  |
| <b>Use descriptors covered</b>        | PROC19: Manual activities involving hand contact<br>Use domain: professional |
| <b>Operational conditions</b>         |  |
| Concentration of the substance        | ammonium chloride<br>Content: >= 0 % - <= 100 %                              |
| Physical state                        | Solid, medium dustiness  |



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Vapour pressure of the substance during use  | 130 Pa                                    |
| Process temperature  | 20 °C                                     |
| Duration and Frequency of activity   | 480 min 5 days per week                   |
| Indoor/Outdoor   | Outdoor                                   |
| <b>Risk Management Measures</b>  |   |
| Use suitable chemically resistant gloves.  | Effectiveness: 80 %                       |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - dermal, long-term - systemic     |
| Exposure estimate  | 28,2857 mg/kg bw/day                      |
| Risk Characterization Ratio (RCR)  | 0,219439                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 3,5 mg/m <sup>3</sup>                     |
| Risk Characterization Ratio (RCR)  | 0,0796                                    |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>   |   |
| <b>Use descriptors covered</b>  | PROC26: Handling of solid inorganic substances at ambient temperature<br>Use domain: professional |
| <b>Operational conditions</b>   |   |
| Physical state  | Solid, medium dustiness   |
| Vapour pressure of the substance during use   | 130 Pa  |
| Process temperature   | 20 °C   |
| <b>Risk Management Measures</b>   |   |
| Use suitable eye protection.  |   |
| <b>Exposure estimate and reference to its source</b>  |   |
| Assessment method   | Qualitative assessment  |
| <b>Additional good practice advice</b>  |   |
| There is no corresponding TRA entry concerning PROC 26 and thus, calculation of PROC 26 with TRA is not possible. To approximately map the activities described by PROC 26, PROC 5, 8b and 9 were used. PROC 8b and 9 were used to address the transfer, packaging, unpacking, and weighing while PROC 5 addresses mixing and blending activities |   |
| There is no corresponding TRA entry concerning PROC 26 and thus, calculation of PROC 26 with TRA is not possible. To approximately map the activities described by PROC 26, PROC 5, 8b and 9 were used. PROC 8b and 9 were used to address the transfer, packaging, unpacking, and weighing while PROC 5 addresses mixing and blending activities |   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

\*\*\*\*\*

#### 14. Short title of exposure scenario

Use in Wood articles, Service life of articles, Consumer applications

C; C; ERC10a, ERC11a; AC11

#### Control of exposure and risk management measures

| Contributing exposure scenario |  |
|--------------------------------|--|
| <b>Use descriptors covered</b> | ERC10a: Widespread use of articles with low release (outdoor)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
| <b>Operational conditions</b>  |  |

| Contributing exposure scenario |   |
|--------------------------------|---|
| <b>Use descriptors covered</b> | ERC11a: Widespread use of articles with low release (indoor)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
| <b>Operational conditions</b>  |   |

| Contributing exposure scenario              |  |
|---|--|
| <b>Use descriptors covered</b>              | AC11-3: Wood and wood furniture: toys.                     |
| <b>Operational conditions</b>               |  |
| Concentration of the substance              | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 2\%$      |
| Vapour pressure of the substance during use | 130 Pa   |
| Process temperature                         | 20 °C  |
| Duration and Frequency of activity          | 365 uses per year  |
| Duration and Frequency of activity          | 365 uses per year  |
| body weight                                 | 7,2 kg   |
| Uptake fraction dermal                      | 100 %  |
| Uptake fraction oral                        | 100 %  |
|   | Amount per use 10 g Relevant for dermal exposure estimates |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
|  | Amount ingested 0,1 g Relevant for oral exposure estimates                                     |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 27,7778 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,503221   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Oral model: direct intake, Uptake model: Uptake fraction         |
|  | Consumer - oral, long-term - systemic  |
| Exposure estimate  | 0,2778 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,005032   |
|  | The calculation is based on the internal chronic dose.   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>  |  |
| <b>Use descriptors covered</b>   | AC11-1: Wood and wood furniture: flooring.   |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 5 %  |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | 365 uses per year  |
| body weight  | 65 kg  |
| Uptake fraction dermal   | 100 %  |
|  | Amount per use 8,75 g Relevant for dermal exposure estimates                                   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 6,7308 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,121934   |
|  | The calculation is based on the internal chronic dose.   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|                                       |                     |
|---------------------------------------|---------------------|
| <b>Contributing exposure scenario</b> |                     |
| <b>Use descriptors covered</b>        | AC11: Wood articles |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 10\%$   |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | 182 uses per year  |
| Duration and Frequency of activity   | 182 uses per year  |
| body weight  | 7,2 kg   |
| Uptake fraction dermal   | 100 %  |
| Uptake fraction oral   | 100 %  |
|  | Amount per use 0,56 g Relevant for dermal exposure estimates                                   |
|  | Amount ingested 0,1 g Relevant for oral exposure estimates                                     |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 3,8782 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,070258   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Oral model: direct intake, Uptake model: Uptake fraction         |
|  | Consumer - oral, long-term - systemic  |
| Exposure estimate  | 0,6925 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,012546   |
|  | The calculation is based on the internal chronic dose.   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|   |  |
|---|--|
| <b>Contributing exposure scenario</b>       |  |
| <b>Use descriptors covered</b>              | AC11-2: Wood and wood furniture: furniture.            |
| <b>Operational conditions</b>               |  |
| Concentration of the substance              | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 10\%$ |
| Vapour pressure of the substance during use | 130 Pa   |
| Process temperature                         | 20 °C  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| Duration and Frequency of activity   | 365 uses per year  |
| body weight  | 65 kg  |
| Uptake fraction dermal   | 100 %  |
|  | Amount per use 8,75 g Relevant for dermal exposure estimates                                   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 13,4615 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,243868   |
|  | The calculation is based on the internal chronic dose.   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

\*\*\*\*\*

## 15. Short title of exposure scenario

Use in Biotechnology, Industrial applications  
ERC6a, ERC6b; PROC4, PROC9

## Control of exposure and risk management measures

|                                       |   |
|---------------------------------------|---|
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | ERC6a: Use of intermediate<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.   |
| <b>Operational conditions</b>         |   |
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | ERC6b: Use of reactive processing aid at industrial site (no inclusion into or onto article)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
| <b>Operational conditions</b>         |   |
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | PROC4: Chemical production where opportunity for exposure arises<br>Use domain: industrial  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| <b>Operational conditions</b>  |   |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$ |
| Physical state   | Solid, medium dustiness                                 |
| Vapour pressure of the substance during use  | 130 Pa  |
| Process temperature  | 20 °C   |
| Duration and Frequency of activity   | 480 min 5 days per week                                 |
| Indoor/Outdoor   | Indoor  |
| <b>Risk Management Measures</b>  |   |
| Use suitable eye protection.   |   |
| <b>Exposure estimate and reference to its source</b>                               |   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - dermal, long-term - systemic                   |
| Exposure estimate  | 6,8571 mg/kg bw/day                                     |
| Risk Characterization Ratio (RCR)  | 0,053197  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker                  |
|  | Worker - inhalation, long-term - systemic               |
| Exposure estimate  | 5 mg/m <sup>3</sup>                                     |
| Risk Characterization Ratio (RCR)  | 0,113714  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing).<br>Use domain: industrial |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$   |
| Physical state                                       | Solid, medium dustiness   |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | 480 min 5 days per week   |
| Indoor/Outdoor                                       | Indoor  |
| <b>Risk Management Measures</b>                      |   |
| Use suitable eye protection.                         |   |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ECETOC TRA v3.0, Worker  |
|  | Worker - dermal, long-term - systemic   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Exposure estimate  | 6,8571 mg/kg bw/day                       |
| Risk Characterization Ratio (RCR)  | 0,053197                                  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA v3.0, Worker    |
|  | Worker - inhalation, long-term - systemic |
| Exposure estimate  | 5 mg/m <sup>3</sup>                       |
| Risk Characterization Ratio (RCR)  | 0,113714                                  |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |   |

\*\*\*\*\*

## 16. Short title of exposure scenario

Use in Cleaning Agents, Use in/as Laundry agents, Consumer applications  
C; C; ERC8a, ERC8d; PC35, PC39

## Control of exposure and risk management measures

| Contributing exposure scenario              |  |
|---|--|
| Use descriptors covered                     | ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.  |
| <b>Operational conditions</b>               |  |
| Contributing exposure scenario              |  |
| Use descriptors covered                     | ERC8d: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
| <b>Operational conditions</b>               |  |
| Contributing exposure scenario              |  |
| Use descriptors covered                     | PC8_2, PC35_2: Subcategory: Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners )  |
| <b>Operational conditions</b>               |  |
| Concentration of the substance              | ammonium chloride<br>Content: >= 0 % - <= 10 %   |
| Vapour pressure of the substance during use | 130 Pa   |
| Process temperature                         | 20 °C  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| Duration and Frequency of activity   | Exposure duration: 0,75 min<br>Relevant for inhalative exposure estimates                      |
| Duration and Frequency of activity   | Application duration: 0,3 min<br>Relevant for inhalative exposure estimates                    |
| Duration and Frequency of activity   | < 1 uses per year  |
| Room size  | 1 m <sup>3</sup>   |
| Ventilation rate per hour  | 0,5  |
| Temperature (Application)  | 20 °C  |
| body weight  | 65 kg  |
| Uptake fraction dermal   | 100 %  |
|  | Amount per use 0,01 g Relevant for dermal exposure estimates                                   |
| Release area   | 20 cm <sup>2</sup>   |
|  | Release area is constant   |
| Release duration   | 0,3 min  |
|  | Relevant for inhalative exposure estimates   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 0,0001 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,000001   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation               |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate  | 0,0001 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,000001   |
|  | The exposure calculation is based on the mean concentration per year.                          |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PC8_2, PC35_2: Subcategory: Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners ) |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: >= 0 % - <= 15 %  |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| Duration and Frequency of activity   | Exposure duration: 0,75 min<br>Relevant for inhalative exposure estimates                      |
| Duration and Frequency of activity   | Application duration: 0,3 min<br>Relevant for inhalative exposure estimates                    |
| Duration and Frequency of activity   | 4 uses per year  |
| Room size  | 1 m <sup>3</sup>   |
| Ventilation rate per hour  | 2  |
| Temperature (Application)  | 20 °C  |
| body weight  | 65 kg  |
| Uptake fraction dermal   | 100 %  |
|  | Amount per use 0,01 g Relevant for dermal exposure estimates                                   |
| Release area   | 20 cm <sup>2</sup>   |
|  | Release area is constant   |
| Release duration   | 0,3 min  |
|  | Relevant for inhalative exposure estimates   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 0,0003 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,000005   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation               |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate  | 0,0001 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,000001   |
|  | The exposure calculation is based on the mean concentration per year.                          |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PC8_2, PC35_2: Subcategory: Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners ) |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: >= 0 % - <= 15 %  |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| Duration and Frequency of activity   | Exposure duration: 0,75 min<br>Relevant for inhalative exposure estimates                      |
| Duration and Frequency of activity   | Application duration: 0,3 min<br>Relevant for inhalative exposure estimates                    |
| Duration and Frequency of activity   | 104 uses per year  |
| Room size  | 58 m <sup>3</sup>  |
| Ventilation rate per hour  | 0,5  |
| Temperature (Application)  | 20 °C  |
| body weight  | 65 kg  |
| Uptake fraction dermal   | 100 %  |
|  | Amount per use 0,01 g Relevant for dermal exposure estimates                                   |
| Release area   | 20 cm <sup>2</sup>   |
|  | Release area is constant   |
| Release duration   | 0,3 min  |
|  | Relevant for inhalative exposure estimates   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 0,0066 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,000119   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation               |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate  | 0,0001 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,000001   |
|  | The exposure calculation is based on the mean concentration per year.                          |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PC8_2, PC35_2: Subcategory: Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners ) |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: >= 0 % - <= 15 %  |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| Duration and Frequency of activity   | Exposure duration: 0,75 min<br>Relevant for inhalative exposure estimates                      |
| Duration and Frequency of activity   | Application duration: 0,3 min<br>Relevant for inhalative exposure estimates                    |
| Duration and Frequency of activity   | 104 uses per year  |
| Room size  | 1 m <sup>3</sup>   |
| Ventilation rate per hour  | 0,5  |
| Temperature (Application)  | 20 °C  |
| body weight  | 65 kg  |
| Uptake fraction dermal   | 100 %  |
|  | Amount per use 0,01 g Relevant for dermal exposure estimates                                   |
| Release area   | 20 cm <sup>2</sup>   |
|  | Release area is constant   |
| Release duration   | 0,3 min  |
|  | Relevant for inhalative exposure estimates   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 0,0066 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,000119   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation               |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate  | 0,0001 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,000001   |
|  | The exposure calculation is based on the mean concentration per year.                          |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PC8_2, PC35_2: Subcategory: Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners ) |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: >= 0 % - <= 10 %  |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| Duration and Frequency of activity   | Exposure duration: 110 min<br>Relevant for inhalative exposure estimates                       |
| Duration and Frequency of activity   | Application duration: 110 min<br>Relevant for inhalative exposure estimates                    |
| Duration and Frequency of activity   | < 1 uses per year  |
| Room size  | 58 m <sup>3</sup>  |
| Ventilation rate per hour  | 0,5  |
| Temperature (Application)  | 20 °C  |
| body weight  | 65 kg  |
| Uptake fraction dermal   | 100 %  |
|  | Amount per use 27 g Relevant for dermal exposure estimates                                     |
| Release area   | 220000 cm <sup>2</sup>   |
|  | Release area increases over time   |
| Release duration   | 110 min  |
|  | Relevant for inhalative exposure estimates   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 0,0569 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,001031   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation               |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate  | 0,0066 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,000706   |
|  | The exposure calculation is based on the mean concentration per year.                          |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PC8_2, PC35_2: Subcategory: Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners ) |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: >= 0 % - <= 15 %  |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| Duration and Frequency of activity   | Exposure duration: 25 min<br>Relevant for inhalative exposure estimates                        |
| Duration and Frequency of activity   | Application duration: 20 min<br>Relevant for inhalative exposure estimates                     |
| Duration and Frequency of activity   | 4 uses per year  |
| Room size  | 10 m <sup>3</sup>  |
| Ventilation rate per hour  | 2  |
| Temperature (Application)  | 20 °C  |
| body weight  | 65 kg  |
| Uptake fraction dermal   | 100 %  |
|  | Amount per use 19 g Relevant for dermal exposure estimates                                     |
| Release area   | 64000 cm <sup>2</sup>  |
|  | Release area increases over time   |
| Release duration   | 20 min   |
|  | Relevant for inhalative exposure estimates   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 0,4805 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,008705   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation               |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate  | 0,0143 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,001519   |
|  | The exposure calculation is based on the mean concentration per year.                          |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PC8_2, PC35_2: Subcategory: Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners ) |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: >= 0 % - <= 50 %  |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| Duration and Frequency of activity   | Exposure duration: 240 min<br>Relevant for inhalative exposure estimates                             |
| Duration and Frequency of activity   | 365 uses per year  |
| Room size  | 58 m <sup>3</sup>  |
| Ventilation rate per hour  | 0,5  |
| body weight  | 65 kg  |
| Uptake fraction dermal   | 100 %  |
| Spray duration   | 42 sec   |
| Contact rate   | 46 mg/min  |
| Release duration   | 0,7 min  |
|  | Relevant for dermal exposure estimates   |
| <b>Risk Management Measures</b>  |  |
| Consumer Measures  | Ensure spraying away from persons.   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 0,2477 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,004487   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: Exposure to spray/dust                               |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate  | 0,0725 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,007712   |
|  | The exposure calculation is based on the mean concentration per year.                                |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PC8_2, PC35_2: Subcategory: Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners ) |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: >= 0 % - <= 50 %  |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |
| Duration and Frequency of activity          | 365 uses per year   |
| body weight                                 | 65 kg   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| Uptake fraction dermal   | 100 %  |
|  | Amount per use 0,29 g Relevant for dermal exposure estimates                                   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 2,2308 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,040412   |
|  | The calculation is based on the internal chronic dose.   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PC8_2, PC35_2: Subcategory: Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners ) |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 50 %  |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | Exposure duration: 3 min<br>Relevant for inhalative exposure estimates  |
| Duration and Frequency of activity                   | Application duration: 2 min<br>Relevant for inhalative exposure estimates   |
| Duration and Frequency of activity                   | 260 uses per year   |
| Room size  | 2,5 m3  |
| Ventilation rate per hour                            | 2   |
| Temperature (Application)                            | 20 °C   |
| body weight  | 65 kg   |
| Uptake fraction dermal                               | 100 %   |
|  | Amount per use 2,2 g Relevant for dermal exposure estimates   |
| Release area   | 750 cm <sup>2</sup>   |
|  | Release area is constant  |
| Release duration                                     | 2 min   |
|  | Relevant for inhalative exposure estimates  |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
|  | application, Uptake model: Uptake fraction                                       |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 12,0548 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,218384   |
|  | The calculation is based on the internal chronic dose.                           |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation |
|  | Consumer - inhalation, long-term - systemic                                      |
| Exposure estimate  | 0,0162 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,001719   |
|  | The exposure calculation is based on the mean concentration per year.            |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PC8_2, PC35_2: Subcategory: Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners ) |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 50 %  |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | Exposure duration: 3 min<br>Relevant for inhalative exposure estimates  |
| Duration and Frequency of activity                   | Application duration: 2 min<br>Relevant for inhalative exposure estimates   |
| Duration and Frequency of activity                   | 260 uses per year   |
| Room size  | 2,5 m <sup>3</sup>  |
| Ventilation rate per hour                            | 2   |
| Temperature (Application)                            | 20 °C   |
| body weight  | 65 kg   |
| Uptake fraction dermal                               | 100 %   |
|  | Amount per use 2,2 g Relevant for dermal exposure estimates   |
| Release area   | 750 cm <sup>2</sup>   |
|  | Release area is constant  |
| Release duration                                     | 2 min   |
|  | Relevant for inhalative exposure estimates  |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant   |



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
|  | application, Uptake model: Uptake fraction                                       |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 12,0548 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)  | 0,218384   |
|  | The calculation is based on the internal chronic dose.                           |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation |
|  | Consumer - inhalation, long-term - systemic                                      |
| Exposure estimate  | 0,0162 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,001719   |
|  | The exposure calculation is based on the mean concentration per year.            |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PC8_2, PC35_2: Subcategory: Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners ) |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 50 %  |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | Exposure duration: 10 min<br>Relevant for inhalative exposure estimates   |
| Duration and Frequency of activity                   | Application duration: 7,6 min<br>Relevant for inhalative exposure estimates   |
| Duration and Frequency of activity                   | 156 uses per year   |
| Room size  | 2,5 m <sup>3</sup>  |
| Ventilation rate per hour                            | 2   |
| Temperature (Application)                            | 20 °C   |
| body weight  | 65 kg   |
| Uptake fraction dermal                               | 100 %   |
|  | Amount per use 0,37 g Relevant for dermal exposure estimates  |
| Release area   | 40000 cm <sup>2</sup>   |
|  | Release area increases over time  |
| Release duration                                     | 7,6 min   |
|  | Relevant for inhalative exposure estimates  |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
|  | application, Uptake model: Uptake fraction                                       |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 1,2164 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,022037   |
|  | The calculation is based on the internal chronic dose.                           |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation |
|  | Consumer - inhalation, long-term - systemic                                      |
| Exposure estimate  | 1,9851 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,211177   |
|  | The exposure calculation is based on the mean concentration per year.            |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PC8_2, PC35_2: Subcategory: Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners ) |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 5 %   |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | Exposure duration: 240 min<br>Relevant for inhalative exposure estimates  |
| Duration and Frequency of activity                   | Application duration: 20 min<br>Relevant for inhalative exposure estimates  |
| Duration and Frequency of activity                   | 104 uses per year   |
| Room size  | 58 m <sup>3</sup>   |
| Ventilation rate per hour                            | 0,5   |
| Temperature (Application)                            | 20 °C   |
| body weight  | 65 kg   |
| Uptake fraction dermal                               | 100 %   |
|  | Amount per use 19 g Relevant for dermal exposure estimates  |
| Release area   | 100000 cm <sup>2</sup>  |
|  | Release area increases over time  |
| Release duration                                     | 20 min  |
|  | Relevant for inhalative exposure estimates  |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
|  | application, Uptake model: Uptake fraction                                       |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 4,1644 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,075442   |
|  | The calculation is based on the internal chronic dose.                           |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation |
|  | Consumer - inhalation, long-term - systemic                                      |
| Exposure estimate  | 1,8649 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,198394   |
|  | The exposure calculation is based on the mean concentration per year.            |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PC8_2, PC35_2: Subcategory: Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners ) |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 50 %  |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | Exposure duration: 60 min<br>Relevant for inhalative exposure estimates   |
| Duration and Frequency of activity                   | Application duration: 2 min<br>Relevant for inhalative exposure estimates   |
| Duration and Frequency of activity                   | 365 uses per year   |
| Room size  | 20 m <sup>3</sup>   |
| Ventilation rate per hour                            | 0,6   |
| Temperature (Application)                            | 20 °C   |
| body weight  | 65 kg   |
| Uptake fraction dermal                               | 100 %   |
|  | Amount per use 0,047 g Relevant for dermal exposure estimates   |
| Release area   | 20000 cm <sup>2</sup>   |
|  | Release area increases over time  |
| Release duration                                     | 2 min   |
|  | Relevant for inhalative exposure estimates  |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
|  | application, Uptake model: Uptake fraction                                       |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 0,3615 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,00655  |
|  | The calculation is based on the internal chronic dose.                           |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation |
|  | Consumer - inhalation, long-term - systemic                                      |
| Exposure estimate  | 2,5757 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,274012   |
|  | The exposure calculation is based on the mean concentration per year.            |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PC8_2, PC35_2: Subcategory: Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners ) |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 5 %   |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | Exposure duration: 240 min<br>Relevant for inhalative exposure estimates  |
| Duration and Frequency of activity                   | Application duration: 30 min<br>Relevant for inhalative exposure estimates  |
| Duration and Frequency of activity                   | 104 uses per year   |
| Room size  | 58 m <sup>3</sup>   |
| Ventilation rate per hour                            | 0,5   |
| Temperature (Application)                            | 20 °C   |
| body weight  | 65 kg   |
| Uptake fraction dermal                               | 100 %   |
|  | Amount per use 19 g Relevant for dermal exposure estimates  |
| Release area   | 220000 cm <sup>2</sup>  |
|  | Release area increases over time  |
| Release duration                                     | 30 min  |
|  | Relevant for inhalative exposure estimates  |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
|  | application, Uptake model: Uptake fraction                                       |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 4,1644 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,075442   |
|  | The calculation is based on the internal chronic dose.                           |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation |
|  | Consumer - inhalation, long-term - systemic                                      |
| Exposure estimate  | 2,0444 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,21749  |
|  | The exposure calculation is based on the mean concentration per year.            |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>                |  |
| <b>Use descriptors covered</b>                       | PC8_3, PC35_3: Subcategory: Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) |
| <b>Operational conditions</b>                        |  |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 20 %   |
| Vapour pressure of the substance during use          | 130 Pa   |
| Process temperature                                  | 20 °C  |
| Duration and Frequency of activity                   | Exposure duration: 60 min<br>Relevant for inhalative exposure estimates  |
| Duration and Frequency of activity                   | 365 uses per year  |
| Room size  | 15 m <sup>3</sup>  |
| Ventilation rate per hour                            | 2,5  |
| body weight  | 65 kg  |
| Uptake fraction dermal                               | 100 %  |
| Spray duration                                       | 24,6 sec   |
| Contact rate   | 46 mg/min  |
| Release duration                                     | 0,41 min   |
|  | Relevant for dermal exposure estimates   |
| <b>Risk Management Measures</b>                      |  |
| Consumer Measures                                    | Ensure spraying away from persons.   |
| <b>Exposure estimate and reference to its source</b> |  |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction           |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate                                    | 0,058 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)                    | 0,001051   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
|  | The calculation is based on the internal chronic dose.                    |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model:<br>Exposure to spray/dust |
|  | Consumer - inhalation, long-term - systemic                               |
| Exposure estimate  | 0,0206 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,002195  |
|  | The exposure calculation is based on the mean concentration per year.     |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp</a> |   |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>                |  |
| <b>Use descriptors covered</b>                       | PC8_3, PC35_3: Subcategory: Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) |
| <b>Operational conditions</b>                        |  |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 20 %   |
| Vapour pressure of the substance during use          | 130 Pa   |
| Process temperature                                  | 20 °C  |
| Duration and Frequency of activity                   | Exposure duration: 25 min<br>Relevant for inhalative exposure estimates  |
| Duration and Frequency of activity                   | 52 uses per year   |
| Room size  | 10 m <sup>3</sup>  |
| Ventilation rate per hour                            | 2  |
| body weight  | 65 kg  |
| Uptake fraction dermal                               | 100 %  |
| Spray duration                                       | 90 sec   |
| Contact rate   | 46 mg/min  |
| Release duration                                     | 2,67 min   |
|  | Relevant for dermal exposure estimates   |
| <b>Risk Management Measures</b>                      |  |
| Consumer Measures                                    | Ensure spraying away from persons.   |
| <b>Exposure estimate and reference to its source</b> |  |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction           |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate                                    | 0,0538 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)                    | 0,000974   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Inhalation model:<br>Exposure to spray/dust                                      |
|  | Consumer - inhalation, long-term - systemic  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Exposure estimate  | 0,0381 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,004051  |
|  | The exposure calculation is based on the mean concentration per year. |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp</a> |   |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>  |  |
| <b>Use descriptors covered</b>   | PC8_3, PC35_3: Subcategory: Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 50 %   |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | Exposure duration: 50 min<br>Relevant for inhalative exposure estimates  |
| Duration and Frequency of activity   | 365 uses per year  |
| body weight  | 65 kg  |
| Release duration   | 86400 min  |
|  | Relevant for inhalative exposure estimates   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model:<br>exposure to vapour - constant rate                          |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate  | 0,0866 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,009215   |
|  | The exposure calculation is based on the mean concentration per year.  |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp</a> |  |

|   |  |
|---|--|
| <b>Contributing exposure scenario</b>       |  |
| <b>Use descriptors covered</b>              | PC8_3, PC35_3: Subcategory: Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) |
| <b>Operational conditions</b>               |  |
| Concentration of the substance              | ammonium chloride<br>Content: >= 0 % - <= 20 %   |
| Vapour pressure of the substance during use | 130 Pa   |
| Process temperature                         | 20 °C  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| Duration and Frequency of activity   | Exposure duration: 25 min<br>Relevant for inhalative exposure estimates                        |
| Duration and Frequency of activity   | Application duration: 20 min<br>Relevant for inhalative exposure estimates                     |
| Duration and Frequency of activity   | 52 uses per year   |
| Room size  | 10 m <sup>3</sup>  |
| Ventilation rate per hour  | 2  |
| Temperature (Application)  | 20 °C  |
| body weight  | 65 kg  |
| Uptake fraction dermal   | 100 %  |
|  | Amount per use 0,3 g Relevant for dermal exposure estimates                                    |
| Release area   | 64000 cm <sup>2</sup>  |
|  | Release area is constant   |
| Release duration   | 20 min   |
|  | Relevant for inhalative exposure estimates   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 0,1315 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,002382   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation               |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate  | 0,7311 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,077777   |
|  | The exposure calculation is based on the mean concentration per year.                          |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|   |  |
|---|--|
| <b>Contributing exposure scenario</b>       |  |
| <b>Use descriptors covered</b>              | PC8_3, PC35_3: Subcategory: Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) |
| <b>Operational conditions</b>               |  |
| Concentration of the substance              | ammonium chloride<br>Content: >= 0 % - <= 20 %   |
| Vapour pressure of the substance during use | 130 Pa   |
| Process temperature                         | 20 °C  |



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| Duration and Frequency of activity   | Exposure duration: 60 min<br>Relevant for inhalative exposure estimates                        |
| Duration and Frequency of activity   | Application duration: 10 min<br>Relevant for inhalative exposure estimates                     |
| Duration and Frequency of activity   | 365 uses per year  |
| Room size  | 15 m <sup>3</sup>  |
| Ventilation rate per hour  | 2,5  |
| Temperature (Application)  | 20 °C  |
| body weight  | 65 kg  |
| Uptake fraction dermal   | 100 %  |
|  | Amount per use 0,16 g Relevant for dermal exposure estimates                                   |
| Release area   | 17100 cm <sup>2</sup>  |
|  | Release area is constant   |
| Release duration   | 10 min   |
|  | Relevant for inhalative exposure estimates   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 0,4923 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,008919   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation               |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate  | 1,3357 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,1421   |
|  | The exposure calculation is based on the mean concentration per year.                          |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PC8_1, PC35_1: Subcategory: Laundry and dish washing products |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: >= 0 % - <= 6 %                 |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |
| Duration and Frequency of activity          | 365 uses per year   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| body weight  | 65 kg  |
| Uptake fraction oral   | 100 %  |
|  | Amount ingested 0,42 mg Relevant for oral exposure estimates                           |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Oral model: direct intake, Uptake model: Uptake fraction |
|  | Consumer - oral, long-term - systemic  |
| Exposure estimate  | 0,0004 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,000007   |
|  | The calculation is based on the internal chronic dose.                                 |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|  |   |
|--|---|
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PC8_1, PC35_1: Subcategory: Laundry and dish washing products               |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 6 %                               |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | Exposure duration: 0,75 min<br>Relevant for inhalative exposure estimates   |
| Duration and Frequency of activity                   | Application duration: 0,3 min<br>Relevant for inhalative exposure estimates |
| Duration and Frequency of activity                   | 426 uses per year   |
| Room size  | 1 m <sup>3</sup>  |
| Ventilation rate per hour                            | 2,5   |
| Temperature (Application)                            | 20 °C   |
| body weight  | 65 kg   |
| Uptake fraction dermal                               | 100 %   |
|  | Amount per use 0,01 g Relevant for dermal exposure estimates                |
| Release area   | 20 cm <sup>2</sup>  |
|  | Release area is constant  |
| Release duration                                     | 0,3 min   |
|  | Relevant for inhalative exposure estimates                                  |
| <b>Exposure estimate and reference to its source</b> |   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 0,0108 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,000195   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation               |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate  | 0,0001 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,000001   |
|  | The exposure calculation is based on the mean concentration per year.                          |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>                |  |
| <b>Use descriptors covered</b>                       | PC8_1, PC35_1: Subcategory: Laundry and dish washing products  |
| <b>Operational conditions</b>                        |  |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 10 %   |
| Vapour pressure of the substance during use          | 130 Pa   |
| Process temperature                                  | 20 °C  |
| Duration and Frequency of activity                   | Exposure duration: 10 min<br>Relevant for inhalative exposure estimates                              |
| Duration and Frequency of activity                   | 128 uses per year  |
| Room size  | 10 m <sup>3</sup>  |
| Ventilation rate per hour                            | 2  |
| body weight  | 65 kg  |
| Uptake fraction dermal                               | 100 %  |
| Spray duration                                       | 3 sec  |
| Contact rate   | 46 mg/min  |
| Release duration                                     | 0,47 min   |
|  | Relevant for dermal exposure estimates   |
| <b>Risk Management Measures</b>                      |  |
| Consumer Measures                                    | Ensure spraying away from persons.   |
| <b>Exposure estimate and reference to its source</b> |  |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate                                    | 0,0116 mg/kg bw/day  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Risk Characterization Ratio (RCR)  | 0,00021   |
|  | The calculation is based on the internal chronic dose.                    |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model:<br>Exposure to spray/dust |
|  | Consumer - inhalation, long-term - systemic                               |
| Exposure estimate  | 0,0006 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,000061  |
|  | The exposure calculation is based on the mean concentration per year.     |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp</a> |   |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>                |  |
| <b>Use descriptors covered</b>                       | PC8_1, PC35_1: Subcategory: Laundry and dish washing products                                  |
| <b>Operational conditions</b>                        |  |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 60 %   |
| Vapour pressure of the substance during use          | 130 Pa   |
| Process temperature                                  | 20 °C  |
| Duration and Frequency of activity                   | Exposure duration: 0,75 min<br>Relevant for inhalative exposure estimates                      |
| Duration and Frequency of activity                   | Application duration: 0,3 min<br>Relevant for inhalative exposure estimates                    |
| Duration and Frequency of activity                   | 365 uses per year  |
| Room size  | 1 m <sup>3</sup>   |
| Ventilation rate per hour                            | 2  |
| Temperature (Application)                            | 60 °C  |
| body weight  | 65 kg  |
| Uptake fraction dermal                               | 100 %  |
|  | Amount per use 0,01 g Relevant for dermal exposure estimates                                   |
| Release area   | 20 cm <sup>2</sup>   |
|  | Release area is constant   |
| Release duration                                     | 0,3 min  |
|  | Relevant for inhalative exposure estimates   |
| <b>Exposure estimate and reference to its source</b> |  |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate                                    | 0,0923 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)                    | 0,001672   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
|  | The calculation is based on the internal chronic dose.                           |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation |
|  | Consumer - inhalation, long-term - systemic                                      |
| Exposure estimate  | 0,0001 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,000015   |
|  | The exposure calculation is based on the mean concentration per year.            |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp</a> |  |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>                |  |
| <b>Use descriptors covered</b>                       | PC8_1, PC35_1: Subcategory: Laundry and dish washing products                                  |
| <b>Operational conditions</b>                        |  |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 60 %   |
| Vapour pressure of the substance during use          | 130 Pa   |
| Process temperature                                  | 20 °C  |
| Duration and Frequency of activity                   | Exposure duration: 240 min<br>Relevant for inhalative exposure estimates                       |
| Duration and Frequency of activity                   | Application duration: 17 min<br>Relevant for inhalative exposure estimates                     |
| Duration and Frequency of activity                   | 365 uses per year  |
| Room size  | 20 m <sup>3</sup>  |
| Ventilation rate per hour                            | 0,6  |
| Temperature (Application)                            | 20 °C  |
| body weight  | 65 kg  |
| Uptake fraction dermal                               | 100 %  |
|  | Amount per use 0,007 g Relevant for dermal exposure estimates                                  |
| Release area   | 10 cm <sup>2</sup>   |
|  | Release area is constant   |
| Release duration                                     | 17 min   |
|  | Relevant for inhalative exposure estimates   |
| <b>Exposure estimate and reference to its source</b> |  |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate                                    | 0,0637 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)                    | 0,001154   |
|  | The calculation is based on the internal chronic dose.   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation |
|  | Consumer - inhalation, long-term - systemic                                      |
| Exposure estimate  | 0,0085 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,000903   |
|  | The exposure calculation is based on the mean concentration per year.            |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp</a> |  |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>  |  |
| <b>Use descriptors covered</b>   | PC8_1, PC35_1: Subcategory: Laundry and dish washing products                        |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 1 %  |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | 365 uses per year  |
| body weight  | 65 kg  |
| Skin contact factor  | 80 %   |
| Uptake fraction dermal   | 100 %  |
| Leachable fraction   | 0,0076 %   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: migration, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 0,1403 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,002542   |
|  | The calculation is based on the internal chronic dose.                               |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp</a> |  |

|                                       |   |
|---------------------------------------|---|
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | PC8_1, PC35_1: Subcategory: Laundry and dish washing products |
| <b>Operational conditions</b>         |   |
| Concentration of the substance        | ammonium chloride<br>Content: >= 0 % - <= 6 %                 |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | 128 uses per year  |
| body weight  | 65 kg  |
| Uptake fraction dermal   | 100 %  |
|  | Amount per use 0,65 g Relevant for dermal exposure estimates                                   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 0,2104 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,003812   |
|  | The calculation is based on the internal chronic dose.   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>                |  |
| <b>Use descriptors covered</b>                       | PC8_1, PC35_1: Subcategory: Laundry and dish washing products  |
| <b>Operational conditions</b>                        |  |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 10 %   |
| Vapour pressure of the substance during use          | 130 Pa   |
| Process temperature                                  | 20 °C  |
| Duration and Frequency of activity                   | 128 uses per year  |
| body weight  | 65 kg  |
| Uptake fraction dermal                               | 100 %  |
| Contact rate   | 46 mg/min  |
| Release duration                                     | 10 min   |
|  | Relevant for dermal exposure estimates   |
| <b>Exposure estimate and reference to its source</b> |  |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate                                    | 0,2482 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)                    | 0,004496   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
|  | The calculation is based on the internal chronic dose. |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp</a> |  |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>  |  |
| <b>Use descriptors covered</b>   | PC8_1, PC35_1: Subcategory: Laundry and dish washing products  |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 1\%$          |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | Exposure duration: 1 h 2 uses per year                         |
| Room size  | 20 m <sup>3</sup>  |
| Ventilation rate per hour  | 0,6  |
| Exposed skin area  | Hands and forearms (1500 cm <sup>2</sup> )                     |
| Uptake fraction dermal   | 100 %  |
|  | Amount per use 19 g Relevant for inhalative exposure estimates |
| <b>Exposure estimate and reference to its source</b>                               |  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA, Consumer                            |
|  | Consumer - dermal, long-term - systemic                        |
| Exposure estimate  | 0,0347 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,000629   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA, Consumer                            |
|  | Consumer - inhalation, long-term - systemic                    |
| Exposure estimate  | 0,0594 mg/m <sup>3</sup>                                       |
| Risk Characterization Ratio (RCR)  | 0,006316   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |  |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PC8_1, PC35_1: Subcategory: Laundry and dish washing products |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 1\%$         |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| Duration and Frequency of activity   | Exposure duration: 0,75 min<br>Relevant for inhalative exposure estimates                      |
| Duration and Frequency of activity   | Application duration: 0,3 min<br>Relevant for inhalative exposure estimates                    |
| Duration and Frequency of activity   | 104 uses per year  |
| Room size  | 1 m <sup>3</sup>   |
| Ventilation rate per hour  | 2  |
| Temperature (Application)  | 60 °C  |
| body weight  | 65 kg  |
| Uptake fraction dermal   | 100 %  |
|  | Amount per use 19 g Relevant for dermal exposure estimates                                     |
| Release area   | 20 cm <sup>2</sup>   |
|  | Release area is constant   |
| Release duration   | 0,3 min  |
|  | Relevant for inhalative exposure estimates   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 0,8329 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,015088   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation               |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate  | 0,0001 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,000001   |
|  | The exposure calculation is based on the mean concentration per year.                          |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PC8_1, PC35_1: Subcategory: Laundry and dish washing products |
| <b>Operational conditions</b>               |   |
| Concentration of the substance              | ammonium chloride<br>Content: >= 0 % - <= 6 %                 |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |
| Duration and Frequency of activity          | Exposure duration: 60 min                                     |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
|  | Relevant for inhalative exposure estimates   |
| Duration and Frequency of activity   | Application duration: 16 min<br>Relevant for inhalative exposure estimates                     |
| Duration and Frequency of activity   | 426 uses per year  |
| Room size  | 15 m <sup>3</sup>  |
| Ventilation rate per hour  | 2,5  |
| Temperature (Application)  | 20 °C  |
| body weight  | 65 kg  |
| Uptake fraction dermal   | 100 %  |
|  | Amount per use 8,6 g Relevant for dermal exposure estimates                                    |
| Release area   | 1500 cm <sup>2</sup>   |
|  | Release area is constant   |
| Release duration   | 16 min   |
|  | Relevant for inhalative exposure estimates   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 9,2652 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,167847   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation               |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate  | 0,056 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,005962   |
|  | The exposure calculation is based on the mean concentration per year.                          |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

|   |   |
|---|---|
| <b>Contributing exposure scenario</b>       |   |
| <b>Use descriptors covered</b>              | PC39: Cosmetics, personal care products.<br>In accordance to the Article 14 (5b) of the REACH Regulation (EC) No 1907/2006, exposure estimation and risk characterisation needs not to be performed for end uses in cosmetic products within the scope of Directive EC 1223/2009. |
| <b>Operational conditions</b>               |   |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

\*\*\*\*\*

## 17. Short title of exposure scenario

Use in Metal surface treatment, Consumer applications

C; C; ERC8b, ERC8e; PC14, PC38

## Control of exposure and risk management measures

| Contributing exposure scenario                |  |
|---|--|
| Use descriptors covered                       | ERC8b: Widespread use of reactive processing aid (no inclusion into or onto article, indoor)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed.  |
| Operational conditions                        |  |
| Contributing exposure scenario                |  |
| Use descriptors covered                       | ERC8e: Widespread use of reactive processing aid (no inclusion into or onto article, outdoor)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
| Operational conditions                        |  |
| Contributing exposure scenario                |  |
| Use descriptors covered                       | PC14: Metal surface treatment products, including galvanic and electroplating products.  |
| Operational conditions                        |  |
| Concentration of the substance                | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 100\%$  |
| Vapour pressure of the substance during use   | 130 Pa   |
| Process temperature                           | 20 °C  |
| Duration and Frequency of activity            | 240 uses per year  |
| Exposure estimate and reference to its source |  |
| Assessment method                             | EASY TRA v4.2, Other consideration (non-standard tool)   |
|   | Consumer - dermal, long-term - systemic  |
| Exposure estimate                             | 2,8 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)             | 0,050725   |
| Assessment method                             | EASY TRA v4.2, Other consideration (non-standard tool)   |
|   | Consumer - inhalation, long-term - systemic  |
| Exposure estimate                             | 5 mg/m <sup>3</sup>  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |          |
|--|----------|
| Risk Characterization Ratio (RCR)  | 0,531915 |
| <b>Guidance to Downstream Users</b>  |          |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |          |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>  |  |
| <b>Use descriptors covered</b>   | PC38: Welding and soldering products, flux products.   |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 100 %        |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | Exposure duration: 4 h 240 uses per year               |
| <b>Exposure estimate and reference to its source</b>                               |  |
| Assessment method  | EASY TRA v4.2, Other consideration (non-standard tool) |
|  | Consumer - dermal, long-term - systemic                |
| Exposure estimate  | 0,3 mg/kg bw/day                                       |
| Risk Characterization Ratio (RCR)  | 0,005435   |
| Assessment method  | EASY TRA v4.2, Other consideration (non-standard tool) |
|  | Consumer - inhalation, long-term - systemic            |
| Exposure estimate  | 6 mg/m <sup>3</sup>                                    |
| Risk Characterization Ratio (RCR)  | 0,638298   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |  |

\*\*\*\*\*

## 18. Short title of exposure scenario

Use in/as Fertilizers, Consumer applications

C; C; ERC8b, ERC8e; PC12, PC27

## Control of exposure and risk management measures

|                                       |   |
|---------------------------------------|---|
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | ERC8b: Widespread use of reactive processing aid (no inclusion into or onto article, indoor)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
| <b>Operational conditions</b>         |   |

|                                       |  |
|---------------------------------------|--|
| <b>Contributing exposure scenario</b> |  |
| <b>Use descriptors covered</b>        | ERC8e: Widespread use of reactive processing aid (no |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|                               |   |
|-------------------------------|---|
|                               | inclusion into or onto article, outdoor)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
| <b>Operational conditions</b> |   |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>  |  |
| <b>Use descriptors covered</b>   | PC12: Fertilizers.                                     |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 35\%$ |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | 12 uses per year                                       |
| Exposed skin area  | Both hands (820 cm <sup>2</sup> )                      |
| Uptake fraction dermal   | 100 %  |
| Uptake fraction oral   | 100 %  |
| <b>Exposure estimate and reference to its source</b>                               |  |
| Assessment method  | EASY TRA v4.2, ECETOC TRA, Consumer                    |
|  | Consumer - dermal, long-term - systemic                |
| Exposure estimate  | 2,0008 mg/kg bw/day                                    |
| Risk Characterization Ratio (RCR)  | 0,036247   |
| Assessment method  | EASY TRA v4.2, ECETOC TRA, Consumer                    |
|  | Consumer - oral, long-term - systemic                  |
| Exposure estimate  | 0,42 mg/kg bw/day                                      |
| Risk Characterization Ratio (RCR)  | 0,007609   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a> |  |

|   |  |
|---|--|
| <b>Contributing exposure scenario</b>       |  |
| <b>Use descriptors covered</b>              | PC27: Plant Protection products.                       |
| <b>Operational conditions</b>               |  |
| Concentration of the substance              | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 35\%$ |
| Vapour pressure of the substance during use | 130 Pa   |
| Process temperature                         | 20 °C  |
| Duration and Frequency of activity          | 1 uses per month                                       |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| Duration and Frequency of activity   | 1 uses per month   |
| body weight  | 65 kg  |
| Uptake fraction dermal   | 100 %  |
| Uptake fraction oral   | 100 %  |
|  | Amount per use 8,6 g Relevant for dermal exposure estimates                                    |
|  | Amount ingested 0,3 g Relevant for oral exposure estimates                                     |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 1,5436 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,027964   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Oral model: direct intake, Uptake model: Uptake fraction         |
|  | Consumer - oral, long-term - systemic  |
| Exposure estimate  | 0,0538 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,000975   |
|  | The calculation is based on the internal chronic dose.   |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

\*\*\*\*\*

## 19. Short title of exposure scenario

Use in Adhesives, Use in Surface treatment products, Wood treatment, Use in Wood articles, Consumer applications

C; C; ERC8c, ERC8f; PC1

## Control of exposure and risk management measures

|                                       |  |
|---------------------------------------|--|
| <b>Contributing exposure scenario</b> |  |
| <b>Use descriptors covered</b>        | ERC8c: Widespread use leading to inclusion into/onto article (indoor)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
| <b>Operational conditions</b>         |  |
| <b>Contributing exposure scenario</b> |  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| <b>Use descriptors covered</b>                       | ERC8f: Widespread use leading to inclusion into/onto article (outdoor)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
| <b>Operational conditions</b>                        |   |
| <b>Contributing exposure scenario</b>                |   |
| <b>Use descriptors covered</b>                       | PC1_2: Subcategory: Glues DIY-use (carpet glue, tile glue, wood parquet glue)   |
| <b>Operational conditions</b>                        |   |
| Concentration of the substance                       | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 20\%$  |
| Vapour pressure of the substance during use          | 130 Pa  |
| Process temperature                                  | 20 °C   |
| Duration and Frequency of activity                   | Exposure duration: 10 min<br>Relevant for inhalative exposure estimates   |
| Duration and Frequency of activity                   | Application duration: 10 min<br>Relevant for inhalative exposure estimates  |
| Duration and Frequency of activity                   | < 1 uses per year   |
| Room size  | 1 m <sup>3</sup>  |
| Ventilation rate per hour                            | 0,6   |
| Temperature (Application)                            | 20 °C   |
| body weight  | 65 kg   |
| Uptake fraction dermal                               | 100 %   |
|  | Amount per use 0,2 g Relevant for dermal exposure estimates   |
| Release area   | 320 cm <sup>2</sup>   |
|  | Release area is constant  |
| Release duration                                     | 10 min  |
|  | Relevant for inhalative exposure estimates  |
| <b>Exposure estimate and reference to its source</b> |   |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction  |
|  | Consumer - dermal, long-term - systemic   |
| Exposure estimate                                    | 0,0006 mg/kg bw/day   |
| Risk Characterization Ratio (RCR)                    | 0,000011  |
|  | The calculation is based on the internal chronic dose.  |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation  |
|  | Consumer - inhalation, long-term - systemic   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Exposure estimate  | 0,0194 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,002064  |
|  | The exposure calculation is based on the mean concentration per year. |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |   |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>                |  |
| <b>Use descriptors covered</b>                       | PC1_2: Subcategory: Glues DIY-use (carpet glue, tile glue, wood parquet glue)                        |
| <b>Operational conditions</b>                        |  |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 30 %   |
| Vapour pressure of the substance during use          | 130 Pa   |
| Process temperature                                  | 20 °C  |
| Duration and Frequency of activity                   | Exposure duration: 75 min<br>Relevant for inhalative exposure estimates                              |
| Duration and Frequency of activity                   | Application duration: 75 min<br>Relevant for inhalative exposure estimates                           |
| Duration and Frequency of activity                   | < 1 uses per year  |
| Room size  | 58 m <sup>3</sup>  |
| Ventilation rate per hour                            | 0,5  |
| Temperature (Application)                            | 20 °C  |
| body weight  | 65 kg  |
| Uptake fraction dermal                               | 100 %  |
| Release area   | 40000 cm <sup>2</sup>  |
|  | Release area is constant   |
| Release duration                                     | 75 min   |
|  | Relevant for inhalative exposure estimates   |
| Contact rate   | 30 mg/min  |
| Release duration                                     | 75 min   |
|  | Relevant for dermal exposure estimates   |
| <b>Exposure estimate and reference to its source</b> |  |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate                                    | 0,0071 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)                    | 0,000129   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation                     |
|  | Consumer - inhalation, long-term - systemic  |



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Exposure estimate  | 0,0978 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,010405  |
|  | The exposure calculation is based on the mean concentration per year. |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp</a> |   |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>                |  |
| <b>Use descriptors covered</b>                       | PC1_2: Subcategory: Glues DIY-use (carpet glue, tile glue, wood parquet glue)                  |
| <b>Operational conditions</b>                        |  |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 30 %   |
| Vapour pressure of the substance during use          | 130 Pa   |
| Process temperature                                  | 20 °C  |
| Duration and Frequency of activity                   | Exposure duration: 240 min<br>Relevant for inhalative exposure estimates                       |
| Duration and Frequency of activity                   | Application duration: 240 min<br>Relevant for inhalative exposure estimates                    |
| Duration and Frequency of activity                   | < 1 uses per year  |
| Room size  | 58 m <sup>3</sup>  |
| Ventilation rate per hour                            | 0,5  |
| Temperature (Application)                            | 20 °C  |
| body weight  | 65 kg  |
| Uptake fraction dermal                               | 100 %  |
|  | Amount per use 0,5 g Relevant for dermal exposure estimates                                    |
| Release area   | 10000 cm <sup>2</sup>  |
|  | Release area is constant   |
| Release duration                                     | 240 min  |
|  | Relevant for inhalative exposure estimates   |
| <b>Exposure estimate and reference to its source</b> |  |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate                                    | 0,0016 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)                    | 0,000029   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation               |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate                                    | 0,1408 mg/m <sup>3</sup>   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Risk Characterization Ratio (RCR)  | 0,014979  |
|  | The exposure calculation is based on the mean concentration per year. |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |   |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>                |  |
| <b>Use descriptors covered</b>                       | PC1_2: Subcategory: Glues DIY-use (carpet glue, tile glue, wood parquet glue)                        |
| <b>Operational conditions</b>                        |  |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 20 %   |
| Vapour pressure of the substance during use          | 130 Pa   |
| Process temperature                                  | 20 °C  |
| Duration and Frequency of activity                   | Exposure duration: 480 min<br>Relevant for inhalative exposure estimates                             |
| Duration and Frequency of activity                   | Application duration: 480 min<br>Relevant for inhalative exposure estimates                          |
| Duration and Frequency of activity                   | < 1 uses per year  |
| Room size  | 58 m <sup>3</sup>  |
| Ventilation rate per hour                            | 0,5  |
| Temperature (Application)                            | 20 °C  |
| body weight  | 65 kg  |
| Uptake fraction dermal                               | 100 %  |
| Release area   | 10000 cm <sup>2</sup>  |
|  | Release area is constant   |
| Release duration                                     | 480 min  |
|  | Relevant for inhalative exposure estimates   |
| Contact rate   | 30 mg/min  |
| Release duration                                     | 480 min  |
|  | Relevant for dermal exposure estimates   |
| <b>Exposure estimate and reference to its source</b> |  |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate                                    | 0,0152 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)                    | 0,000275   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation                     |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate                                    | 0,3041 mg/m <sup>3</sup>   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
| Risk Characterization Ratio (RCR)  | 0,032355  |
|  | The exposure calculation is based on the mean concentration per year. |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp</a> |   |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>                |  |
| <b>Use descriptors covered</b>                       | PC1_2: Subcategory: Glues DIY-use (carpet glue, tile glue, wood parquet glue)                  |
| <b>Operational conditions</b>                        |  |
| Concentration of the substance                       | ammonium chloride<br>Content: >= 0 % - <= 30 %   |
| Vapour pressure of the substance during use          | 130 Pa   |
| Process temperature                                  | 20 °C  |
| Duration and Frequency of activity                   | Exposure duration: 240 min<br>Relevant for inhalative exposure estimates                       |
| Duration and Frequency of activity                   | Application duration: 30 min<br>Relevant for inhalative exposure estimates                     |
| Duration and Frequency of activity                   | 2 uses per year  |
| Room size  | 20 m3  |
| Ventilation rate per hour                            | 0,6  |
| Temperature (Application)                            | 20 °C  |
| body weight  | 65 kg  |
| Uptake fraction dermal                               | 100 %  |
|  | Amount per use 0,25 g Relevant for dermal exposure estimates                                   |
| Release area   | 10000 cm <sup>2</sup>  |
|  | Release area increases over time   |
| Release duration                                     | 30 min   |
|  | Relevant for inhalative exposure estimates   |
| <b>Exposure estimate and reference to its source</b> |  |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate                                    | 0,0063 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)                    | 0,000115   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation               |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate                                    | 1,2723 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)                    | 0,135346   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |   |
|--|---|
|  | The exposure calculation is based on the mean concentration per year. |
| <b>Guidance to Downstream Users</b>  |   |
| For scaling see: <a href="http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp</a> |   |

|  |  |
|--|--|
| <b>Contributing exposure scenario</b>                |  |
| <b>Use descriptors covered</b>                       | PC1_1: Subcategory: Glues, hobby use   |
| <b>Operational conditions</b>                        |  |
| Concentration of the substance                       | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 30\%$   |
| Vapour pressure of the substance during use          | 130 Pa   |
| Process temperature                                  | 20 °C  |
| Duration and Frequency of activity                   | Exposure duration: 240 min<br>Relevant for inhalative exposure estimates                       |
| Duration and Frequency of activity                   | Application duration: 5 min<br>Relevant for inhalative exposure estimates                      |
| Duration and Frequency of activity                   | 12 uses per year   |
| Room size  | 20 m <sup>3</sup>  |
| Ventilation rate per hour                            | 0,6  |
| Temperature (Application)                            | 20 °C  |
| body weight  | 65 kg  |
| Uptake fraction dermal                               | 100 %  |
|  | Amount per use 0,025 g Relevant for dermal exposure estimates                                  |
| Release area   | 2 cm <sup>2</sup>  |
|  | Release area increases over time   |
| Release duration                                     | 5 min  |
|  | Relevant for inhalative exposure estimates   |
| <b>Exposure estimate and reference to its source</b> |  |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate                                    | 0,0038 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)                    | 0,000069   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method                                    | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation               |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate                                    | 0,0155 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)                    | 0,001647   |
|  | The exposure calculation is based on the mean concentration per year.                          |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

### **Guidance to Downstream Users**

For scaling see: <http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp>

### **Contributing exposure scenario**

|  |  |
|--|--|
| <b>Use descriptors covered</b>   | PC1_1: Subcategory: Glues, hobby use   |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 30\%$   |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | Exposure duration: 5 min<br>Relevant for inhalative exposure estimates                         |
| Duration and Frequency of activity   | Application duration: 5 min<br>Relevant for inhalative exposure estimates                      |
| Duration and Frequency of activity   | 3 uses per year  |
| Room size  | 1 m <sup>3</sup>   |
| Ventilation rate per hour  | 0,6  |
| Temperature (Application)  | 20 °C  |
| body weight  | 65 kg  |
| Uptake fraction dermal   | 100 %  |
|  | Amount per use 0,05 g Relevant for dermal exposure estimates                                   |
| Release area   | 20 cm <sup>2</sup>   |
|  | Release area is constant   |
| Release duration   | 5 min  |
|  | Relevant for inhalative exposure estimates   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 0,0019 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,000034   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation               |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate  | 0,0763 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,008118   |
|  | The exposure calculation is based on the mean concentration per year.                          |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

| <b>Contributing exposure scenario</b>  |  |
|--|--|
| <b>Use descriptors covered</b>   | PC1_1: Subcategory: Glues, hobby use   |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: >= 0 % - <= 30 %   |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | Exposure duration: 240 min<br>Relevant for inhalative exposure estimates                       |
| Duration and Frequency of activity   | Application duration: 30 min<br>Relevant for inhalative exposure estimates                     |
| Duration and Frequency of activity   | 3 uses per year  |
| Room size  | 20 m3  |
| Ventilation rate per hour  | 0,6  |
| Temperature (Application)  | 20 °C  |
| body weight  | 65 kg  |
| Uptake fraction dermal   | 100 %  |
|  | Amount per use 0,1 g Relevant for dermal exposure estimates                                    |
| Release area   | 500 cm <sup>2</sup>  |
|  | Release area increases over time   |
| Release duration   | 30 min   |
|  | Relevant for inhalative exposure estimates   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 0,0038 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,000069   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation               |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate  | 0,153 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,01628  |
|  | The exposure calculation is based on the mean concentration per year.                          |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp</a> |  |

|                                       |
|---------------------------------------|
| <b>Contributing exposure scenario</b> |
|---------------------------------------|

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| <b>Use descriptors covered</b>   | PC1_1: Subcategory: Glues, hobby use   |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 30\%$   |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | Exposure duration: 45 min<br>Relevant for inhalative exposure estimates                              |
| Duration and Frequency of activity   | Application duration: 30 min<br>Relevant for inhalative exposure estimates                           |
| Duration and Frequency of activity   | 3 uses per year  |
| Room size  | 10 m <sup>3</sup>  |
| Ventilation rate per hour  | 2  |
| Temperature (Application)  | 20 °C  |
| body weight  | 65 kg  |
| Uptake fraction dermal   | 100 %  |
| Release area   | 250 cm <sup>2</sup>  |
|  | Release area increases over time   |
| Release duration   | 30 min   |
|  | Relevant for inhalative exposure estimates   |
| Contact rate   | 50 mg/min  |
| Release duration   | 30 min   |
|  | Relevant for dermal exposure estimates   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 0,0569 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,001031   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation                     |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate  | 0,2373 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,025246   |
|  | The exposure calculation is based on the mean concentration per year.                                |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp</a> |  |
| <b>Contributing exposure scenario</b>  |  |
| <b>Use descriptors covered</b>   | PC1_1: Subcategory: Glues, hobby use   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 30\%$   |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | Exposure duration: 240 min<br>Relevant for inhalative exposure estimates                       |
| Duration and Frequency of activity   | Application duration: 30 min<br>Relevant for inhalative exposure estimates                     |
| Duration and Frequency of activity   | 1 uses per year  |
| Room size  | 20 m <sup>3</sup>  |
| Ventilation rate per hour  | 0,6  |
| Temperature (Application)  | 20 °C  |
| body weight  | 65 kg  |
| Uptake fraction dermal   | 100 %  |
|  | Amount per use 0,5 g Relevant for dermal exposure estimates                                    |
| Release area   | 15000 cm <sup>2</sup>  |
|  | Release area increases over time   |
| Release duration   | 30 min   |
|  | Relevant for inhalative exposure estimates   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 0,0063 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,000115   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation               |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate  | 0,9541 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,101499   |
|  | The exposure calculation is based on the mean concentration per year.                          |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp</a> |  |
| <b>Contributing exposure scenario</b>  |  |
| Use descriptors covered  | PC1_1: Subcategory: Glues, hobby use   |
| <b>Operational conditions</b>  |  |



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 5\%$  |
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | Exposure duration: 240 min<br>Relevant for inhalative exposure estimates                       |
| Duration and Frequency of activity   | Application duration: 10 min<br>Relevant for inhalative exposure estimates                     |
| Duration and Frequency of activity   | 52 uses per year   |
| Room size  | 20 m <sup>3</sup>  |
| Ventilation rate per hour  | 0,6  |
| Temperature (Application)  | 20 °C  |
| body weight  | 65 kg  |
| Uptake fraction dermal   | 100 %  |
|  | Amount per use 0,08 g Relevant for dermal exposure estimates                                   |
| Release area   | 200 cm <sup>2</sup>  |
|  | Release area increases over time   |
| Release duration   | 10 min   |
|  | Relevant for inhalative exposure estimates   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 0,0088 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,000159   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation               |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate  | 1,411 mg/m <sup>3</sup>  |
| Risk Characterization Ratio (RCR)  | 0,150111   |
|  | The exposure calculation is based on the mean concentration on the day of exposure.            |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp</a> |  |
| <b>Contributing exposure scenario</b>  |  |
| Use descriptors covered  | PC1_1: Subcategory: Glues, hobby use   |
| <b>Operational conditions</b>  |  |
| Concentration of the substance   | ammonium chloride<br>Content: $\geq 0\%$ - $\leq 5\%$  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| Vapour pressure of the substance during use  | 130 Pa   |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | Exposure duration: 240 min<br>Relevant for inhalative exposure estimates                       |
| Duration and Frequency of activity   | Application duration: 20 min<br>Relevant for inhalative exposure estimates                     |
| Duration and Frequency of activity   | 52 uses per year   |
| Room size  | 20 m <sup>3</sup>  |
| Ventilation rate per hour  | 0,6  |
| Temperature (Application)  | 20 °C  |
| body weight  | 65 kg  |
| Uptake fraction dermal   | 100 %  |
|  | Amount per use 0,08 g Relevant for dermal exposure estimates                                   |
| Release area   | 400 cm <sup>2</sup>  |
|  | Release area increases over time   |
| Release duration   | 20 min   |
|  | Relevant for inhalative exposure estimates   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 0,0088 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,000159   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation               |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate  | 1,5604 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,166004   |
|  | The exposure calculation is based on the mean concentration on the day of exposure.            |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthandddisease/productsafety/ConsExpo.jsp</a> |  |

|                                       |  |
|---------------------------------------|--|
| <b>Contributing exposure scenario</b> |  |
| <b>Use descriptors covered</b>        | PC1_3: Subcategory: Glue from spray            |
| <b>Operational conditions</b>         |  |
| Concentration of the substance        | ammonium chloride<br>Content: >= 0 % - <= 10 % |
| Vapour pressure of the substance      | 130 Pa   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|  |  |
|--|--|
| during use   |  |
| Process temperature  | 20 °C  |
| Duration and Frequency of activity   | Exposure duration: 240 min<br>Relevant for inhalative exposure estimates                             |
| Duration and Frequency of activity   | 12 uses per year   |
| Room size  | 20 m <sup>3</sup>  |
| Ventilation rate per hour  | 0,6  |
| body weight  | 65 kg  |
| Uptake fraction dermal   | 100 %  |
| Spray duration   | 169,8 sec  |
| Contact rate   | 100 mg/min   |
| Release duration   | 2,83 min   |
|  | Relevant for dermal exposure estimates   |
| <b>Risk Management Measures</b>  |  |
| Consumer Measures  | Ensure spraying away from persons.   |
| <b>Exposure estimate and reference to its source</b>   |  |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction |
|  | Consumer - dermal, long-term - systemic  |
| Exposure estimate  | 0,0143 mg/kg bw/day  |
| Risk Characterization Ratio (RCR)  | 0,000259   |
|  | The calculation is based on the internal chronic dose.   |
| Assessment method  | EASY TRA v4.2, ConsExpo v4.1, Inhalation model: Exposure to spray/dust                               |
|  | Consumer - inhalation, long-term - systemic  |
| Exposure estimate  | 0,1799 mg/m <sup>3</sup>   |
| Risk Characterization Ratio (RCR)  | 0,019135   |
|  | The exposure calculation is based on the mean concentration per year.                                |
| <b>Guidance to Downstream Users</b>  |  |
| For scaling see: <a href="http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp">http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp</a> |  |

\*\*\*\*\*

## 20. Short title of exposure scenario

Use in Batteries, Consumer applications

C; C; ERC9a, ERC9b; PC42

## Control of exposure and risk management measures

|                                       |   |
|---------------------------------------|---|
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | ERC9a: Widespread use of functional fluid (indoor)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|                               |                                 |
|-------------------------------|---------------------------------|
|                               | characterization was performed. |
| <b>Operational conditions</b> |                                 |

|                                       |  |
|---------------------------------------|--|
| <b>Contributing exposure scenario</b> |  |
| <b>Use descriptors covered</b>        | ERC9b: Widespread use of functional fluid (outdoor)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
| <b>Operational conditions</b>         |  |

|   |  |
|---|--|
| <b>Contributing exposure scenario</b>       |  |
| <b>Use descriptors covered</b>              | PC42: Electrolytes for batteries<br>Use in closed system is assumed Exposure of the consumer can be ruled out. |
| <b>Operational conditions</b>               |  |
| Vapour pressure of the substance during use | 130 Pa   |
| Process temperature                         | 20 °C  |

\*\*\*\*\*

## 21. Short title of exposure scenario

Use in Batteries, Service life of articles, Consumer applications  
C; C; ERC10a, ERC11a, ERC12a; AC3

## Control of exposure and risk management measures

|                                       |  |
|---------------------------------------|--|
| <b>Contributing exposure scenario</b> |  |
| <b>Use descriptors covered</b>        | ERC10a: Widespread use of articles with low release (outdoor)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
| <b>Operational conditions</b>         |  |

|                                       |   |
|---------------------------------------|---|
| <b>Contributing exposure scenario</b> |   |
| <b>Use descriptors covered</b>        | ERC11a: Widespread use of articles with low release (indoor)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
| <b>Operational conditions</b>         |   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

| <b>Contributing exposure scenario</b> |  |
|---------------------------------------|--|
| <b>Use descriptors covered</b>        | ERC12a: Processing of articles at industrial sites with low release<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
| <b>Operational conditions</b>         |  |

| <b>Contributing exposure scenario</b>       |  |
|---|--|
| <b>Use descriptors covered</b>              | AC3: Electrical batteries and accumulators<br>Use in closed system is assumed Exposure of the consumer can be ruled out. |
| <b>Operational conditions</b>               |  |
| Vapour pressure of the substance during use | 130 Pa   |
| Process temperature                         | 20 °C  |

\*\*\*\*\*

## 22. Short title of exposure scenario

Use in pharmaceuticals, Use as Additive, Dietary intake, Use in cosmetics, Use in/as Flavouring agent(s), Consumer applications

C; C; ERC8a, ERC8b, ERC8e; PC20, PC29, PC39

## Control of exposure and risk management measures

| <b>Contributing exposure scenario</b> |   |
|---------------------------------------|---|
| <b>Use descriptors covered</b>        | ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
| <b>Operational conditions</b>         |   |

| <b>Contributing exposure scenario</b> |   |
|---------------------------------------|---|
| <b>Use descriptors covered</b>        | ERC8b: Widespread use of reactive processing aid (no inclusion into or onto article, indoor)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
| <b>Operational conditions</b>         |   |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

| Contributing exposure scenario |  |
|--------------------------------|--|
| <b>Use descriptors covered</b> | ERC8e: Widespread use of reactive processing aid (no inclusion into or onto article, outdoor)<br>As no environmental hazard was identified no environmental-related exposure assessment and risk characterization was performed. |
| <b>Operational conditions</b>  |  |

| Contributing exposure scenario              |   |
|---|---|
| <b>Use descriptors covered</b>              | PC20: Products such as ph-regulators, flocculants, precipitants, neutralisation agents.<br>In accordance to Article 2 (5a and 5b i and 5b ii) of the REACH Regulation (EC) No 1907/2006, use in medicinal products for humans as well as use as a food additive and as a flavoring agent is not subject to registration and is covered within the scopes of Directive 2001/83/EC, Directive 89/107/EEC, and Decision 1999/217/EC. |
| <b>Operational conditions</b>               |   |
| Vapour pressure of the substance during use | 130 Pa  |
| Process temperature                         | 20 °C   |

| Contributing exposure scenario              |  |
|---|--|
| <b>Use descriptors covered</b>              | PC29: Pharmaceuticals.<br>In accordance to Article 2 (5a and 5b i and 5b ii) of the REACH Regulation (EC) No 1907/2006, use in medicinal products for humans as well as use as a food additive and as a flavoring agent is not subject to registration and is covered within the scopes of Directive 2001/83/EC, Directive 89/107/EEC, and Decision 1999/217/EC. |
| <b>Operational conditions</b>               |  |
| Vapour pressure of the substance during use | 130 Pa   |
| Process temperature                         | 20 °C  |

| Contributing exposure scenario   |   |
|----------------------------------|---|
| <b>Use descriptors covered</b>   | PC39: Cosmetics, personal care products.<br>In accordance to the Article 14 (5b) of the REACH Regulation (EC) No 1907/2006, exposure estimation and risk characterisation needs not to be performed for end uses in cosmetic products within the scope of Directive EC 1223/2009. |
| <b>Operational conditions</b>    |   |
| Vapour pressure of the substance | 130 Pa  |

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 08.08.2025

Version: 2.0

Date / Previous version: 25.04.2025

Previous version: 1.0

Product: **Ammonium chloride RWS food grade**

(ID no. 30042426/SDS\_GEN\_GR/EN)

Date of print 13.10.2025

|                     |       |
|---------------------|-------|
| during use          |       |
| Process temperature | 20 °C |

\*\*\*\*\*