

Foamaster[®] MO 2119

Product description Liquid defoamer based on mineral oil.

- Key benefits**
- Excellent pigment wetting properties
 - Suited for water-borne pigment dispersions and paper coatings

Chemical nature Polyether polyol that is mineral oil and silicone free.

Properties

Physical form Clear liquid

Technical data (no supply specification)	Color (APHA)		~ 100
	Specific Gravity		~ 0.980
	pH (10:6, IpA-water)		< 6.75
	Moisture	%	< 0.5
	Density	lbs/gal	8.2

Application

No one defoamer can best service all manufacturing procedures. Individual manufacturing methods will determine the optimum amount of defoamer. Proper recommendations for individual systems and operating conditions can be made by our Technical Representatives.

Formulation guideline

A defoamer level of 0.5% based on the total weight of the material to be defoamed is a good starting point for determining the optimum use level.

Storage

Foamaster MO 2119 is shipped in 55 gallon steel tightened drums. Foamaster MO 2119 will not settle or separate under normal room temperature conditions, therefore no stirring is required.

Contacts worldwide

Asia
BASF East Asia Regional Headquarters Ltd
45/F, Jardine House
No. 1 Connaught Place
Central Hong Kong
China
formulation-additives-asia@basf.com

North America
BASF Corporation
11501 Steele Creek Road
Charlotte, NC 28273
USA
formulation-additives-nafta@basf.com

Europe
BASF SE
Formulation Additives
67056 Ludwigshafen
Germany
formulation-additives-europe@basf.com

South America
BASF S.A
Rochaverá - Crystal Tower
Av. das Nações Unidas, 14.171
Morumbi - São Paulo-SP
Brazil
formulation-additives-south-america@basf.com

Validity

This Technical Data Sheet is valid for all versions of the Foamaster® MO 2119.

Safety

When handling this product, please comply with the advice and information given in the safety data sheet and observe protective and workplace hygiene measures adequate for handling chemicals.

Note

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the product for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreed contractual quality of the product. The agreed contractual quality of the product results exclusively from the statements made in the product specification. It is the responsibility of the recipient of our product to ensure that any proprietary rights and existing laws and legislation are observed.

® = Registered trademark

™ = Trademark of the BASF Group, unless otherwise noted

www.basf.com/formulation-additives