

Tinuvin® 249

Product Description Tinuvin 249 is a liquid non-basic HALS for coatings. It is designed to meet the high

performance and durability requirements of all solvent-based automotive, industrial and decorative coatings where other HALS fail either related to their basicity or for

compatibility reasons.

Key Features & Benefits - non-basic HALS

- low viscosity, solvent-free

- does not interact with acidic paint ingredients such as catalyst, biocides or pigments

- high thermal stability, excellent color stability during shelf life

- broad compatibility in solvent-based systems of different polarity, non-exuding

- good long-term performance

Chemical Structure

piperidine derivative

Properties

Typical Properties

CAS No: proprietary

Appearance slightly yellow liquid

Miscibility readily miscible with most common organic solvents,

immiscible with water

These typical values should not be interpreted as specifications.

Applications

Tinuvin 249 is designed for coatings where traditional HALS fail either related to their basicity (e.g. acid/base interactions) or for compatibility reasons (e.g. exudation).

Fields of application include:

- Automotive OEM and Refinish coatings
- · Industrial coatings
- · Coil coatings
- Decorative coatings
- Adhesives

For clear-coat applications, Tinuvin 249 needs to be combined with a UV absorber (UVA) such as Tinuvin 400 or Tinuvin 384-2 (automotive finishes) or Tinuvin 1130 (industrial finishes) or Tinuvin 99-2 (decorative finishes).

Binders:

- acid catalyzed thermosetting (acrylic/melamine, PES/melamine...)
- epoxy/carboxy (amine and/or metal catalyzed)
- 2p-PU (polyol/polyester/isocyanate)
- · alkyd/acrylic oxidative curing coatings

Recommended Concentrations

The concentration of Tinuvin 249 needed depends on the level of pigmentation of the coating. The amount required for optimum performance should be determined in laboratory trials covering a concentration range.

Coating type by weight on binder solids

Clear coats 1%
Semi-transparent 1 – 2%
Opaque / solid shade 2 – 4%

(concentrations are based on weight percent binder solids)

Safety

General

The usual safety precautions when handling chemicals must be observed. These include the measure described in Federal, State and Local health and safety regulations, thorough ventilation of the workplace, good skin care, and wearing of protective goggles.

Safety Data Sheet

All safety information is provided in the Safety Data Sheet for Tinuvin 249.

Storage

Please refer to the "Handling and Storage of Polymer Dispersions" brochure.

Important

WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, THEY ARE PROVIDED FOR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, BASF RECOMMENDS THAT THE READER MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR A PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESCRIPTIONS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF BASF'S TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTIONS, DESIGNS, DATA OR INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT THE READER'S RISK.

Tinuvin is a registered trademark of BASF Group.

© BASF Corporation, 2022



BASF Corporation is fully committed to the Responsible Care® initiative in the USA, Canada, and Mexico. For more information on Responsible Care® go to: U.S.: www.basf.us/responsiblecare_usa Canada: www.basf.us/responsiblecare_canada México: www.basf.us/responsiblecare_mexico

BASF Corporation

Dispersions and Resins
11501 Steele Creek Road
Charlotte, North Carolina 28273
Phone: (800) 251 – 0612
Email: CustCare-Charlotte@basf.com
www.basf.us/dpsolutions