

Safety data sheet

Page: 1/24

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.05.2025 Version: 3.4
Date / Previous version: 18.01.2024 Previous version: 3.3

Product: Na-Methylate sol. 30 %

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Na-Methylate sol. 30 %

UFI: 364V-DFPR-N00R-X177

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: industrial chemicals

Recommended use: process chemical, Intermediate, catalyst

1.3. Details of the supplier of the safety data sheet

Company:
BASF SE
67056 Ludwigshafen
GERMANY
Division Monomers

Telephone: +49 621 60 42737

E-mail address: pss.monomers@basf.com

1.4. Emergency telephone number

International emergency number: Telephone: +49 180 2273-112

Date / Revised: 16.05.2025 Version: 3.4
Date / Previous version: 18.01.2024 Previous version: 3.3

Product: Na-Methylate sol. 30 %

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

According to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 3 H226 Flammable liquid and vapour. Met. Corr. 1 H290 May be corrosive to metals.

Acute Tox. 3 (Inhalation - H331 Toxic if inhaled.

vapour)

Acute Tox. 3 (oral)

Acute Tox. 3 (oral)

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage. STOT SE 1 H370 Causes damage to organs.

According to BASF current knowledge and application of the criteria given in Annex I of Regulation (EC) No. 1272/2008, the following classification exceeding the classification given in Regulation (EC) No 1272/2008, Annex VI, Table 3.1 is required.

Skin Corr. 1A

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

Pictogram:









Signal Word:

Danger

Hazard Statement:

H226 Flammable liquid and vapour. H290 May be corrosive to metals. H370 Causes damage to organs.

H314 Causes severe skin burns and eye damage. H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled.

Precautionary Statements (Prevention):

P280 Wear protective gloves, protective clothing and eye protection or face

protection.

P271 Use only outdoors or in a well-ventilated area.

Precautionary Statements (Response):

P310 Immediately call a POISON CENTER or physician.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

to Regulation (EC) No 1907/2006.

Date / Revised: 16.05.2025 Version: 3.4
Date / Previous version: 18.01.2024 Previous version: 3.3

Product: Na-Methylate sol. 30 %

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

Precautionary Statements (Storage):

P403 + P235 Store in a well-ventilated place. Keep cool.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste

collection point.

Hazard determining component(s) for labelling: sodium methanolate, methanol

2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

No specific dangers known, if the regulations/notes for storage and handling are considered. If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture. The product does not contain a substance above legal limits fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria. Product does not contain a substance above legal limits included in the list established in

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Chemical nature

Preparation based on:sodium methanolate, methanol

Regulatory relevant ingredients

methanol

to Regulation (EC) No 1907/2006.

Date / Revised: 16.05.2025 Version: 3.4 Date / Previous version: 18.01.2024 Previous version: 3.3

Product: Na-Methylate sol. 30 %

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

Content (W/W): >= 50 % - < 75 % Flam. Liq. 2

CAS Number: 67-56-1 Acute Tox. 3 (Inhalation - vapour)

Acute Tox. 3 (oral) EC-Number: 200-659-6 REACH registration number: 01-Acute Tox. 3 (dermal)

2119433307-44

STOT SE (Central nervous system, Optic nerve)

INDEX-Number: 603-001-00-X

H225, H301 + H311 + H331, H370

Substance with EU occupational

exposure limit

Specific concentration limit:

STOT SE 2: 3 - < 10 % STOT SE 1: >= 10 %

Acute toxicity estimate:

oral: 100 mg/kg Inhalation: 3 mg/l dermal: 300 mg/kg

sodium methanolate

Content (W/W): >= 25 % - < 50 %

CAS Number: 124-41-4 EC-Number: 204-699-5

REACH registration number: 01-

2119519241-51

INDEX-Number: 603-040-00-2

Flam. Sol. 1

Self-heat. 1

Acute Tox. 4 (oral) Skin Corr. 1B

Eve Dam. 1

H228, H251, H302, H314

EUH014, EUH071

Differing classification according to current knowledge and the criteria given in Annex I of

Regulation (EC) No. 1272/2008

Flam. Sol. 1 Self-heat. 1 Acute Tox. 4 (oral) Skin Corr. 1A Eye Dam. 1 EUH014, EUH071

Acute toxicity estimate:

oral: 1.687 mg/kg

sodium hydroxide

Content (W/W): >= 0 % - < 1 %Met. Corr. 1 CAS Number: 1310-73-2 Skin Corr. 1A EC-Number: 215-185-5 Eye Dam. 1 REACH registration number: 01-H290, H314

2119457892-27

INDEX-Number: 011-002-00-6

Specific concentration limit:

Skin Irrit. 2: 0,5 - < 2 % Eye Irrit. 2: 0,5 - < 2 % Skin Corr. 1A: >= 5 % Skin Corr. 1B: 2 - < 5 %

to Regulation (EC) No 1907/2006. Date / Revised: 16.05.2025

Version: 3.4 Previous version: 3.3

Date / Previous version: 18.01.2024 Product: **Na-Methylate sol. 30 %**

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

On contact with eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200 - 300 ml water, do not induce vomiting, seek medical attention. Administer 50 ml of pure ethanol in a drinkable concentration. Seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: skin corrosion, irritates the eyes and respiratory tract, blindness, Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

Hazards: No hazard is expected under intended use and appropriate handling.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Symptomatic treatment (decontamination, vital functions).

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media: dry powder, Dry sand, alcohol-resistant foam

Unsuitable extinguishing media for safety reasons: water, carbon dioxide

to Regulation (EC) No 1907/2006.

Date / Revised: 16.05.2025 Version: 3.4
Date / Previous version: 18.01.2024 Previous version: 3.3

Product: Na-Methylate sol. 30 %

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

5.2. Special hazards arising from the substance or mixture

Advice: Risk of exothermic reaction.

5.3. Advice for fire-fighters

Special protective equipment:

Wear self-contained breathing apparatus and chemical-protective clothing.

Further information:

Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Sealed containers should be protected against heat as this results in pressure build-up.

SECTION 6: Accidental Release Measures

Release of substance/product can cause fire or explosion.

6.1. Personal precautions, protective equipment and emergency procedures

Sources of ignition should be kept well clear. Avoid inhalation. Avoid contact with skin and eyes.

For non-emergency personnel: Use personal protective clothing. Information regarding personal protective measures, see section 8.

For emergency responders: Take appropriate protective measures.

6.2. Environmental precautions

Do not discharge into drains/surface waters/groundwater. Contain contaminated water/firefighting water.

6.3. Methods and material for containment and cleaning up

For large amounts: Pump off product.

For residues: Pick up with suitable absorbent material (e.g. sand, sawdust, general-purpose binder, kieselguhr). Dispose of absorbed material in accordance with regulations.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Ensure thorough ventilation of stores and work areas. Protect against moisture. Protect against heat.

to Regulation (EC) No 1907/2006.

Date / Revised: 16.05.2025 Version: 3.4
Date / Previous version: 18.01.2024 Previous version: 3.3

Product: Na-Methylate sol. 30 %

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

Solidified/precipitated product can be redissolved with a non-igniting heat source provided that the formation of an atmosphere capable to explode is suppressed by inertization or sources of ignition are absent. A possible rise in pressure caused by evaporating solvent has to be taken into account.

When using do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. Change clothes immediately after contamination.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Take precautionary measures against static discharges. Use antistatic tools. Render equipment and apparatus inert (nitrogen, inert gases) and ground before putting into operation. Fire extinguishers should be kept handy.

7.2. Conditions for safe storage, including any incompatibilities

Segregate from acids and acid forming substances. Keep away from water.

Suitable materials for containers: Stove-lacquer KNS L-35, Carbon steel (Iron), Stainless steel 1.4401, Stainless steel 1.4301 (V2), High density polyethylene (HDPE), glass, Low density polyethylene (LDPE), Stainless steel 1.4541, Stainless steel 1.4571 Unsuitable materials for containers: Aluminium, Galvanized carbon steel (Zinc), Paper/Fibreboard Further information on storage conditions: Keep container tightly closed in a cool, well-ventilated place. Keep under dry nitrogen. Protect against moisture. Protect against heat. Keep away from sources of ignition - No smoking.

Storage class according to TRGS 510 (originally VCI, Germany): (3) Flammable liquids

Protect from temperatures below:7 °C

The product crystallizes below the limit temperature.

7.3. Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

The surveillance of the workplace by exposure measurements may be necessary, in order to prove the efficiency of safety measures, for example ventilation or the need of respiratory protection. Since this requires a specific competency, only accredited laboratories should be contracted. Regarding suitable methods to assess inhalation exposure, the European Standards EN 482, 689 and 14042 are to be considered. In addition, the TRGS 402 has to be observed in Germany.

67-56-1: methanol

Skin Designation (OEL (EU))

The substance can be absorbed through the skin.

to Regulation (EC) No 1907/2006.

Date / Revised: 16.05.2025 Version: 3.4
Date / Previous version: 18.01.2024 Previous version: 3.3

Product: Na-Methylate sol. 30 %

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

TWA value 260 mg/m3; 200 ppm (OEL (EU))

indicative

Skin Designation (TRGS 900 (DE))

The substance can be absorbed through the skin. Short Term Exposure Classification: (TRGS 900 (DE))

Category II: Substances with a resorptive effect OEL 130 mg/m3; 100 ppm (TRGS 900 (DE))

Ceiling limit value/factor: 2

If the occupational exposure limit value (AGW) and the biological limit value (BGW) are complied with, there should be no risk of damage for the unborn child (see TRGS 900, Number 2.7)

Components with PNEC

67-56-1: methanol

freshwater:

No hazard identified.

marine water:

No hazard identified.

intermittent release:

No hazard identified.

STP:

No hazard identified.

sediment (freshwater):

No hazard identified.

sediment (marine water):

No hazard identified.

soil:

No hazard identified.

oral (secondary poisoning):

No bioaccumulation potential.

124-41-4: sodium methanolate

freshwater:

No hazard identified.

marine water:

No hazard identified.

intermittent release:

No hazard identified.

sediment (freshwater):

No hazard identified.

sediment (marine water):

No hazard identified.

soil:

No hazard identified.

STP:

No hazard identified.

oral (secondary poisoning):

No PNEC oral derived, as accumulation in organisms is not to be expected.

to Regulation (EC) No 1907/2006.

Date / Revised: 16.05.2025 Version: 3.4
Date / Previous version: 18.01.2024 Previous version: 3.3

Product: Na-Methylate sol. 30 %

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

Components with DNEL

67-56-1: methanol

worker: Long-term exposure- systemic effects, dermal: 20 mg/kg worker: Short-term exposure - systemic effects, dermal: 20 mg/kg worker: Long- and short-term exposure - local effects, dermal No hazard identified.

worker: Long-term exposure - systemic effects, Inhalation: 130 mg/m3 worker: Short-term exposure - systemic effects, Inhalation: 130 mg/m3 worker: Long-term exposure - local effects, Inhalation: 130 mg/m3 worker: Short-term exposure - local effects, Inhalation: 130 mg/m3 consumer: Long-term exposure - systemic effects, oral: 4 mg/kg consumer: Short-term exposure - systemic effects, oral: 4 mg/kg consumer: Long-term exposure - systemic effects, dermal: 4 mg/kg consumer: Short-term exposure - systemic effects, dermal: 4 mg/kg consumer: Long- and short-term exposure - local effects, dermal No hazard identified.

consumer: Long-term exposure- systemic effects, Inhalation: 26 mg/m3 consumer: Short-term exposure - systemic effects, Inhalation: 26 mg/m3 consumer: Long-term exposure - local effects, Inhalation: 26 mg/m3 consumer: Short-term exposure - local effects, Inhalation: 26 mg/m3

124-41-4: sodium methanolate

No DNELs have been derived.

1310-73-2: sodium hydroxide

worker: Long-term exposure - local effects, Inhalation: 1,0 mg/m3

8.2. Exposure controls

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

butyl rubber (butyl) - 0.7 mm coating thickness fluoroelastomer (FKM) - 0.7 mm coating thickness

polyvinylchloride (PVC) - 0.7 mm coating thickness

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1) nitrile rubber (NBR) - 0.4 mm coating thickness chloroprene rubber (CR) - 0.5 mm coating thickness

to Regulation (EC) No 1907/2006.

Date / Revised: 16.05.2025 Version: 3.4
Date / Previous version: 18.01.2024 Previous version: 3.3

Product: Na-Methylate sol. 30 %

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Safety glasses with side-shields (frame goggles) (f.e. EN 166) and face shield

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Avoid contact with the skin, eyes and clothing. Do not breathe vapour/spray. Handle in accordance with good industrial hygiene and safety practice. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

State of matter: liquid Form: liquid

Colour: colourless to yellowish Odour: perceptible, of methanol

Odour threshold:

Not determined since harmful by

inhalation.

crystallization temperature: 6,8 °C

Boiling point: 92 °C

(1.013 bar)

Flammability: Flammable liquid and vapour. (other)

Lower explosion limit:

(DIN EN 15794)

(29,6 °C)

The lower explosion point of the substance/mixture has been determined. The explosion point describes the temperature of a flammable liquid at which the

concentration of the saturated vapour mixed with air equals the lower

explosion limit.

Information on: methanol

Lower explosion limit: 5,5 %(V)

to Regulation (EC) No 1907/2006.

Date / Revised: 16.05.2025 Version: 3.4
Date / Previous version: 18.01.2024 Previous version: 3.3

Product: Na-Methylate sol. 30 %

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

Upper explosion limit:

For liquids not relevant for classification and labelling.

Information on: methanol

Upper explosion limit: 36,5 %(V)

Flash point: 33 °C (DIN 51755)

Auto-ignition temperature:

not applicable

Information on: methanol

Auto-ignition temperature: 455 °C

Thermal decomposition: It is not a self-decompositionable substance. Stable up to boiling point.

pH value: approx. 11 (ISO 1148)

Viscosity, kinematic: 66 mm2/s (calculated (from dynamic

(20 °C) viscosity))

Viscosity, dynamic: 64 mPa.s (DIN 51562)

(20 °C) hydrolyzes

Solubility in water: hydrolyzes

(20 °C)

Information on: methanol

Partitioning coefficient n-octanol/water (log Kow): -0,77 (measured)

(20 °C) Literature data.

Vapour pressure: approx. 34 hPa

(20 °C)

approx. 150 hPa

(50 °C)

Relative density:

No data available.

Density: 0,969 g/cm3 (ISO 2811-3)

(20 °C)

0,943 g/cm3 (ISO 2811-3)

(50 °C)

0,938 g/cm3 (ISO 2811-3)

(55 °C)

Relative vapour density (air):

not determined

Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular

form. -

9.2. Other information

Information with regard to physical hazard classes

Explosives

Explosion hazard: not explosive

to Regulation (EC) No 1907/2006.

Date / Revised: 16.05.2025 Version: 3.4
Date / Previous version: 18.01.2024 Previous version: 3.3

Product: Na-Methylate sol. 30 %

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

Oxidizing properties

Fire promoting properties: not fire-propagating

Corrosion to metals

42 mm/a

Corrosive effect on metals. - Aluminium - Corrosion rate > 6.25 mm/a

using 7075-T6 or AZ5GU-T6

Other safety characteristics

Radioactivity:

not radioactive for transport

purposes

Miscibility with water:

Reacts with water.

hygroscopic

Hygroscopy: Evaporation rate:

,

No applicable information available., Value can be approximated from Henry's Law Constant or vapor

pressure.

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated., Strong exothermic reaction with acids., Vapours may form explosive mixture with air.

Corrosion to metals: Corrosive effect on metals. Aluminium Corrosion rate > 6.25 mm/a using

7075-T6 or AZ5GU-T6

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Peroxides: The product/the substance has not a tendency towards the formation of

peroxide.

10.3. Possibility of hazardous reactions

Exothermic reaction. Reacts with water and acids.

10.4. Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid contact with air. Avoid moisture.

10.5. Incompatible materials

Substances to avoid:

to Regulation (EC) No 1907/2006.

Date / Revised: 16.05.2025 Version: 3.4
Date / Previous version: 18.01.2024 Previous version: 3.3

Product: Na-Methylate sol. 30 %

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

Carbon dioxide, water, acids, substances with an acid reaction, light metals

10.6. Hazardous decomposition products

Hazardous decomposition products: sodium hydroxide, methanol

SECTION 11: Toxicological Information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Assessment of acute toxicity:

The toxicity of the product is based on its corrosivity.

Experimental/calculated data:

ATE (oral): 138 mg/kg ATE (by inhalation): 3 mg/l Determined for vapor ATE (by inhalation): > 5 mg/l

Determined for mist ATE (dermal): 422 mg/kg

Information on: sodium methanolate Assessment of acute toxicity:

Of moderate toxicity after single ingestion. The toxicity of the product is based on its corrosivity.

Information on: methanol Assessment of acute toxicity:

Of high toxicity after single ingestion. Of high toxicity after short-term inhalation. Of high toxicity after

short-term skin contact.

Information on: sodium methanolate

Experimental/calculated data:

LD50 rat (oral): 1.687 mg/kg (OECD Guideline 401)

An aqueous solution was tested.

ATE (oral): 1.687 mg/kg

Information on: methanol

Experimental/calculated data:

LD50 rat (oral): > 1187 - 2769 mg/kg (BASF-Test)

ATE (oral): 100 mg/kg

to Regulation (EC) No 1907/2006.

Date / Revised: 16.05.2025 Version: 3.4
Date / Previous version: 18.01.2024 Previous version: 3.3

Product: Na-Methylate sol. 30 %

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

Information on: sodium methanolate Experimental/calculated data:

(by inhalation): Study does not need to be conducted.

Information on: methanol Experimental/calculated data:

LC50 rat (by inhalation): 128 mg/l 4 h (BASF-Test)

The vapour was tested.

ATE (by inhalation): 3 mg/l

Information on: sodium methanolate Experimental/calculated data:

LD50 rat (dermal): > 2.000 mg/kg (BASF-Test)

No mortality was observed. An aqueous solution was tested.

Information on: methanol Experimental/calculated data:

LD50 rabbit (dermal): 17100 mg/kg (other)

ATE (dermal): 300 mg/kg

Irritation

Assessment of irritating effects: Corrosive! Damages skin and eyes.

Experimental/calculated data:

Skin corrosion/irritation

rabbit: Corrosive. (OECD Guideline 404)

Serious eye damage/irritation

: As the product corrodes the skin, it can be expected to have a similar effect on the eyes also.

Information on: sodium methanolate Experimental/calculated data: Skin corrosion/irritation

rabbit: Corrosive. (similar to OECD guideline 404)

Information on: methanol Experimental/calculated data: Skin corrosion/irritation rabbit: non-irritant (BASF-Test)

Information on: sodium methanolate Experimental/calculated data: Serious eye damage/irritation

to Regulation (EC) No 1907/2006.

Date / Revised: 16.05.2025 Version: 3.4
Date / Previous version: 18.01.2024 Previous version: 3.3

Product: Na-Methylate sol. 30 %

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

rabbit: irreversible damage (BASF-Test)

Information on: methanol Experimental/calculated data: Serious eye damage/irritation rabbit: non-irritant (BASF-Test)

Respiratory/Skin sensitization

Assessment of sensitization:

As the substance is corrosive, conducting sensitization studies is not feasible.

Experimental/calculated data:

Mouse Local Lymph Node Assay (LLNA) mouse: Non-sensitizing. (similar to OECD guideline 429) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Patch test human: Non-sensitizing. (Human patch test)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: sodium methanolate

Assessment of sensitization:

As the substance is corrosive, conducting sensitization studies is not feasible. The chemical structure does not suggest a sensitizing effect.

Information on: methanol Assessment of sensitization:

Skin sensitizing effects were not observed in animal studies.

Germ cell mutagenicity

Assessment of mutagenicity:

Based on the ingredients, there is no suspicion of a mutagenic effect.

Information on: sodium methanolate

Assessment of mutagenicity:

The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture. The substance was not mutagenic in a test with mammals. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Information on: methanol Assessment of mutagenicity:

In the majority of studies performed with microorganisms and in mammalian cell culture, a mutagenic effect was not found. A mutagenic effect was also not observed in in vivo tests.

Carcinogenicity

Assessment of carcinogenicity:

Based on the ingredients there is no suspicion of a carcinogenic effect in humans.

to Regulation (EC) No 1907/2006.

Date / Revised: 16.05.2025 Version: 3.4
Date / Previous version: 18.01.2024 Previous version: 3.3

Product: Na-Methylate sol. 30 %

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

Information on: sodium methanolate Assessment of carcinogenicity:

Study does not need to be conducted. The chemical structure does not suggest a specific alert for such an effect.

Information on: methanol Assessment of carcinogenicity:

In long-term studies in rats and mice in which the substance was given by inhalation, a carcinogenic effect was not observed. In long-term animal studies in which the substance was given in the drinking water in high concentrations, a carcinogenic effect was observed. These effects are not relevant to humans at occupational levels of exposure.

Reproductive toxicity

Assessment of reproduction toxicity:

Based on the ingredients, there is no suspicion of a toxic effect on reproduction.

Information on: sodium methanolate Assessment of reproduction toxicity:

Study does not need to be conducted. The chemical structure does not suggest a specific alert for such an effect.

Information on: methanol

Assessment of reproduction toxicity:

The results of animal studies gave no indication of a fertility impairing effect.

Developmental toxicity

Assessment of teratogenicity:

Based on the ingredients, there is no suspicion of a teratogenic effect.

Information on: sodium methanolate

Assessment of teratogenicity:

Study does not need to be conducted. The chemical structure does not suggest a specific alert for such an effect.

Information on: methanol

Assessment of teratogenicity:

The results of animal studies gave indication of a developmental toxic/teratogenic effects with high

Specific target organ toxicity (single exposure)

Remarks: No data available.

to Regulation (EC) No 1907/2006.

Date / Revised: 16.05.2025 Version: 3.4
Date / Previous version: 18.01.2024 Previous version: 3.3

Product: Na-Methylate sol. 30 %

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

The substance may cause blindness after repeated ingestion. The substance may cause blindness after repeated inhalation.

Information on: sodium methanolate

Assessment of repeated dose toxicity:

Study does not need to be conducted. The chemical structure does not suggest a specific alert of toxicity on target organs after repeated exposure.

Information on: methanol

Assessment of repeated dose toxicity:

The substance may cause blindness after repeated ingestion. The substance may cause blindness

after repeated inhalation.

Aspiration hazard

Toxic if swallowed.

Interactive effects

No data available.

11.2. Information on other hazards

Endocrine disrupting properties

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

The product has not been tested. The statement has been derived from the properties of the hydrolysis products.

Information on:sodium hydroxide

Assessment of aquatic toxicity:

Depending on local conditions and existing concentrations, disturbances in the biodegradation process of activated sludge are possible. There is a high probability that the product is not acutely harmful to aquatic organisms.

to Regulation (EC) No 1907/2006. Date / Revised: 16.05.2025

Version: 3.4 Previous version: 3.3

Date / Previous version: 18.01.2024 Product: **Na-Methylate sol. 30 %**

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

The effect strongly depends on the pH-value. The data refers to the dissociated form of the substance.

Information on:methanol

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Information on:sodium hydroxide

Toxicity to fish:

LC50 (96 h) 125 mg/l, Gambusia affinis (other, static)

The product will cause changes in the pH value of the test system. The result refers to an unneutralized sample. Literature data.

Information on:methanol

Toxicity to fish:

LC50 (96 h) 15.400 mg/l, Lepomis macrochirus (other, Flow through.)

Information on:sodium hydroxide

Aquatic invertebrates:

EC50 (48 h) 40,4 mg/l, Ceriodaphnia sp. (other, static)

Literature data.

Information on:methanol

Aquatic invertebrates:

EC50 (48 h) 18.260 mg/l, Daphnia magna (OECD Guideline 202, part 1, semistatic)

Information on:methanol

Aquatic plants:

EC50 (96 h) approx. 22.000 mg/l (growth rate), Selenastrum capricornutum (OECD Guideline 201, static)

Information on:methanol

Microorganisms/Effect on activated sludge:

EC50 (3 h) > 1.000 mg/l, (OECD Guideline 209, aquatic)

EC50 (24 h) 880 mg/l, Nitrosomonas sp. (Inhibition of nitrification, aquatic)

12.2. Persistence and degradability

to Regulation (EC) No 1907/2006.

Date / Revised: 16.05.2025 Version: 3.4
Date / Previous version: 18.01.2024 Previous version: 3.3

Product: Na-Methylate sol. 30 %

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

Assessment biodegradation and elimination (H2O):

The product is unstable in water. The elimination data also refer to products of hydrolysis.

Information on:sodium hydroxide

Assessment biodegradation and elimination (H2O):

Inorganic product which cannot be eliminated from water by biological purification processes.

Information on:methanol

Assessment biodegradation and elimination (H2O):

Readily biodegradable (according to OECD criteria).

Information on:methanol

Elimination information:

95 % BOD of the ThOD (20 d) (OECD 301D; 92/69/EWG, C.4-E) (aerobic, activated sludge, domestic, non-adapted) Readily biodegradable (according to OECD criteria).

· /

12.3. Bioaccumulative potential

Information on:methanol

Assessment bioaccumulation potential:

Significant accumulation in organisms is not to be expected.

Information on:sodium hydroxide

Assessment bioaccumulation potential:

Accumulation in organisms is not to be expected.

12.4. Mobility in soil

Assessment transport between environmental compartments: Adsorption in soil: Adsorption to solid soil phase is not expected.

12.5. Results of PBT and vPvB assessment

The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative).

12.6. Endocrine disrupting properties

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

to Regulation (EC) No 1907/2006.

Date / Revised: 16.05.2025 Version: 3.4
Date / Previous version: 18.01.2024 Previous version: 3.3

Product: Na-Methylate sol. 30 %

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

12.7. Other adverse effects

The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

Additional information

Other ecotoxicological advice:

Due to the pH-value of the product, neutralization is generally required before discharging sewage into treatment plants. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations. Do not release untreated into natural waters.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Obtain the consent of pollution control authorities before discharging to wastewater treatment plants.

Contaminated packaging:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

SECTION 14: Transport Information

Land transport

ADR

UN number or ID number: UN1289

UN proper shipping name: SODIUM METHYLATE SOLUTION

Transport hazard class(es): 3, 8
Packing group: III
Environmental hazards: no

Special precautions for Tunnel code: D/E

user:

RID

UN number or ID number: UN1289

UN proper shipping name: SODIUM METHYLATE SOLUTION

Transport hazard class(es): 3, 8
Packing group: III
Environmental hazards: no

Special precautions for None known

user:

to Regulation (EC) No 1907/2006.

Date / Revised: 16.05.2025 Version: 3.4
Date / Previous version: 18.01.2024 Previous version: 3.3

Product: Na-Methylate sol. 30 %

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

Inland waterway transport

ADN

UN number or ID number: UN1289

UN proper shipping name: SODIUM METHYLATE SOLUTION

Transport hazard class(es): 3, 8
Packing group: III
Environmental hazards: no

Special precautions for None known

user:

<u>Transport in inland waterway vessel</u>
UN number or ID number: UN1289

UN proper shipping name: SODIUM METHYLATE SOLUTION

Transport hazard class(es): 3, 8
Packing group: III
Environmental hazards: no
Type of inland waterway N

vessel:

Cargo tank design: 3 Cargo tank type: 2

Sea transport

IMDG

UN number or ID number: UN 1289

UN proper shipping name: SODIUM METHYLATE SOLUTION

Transport hazard class(es): 3, 8
Packing group: III
Environmental hazards: no

Marine pollutant: NO

Special precautions for

user:

EmS: F-E; S-C

Air transport

IATA/ICAO

UN number or ID number: UN 1289

UN proper shipping name: SODIUM METHYLATE SOLUTION

to Regulation (EC) No 1907/2006.

Date / Revised: 16.05.2025 Version: 3.4
Date / Previous version: 18.01.2024 Previous version: 3.3

Product: Na-Methylate sol. 30 %

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

Transport hazard class(es): 3, 8 Packing group: III

Environmental hazards: No Mark as dangerous for the environment is needed

Special precautions for None known

user:

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Regulation: IBC-Code

Product name: Sodium methylate 21-30% in methanol

Pollution category: Y Ship Type: 2

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibitions, Restrictions and Authorizations

Chemical Prohibition Ordinance (DE): Annex 2

to Regulation (EC) No 1907/2006.

Date / Revised: 16.05.2025 Version: 3.4
Date / Previous version: 18.01.2024 Previous version: 3.3

Product: Na-Methylate sol. 30 %

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

Restriction Type: Restricted substance

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 3, 40, 69, 75

Hazardous Incident Ordinance (Germany):

List entry in regulation: 1.1.2

Classification applies for standard conditions of temperature and pressure.

List entry in regulation: 1.1.3

Classification applies for standard conditions of temperature and pressure.

List entry in regulation: 1.2.5.3

Classification applies for standard conditions of temperature and pressure.

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):

List entry in regulation: H2

Classification applies for standard conditions of temperature and pressure.

List entry in regulation: H3

Classification applies for standard conditions of temperature and pressure.

List entry in regulation: P5c

Classification applies for standard conditions of temperature and pressure.

Water hazard class (§8/§10 AwSV (Self-classification of the mixture according to calculation method)): (2) significantly water polluting.

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

15.2. Chemical Safety Assessment

Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

SECTION 16: Other Information

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned

in section 2 or 3:

Flam. Liq. Flammable liquids

Met. Corr. Corrosive to metals

Acute Tox. Acute toxicity

Skin Corr. Skin corrosion

Eye Dam. Serious eye damage

STOT SE Specific target organ toxicity — single exposure

Flam. Sol. Flammable solids

Self-heat. Self-heating substances and mixtures

Skin Irrit. Skin irritation Eye Irrit. Eye irritation

H226 Flammable liquid and vapour. H290 May be corrosive to metals.

Date / Revised: 16.05.2025 Version: 3.4
Date / Previous version: 18.01.2024 Previous version: 3.3

Product: Na-Methylate sol. 30 %

(ID no. 30036699/SDS_GEN_DE/EN)

Date of print 08.10.2025

H370	Causes damage to organs.
H314	Causes severe skin burns and eye damage.
H301 + H311 + H331	Toxic if swallowed, in contact with skin or if inhaled.
H225	Highly flammable liquid and vapour.
H370	Causes damage to organs (Central nervous system, Optic nerve).
H228	Flammable solid.
H251	Self-heating: may catch fire.
H302	Harmful if swallowed.
EUH014	Reacts violently with water.
EUH071	Corrosive to the respiratory tract.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code, IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.