

Specification data sheet

Page: 1/2

BASF Specification data sheet

Date / Revised: 2025/01/21

Product: **Luvitec® VA 6436 P**

Version: 1.2

(30856234/SPE_GEN_P/EN)

Date of print 10.10.2025

1. Substance/preparation and company identification

Luvitec® VA 6436 P

BASF SE

Regional Business Unit Dispersions Europe

67056 Ludwigshafen, Germany

E-mail address: ede-qm@basf.com

2. Characterization

Copolymer based on: polyvinylpyrrolidone, Acetic acid ethenyl ester, polymer with 1-ethenyl-2-pyrrolidinone

Form: powder

3. Specified tests

Property	Test method (parameter)	Value
Solid content	Ph. Eur. 2.2.32	95.0 - 100.0 %
pH value	Ph. Eur. 2.2.3 (20 °C, 10 %(m))	2.5 - 6.0
Viscosity, dynamic	(not applicable, the product is a solid)	
K value according to Fikentscher	(1 %(m), Ethanol)	25.0 - 36.0
1-vinyl-2-pyrrolidone	HPLC method	<= 10 PPM
vinyl acetate	HPLC method	<= 10 PPM
hydrazine	BASF method	<= 1 PPM

BASF Specification data sheet
Date / Revised: 2025/01/21
Product: **Luvitec® VA 6436 P**

Version: 1.2

(30856234/SPE_GEN_P/EN)

Date of print 10.10.2025

4. Handling and Storage

Advice on safe handling:
Protect against heat.

Keep container tightly closed and dry.

Avoid dust formation.

Take precautionary measures against static discharges.

Storage stability:
24 Months at 10 - 30 °C

Vertical lines in the left hand margin indicate an amendment from the previous version.

The Specified Parameters listed in section 3 represent the contractual quality at the time of the transfer of risk. The data are controlled at regular intervals as part of our quality assurance program. BASF MAKES NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, BY FACT OR LAW, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

This product specification was issued automatically and is not signed.