

# Safety data sheet

Page: 1/59

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

## ETHYL ACRYLATE

Chemical name: ethyl acrylate

CAS Number: 140-88-5

REACH registration number: 01-2119459301-46-0001, 01-2119459301-46-0033, 01-2119459301-46-0068, 01-2119459301-46

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Monomer.

Uses advised against: All consumer uses are strongly advised against., Use of substance in adhesives (professional), Use of substance in coatings (professional), Use of substance in inks and toners (professional)

For the detailed identified uses of the product see appendix of the safety data sheet.

### 1.3. Details of the supplier of the safety data sheet

Company:

BASF SE

67056 Ludwigshafen

GERMANY

Operating Division Petrochemicals

Telephone: +49 621 60-42151

E-mail address: sds-petrochemicals@basf.com

### 1.4. Emergency telephone number

International emergency number:

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Telephone: +49 180 2273-112

## SECTION 2: Hazards Identification

### 2.1. Classification of the substance or mixture

According to Regulation (EC) No 1272/2008 [CLP]

Flam. Liq. 2	H225 Highly flammable liquid and vapour.
Acute Tox. 3 (Inhalation - vapour)	H331 Toxic if inhaled.
Acute Tox. 4 (oral)	H302 Harmful if swallowed.
Acute Tox. 4 (dermal)	H312 Harmful in contact with skin.
Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.
STOT SE 3	H335 May cause respiratory irritation.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.

Specific Concentration Limits According to Regulation (EC) No 1272/2008 [CLP]

Skin Corr./Irrit. 2:  $\geq 5$  %  
 STOT SE 3, irr. to respiratory syst.:  $\geq 5$  %  
 Eye Dam./Irrit. 2:  $\geq 5$  %

According to BASF current knowledge and application of the criteria given in Annex I of Regulation (EC) No. 1272/2008, the following classification exceeding the classification given in Regulation (EC) No 1272/2008, Annex VI, Table 3.1 is required.

Flam. Liq. 2  
 Acute Tox. 4 (dermal)  
 Acute Tox. 4 (oral)  
 Acute Tox. 3 (Inhalation - vapour)  
 Skin Irrit. 2  
 Skin Sens. 1B  
 STOT SE 3 (irritating to respiratory system)  
 Eye Irrit. 2  
 Aquatic Chronic 3

For the classifications not written out in full in this section the full text can be found in section 16.

### 2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

Pictogram:



Signal Word:

Danger

Hazard Statement:

H225 Highly flammable liquid and vapour.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

H319	Causes serious eye irritation.
H315	Causes skin irritation.
H331	Toxic if inhaled.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H302 + H312	Harmful if swallowed or in contact with skin.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary Statements (Prevention):**

P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves and eye protection or face protection.

**Precautionary Statements (Response):**

P311	Call a POISON CENTER or physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Precautionary Statements (Storage):**

P403 + P235	Store in a well-ventilated place. Keep cool.
-------------	--

**Precautionary Statements (Disposal):**

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

Hazard determining component(s) for labelling: ethyl acrylate

## 2.3. Other hazards

### According to Regulation (EC) No 1272/2008 [CLP]

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture. See section 12 - Results of PBT and vPvB assessment.

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative).  
Skin resorption hazard.

## SECTION 3: Composition/Information on Ingredients

### 3.1. Substances

#### Chemical nature

ethyl acrylate

CAS Number: 140-88-5

Flam. Liq. 2  
Acute Tox. 3 (Inhalation - vapour)

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

EC-Number: 205-438-8

INDEX-Number: 607-032-00-X

Substance with EU occupational exposure limit

Acute Tox. 4 (oral)

Acute Tox. 4 (dermal)

Skin Irrit. 2

Eye Irrit. 2

Skin Sens. 1

STOT SE 3 (irr. to respiratory syst.)

Aquatic Chronic 3

H225, H319, H315, H331, H317, H335, H302 + H312, H412

Differing classification according to current knowledge and the criteria given in Annex I of Regulation (EC) No. 1272/2008

Flam. Liq. 2

Acute Tox. 4 (dermal)

Acute Tox. 4 (oral)

Acute Tox. 3 (Inhalation - vapour)

Skin Irrit. 2

Skin Sens. 1B

STOT SE 3 (irr. to respiratory syst.)

Eye Irrit. 2

Aquatic Chronic 3

Specific concentration limit:

Skin Corr./Irrit. 2:  $\geq 5\%$

STOT SE 3, irr. to respiratory syst.:  $\geq 5\%$

Eye Dam./Irrit. 2:  $\geq 5\%$

Regulatory relevant ingredients

ethyl acrylate

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Content (W/W): $\geq 99,7\%$ - $\leq 100\%$	Flam. Liq. 2
CAS Number: 140-88-5	Acute Tox. 3 (Inhalation - vapour)
EC-Number: 205-438-8	Acute Tox. 4 (oral)
INDEX-Number: 607-032-00-X	Acute Tox. 4 (dermal)
Substance with EU occupational exposure limit	Skin Irrit. 2
	Eye Irrit. 2
	Skin Sens. 1
	STOT SE 3 (irr. to respiratory syst.)
	Aquatic Chronic 3
	H225, H319, H315, H331, H317, H335, H302 + H312, H412
	<u>Differing classification according to current knowledge and the criteria given in Annex I of Regulation (EC) No. 1272/2008</u>
	Flam. Liq. 2
	Acute Tox. 4 (dermal)
	Acute Tox. 4 (oral)
	Acute Tox. 3 (Inhalation - vapour)
	Skin Irrit. 2
	Skin Sens. 1B
	STOT SE 3 (irr. to respiratory syst.)
	Eye Irrit. 2
	Aquatic Chronic 3
	<u>Specific concentration limit:</u>
	Skin Corr./Irrit. 2: $\geq 5\%$
	STOT SE 3, irr. to respiratory syst.: $\geq 5\%$
	Eye Dam./Irrit. 2: $\geq 5\%$

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

### 3.2. Mixtures

Not applicable

## SECTION 4: First-Aid Measures

### 4.1. Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:

Immediately wash thoroughly with soap and water, seek medical attention.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

On contact with eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

#### **4.2. Most important symptoms and effects, both acute and delayed**

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Hazards: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. (Further) symptoms and / or effects are not known so far

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

### **SECTION 5: Fire-Fighting Measures**

#### **5.1. Extinguishing media**

Suitable extinguishing media:

dry powder, water spray, carbon dioxide, foam

Unsuitable extinguishing media for safety reasons:

water jet

Additional information:

Use extinguishing measures to suit surroundings.

#### **5.2. Special hazards arising from the substance or mixture**

Advice: Risk of violent self-polymerization if overheated in a container. Cool endangered containers with water-spray.

Advice: Flammable. See SDS section 7 - Handling and storage.

#### **5.3. Advice for fire-fighters**

Special protective equipment:

Wear a self-contained breathing apparatus. Special protective equipment for firefighters

Further information:

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Extend fire extinguishing measures to the surroundings. Fight fire from maximum distance. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

In case of a fire in the vicinity a restabilization system should be used if the temperature in the bulk storage-tank reaches 45°C. Evacuate area of all unnecessary personnel. In case of a fire in the vicinity evacuate all personnel in a greater area if the temperature in the bulk storage-tank reaches 60°C.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

---

## SECTION 6: Accidental Release Measures

High risk of slipping due to leakage/spillage of product.

Release of substance/product can cause fire or explosion. Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

### 6.1. Personal precautions, protective equipment and emergency procedures

Handle in accordance with good industrial hygiene and safety practice.

Avoid all sources of ignition: heat, sparks, open flame. Use antistatic tools.

### 6.2. Environmental precautions

Do not discharge into drains/surface waters/groundwater. Contain contaminated water/firefighting water.

### 6.3. Methods and material for containment and cleaning up

For large amounts: Pump off product.

Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations. Ensure adequate ventilation. Suppress gases/vapours/mists with water spray jet. Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Cleaning operations should be carried out only while wearing breathing apparatus. Pick up with suitable appliance and dispose of.

### 6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

---

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

## SECTION 7: Handling and Storage

### 7.1. Precautions for safe handling

The substance/ product may be handled only by appropriately trained personnel. Facility parts must be checked for polymer residues and cleaned on regular basis in order to avoid hazardous reactions.

Ensure thorough ventilation of stores and work areas. Encapsulation or exhaust ventilation required. When filling, transferring, or emptying of containers, adequate local exhaust ventilation is necessary. Vent waste air to atmosphere only through suitable separators. Check the condition of seals and connector screw threads.

The temperatures which must be avoided are to be considered. Protect against heat. Protect from direct sunlight. Protect contents from the effects of light. Do not open warm or swollen product containers. Remove persons to safety and alert fire brigade.

Ensure adequate inhibitor and dissolved oxygen level.

Avoid inhalation of dusts/mists/vapours. Avoid aerosol formation. Avoid all direct contact with the substance/product.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Substance/product can form explosive mixture with air. Ground all transfer equipment properly to prevent electrostatic discharge. It is recommended that all conductive parts of the machinery are grounded. Explosion-proof equipment is not necessary when loading and processing of the product takes place at a minimum of 5 °C below the flash point.

Heated containers should be cooled to prevent polymerization. If exposed to fire, keep containers cool by spraying with water. Emergency cooling must be provided for the eventuality of a fire in the vicinity.

### 7.2. Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Prior to storage ensure that the transfer equipment used and the intended storage containers do not contain other substances/products. Before transfer to stock the identity of the product must be proved to be without doubt. The entrance to storage rooms is to be granted only to appropriately trained personnel.

The stabilizer is only effective in the presence of oxygen. Maintain contact with atmosphere containing 5 - 21% oxygen. Never use tanks with inert-gas installation for storage.

Risk of polymerization. Protect against heat. Protect from direct sunlight. Avoid UV-light and other radiation with high energy. Protect against contamination.

In case of bulk storage, the storage-tanks should at least be equipped with two high temperature alert devices.

Even if the product is stored and handled as prescribed/indicated it should be used up within the indicated duration of storage.

Storage class according to TRGS 510 (originally VCI, Germany): (3) Flammable liquids

Storage stability:

Storage temperature: < 35 °C



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Storage duration: 12 Months

The stated storage temperature should be noted.

Avoid prolonged storage.

This product should be processed as soon as possible.

Ensure adequate inhibitor and dissolved oxygen level.

Do not store with less than 10 % headspace above liquid.

Storage stability is based upon ambient temperatures and conditions described.

It is recommended to keep a safe distance of +2 degrees above the crystallization range.

The product is stabilized, the shelf life should be noted.

Storage temperature: 45 °C

A restabilization system should be used if the temperature in the bulk storage-tank reaches the indicated value.

Storage temperature: 60 °C

All personnel in a greater area should be evacuated if the temperature in the bulk storage-tank reaches the indicated value.

### 7.3. Specific end use(s)

See exposure scenario(s) in the attachment to this safety data sheet.

## SECTION 8: Exposure Controls/Personal Protection

### 8.1. Control parameters

Components with occupational exposure limits

The surveillance of the workplace by exposure measurements may be necessary, in order to prove the efficiency of safety measures, for example ventilation or the need of respiratory protection. Since this requires a specific competency, only accredited laboratories should be contracted. Regarding suitable methods to assess inhalation exposure, the European Standards EN 482, 689 and 14042 are to be considered. In addition, the TRGS 402 has to be observed in Germany.

140-88-5: ethyl acrylate

STEL value 42 mg/m<sup>3</sup> ; 10 ppm (OEL (EU))  
indicative

TWA value 21 mg/m<sup>3</sup> ; 5 ppm (OEL (EU))  
indicative

Skin Designation (TRGS 900 (DE))

The substance can be absorbed through the skin.

Short Term Exposure Classification: (TRGS 900 (DE))

Category I: Substances for which the localized effect has an assigned exposure limit or for substances with a sensitizing effect in respiratory passages

OEL 8,3 mg/m<sup>3</sup> ; 2 ppm (TRGS 900 (DE))

Ceiling limit value/factor: 2

If the occupational exposure limit value (AGW) and the biological limit value (BGW) are complied with, there should be no risk of damage for the unborn child (see TRGS 900, Number 2.7)

TWA value 21 mg/m<sup>3</sup> ; 5 ppm (EU SCOEL)

Ceiling limit value/factor: 8HR

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

STEL value 42 mg/m<sup>3</sup> ; 10 ppm (EU SCOEL)  
Ceiling limit value/factor: 15 min

#### PNEC

freshwater: 0,0027 mg/l

intermittent release: 0,011 mg/l

marine water: 0,0003 mg/l

STP: 10 mg/l

sediment (freshwater): 0,0213 mg/kg

sediment (marine water): 0,0021 mg/kg

soil: 1 mg/kg

#### DNEL

worker:

Long-term exposure - local effects, Inhalation: 21 mg/m<sup>3</sup>

## **8.2. Exposure controls**

### Personal protective equipment

Respiratory protection:

Suitable respiratory protection for lower concentrations or short-term effect: Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):

butyl rubber (butyl) - 0.7 mm coating thickness

Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

### General safety and hygiene measures

Avoid contact with the skin, eyes and clothing. Avoid inhalation of vapour. Wearing of closed work clothing is required additionally to the stated personal protection equipment. Handle in accordance with good industrial hygiene and safety practice.

### Environmental exposure controls

All appropriate measures must be taken to prevent the release of this product to the environment and to limit the dispersion of any release when it occurs. Suitable risk management measures should be in place.

## **SECTION 9: Physical and Chemical Properties**

### **9.1. Information on basic physical and chemical properties**

State of matter:	liquid	
Form:	liquid	
Colour:	colourless	
Odour:	acrylic-like	
Odour threshold:	2 ppb	
Melting point:	-71,2 °C	
	Literature data.	
Boiling point:	99,8 °C	(other)
	(1.013 hPa)	
Flammability:	Highly flammable.	(derived from flash - and boiling point)
Lower explosion limit:	For liquids not relevant for classification and labelling., The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Flash point:	9 °C	(closed cup)
	Literature data.	
Auto-ignition temperature:	372 °C	
	Literature data.	
Thermal decomposition:	155 °C, 1.220 J/g (DSC (DIN 51007))	
SADT:	Not a substance/mixture liable to self-decomposition according to GHS.	
pH value:	(20 °C)	
	not applicable, of low solubility	
Viscosity, kinematic:	approx. 0,582 mm <sup>2</sup> /s	
	(25 °C)	
Viscosity, dynamic:	0,535 mPa.s	
	(25 °C)	
	Literature data.	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Thixotropy:	not thixotropic	
Solubility in water:	Literature data. 20 g/l (20 °C)	(other)
Solubility (qualitative) solvent(s):	organic solvents miscible	
Partitioning coefficient n-octanol/water (log Kow):	1,18 (25 °C)	(OECD Guideline 107)
Vapour pressure:	40 hPa (20,9 °C)	
Relative density:	0,9234 (20 °C)	
Density:	0,92 g/cm <sup>3</sup> (20 °C) Literature data. 0,8867 g/cm <sup>3</sup> (50 °C) 0,8812 g/cm <sup>3</sup> (55 °C)	(other)    (calculated)
Relative vapour density (air):	3,45 (20 °C) Heavier than air.	(calculated)

#### Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular form. -

## 9.2. Other information

### Information with regard to physical hazard classes

#### Explosives

Explosion hazard: Based on the chemical structure (other)  
there is no indication of explosive properties.

Impact sensitivity:  
Based on the chemical structure there is no shock-sensitivity.

#### Oxidizing properties

Fire promoting properties: Based on its structural properties (other)  
the product is not classified as oxidizing.

#### Pyrophoric properties

Self-ignition temperature: Test type: Spontaneous self-ignition at room-temperature.

Based on its structural properties the product is not classified as self-igniting.

#### Self-heating substances and mixtures

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Self heating ability: It is not a substance capable of spontaneous heating.  
Not tested on account of the low melting-point.

#### Substances and mixtures, which emit flammable gases in contact with water

Formation of flammable gases:  
Forms no flammable gases in the presence of water.

#### Corrosion to metals

No corrosive effect on metal.

#### **Other safety characteristics**

pKA:

The substance does not dissociate.

Adsorption/water - soil: KOC: 3,9 - 85; log KOC: 1,9 (OECD Guideline 106)

Surface tension:

Based on chemical structure, surface activity is not to be expected.

Molar mass:

100,12 g/mol

SAPT-Temperature:

According to SP386 it is ensured that the level of chemical stabilization is sufficient to prevent dangerous polymerization during total duration of carriage. - This information is valid for the recently stabilized product.

Evaporation rate:

Value can be approximated from Henry's Law Constant or vapor pressure.

## **SECTION 10: Stability and Reactivity**

### **10.1. Reactivity**

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals: No corrosive effect on metal.

Formation of flammable gases:

Remarks:

Forms no flammable gases in the presence of water.

### **10.2. Chemical stability**

The product is stable if stored and handled as prescribed/indicated.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

### **10.3. Possibility of hazardous reactions**

Explosion and fire hazard exists under confined conditions. Ignitable air mixtures can form when the product is heated above the flash point and/or when sprayed or atomized. Formation of explosive gas/air mixtures.

#### **Polymerization coupled with heat formation.**

**Risk of spontaneous polymerization by oxygen depletion of the liquid phase. Risk of spontaneous polymerization when heated or in the presence of UV radiation. Risk of spontaneous and violent self-polymerization if inhibitor is lost or product is exposed to excessive heat. Polymerization produces gases which may burst closed or confined containers. Reactions may cause ignition.**

**Risk of spontaneous polymerization in the presence of starters for radical chain reactions (e.g. peroxides). Reacts with nitric acid. Risk of spontaneous polymerization in the presence of oxidizing agents.**

**Hazardous reactions in presence of mentioned substances to avoid.**

**The product is stabilized against spontaneous polymerization prior to despatch. The product is stable if stored and handled as prescribed/indicated.**

### **10.4. Conditions to avoid**

Avoid heat. Avoid oxygen content above the product of less than 5 %. Avoid UV-light and other radiation with high energy. Avoid direct sunlight. Avoid prolonged storage. Avoid inhibitor loss. Avoid excessive temperatures. Avoid all sources of ignition: heat, sparks, open flame. Avoid freezing. Avoid moisture.

### **10.5. Incompatible materials**

Substances to avoid:

radical formers, free radical initiators, peroxides, mercaptans, nitro-compounds, perborates, azides, ether, ketones, aldehydes, amines, nitrates, nitrites, oxidizing agents, reducing agents, strong bases, alkaline reactive substances, acid anhydrides, acid chlorides, concentrated mineral acids, metal salts  
Inert gas

### **10.6. Hazardous decomposition products**

Hazardous decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

## SECTION 11: Toxicological Information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Assessment of acute toxicity:

Of moderate toxicity after single ingestion. Of pronounced toxicity after short-term inhalation. Of low toxicity after short-term skin contact. The European Union (EU) has classified this substance as 'harmful' after dermal exposure.

Experimental/calculated data:

LD50 rat (oral): 1.120 mg/kg (similar to OECD guideline 401)

LC50 rat (by inhalation): 9 mg/l 4 h (OECD Guideline 403)

The vapour was tested.

LD50 rat (dermal): 3.049 mg/kg (similar to OECD guideline 402)

#### Irritation

Assessment of irritating effects:

Eye contact causes irritation. Skin contact causes irritation.

Experimental/calculated data:

Skin corrosion/irritation

rabbit: Irritant. (OECD Guideline 404)

Serious eye damage/irritation

rabbit: Irritant. (Draize test)

#### Respiratory/Skin sensitization

Assessment of sensitization:

Sensitization after skin contact possible.

Experimental/calculated data:

Mouse Local Lymph Node Assay (LLNA) mouse: skin sensitizing (OECD Guideline 429)

#### Germ cell mutagenicity

Assessment of mutagenicity:

In the majority of tests performed (bacteria/microorganisms/cell cultures) a mutagenic effect was not found. A mutagenic effect was also not observed in in-vivo assays.

#### Carcinogenicity

Assessment of carcinogenicity:

In long-term animal studies in which the substance was given by inhalation, a carcinogenic effect was not observed. The substance showed no carcinogenic activity in animals after chronic administration to the skin. In long-term studies in rats and mice in which the substance was given by gavage, a carcinogenic effect was observed. A carcinogenic potential can essentially be excluded after a single or short-term exposure to the substance. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).

#### Reproductive toxicity

Assessment of reproduction toxicity:

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

The results of animal studies gave no indication of a fertility impairing effect. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

#### Developmental toxicity

Assessment of teratogenicity:

No indications of a developmental toxic / teratogenic effect were seen in animal studies. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

#### Specific target organ toxicity (single exposure)

Assessment of STOT single:

Causes temporary irritation of the respiratory tract.

#### Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

The substance may cause damage to the olfactory epithelium after repeated inhalation. After repeated exposure the prominent effect is local irritation.

#### Aspiration hazard

not applicable

#### Interactive effects

No data available.

## **11.2. Information on other hazards**

#### Endocrine disrupting properties

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACH Article 59 for having endocrine disrupting properties.

---

## **SECTION 12: Ecological Information**

### **12.1. Toxicity**

Assessment of aquatic toxicity:

Acutely toxic for aquatic organisms. Harmful to aquatic organisms based on long-term (chronic) toxicity study data. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

**Toxicity to fish:**

LC50 (96 h) 4,6 mg/l, *Salmo gairdneri*, syn. *O. mykiss* (OECD 203; ISO 7346; 84/449/EWG, C.1, Flow through.)

The statement of the toxic effect relates to the analytically determined concentration.

**Aquatic invertebrates:**

EC50 (48 h) 7,9 mg/l, *Daphnia magna* (OECD Guideline 202, part 1, Flow through.)

The statement of the toxic effect relates to the analytically determined concentration.

**Aquatic plants:**

EC50 (72 h) 4,5 mg/l (biomass), *Selenastrum capricornutum* (OECD Guideline 201, static)

The statement of the toxic effect relates to the analytically determined concentration.

**Microorganisms/Effect on activated sludge:**

EC10 (72 h) > 100 mg/l, activated sludge, domestic (aerobic)

Nominal concentration.

**Chronic toxicity to fish:**

No data available.

**Chronic toxicity to aquatic invertebrates:**

No observed effect concentration (21 d) 0,19 mg/l, *Daphnia magna* (OECD Guideline 202, part 2, Flow through.)

The statement of the toxic effect relates to the analytically determined concentration.

**Assessment of terrestrial toxicity:**

No toxic effects have been observed in studies with soil living organisms.

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

**Soil living organisms:**

other (28 d) > 1.000 mg/kg, soil dwelling microorganisms (OECD Guideline 217)

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

**Terrestrial plants:**

No data available.

**Other terrestrial non-mammals:**

No data available.

## 12.2. Persistence and degradability

**Assessment biodegradation and elimination (H<sub>2</sub>O):**

Readily biodegradable (according to OECD criteria).

**Elimination information:**

80 - 90 % TIC of the ThIC (28 d) (ISO 14593) (aerobic, activated sludge, domestic)

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Assessment of stability in water:

In contact with water the substance will hydrolyse slowly.

Information on Stability in Water (Hydrolysis):

approx.  $t_{1/2}$  1.500 d (25 °C, pH value 7), (OPPTS 835.2130, pH 7)

In contact with water the substance will hydrolyse slowly.

### 12.3. Bioaccumulative potential

Assessment bioaccumulation potential:

Does not accumulate in organisms.

Bioaccumulation potential:

Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

### 12.4. Mobility in soil

Assessment transport between environmental compartments:

Volatility: No data available.

Adsorption in soil: Adsorption to solid soil phase is not expected.

### 12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative). Self classification

### 12.6. Endocrine disrupting properties

The substance is not identified to have endocrine disrupting properties according to Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 nor is included in the Candidate List of substances of very high concern according to EU REACH Article 59 for having endocrine disrupting properties.

### 12.7. Other adverse effects

The substance is not listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

#### Additional information

Other ecotoxicological advice:

Do not discharge product into the environment without control.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

## SECTION 13: Disposal Considerations

### 13.1. Waste treatment methods

Must be sent to a suitable incineration plant, observing local regulations.

Contaminated packaging:

Uncleaned empties should be disposed of in the same manner as the contents.

## SECTION 14: Transport Information

### Land transport

ADR

UN number or ID number: UN1917

UN proper shipping name: ETHYL ACRYLATE, STABILIZED

Transport hazard class(es): 3

Packing group: II

Environmental hazards: no

Special precautions for user: Tunnel code: D/E

RID

UN number or ID number: UN1917

UN proper shipping name: ETHYL ACRYLATE, STABILIZED

Transport hazard class(es): 3

Packing group: II

Environmental hazards: no

Special precautions for user: None known

### Inland waterway transport

ADN

UN number or ID number: UN1917

UN proper shipping name: ETHYL ACRYLATE, STABILIZED

Transport hazard class(es): 3

Packing group: II

Environmental hazards: no

Special precautions for user: None known

### Transport in inland waterway vessel

UN number or ID number: UN1917

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

UN proper shipping name: ETHYL ACRYLATE, STABILIZED

Transport hazard class(es): 3, INST, N3

Packing group: II

Environmental hazards: yes

Type of inland waterway vessel: C

Cargo tank design: 2

Cargo tank type: 2

### **Sea transport**

IMDG

UN number or ID number: UN 1917

UN proper shipping name: ETHYL ACRYLATE, STABILIZED

Transport hazard class(es): 3

Packing group: II

Environmental hazards: no

Marine pollutant: NO

Special precautions for user: EmS: F-E; S-D

### **Air transport**

IATA/ICAO

UN number or ID number: UN 1917

UN proper shipping name: ETHYL ACRYLATE, STABILIZED

Transport hazard class(es): 3

Packing group: II

Environmental hazards: No Mark as dangerous for the environment is needed

Special precautions for user: None known

#### **14.1. UN number or ID number**

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

#### **14.2. UN proper shipping name**

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

### 14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

### 14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

### 14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

### 14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

### 14.7. Maritime transport in bulk according to IMO instruments

Regulation:	IBC-Code
Product name:	Ethyl acrylate
Pollution category:	Y
Ship Type:	2

---

## SECTION 15: Regulatory Information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Prohibitions, Restrictions and Authorizations

Chemical Prohibition Ordinance (DE): Annex 2

Restriction Type: Restricted substance

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 3, 40, 75

Hazardous Incident Ordinance (Germany):

List entry in regulation: 1.1.2

Classification applies for standard conditions of temperature and pressure.

List entry in regulation: 1.2.5.1

List entry in regulation: 1.2.5.2

List entry in regulation: 1.2.5.3

Classification applies for standard conditions of temperature and pressure.

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

List entry in regulation: H2

Classification applies for standard conditions of temperature and pressure.

List entry in regulation: P5a

List entry in regulation: P5b

List entry in regulation: P5c

Classification applies for standard conditions of temperature and pressure.

Classification according to 'TA-Luft' (Germany):

5.2.5 class I: Organic gases class I

ethyl acrylate

Water hazard class (§6 AwSV para.4 (Legal binding announcement of the substance in the Federal Gazette)): (2) significantly water polluting. ID-No.: 208

The specifications of the Technical Rule for Hazardous Substances (TRGS) 401 must be observed (TRGS 401: Risks resulting from skin contact - identification, assessment, measures).

The Maternity Protection Act needs to be considered.

German Regulation TA Luft (Technical Instruction on Air Quality Control, i.e. first Directive to the Federal Immission Control Ordinance)

Regulation on prohibitions and restrictions on the marketing of dangerous substances, preparations and goods in accordance with the chemical law (Germany)

Law on the Protection of Working Youth

## 15.2. Chemical Safety Assessment

Chemical Safety Assessment performed

---

## SECTION 16: Other Information

Assessment of the hazard classes according to UN GHS criteria (most recent version)

Flam. Liq. 2

Acute Tox. 4 (oral)

Skin Irrit. 2

Eye Irrit. 2A

STOT SE 3 (irritating to respiratory system)

Aquatic Acute 2

Aquatic Chronic 3

Acute Tox. 3 (Inhalation - vapour)

Skin Sens. 1B

Acute Tox. 5 (dermal)

This product is of industrial quality and unless otherwise specified or agreed intended exclusively for industrial use. Any other intended applications should be discussed with the manufacturer.

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Flam. Liq.	Flammable liquids
Acute Tox.	Acute toxicity
Skin Irrit.	Skin irritation
Eye Irrit.	Eye irritation
Skin Sens.	Skin sensitization
STOT SE	Specific target organ toxicity — single exposure
Aquatic Chronic	Hazardous to the aquatic environment - chronic
Skin Corr./Irrit.	Skin corrosion/irritation
Eye Dam./Irrit.	Serious eye damage/eye irritation
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H331	Toxic if inhaled.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H302 + H312	Harmful if swallowed or in contact with skin.
H412	Harmful to aquatic life with long lasting effects.

#### Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.  
 ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

## Annex: Exposure Scenarios

### Index

1. Polymer production, (producer site), (use in industrial settings)  
SU8, SU9, SU12; ERC6c; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC15
2. Polymer production, Downstream User, (use in industrial settings)  
SU8, SU9, SU12; ERC6c; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC15
3. Use as an intermediate, (producer site), (use in industrial settings)  
SU8, SU9; ERC6a; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC15
4. Use as an intermediate, Downstream User, (use in industrial settings)  
SU8, SU9; ERC6a; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC15

\*\*\*\*\*

### 1. Short title of exposure scenario

Polymer production, (producer site), (use in industrial settings)  
SU8, SU9, SU12; ERC6c; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC15

### Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC6c: Use of monomer in polymerisation processes at industrial site (inclusion or not into/onto article)
<b>Operational conditions</b>	
Annual amount used in the EU	15.600.000 kg
Minimum emission days per year	300
Emission factor air	5 %
Emission factor water	0,01 ppm
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

<b>Risk Management Measures</b>	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,076817
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	676.936,9 kg/d
Risk from environmental exposure is driven by soil.	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Assumes activities are at ambient temperature.	
<b>Risk Management Measures</b>	
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	0,0417 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,001986

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	6,2572 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,297964
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	4,1715 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,198643
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	8,343 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,397286
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC5: Mixing or blending in batch processes Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: $\geq 0\%$ - $\leq 25\%$
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	12,5145 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,595929
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %
Provide a good standard of general or	Effectiveness: 70 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

controlled ventilation (5 to 10 air changes per hour)	
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	6,2572 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,297964
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 95 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	5,2144 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,248304
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	6,2572 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,297964
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC15: Use a laboratory reagent. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Exposure estimate	4,1715 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,198643
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

## 2. Short title of exposure scenario

Polymer production, Downstream User, (use in industrial settings)  
SU8, SU9, SU12; ERC6c; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC15

## Control of exposure and risk management measures

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ERC6c: Use of monomer in polymerisation processes at industrial site (inclusion or not into/onto article)
<b>Operational conditions</b>	
Annual amount used in the EU	87.500.000 kg
Minimum emission days per year	300
Emission factor air	5 %
Emission factor water	0,01 ppm
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
<b>Risk Management Measures</b>	
Soil treatment measures considered suitable are, e.g.	No application of sludge to soil
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,062973
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	463.159,2 kg/d

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Risk from environmental exposure is driven by marine water.

#### Contributing exposure scenario

<b>Use descriptors covered</b>	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
--------------------------------	--

#### Operational conditions

Concentration of the substance	ethyl acrylate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.

#### Risk Management Measures

Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	

#### Exposure estimate and reference to its source

Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	0,0417 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,001986
Assessment method	Qualitative assessment
	Worker - dermal

#### Guidance to Downstream Users

For scaling see: <http://www.ecetoc.org/tra>

#### Contributing exposure scenario

<b>Use descriptors covered</b>	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
--------------------------------	---

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

	Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	6,2572 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,297964
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	
<b>Contributing exposure scenario</b>	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
<b>Operational conditions</b>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Concentration of the substance	ethyl acrylate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	4,1715 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,198643
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	8,343 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,397286
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC5: Mixing or blending in batch processes Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: >= 0 % - <= 25 %
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	12,5145 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,595929
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	6,2572 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,297964
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 95 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	5,2144 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,248304
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	6,2572 mg/m <sup>3</sup>



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Risk Characterization Ratio (RCR)	0,297964
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC15: Use a laboratory reagent. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	4,1715 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,198643
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

### 3. Short title of exposure scenario

Use as an intermediate, (producer site), (use in industrial settings)

SU8, SU9; ERC6a; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC15

### Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC6a: Use of intermediate
Operational conditions	
Annual amount used in the EU	29.100.000 kg
Minimum emission days per year	300
Emission factor air	5 %
Emission factor water	0,01 ppm
Emission factor soil	0,1 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Soil treatment measures considered suitable are, e.g.	No application of sludge to soil
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,14323
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	677.234,1 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
Operational conditions	
Concentration of the substance	ethyl acrylate Content: >= 0 % - <= 100 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	0,0417 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,001986
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	6,2572 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,297964
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	4,1715 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,198643
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	8,343 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,397286
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC5: Mixing or blending in batch processes Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: >= 0 % - <= 25 %
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	12,5145 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,595929
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	6,2572 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,297964

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 95 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	5,2144 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,248304
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC9: Transfer of substance or preparation into small



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

	containers (dedicated filling line, including weighing). Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	6,2572 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,297964
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	
<b>Contributing exposure scenario</b>	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

	Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	4,1715 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,198643
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*

#### 4. Short title of exposure scenario

Use as an intermediate, Downstream User, (use in industrial settings)

SU8, SU9; ERC6a; PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC15

#### Control of exposure and risk management measures

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	ERC6a: Use of intermediate
<b>Operational conditions</b>	
Annual amount used in the EU	29.100.000 kg

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Minimum emission days per year	300
Emission factor air	5 %
Emission factor water	0,01 ppm
Emission factor soil	0,1 %
Receive Surf. Water (Flow Rate).	18.000 m3/d
Dilution factor river	10
Dilution factor coast	100
<b>Risk Management Measures</b>	
Soil treatment measures considered suitable are, e.g.	No application of sludge to soil
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2.000 m3/d
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0,062708
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	154.685,1 kg/d
Risk from environmental exposure is driven by marine water.	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Wash off any skin contamination immediately. Avoid contact with	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	0,0417 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,001986
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	6,2572 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,297964
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	4,1715 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,198643
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	8,343 mg/m <sup>3</sup>

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Risk Characterization Ratio (RCR)	0,397286
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC5: Mixing or blending in batch processes Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: $\geq 0\%$ - $\leq 25\%$
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	12,5145 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,595929
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC8a: Transfer of substance or mixture (charging and

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

	discharging) at non-dedicated facilities Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	6,2572 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,297964
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	
<b>Contributing exposure scenario</b>	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
<b>Operational conditions</b>	



BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Concentration of the substance	ethyl acrylate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 95 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	5,2144 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,248304
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: $\geq 0\%$ - $\leq 100\%$
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	6,2572 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,297964
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

<b>Contributing exposure scenario</b>	
<b>Use descriptors covered</b>	PROC15: Use a laboratory reagent. Use domain: industrial
<b>Operational conditions</b>	
Concentration of the substance	ethyl acrylate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	3940 Pa
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
	Assumes activities are at ambient temperature.
<b>Risk Management Measures</b>	
Local exhaust ventilation	Effectiveness: 90 %

BASF safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 16.04.2025

Version: 4.0

Date / Previous version: 14.09.2023

Previous version: 3.1

Product: **ETHYL ACRYLATE**

(ID no. 30041302/SDS\_GEN\_DE/EN)

Date of print 21.10.2025

Wash off any skin contamination immediately. Avoid contact with contaminated tools. Clean up contamination as soon as they occur. Avoid frequent and direct contact with substance.	
Wear suitable personal protective equipment.	
Use suitable eye protection.	
Avoid skin contact. Wash off any skin contamination immediately.	
Wear chemically resistant gloves in combination with 'basic' employee training.	
<b>Exposure estimate and reference to its source</b>	
Assessment method	EASY TRA v5.2, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	4,1715 mg/m <sup>3</sup>
Risk Characterization Ratio (RCR)	0,198643
Assessment method	Qualitative assessment
	Worker - dermal
<b>Guidance to Downstream Users</b>	
For scaling see: <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>	

\*\*\*\*\*