We create chemistry

Safety Data Sheet
Elastollan® 1188 A 10FR000

1. Identification

Product identifier used on the label

Elastollan® 1188 A 10FR000

Recommended use of the chemical and restriction on use

Recommended use*: Polymer
Suitable for use in industrial sector: plastics processing industry
Unsuitable for use: Uses other than recommended

* The “Recommended use” identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

24 Hour Emergency Response Information
CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family:	Polymer based on: polyurethane, stabilizing agents, additives
Synonyms:	THERMOPLASTIC POLYURETHANE ELASTOMER

2. Hazards Identification

According to Regulation 2024 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

No need for classification according to GHS criteria for this product.

Label elements

The product does not require a hazard warning label in accordance with GHS criteria.

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

Labeling of special preparations (GHS):
UNDER HOT MELT PROCESSING CONDITIONS, WEAR PERSONAL PROTECTIVE EQUIPMENT TO PREVENT THERMAL BURNS.

3. Composition / Information on Ingredients

According to Regulation 2024 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Limestone
CAS Number: 1317-65-3
Content (W/W): >= 0.1 - <= 1.5%
Synonym: No data available.

The actual concentration is withheld as a trade secret.

4. First-Aid Measures

Description of first aid measures

General advice:
Avoid contact with the skin, eyes and clothing. Remove contaminated clothing.

If inhaled:
Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

If on skin:
Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention. Skin contact with hot molten substance/product may cause thermal burns.

If in eyes:
In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

If swallowed:
Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Do not induce vomiting. Immediate medical attention required.

Most important symptoms and effects, both acute and delayed

Symptoms: No applicable information available., (Further) symptoms and / or effects are not known so far

Information on: Limestone
Symptoms: Overexposure may cause:, rhinitis, irritation of the mucous membranes, irritates the eyes and respiratory tract, skin irritation, coughing, nausea, vomiting, dizziness, diarrhea, abdominal cramps
---
Hazards: No hazards anticipated.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:	Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
water spray, foam, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture
Hazards during fire-fighting:
No particular hazards known.

Advice for fire-fighters
Protective equipment for fire-fighting:
Wear a self-contained breathing apparatus.

Further information:
Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Further accidental release measures:
High risk of slipping due to leakage/spillage of product.

Personal precautions, protective equipment and emergency procedures
No special precautions necessary.

Environmental precautions
No special precautions necessary.

Methods and material for containment and cleaning up
Spills should be contained and placed in suitable containers for disposal.

7. Handling and Storage

Precautions for safe handling
Provide suitable exhaust ventilation at the drying process and in the area surrounding the melt outlet of processing machines.

Protection against fire and explosion:
No explosion proofing necessary.

Conditions for safe storage, including any incompatibilities
Segregate from foods and animal feeds.

Suitable materials for containers: High density polyethylene (HDPE), Low density polyethylene (LDPE), Paper/Fibreboard

Further information on storage conditions: From this information no suitability of the materials mentioned above for the design of installations, including containers for permanent storage, can be inferred. Special conditions apply to the selection of materials in this regard, which we can communicate on request.
Avoid extreme heat. Avoid deposition of dust.

Storage stability:
Protect against moisture.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Limestone	OSHA Z1:	PEL 5 mg/m3 Respirable fraction ;
	OSHA Z1:	PEL 15 mg/m3 Total dust ;
	ACGIH, US:	TWA value 10 mg/m3 Inhalable particles ;
	ACGIH, US:	TWA value 3 mg/m3 Respirable particles ;
	OSHA Z3:	TWA value 5 mg/m3 Respirable fraction ;
	OSHA Z3:	TWA value 15 mg/m3 Total dust ;
	OSHA Z3:	TWA value 15 millions of particles per cubic foot of air Respirable fraction ;
	OSHA Z3:	TWA value 50 millions of particles per cubic foot of air Total dust ;

Advice on system design:
Provide local exhaust ventilation to control dust.

Personal protective equipment

Respiratory protection:
Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator as needed.

Hand protection:
Wear gloves to prevent contact during mechanical processing and/or hot melt conditions., Protective glove selection must be based on the user's assessment of the workplace hazards.

Eye protection:
Wear splash goggles to protect from hot molten substance/product.

Body protection:
Standard work clothes and shoes., light protective clothing, Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:
Wear protective clothing to prevent contact during mechanical processing and/or hot melt conditions. Avoid inhalation of dust. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied.

9. Physical and Chemical Properties

Physical state:	solid	
Form:	granules	
Odour:	odourless	
Odour threshold:	not determined	
Colour:	transparent to opaque	
pH value:	substance/mixture is non-soluble (in water)	
softening temperature:	> 120 °C	
Melting point:	No applicable information available.	
Freezing point:	No applicable information available.	
boiling temperature:	The product is a non-volatile solid.	
Sublimation point:	No applicable information available.	
Flash point:	not applicable, the product is a solid	
Flammability:	not flammable	(Directive 92/69/EEC, A.10)
Lower explosion limit:	For solids not relevant for classification and labelling.	
Upper explosion limit:	For solids not relevant for classification and labelling.	
Autoignition:	> 400 °C	
SADT:	Not a substance liable to self-decomposition according to UN transport regulations, class 4.1.	
Vapour pressure:	not applicable	
Density:	approx. 1.17 g/cm3 (20 °C)	
Relative density:	approx. 1.1 - 1.2 (20 °C)	
Bulk density:	500 - 700 kg/m3 (20 °C)	
Relative vapour density:	not applicable	
Partitioning coefficient n-octanol/water (log Pow):	not applicable	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated. > 230 °C Thermal decomposition above the indicated temperature is possible. Prolonged thermal loading can result in products of degradation being given off.	
Viscosity, dynamic:	not applicable	
Viscosity, kinematic:	not applicable, the product is a solid	

Solubility in water:	insoluble
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Molecular weight:	No data available.
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.

Particle characteristics
Particle size distribution: typically 4.5 - 4.7 mm (standard deviation 0.1 mm)

10. Stability and Reactivity

Reactivity
No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:
No corrosive effect on metal.

Oxidizing properties:
not fire-propagating

Reactions with water/air:	Reaction with:	water
	Flammable gases:	no
	Toxic gases:	no

Chemical stability
The product is chemically stable.

Peroxides: The product does not contain peroxides. The product/the substance has not a tendency towards the formation of peroxide.

Possibility of hazardous reactions
The product is chemically stable.
No hazardous reactions when stored and handled according to instructions.

Conditions to avoid
No conditions known that should be avoided.

Incompatible materials
No substances known that should be avoided.

Hazardous decomposition products

Decomposition products:
Hazardous decomposition products: carbon monoxide, carbon dioxide, hydrogen cyanide

Thermal decomposition:
No decomposition if stored and handled as prescribed/indicated.
> 230 °C

Thermal decomposition above the indicated temperature is possible.
Prolonged thermal loading can result in products of degradation being given off.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity
Assessment of acute toxicity: Inhalation of particulates may cause respiratory tract irritation. Ingestion may cause gastrointestinal disturbances. Contact with molten product may cause thermal burns. The resin in pelleted form poses a low hazard.

Oral
Type of value: LD50
Species: rat
Value: > 5,000 mg/kg
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Inhalation
No applicable information available.

Dermal
No applicable information available.

Assessment other acute effects
Assessment of STOT single:
Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Irritation / corrosion
Assessment of irritating effects: Not irritating to the eyes. Not irritating to the skin. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Sensitization
Assessment of sensitization: The chemical structure does not suggest a sensitizing effect.

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aspiration Hazard
No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: No known chronic effects. Repeated exposure to the substance by dermal administration leads to effects similar to those found after single exposure. Repeated exposure to the substance by inhalative administration leads to effects similar to those found after single exposure. Repeated exposure to the substance by oral administration leads to effects similar to those found after single exposure. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Genetic toxicity
Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Carcinogenicity
Assessment of carcinogenicity: The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Reproductive toxicity
Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Teratogenicity
Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Other Information
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Medical conditions aggravated by overexposure
Data available do not indicate that there are medical conditions that are generally recognized as being aggravated by exposure to this substance/product.

12. Ecological Information

Toxicity

Aquatic toxicity
Assessment of aquatic toxicity:
There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Toxicity to fish

Information on: triphenyl phosphate
LC50 (96 h) 0.4 mg/l, Oncorhynchus mykiss (other, static)

Aquatic invertebrates

Information on: triphenyl phosphate

EC50 (48 h) 2.41 mg/l, Daphnia magna (OECD Guideline 202, part 1, static)
Literature data.

Aquatic plants

Information on: triphenyl phosphate
EC50 (72 h) 3.73 mg/l (growth rate), Pseudokirchneriella subcapitata (OECD Guideline 201, static)
No observed effect concentration (72 h) 2.3 mg/l (growth rate), Pseudokirchneriella subcapitata (OECD Guideline 201, static)

Chronic toxicity to fish

Information on: triphenyl phosphate
EC10 (30 d) 0.037 mg/l, Oncorhynchus mykiss (other, Flow through.)

Chronic toxicity to aquatic invertebrates

Information on: triphenyl phosphate
No observed effect concentration (21 d) 0.254 mg/l, Daphnia magna (OECD Guideline 211, semistatic)

Microorganisms/Effect on activated sludge

Toxicity to microorganisms

Information on: triphenyl phosphate
:
No data available.

Persistence and degradability

Assessment biodegradation and elimination (H2O)
Poorly biodegradable.

Elimination information

Poorly biodegradable.

Bioaccumulative potential

Assessment bioaccumulation potential
Does not significantly accumulate in organisms.

Mobility in soil

Assessment transport between environmental compartments
Adsorption to solid soil phase is not expected.

Additional information

Adsorbable organically-bound halogen(AOX):

This product contains no organically-bound halogen.

13. Disposal considerations

Waste disposal of substance:
Incinerate or dispose of in a licensed facility. Do not discharge substance/product into sewer system.

Container disposal:
Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport
USDOT
Not classified as a dangerous good under transport regulations

Sea transport
IMDG
Not classified as a dangerous good under transport regulations

Air transport
IATA/ICAO
Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:
Chemical TSCA, US

All substances are TSCA listed and active.

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

State regulations

State RTK	CAS Number	Chemical name
NJ	1317-65-3	Limestone
PA	1317-65-3	Limestone

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including SILICA, CRYSTALLINE (AIRBORNE PARTICLES OF RESPIRABLE SIZE), which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:
Health: 1 Fire: 0 Reactivity: 0 Special:

HMIS III rating

Health: 1 Flammability: 0 Physical hazard: 0

16. Other Information

SDS Prepared by:
BASF NA Product Regulations
SDS Prepared on: 2025/06/16

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Elastollan® 1188 A 10FR000 is a registered trademark of BASF Corporation or BASF SE
IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
Trademark potentially not registered in all countries.

Date / Revised: 2025/06/16 Version: 3.0
Date / Previous version: 2020/11/03 Previous version: 2.0

END OF DATA SHEET