We create chemistry

Helaian Data Keselamatan
Safety data sheet

1. Pengenalan bahan kimia dan pembekal

DisPlus 39L

Kegunaan: kadmium (Cd)

Syarikat:
BASF (Malaysia) Sdn Bhd
Lot 19.02 Level 19, 1 Powerhouse
No 1 Persiaran Bandar Utama
47800 Petaling Jaya
Selangor D.E, MALAYSIA
Nombor Telefon: +60 3 7612 1888
Nombor Telefax: +60 3 7612 1777

Maklumat kecemasan:
Nombor Kecemasan Kebangsaan
+603 7612 1999
Nombor Kecemasan Antarabangsa:
Nombor Telefon: +49 180 2273-112

2. Pengenalan Bahaya

Pengelasan bahan dan campuran:
Toks. Akut 4 (oral)
Toks. Akut 4 (dermis)
Kks./Kreng. Kulit 2
Kros./Kreng. Mata 1
Akuatik Kronik 3

Bagi pengelasan yang tidak ditulis dengan penuh dalam bahagian ini, teks lengkap boleh didapati di bahagian 16.

Unsur label dan pernyataan berjaga-jaga:

Piktogram:

Kata Isyarat:
bahaya

Pernyataan Bahaya:

H318	Menyebabkan kerosakan mata yang serius.
H315	Menyebabkan kerengsaan kulit. Berbahaya jika tertelan atau terkena kulit.
H412	Memudaratkan kepada hidupan akuatik dengan kesan yang berpanjangan.

Pernyataan Berjaga-jaga (Pencegahan):

P280	Pakai sarung tangan perlindung, pakaian perlindung dan perlindung mata atau perlindung muka.
P273	Elakkan pelepasan bahan ke persekitaran.
P270	Jangan makan, minum atau merokok semasa menggunakan produk ini.
P264	Basuh bahagian badan yang tercemar dengan sepenuhnya selepas pengendalian.

Pernyataan Berjaga-jaga (Tindak Balas):

P310	Segera hubungi PUSAT RACUN atau pakar perubatan.
P305 + P351 + P338	JIKA TERKENA MATA: Bilas berhati-hati dengan air selama beberapa minit.Tanggalkan kanta lekap, jika ada dan dapat dilakukan dengan mudah. Teruskan membilas.
P302 + P352	JIKA TERKENA KULIT (pada rambut): Basuh dengan sabun dan air yang banyak.
P361 + P364	Segera tanggalkan/buka semua pakaian yang tercemar dan basuh sebelum menggunakannya semula.
P330	Bilas mulut.

Pernyataan Berjaga-jaga (Pelupusan):

P501	Buangkan kandungan dan berkas ke tempat penggumpulan bahan sisa merbahaya atau khas.

Bahaya lain yang tidak menyebabkan pengelasan:
Jika berkenaan, maklumat yang diberikan dalam bahagian ini tentang bahaya lain tidak menyebabkan pengelasan tetapi mungkin menyumbang kepada bahaya bahan atau campuran secara keseluruhan.
Produk ini tidak mengandungi bahan yang melebihi had undang-undang untuk mematuhi kriteria PBT (berketerusan/bioakumulatif/bertoksik atau kriteria vPvB (amat berketerusan/amat bioakumulatif).
Produk tidak mengandungi bahan melebihi had undang-undang yang termasuk di dalam senarai yang disediakan mengikut Artikel 59(1) Peraturan (EC) No. 1907/2006 kerana mengandungi ciri-ciri gangguan endokrin atau telah dikenalpasti untuk mengandungi ciri-ciri gangguan endokrin mengikut kriteria yang ditetapkan dalam Peraturan Wakilan Suruhanjaya (EU) 2017/2100 atau Peraturan Suruhanjaya (EU) 2018/605.

3. Komposisi dan Maklumat Mengenai Ramuan Bahan Kimia

Keadaan kimia

Sediaan berdasarkan: Zat aktif permukaan anion dan bukan ion

Ramuan berbahaya

(OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)

Kandungan (berat/berat): >= 25 %	Kreng. Kulit 2
- < 50 %	Kros. Mata 1
Nombor CAS: 68891-38-3	

Alcohols, C13-15, branched and linear, ethoxylated

Kandungan (berat/berat): >= 25 %	Toks. Akut 4 (oral)
- < 50 %	Kros./Kreng. Mata 1
Nombor CAS: 157627-86-6	Akuatik Kronik 3

2-butoksietanol

Kandungan (berat/berat): >= 20 %	Toks. Akut 4 (oral)
- < 25 %	Kreng. Kulit 2
Nombor CAS: 111-76-2	Kreng. Mata 2
	Toks. Akut 3 (tersedut - wap)

Bagi pengelasan yang tidak ditulis dengan penuh dalam bahagian ini, teks lengkap boleh didapati di bahagian 16.

4. Langkah-Langkah Pertolongan Cemas

Nasihat am:
Segera tanggalkan pakaian yang tercemar.

Jika tersedut:
Tenangkan pesakit, alihkan ke tempat berudara bersih, dapatkan rawatan perubatan. Segera sedut aerosol dos kortikosteroid.

Apabila terkena kulit:
Segera basuh bersih-bersih dengan air yang banyak, gunakan balutan steril, rujuk pakar kulit.

Apabila terkena mata:
Segera basuh mata yang terkena produk selama sekurang-kurangnya 15 minit di bawah aliran air dengan membuka mata, rujuk pakar mata.

Apabila tertelan:
Segera berkumur, kemudian minum 200-300 ml air, dapatkan rawatan perubatan.

Nota kepada doktor:

Gejala: Maklumat, iaitu maklumat tambahan mengenai simptom dan kesan boleh termasuk di dalam fasa palabelan GHS yang tersedia ada dalam Seksyen 2 dan di dalam penaksiran Toksikologi yang tersedia ada dalam Seksyen 11., Simptom dan/atau kesan tidak diketahui setakat ini
Nota kepada doktor:
Rawatan: Rawat mengikut gejala (nyahcemar, fungsi utama), tiada penawar khusus diketahui.

5. Langkah-Langkah Pemadaman Kebakaran

Bahan pemadam yang sesuai:
semburan air, serbuk kering, busa

Bahaya tertentu:
wap yang merbahaya, karbon oksida
Evolusi wasap/kabus. Bahan/kumpulan bahan yang dinyatakan boleh dibebaskan jika berlaku kebakaran.

Peralatan perlindungan khusus:
Gunakan alat pernafasan serba lengkap.

Maklumat lanjut:
Tahap risiko ditentukan oleh bahan yang terbakar dan keadaan kebakaran. Air pemadam api yang tercemar mestilah dilupuskan mengikut peraturan rasmi.

6. Langkah-Langkah Pelepasan Tidak Sengaja

Perlindungan diri, kelengkapan pelindung dan tatacara kecemasan:
Gunakan pakaian pelindung diri.Perlindungan pernafasan diperlukan.Elakkan daripada bersentuhan dengan kulit dan mata.Elakkan daripada tersedut.Pastikan pengalihudaraan yang mencukupi.

Langkah berjaga-jaga untuk alam sekitar:
Bendung air yang tercemar/air yang digunakan untuk memadam kebakaran. Jangan lepaskan ke dalam parit/air permukaan/air tanah.

Kaedah pembersihan atau penyerapan:
Bagi sejumlah besar: Pam produk.
Bagi baki: Kutip dengan bahap penyerap yang sesuai. Lupuskan bahan yang diserap mengikut peraturan.

7. Pengendalian dan Penyimpanan

Pengendalian

Jangan makan, minum, merokok atau menggunakan tembakau di tempat kerja. Tangan dan/atau muka hendaklah dibasuh sebelum rehat dan setelah tamat waktu bekerja. Tanggalkan pakaian yang tercemar dan alat pelindung sebelum memasuki tempat makan.

Perlindungan terhadap kebakaran dan letupan:
Ambil langkah berjaga-jaga terhadap luahan statik.

Penyimpanan

Asingkan daripada makanan dan makanan haiwan. Asingkan daripada asid kuat. Asingkan daripada alkali kuat.
Maklumat lanjut tentang keadaan penyimpanan: Pastikan bekas tertutup rapat dan kering; simpan di tempat yang dingin.

8. Kawalan pendedahan dan perlindungan diri

Komponen dengan parameter kawalan tempat kerja

2-butoksietanol, 111-76-2;

Peralatan perlindungan peribadi

Perlindungan pernafasan:
Pakai perlindungan pernafasan jika pengalihudaraan tidak mencukupi. Penapis gabungan bagi gas/wap sebatian organik dan zarah pepejal dan cecair (cth. EN 14387 Jenis A-P2)

Perlindungan tangan:
Sarung tangan keselamatan kalis bahan kimia.
Bahan yang sesuai juga sekiranya terkena produk secara berpanjangan dan langsung. (Syor: Indeks perlindungan 6, bersamaan > 480 minit tempoh penelapan menurut EN ISO 374-1):
getah nitril (NBR) - 0.4 mm ketebalan salutan
Nota tambahan : Spesifikasi adalah berdasarkan ujian –ujian, data penerbitan dan maklumat dari pengeluar sarung tangan atau diambil yang serupa secara analogi. Oleh sebab banyak keadaan yang perlu dipertimbangkan (misalnya suhu), perlulah diambil kira, bahawa secara praktikalnya tempoh penggunaan sarung tangan pelindung kimia mungkin lebih pendek daripada tempoh penelapan yang ditentukan menurut ujian.
Arahan penggunaan pengilang hendaklah dipatuhi kerana jenisnya yang pelbagai.

Perlindungan mata:
Gogal keselamatan yang betul-betul muat (cth gogal tertutup) (EN 166) dan pelindung muka

Perlindungan badan:
Perlindungan badan mesti dipilih bergantung kepada aktiviti dan pendedahan, contohnya apron, kasut perlindungan, pakaian perlindungan bahan kimia (Berdasarkan DIN-EN 465)

Langkah kebersihan dan keselamatan am:
Memakai pakaian kerja yang tertutup diperlukan sebagai tambahan kepada kelengkapan perlindungan diri yang dinyatakan. Tanggalkan semua pakaian yang tercemar dengan segera. Basuh pakaian yang tercemar sebelum digunakan semula. Kendalikan mengikut amalan kesihatan dan keselamatan industri yang baik.

9. Sifat Fizikal dan Kimia

Bentuk:	cecair
Warna:	jernih
Bau:	khusus
Ambang bau:	tidak ditentukan

nilai pH:	> 5.5 (100 %(m))	(DIN 19268)
julat beku:	tidak ditentukan	
Suhu didih:	100 - 101 °C (1,013 hPa)	(Garispanduan OECD 103)
Takat kilat:	100 - 101 °C	(ISO 2719)
Tahap penyejatan:	tidak ditentukan	
Kemudahbakaran (pepejal/gas):	tidak mudah terbakar	(diterbitkan daripada takat kilat)
Had letupan bawah:	Untuk cecair tiada kaitan untuk pengelasan dan pelabelan., Had letupan bawah mungkin 5 - 15 °C dibawah takat kilat.	
Had letupan atas:	Untuk cecair tiada kaitan untuk pengelasan dan pelabelan.	(DIN 51649-1)
Suhu pencucuhan:	232 °C Produk belum diuji. Penyataan diambil daripada ciri setiap komponen.	

Maklumat tentang : 2-butoksietanol

Suhu pencucuhan:	232 °C	(DIN EN 14522)

Penguraian terma:	tidak ditentukan
pencucuhan sendiri:	Tidak swacucuh.
Kebolehan swapemanasan sendiri:	Ia bukanlah bahan yang mampu pemanasan spontan.
Bahaya letupan:	tidak mudah meletup
Sifat yang menggalakkan kebakaran:	tidak merebakkan api

Tekanan Wap:	62.74 hPa (20 °C)	(OECD Guideline 104)
	71.71 hPa (50 °C)	(OECD Guideline 104)
	155.82 hPa (55 °C)	(OECD Guideline 104)
Kepekatan:	1.02 g/cm3 (15 °C)	(ISO 2811-3)
	1.02 g/cm3 (20 °C)	(ISO 2811-3)
	1.00 g/cm3 (50 °C)	

Ketumpatan wap relatif (udara):
tidak ditentukan

Keterlarutan dalam air: terlarut
Higroskopi: higroskopik
Keterlarutan (kualitatif) pelarut: alkohol
terlarut
Pekali petakan n-oktanol/air (log Pow):
tidak berkenaan untuk campuran

Kelikatan, dinamik: 60 mPa.s
(23 °C)
Kelikatan, kinematik: dianggarkan 59 mm2/s (23 °C) (calculated (from dynamic viscosity))

10. Kestabilan dan Kereaktifan

Keadaan yang perlu dielakkan:
Jauhi daripada nyalaan terbuka.

Penguraian terma: tidak ditentukan

Bahan yang perlu dielakkan:
asid kuat, bes kuat, agen pengoksida yang kuat

Kakisan kepada logam: Tiada kesan mengakis pada logam

Tindak balas berbahaya:
Tiada tindakbalas berbahaya jika disimpan dan dikendalikan seperti yang dinyatakan.

Bahan penguraian berbahaya:
Tidak produk penguraian yang berbahaya diketahui.

Kereaktifan:
Tiada produk penguraian yang berbahaya jika disimpan dan dikendalikan seperti yang ditetapkan/dinyatakan.

Kestabilan kimia:
Produk adalah stabil jika disimpan dan dikendalikan sebagaimana

11. Maklumat Toksikologi

Ketoksikan akut

Penilaian ketoksikan akut:
Ketoksikan sederhana selepas berlaku sentuhan kulit jangka pendek. Ketoksikan sederhana selepas kali pertama tertelan.

Data eksperimen/dikira:
ATE (melalui mulut): > 300 - < 2,000 mg/kg (dikira)

ATE (melalui penyedutan): 50 mg/l

ATE (dermal): 2,000 mg/kg

Maklumat tentang : 2-butoksietanol
Penilaian ketoksikan akut:
Ketoksikan sederhana selepas kali pertama tertelan. Penyedutan campuran wap-udara yang diperkaya/tepu mungkin tidak menimbulkan bahaya akut. Tidak toksik selepas sekali terkena kulit
---

Maklumat tentang : (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Data eksperimen/dikira:
LD50 tikus (melalui mulut): > 2,000 mg/kg (Ujian BASF)
Produk belum diuji. Penyataan diambil daripada bahan/produk yang mempunyai struktur dan komposisi yang sama.

LD50 tikus (melalui mulut): > 2,000 mg/kg (Ujian BASF)
Produk belum diuji. Penyataan diambil daripada bahan/produk yang mempunyai struktur dan komposisi yang sama.

Maklumat tentang : Alcohols, C13-15, branched and linear, ethoxylated
Data eksperimen/dikira:
LD50 tikus (melalui mulut): > 300 - 2,000 mg/kg (Garispanduan OECD 401)
Data penulisan.

Maklumat tentang : 2-butoksietanol
Data eksperimen/dikira:
LD50 marmut (melalui mulut): 1,200 mg/kg

Maklumat tentang : (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Data eksperimen/dikira:
LD50 tikus (dermal): 2,000 mg/kg (Garispanduan OECD 402)

Kerengsaan

Penilaian kesan merengsa:
Terkena kulit boleh menyebabkan kerengsaan. Boleh menyebabkan kerosakkan teruk kepada mata.

Maklumat tentang : (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Data eksperimen/dikira:
Kakisan/Kerengsaan kulit Cerakin in vitro: Merengsa (Garispanduan OECD 439)

Kakisan/Kerengsaan kulit arnab: Merengsa (Garispanduan OECD 404)

Maklumat tentang : Alcohols, C13-15, branched and linear, ethoxylated
Data eksperimen/dikira:
Kakisan/Kerengsaan kulit arnab: tidak merengsa (Garispanduan OECD 404)
Data penulisan.

Maklumat tentang : 2-butoksietanol
Data eksperimen/dikira:
Kakisan/Kerengsaan kulit arnab: Merengsa (Ujian BASF)

Maklumat tentang : (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Data eksperimen/dikira:
Kerosakkan/kerengsaan mata yang serius Cerakin in vitro: tiada kerosakan yang tidak boleh dipulihkan

Kerosakkan/kerengsaan mata yang serius arnab: kerosakan tak berbalik (Garispanduan OECD 405)

Maklumat tentang : Alcohols, C13-15, branched and linear, ethoxylated
Data eksperimen/dikira:
Kerosakkan/kerengsaan mata yang serius arnab: kerosakan tak berbalik (Ujian Draize)
Data penulisan.

Maklumat tentang : 2-butoksietanol
Data eksperimen/dikira:
Kerosakkan/kerengsaan mata yang serius arnab: Merengsa (Garispanduan OECD 405)

Pemekaan pernafasan/kulit

Penilaian pemekaan:
Berdasarkan data yang ada, kriteria pengelasan tidak dipenuhi.

Kemutagenan sel germa

Penilaian kemutagenan:
Berdasarkan data yang ada, kriteria pengelasan tidak dipenuhi.

Kekarsinogenan

Penilaian kekarsinogenan:
Berdasarkan data yang ada, kriteria pengelasan tidak dipenuhi.

Ketoksikan pembiakan

Penilaian ketoksikan pembiakan:
Berdasarkan data yang ada, kriteria pengelasan tidak dipenuhi.

Ketoksikan perkembangan

Penilaian keteratogenan:
Berdasarkan ramuan, tiada kesangsian tentang kesan teratogenik.

Ketoksikan khusus organ sasaran (sekali pendedahan):

Penilaian sekali STOT:
Berdasarkan maklumat yang ada, ketoksikan organ sasaran yang khusus adalah tidak dijangka selepas sekali pendedahan.

Ketoksikan dos berulang dan Ketoksikan organ sasaran tertentu (pendedahan berulang)

Penilaian ketoksikan dos berulang:
Berdasarkan pengalaman kami dan maklumat yang ada, tiada kesan buruk kepada kesihatan dijangka sekiranya dikendalikan menurut cara yang disyorkan dengan langkah berjaga-jaga untuk kegunaan yang khusus.

Bahaya penyedutan

Tiada bahaya penyedutan dijangka.

Maklumat lain yang berkaitan dengan ketoksikan

Produk belum diuji. Penyataan tentang toksikologi diambil daripada ciri setiap komponen.

12. Maklumat Ekologi

Keekotoksikan

Penilaian ketoksikan akuatik:
Toksik secara akut kepada organisma akuatik. Memudaratkan kepada hidupan akuatik dengan kesan yang berpanjangan.

Maklumat tentang : (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Ketoksikan kepada ikan:
LC50 (96 h) 7.1 mg/l, Brachydanio rerio (Garispanduan OECD 203, Alirkan.)
Perincian kesan toksik berkaitan dengan kepekatan nominal.

Maklumat tentang : Alcohols, C13-15, branched and linear, ethoxylated
Ketoksikan kepada ikan:
LC50 (96 h) > 1 - 10 mg/l, Brachydanio rerio (OECD 203; ISO 7346; 84/449/EEC, C.1, statik)
Data penulisan.

Maklumat tentang : (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Invertebrat air:
EC50 (48 h) 7.4 mg/l, Daphnia magna (Garispanduan OECD 202, Bahagian 1, statik)
Perincian kesan toksik berkaitan dengan kepekatan nominal.

Maklumat tentang : Alcohols, C13-15, branched and linear, ethoxylated
Invertebrat air:
EC50 (48 h) > 1 - 10 mg/l, Daphnia magna (Arahan 79/831/EEC)
Data penulisan.

Maklumat tentang : (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)

Tumbuhan akuatik:
Tiada kesan kepekatan yang diperhatikan (72 h) 0.95 mg/l (kadar pertumbuhan), Scenedesmus subspicatus ()
Penyataan kesan toksik berkaitan dengan kepekatan yang ditentukan secara analisis.

EC50 (72 h) 27.7 mg/l (kadar pertumbuhan), Desmodesmus subspicatus (Garispanduan OECD 201)
Penyataan kesan toksik berkaitan dengan kepekatan yang ditentukan secara analisis.

EC10 (72 h) 4.4 mg/l (kadar pertumbuhan), Pseudokirchneriella subcapitata (Garispanduan OECD 201)
Penyataan kesan toksik berkaitan dengan kepekatan yang ditentukan secara analisis.

Maklumat tentang : Alcohols, C13-15, branched and linear, ethoxylated
Tumbuhan akuatik:
EC50 (72 h) > 1 - 10 mg/l (kadar pertumbuhan), Scenedesmus subspicatus (Garispanduan OECD 201, statik)
Data penulisan.

Maklumat tentang : (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Ketoksikan kronik kepada ikan:
EC10 (28 hari) 1.7 mg/l, Pimephales promelas (OECD Guideline 210, Alirkan.)
Penyataan kesan toksik berkaitan dengan kepekatan yang ditentukan secara analisis. Produk belum diuji. Penyataan diambil daripada bahan/produk yang mempunyai struktur dan komposisi yang sama.

Maklumat tentang : (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Ketoksikan kronik kepada invertebrata akuatik:
Tiada kesan kepekatan yang diperhatikan (21 hari), > 1.19 mg/l, Daphnia magna (Garispanduan OECD 211, lain)
Penyataan kesan toksik berkaitan dengan kepekatan yang ditentukan secara analisis.

Maklumat tentang : Alcohols, C13-15, branched and linear, ethoxylated
Ketoksikan kronik kepada invertebrata akuatik:
Tiada kesan kepekatan yang diperhatikan, > 0.1 - 1 mg/l, Daphnia magna
Data penulisan.

Mobiliti

Maklumat tentang : (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Penilaian pengangkutan di antara bahagian di persekitaran:
Bahan tidak akan menyejat ke atmosfera daripada permukaan air
Selepas terdedah kepada tanah, produk ini bergerak dan mungkin - bergantung kepada degradasi - menyerap masuk kedalam tanah yang mengandungi kandungan air yang banyak
Kajian secara saintifiknya tidak wajar.

Maklumat tentang : 2-butoksietanol
Penilaian pengangkutan di antara bahagian di persekitaran:
Bahan tidak akan menyejat ke atmosfera daripada permukaan air
Penjerapan kepada fasa tanah pejal tidak dijangka

Keterusan dan boleh keterdegradasikan

Maklumat tentang : (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)

Maklumat tentang : 2-butoksietanol
Penilaian biodegradasi dan penyingkiran (H2O):
Mudah terbiodegradasikan (menurut kriteria OECD)

Potensi Biotumpukan

Maklumat tentang : (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Penilaian potensi bioakumilasi:
Akumulasi yang ketara dalam organisma tidak dijangka.

Maklumat tentang : Alcohols, C13-15, branched and linear, ethoxylated
Penilaian potensi bioakumilasi:
Tidak dijangka terakumulasi dalam organisma.

Maklumat tentang : 2-butoksietanol
Penilaian potensi bioakumilasi:
Oleh sebab pekali agihan n-oktanol/air (log Pow), tidak dijangka terakumulasi dalam organisma.

Maklumat tambahan

Nasihat ekotoksikologi lain:
Produk belum diuji. Penyataan tentang ekotoksikologi diambil daripada ciri setiap komponen.

13. Maklumat Pelupusan

Mestilah dibuang atau dibakar mengikut peraturan tempatan.

Pembungkusan tercemar:
Bungkusan yang tidak tercemar boleh diguna semula.
Bungkusan yang tidak boleh dibersihkan hendaklah dilupuskan dengan cara yang sama dengan kandungannya.

14. Maklumat Pengangkutan

Pengangkutan domestik:

Tidak dikelaskan sebagai berbahaya di bawah peraturan pengangkutan

Pengangkutan laut
IMDG

Tidak dikelaskan sebagai berbahaya di bawah peraturan pengangkutan

Pengangkutan udara
IATA/ICAO

Tidak dikelaskan sebagai berbahaya di bawah peraturan pengangkutan

Pengangkutan secara pukal menurut Lampiran II MARPOL dan IBC

Peraturan:	Tidak dinilai
Penghantaran yang diluluskan:	Tidak dinilai
Nama pencemaran:	Tidak dinilai
Kategori pencemaran:	Tidak dinilai
Jenis Kapal:	Tidak dinilai

15. Maklumat Pengawalseliaan

Peraturan-Peraturan Keselamatan dan Kesihatan Pekerjaan (Pengelasan, Pelabelan dan Helaian Data Keselamatan Bahan kimia Berbahaya) 2013
Akta OSHA 1994 dan peraturan berkaitan
Akta Kualiti Alam Sekeliling 1974

Maklumat tentang peraturan-peraturan tidak meliputi kesemuanya. Peraturan-peraturan lain mungkin dikenakan kepada bahan ini.

16. Maklumat lain

Tarikh Penyediaan / Tarikh Penyemakan: 23.04.2025

Sumber Maklumat dan Rujukan :
SDS ini disediakan dengan menggunakan data dan maklumat tersimpan di dalam sistem berasaskan IT dalaman kami dan dibekalkan oleh pembekal perkhidmatan syarikat kami.

Singkatan Petunjuk:
ATE - Anggaran Ketoksikan Akut
GHS - Sistem Terharmoni Global
IATA / ICAO - Persatuan Pengangkutan Udara Antarabangsa / Organisasi Penerbangan Awam Antarabangsa
IBC - Kontena Pukal Pertengahan
IMDG - Barangan Merbahaya Kelautan Antarabangsa
LC - Kepekatan Maut
LD - Dos Maut
OECD - Organisasi Untuk Kerjasama dan Pembangunan Ekonomi
OEL - Had Pendedahan Pekerjaan
OSHA - Akta Keselamatan dan Kesihatan Pekerjaan
STOT - Ketoksikan Organ Sasaran Khusus

Teks penuh pengelasan, simbol bahaya dan pernyataan bahaya, jika dinyatakan dalam seksyen 2 atau 3:

Bhn. Ltp. T. Stab.	Bahan letup tidak stabil
Bhn. Ltp. 1.1	Bahan letup divisyen 1.1
Bhn. Ltp. 1.2	Bahan letup divisyen 1.2
Bhn. Ltp. 1.3	Bahan letup divisyen 1.3
Bhn. Ltp. 1.4	Bahan letup divisyen 1.4
Bhn. Ltp. 1.5	Bahan letup divisyen 1.5
Bhn. Ltp. 1.6	Bahan letup divisyen 1.6
Gas M. Bkr 1	Gas mudah terbakar kategori 1
Gas M. Bkr 2	Gas mudah terbakar kategori 2
Aerosol M. Bkr1	Aerosol mudah terbakar kategori 1
Aerosol M. Bkr 2	Aerosol mudah terbakar kategori 2
Cec. M. Bkr 1	Cecair mudah terbakar kategori 1
Cec. M. Bkr 2	Cecair mudah terbakar kategori 2
Cec. M. Bkr 3	Cecair mudah terbakar kategori 3
Pep. M. Bkr 1	Pepejal mudah terbakar kategori 1
Pep. M. Bkr 2	Pepejal mudah terbakar kategori 2
Gas Oks. 1	Gas mengoksida kategori 1
Cec. Oks. 1	Cecair mengoksida kategori 1
Cec. Oks. 2	Cecair mengoksida kategori 2
Cec. Oks. 3	Cecair mengoksida kategori 3
Pep. Oks. 1	Pepejal mengoksida kategori 1
Pep. Oks. 2	Pepejal mengoksida kategori 2
Pep. Oks. 3	Pepejal mengoksida kategori 3
Gas Tkn.	Gas di bawah tekanan
Swareak. A	Bahan kimia swareaktif jenis A
Swareak. B	Bahan kimia swareaktif jenis B
Swareak. CD	Bahan kimia swareaktif jenis C dan D
Swareak. EF	Bahan kimia swareaktif jenis E dan F
Swareak. G	Bahan kimia swareaktif jenis G
Cec. Pir. 1	Cecair piroforik kategori 1
Pep. Pir. 1	Pepejal piroforik kategori 1
Swapanas. 1	Bahan kimia swapanasan kategori 1
Swapanas. 2	Bahan kimia swapanasan kategori 2
Tdk. Bls. Air 1	Bahan kimia yang, jika terkena air, membebaskan gas mudah terbakar kategori 1
Tdk. Bls. Air 2	Bahan kimia yang, jika terkena air, membebaskan gas mudah terbakar kategori 2
Tdk. Bls. Air 3	Bahan kimia yang, jika terkena air, membebaskan gas mudah terbakar kategori 3
Peroks. Org. A	Peroksida organik jenis A
Peroks. Org. B	Peroksida organik jenis B
Peroks. Org. CD	Peroksida organik jenis C and D
Peroks. Org. EF	Peroksida organik jenis E and F
Peroks. Org. G	Peroksida organik jenis G
Kakis. Log. 1	Mengakis logam kategori 1
Toks. Akut 1	Ketoksikan akut kategori 1
Toks. Akut 2	Ketoksikan akut kategori 2
Toks. Akut 3	Ketoksikan akut kategori 3
Toks. Akut 4	Ketoksikan akut kategori 4
Kks. Kulit 1A	Kakisan atau kerengsaan kulit kategori 1A
Kks. Kulit 1B	Kakisan atau kerengsaan kulit kategori 1B

Kks. Kulit 1C	Kakisan atau kerengsaan kulit kategori 1C
Kreng. Kulit 2	Kakisan atau kerengsaan kulit kategori 2
Kros. Mata 1	Kerosakan mata atau kerengsaan mata yang serius kategori 1
Kreng. Mata 2	Kerosakan mata atau kerengsaan mata yang serius kategori 2
Pem. Naf. 1	Pemekaan pernafasan kategori 1
Pem. Kulit 1	Pemekaan kulit kategori 1
Muta. 1A	Kemutagenan sel germa kategori 1A
Muta. 1B	Kemutagenan sel germa kategori 1B
Muta. 2	Kemutagenan sel germa kategori 2
Kars. 1A	Kekarsinogenan kategori 1A
Kars. 1B	Kekarsinogenan kategori 1B
Kars. 2	Kekarsinogenan kategori 2
Pemb. 1A	Ketoksikan pembiakan kategori 1A
Pemb. 1B	Ketoksikan pembiakan kategori 1B
Pemb. 2	Ketoksikan pembiakan kategori 2
Laktasi	Kesan ke atas atau melalui penyusuan
STOT SE 1	Ketoksikan organ sasaran khusus - pendedahan tunggal kategori 1
STOT SE 2	Ketoksikan organ sasaran khusus - pendedahan tunggal kategori 2
STOT SE 3	Ketoksikan organ sasaran khusus - pendedahan tunggal kategori 3
STOT RE 1	Ketoksikan organ sasaran khusus - pendedahan berulang kategori 1
STOT RE 2	Ketoksikan organ sasaran khusus - pendedahan berulang kategori 2
Bhy. Asp.	Bahaya aspirasi kategori 1
Akuatik Akut 1	Berbahaya kepada persekitaran akuatik – bahaya akut kategori 1
Akuatik Kronik 1	Berbahaya kepada persekitaran akuatik – bahaya kronik kategori 1
Akuatik Kronik 2	Berbahaya kepada persekitaran akuatik – bahaya kronik kategori 2
Akuatik Kronik 3	Berbahaya kepada persekitaran akuatik – bahaya kronik kategori 3
Akuatik Kronik 4	Berbahaya kepada persekitaran akuatik – bahaya kronik kategori 4
Ozon	Berbahaya bagi lapisan ozon kategori 1

Garis menegak pada margin sebelah kiri tangan menunjukkan pindaan dari versi sebelumnya.

Data yang terdapat dalam risalah data keselamatan ini adalah berdasarkan pengetahuan dan pengalaman kami, dan menerangkan tentang produk yang berkaitan dengan keperluan keselamatan sahaja. Data tidak menyatakan ciri produk (spesifikasi produk). Data dalam risalah data keselamatan ini juga tidak menyatakan apa-apa ciri khusus atau kesesuaian produk yang dipersetujui untuk apa-apa tujuan tertentu. Penerima produk bertanggungjawab untuk memastikan bahawa apa-apa hak pemilikan serta undang-undang dan perundangan sedia ada dipatuhi.

1. Identification of the chemical and of the supplier

DisPlus 39L

Use: Performance Chemicals for Oilfield Applications

Company:
BASF (Malaysia) Sdn Bhd
Lot 19.02 Level 19, 1 Powerhouse
No 1 Persiaran Bandar Utama
47800 Petaling Jaya
Selangor D.E, MALAYSIA
Telephone: +60 3 7612 1888
Telefax number: +60 3 7612 1777

Emergency information:
National emergency number:
+603 7612 1999
International emergency number:
Telephone: +49 180 2273-112

2. Hazard identification

Classification of the substance and mixture:
Acute Tox. 4 (oral)
Acute Tox. 4 (dermal)
Skin Corr./Irrit. 2
Eye Dam./Irrit. 1
Aquatic Chronic 3

For the classifications not written out in full in this section the full text can be found in section 16.

Label elements and precautionary statement:

Pictogram:

Signal Word:
Danger

Hazard Statement:

H318	Causes serious eye damage.
H315	Causes skin irritation.
H302 + H312	Harmful if swallowed or in contact with skin.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P273	Avoid release to the environment.
P270	Do not eat, drink or smoke when using this product.
P264	Wash contaminated body parts thoroughly after handling.

Precautionary Statements (Response):

P310	Immediately call a POISON CENTER or physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303 + P352	IF ON SKIN (or hair): Wash with plenty of soap and water.
P361 + P364	Take off immediately all contaminated clothing and wash it before reuse.
P330	Rinse mouth.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.

Other hazards which do not result in classification:
If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.
The product does not contain a substance above legal limits fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.
Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

3. Composition/information on ingredients

Chemical nature

Preparation based on: anionic and non-ionic surfactants

Hazardous ingredients

(OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)

Content (W/W): >= 25 % - < 50 %	Skin Irrit. 2
CAS Number: 68891-38-3	Eye Dam. 1

Alcohols, C13-15, branched and linear, ethoxylated

Content (W/W): >= 25 % - < 50 %	Acute Tox. 4 (oral)
CAS Number: 157627-86-6	Eye Dam./Irrit. 1
	Aquatic Chronic 3

2-butoxyethanol

Content (W/W): >= 20 % - < 25 %	Acute Tox. 4 (oral)
CAS Number: 111-76-2	Skin Irrit. 2
	Eye Irrit. 2
	Acute Tox. 3 (Inhalation - vapour)

For the classifications not written out in full in this section the full text can be found in section 16.

4. First-Aid Measures

General advice:
Immediately remove contaminated clothing.

If inhaled:
Keep patient calm, remove to fresh air, seek medical attention. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

On skin contact:
Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

On contact with eyes:
Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:
Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Note to physician:
Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far
Note to physician:
Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Suitable extinguishing media:
water spray, dry powder, foam

Specific hazards:
harmful vapours, carbon oxides
Generation of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

Special protective equipment:
Wear a self-contained breathing apparatus.

Further information:
The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:
Use personal protective clothing.Breathing protection required.Avoid contact with skin and eyes.Avoid inhalation.Ensure adequate ventilation.

Environmental precautions:
Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods for cleaning up or taking up:
For large amounts: Pump off product.
For residues: Pick up with suitable absorbent material. Dispose of absorbed material in accordance with regulations.

7. Handling and Storage

Handling

No eating, drinking, smoking or tobacco use at the place of work. Hands and/or face should be washed before breaks and at the end of the shift. Remove contaminated clothing and protective equipment before entering eating areas.

Protection against fire and explosion:
Take precautionary measures against static discharges.

Storage

Segregate from foods and animal feeds. Segregate from strong acids. Segregate from strong bases.
Further information on storage conditions: Keep container tightly closed and dry; store in a cool place.

8. Exposure controls and personal protection

Components with occupational exposure limits

2-butoxyethanol, 111-76-2;

Personal protective equipment

Respiratory protection:
Wear respiratory protection if ventilation is inadequate. Combination filter for gases/vapours of organic compounds and solid and liquid particles (f.e. EN 14387 Type A-P2)

Hand protection:
Chemical resistant protective gloves

Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):
nitrile rubber (NBR) - 0.4 mm coating thickness
Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:
Tightly fitting safety goggles (cage goggles) (e.g. EN 166) and face shield.

Body protection:
Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures:
Wearing of closed work clothing is required additionally to the stated personal protection equipment. Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

Form:	liquid	
Colour:	clear	
Odour:	product specific	
Odour threshold:	not determined	
pH value:	> 5.5 (100 %(m))	(DIN 19268)
freezing range:	not determined	
boiling temperature:	100 - 101 °C (1,013 hPa)	(OECD Guideline 103)
Flash point:	100 - 101 °C	(ISO 2719)
Evaporation rate:	not determined	
Flammability (solid/gas):	hardly combustible	(derived from flash point)
Lower explosion limit:	For liquids not relevant for classification and labelling., The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	(DIN 51649-1)

Ignition temperature:	232 °C The product has not been tested. The statement has been derived from the properties of the individual components.	
Information on: 2-butoxyethanol		
Ignition temperature:	232 °C	(DIN EN 14522)

Thermal decomposition:	not determined	
Self ignition:	not self-igniting	
Self heating ability:	It is not a substance capable of spontaneous heating.	
Explosion hazard:	not explosive	
Fire promoting properties:	not fire-propagating	
Vapour pressure:	62.74 hPa (20 °C)	(OECD Guideline 104)
	71.71 hPa (50 °C)	(OECD Guideline 104)
	155.82 hPa (55 °C)	(OECD Guideline 104)
Density:	1.02 g/cm3 (15 °C)	(ISO 2811-3)
	1.02 g/cm3 (20 °C)	(ISO 2811-3)
	1.00 g/cm3 (50 °C)	
Relative vapour density (air):	not determined	
Solubility in water:	soluble	
Hygroscopy:	hygroscopic	
Solubility (qualitative) solvent(s):	alcohols soluble	
Partitioning coefficient n-octanol/water (log Pow):	not applicable for mixtures	
Viscosity, dynamic:	60 mPa.s (23 °C)	
Viscosity, kinematic:	approx. 59 mm2/s (23 °C)	(calculated (from dynamic viscosity))

10. Stability and Reactivity

Conditions to avoid:
Avoid open flames.

Thermal decomposition: not determined

Substances to avoid:
strong acids, strong bases, strong oxidizing agents

Corrosion to metals: No corrosive effect on metal.

Hazardous reactions:
No hazardous reactions when stored and handled according to instructions.

Hazardous decomposition products:
No hazardous decomposition products known.

Reactivity:
No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability:
The product is stable if stored and handled as prescribed/indicated.

11. Toxicological Information

Acute toxicity

Assessment of acute toxicity:
Of moderate toxicity after short-term skin contact. Of moderate toxicity after single ingestion.

Experimental/calculated data:
ATE (oral): > 300 - < 2,000 mg/kg (calculated)

ATE (by inhalation): 50 mg/l

ATE (dermal): 2,000 mg/kg

Information on: 2-butoxyethanol
Assessment of acute toxicity:
Of moderate toxicity after single ingestion. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard. Virtually nontoxic after a single skin contact.

Information on: (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Experimental/calculated data:
LD50 rat (oral): > 2,000 mg/kg (BASF-Test)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

LD50 rat (oral): > 2,000 mg/kg (BASF-Test)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: Alcohols, C13-15, branched and linear, ethoxylated
Experimental/calculated data:
LD50 rat (oral): > 300 - 2,000 mg/kg (OECD Guideline 401)
Literature data.

Information on: 2-butoxyethanol
Experimental/calculated data:
LD50 guinea pig (oral): 1,200 mg/kg (similar to OECD guideline 401)

Information on: (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Experimental/calculated data:
LD50 rat (dermal): 2,000 mg/kg (OECD Guideline 402)

Irritation

Assessment of irritating effects:
Skin contact causes irritation. May cause severe damage to the eyes.

Information on: (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Experimental/calculated data:
Skin corrosion/irritation In vitro assay: Irritant. (OECD Guideline 439)

Skin corrosion/irritation rabbit: Irritant. (OECD Guideline 404)

Information on: Alcohols, C13-15, branched and linear, ethoxylated
Experimental/calculated data:
Skin corrosion/irritation rabbit: non-irritant (OECD Guideline 404)
Literature data.

Information on: 2-butoxyethanol
Experimental/calculated data:
Skin corrosion/irritation rabbit: Irritant. (BASF-Test)

Information on: (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Experimental/calculated data:
Serious eye damage/irritation In vitro assay: no irreversible damage (BCOP)

Serious eye damage/irritation rabbit: irreversible damage (OECD Guideline 405)

Information on: Alcohols, C13-15, branched and linear, ethoxylated
Experimental/calculated data:
Serious eye damage/irritation rabbit: irreversible damage (Draize test)
Literature data.

Information on: 2-butoxyethanol
Experimental/calculated data:
Serious eye damage/irritation rabbit: Irritant. (OECD Guideline 405)

Respiratory/Skin sensitization

Assessment of sensitization:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Assessment of mutagenicity:
Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:
Based on available data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity:
Based on available data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity:
Based on the ingredients, there is no suspicion of a teratogenic effect.

Specific target organ toxicity (single exposure):

Assessment of STOT single:
Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:
Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Aspiration hazard

No aspiration hazard expected.

Other relevant toxicity information

The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

12. Ecological Information

Ecotoxicity

Assessment of aquatic toxicity:
Acutely toxic for aquatic organisms. Harmful to aquatic life with long lasting effects.

Information on: (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Toxicity to fish:
LC50 (96 h) 7.1 mg/l, Brachydanio rerio (OECD Guideline 203, Flow through.)
The details of the toxic effect relate to the nominal concentration.

Information on: Alcohols, C13-15, branched and linear, ethoxylated
Toxicity to fish:
LC50 (96 h) > 1 - 10 mg/l, Brachydanio rerio (OECD 203; ISO 7346; 84/449/EWG, C.1, static)
Literature data.

Information on: (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Aquatic invertebrates:
EC50 (48 h) 7.4 mg/l, Daphnia magna (OECD Guideline 202, part 1, static)
The details of the toxic effect relate to the nominal concentration.

Information on: Alcohols, C13-15, branched and linear, ethoxylated
Aquatic invertebrates:
EC50 (48 h) > 1 - 10 mg/l, Daphnia magna (Directive 79/831/EEC)
Literature data.

Information on: (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Aquatic plants:
No observed effect concentration (72 h) 0.95 mg/l (growth rate), Scenedesmus subspicatus (Algal growth inhibition test)
The statement of the toxic effect relates to the analytically determined concentration.

EC50 (72 h) 27.7 mg/l (growth rate), Desmodesmus subspicatus (OECD Guideline 201)
The statement of the toxic effect relates to the analytically determined concentration.

EC10 (72 h) 4.4 mg/l (growth rate), Pseudokirchneriella subcapitata (OECD Guideline 201)
The statement of the toxic effect relates to the analytically determined concentration.

Information on: Alcohols, C13-15, branched and linear, ethoxylated
Aquatic plants:
EC50 (72 h) > 1 - 10 mg/l (growth rate), Scenedesmus subspicatus (OECD Guideline 201, static)
Literature data.

Information on: (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Chronic toxicity to fish:
EC10 (28 d) 1.7 mg/l, Pimephales promelas (OECD Guideline 210, Flow through.)
The statement of the toxic effect relates to the analytically determined concentration. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)

Chronic toxicity to aquatic invertebrates:
No observed effect concentration (21 d), > 1.19 mg/l, Daphnia magna (OECD Guideline 211, other)
The statement of the toxic effect relates to the analytically determined concentration.

Information on: Alcohols, C13-15, branched and linear, ethoxylated
Chronic toxicity to aquatic invertebrates:
No observed effect concentration, > 0.1 - 1 mg/l, Daphnia magna
Literature data.

Mobility

Information on: (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Assessment transport between environmental compartments:
The substance will not evaporate into the atmosphere from the water surface.
Following exposure to soil, the product trickles away and can - dependant on degradation - be transported to deeper soil areas with larger water loads.
Study scientifically not justified.

Information on: 2-butoxyethanol
Assessment transport between environmental compartments:
The substance will not evaporate into the atmosphere from the water surface.
Adsorption to solid soil phase is not expected.

Persistence and degradability

Information on: (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)

Information on: 2-butoxyethanol
Assessment biodegradation and elimination (H2O):
Readily biodegradable (according to OECD criteria).

Bioaccumulation potential

Information on: (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Assessment bioaccumulation potential:
Significant accumulation in organisms is not to be expected.

Information on: Alcohols, C13-15, branched and linear, ethoxylated
Assessment bioaccumulation potential:
Accumulation in organisms is not to be expected.

Information on: 2-butoxyethanol
Assessment bioaccumulation potential:
Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

Additional information

Other ecotoxicological advice:

The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

13. Disposal Information

Must be disposed of or incinerated in accordance with local regulations.

Contaminated packaging:
Uncontaminated packaging can be re-used.
Packs that cannot be cleaned should be disposed of in the same manner as the contents.

14. Transportation Information

Domestic transport:

Not classified as a dangerous good under transport regulations

Sea transport
IMDG

Not classified as a dangerous good under transport regulations

Air transport
IATA/ICAO

Not classified as a dangerous good under transport regulations

Transport in bulk according to Annex II of MARPOL and the IBC Code

Regulation:	Not evaluated
Shipment approved:	Not evaluated
Pollution name:	Not evaluated
Pollution category:	Not evaluated
Ship Type:	Not evaluated

15. Regulatory Information

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013
OSHA 1994 and relevant regulations
Environmental Quality Act, 1974

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

16. Other Information

Date of Preparation / Date of Revision: 23.04.2025

Information Source and References:
This SDS is prepared using data and information saved in our internal IT-based system and supplied by our company's service providers.

Key Abbreviations:
ATE - Acute Toxicity Estimates
GHS - Globally Harmonized System
IATA / ICAO - International Air Transport Association / International Civil Aviation Organization
IBC - Intermediate Bulk Container
IMDG - International Maritime Dangerous Goods
LC - Lethal Concentration
LD - Lethal Dose
OECD - Organisation for Economic Co-operation and Development
OEL - Occupational Exposure Limit
OSHA - Occupational Safety and Health Act
STOT - Specific Target Organ Toxicity

Full text of classifications, hazard symbols and hazard statements, if mentioned in section 2 or 3:

Unst. Expl.	Unstable explosives
Expl. 1.1	Explosives division 1.1
Expl. 1.2	Explosives division 1.2
Expl. 1.3	Explosives division 1.3
Expl. 1.4	Explosives division 1.4
Expl. 1.5	Explosives division 1.5
Expl. 1.6	Explosives division 1.6
Flam. Gas 1	Flammable gases category 1
Flam. Gas 2	Flammable gases category 2
Flam. Aerosol 1	Flammable aerosols category 1
Flam. Aerosol 2	Flammable aerosols category 2
Flam. Liq. 1	Flammable liquids category 1
Flam. Liq. 2	Flammable liquids category 2
Flam. Liq. 3	Flammable liquids category 3
Flam. Sol. 1	Flammable solids category 1
Flam. Sol. 2	Flammable solids category 2
Ox. Gas 1	Oxidizing gases category 1
Ox. Liq. 1	Oxidizing liquids category 1
Ox. Liq. 2	Oxidizing liquids category 2
Ox. Liq. 3	Oxidizing liquids category 3
Ox. Sol. 1	Oxidizing solids category 1
Ox. Sol. 2	Oxidizing solids category 2
Ox. Sol. 3	Oxidizing solids category 3
Press. Gas	Gases under pressure
Self-react. A	Self-reactive chemicals type A
Self-react. B	Self-reactive chemicals type B
Self-react. CD	Self-reactive chemicals type C and D
Self-react. EF	Self-reactive chemicals type E and F
Self-react. G	Self-reactive chemicals type G
Pyr. Liq. 1	Pyrophoric liquids category 1
Pyr. Sol. 1	Pyrophoric solids category 1

Self-heat. 1	Self-heating chemicals category 1
Self-heat. 2	Self-heating chemicals category 2
Water-react. 1	Chemicals which, if in contact with water, emits flammable gases category 1
Water-react. 2	Chemicals which, if in contact with water, emits flammable gases category 2
Water-react. 3	Chemicals which, if in contact with water, emits flammable gases category 3
Org. Perox. A	Organic peroxides type A
Org. Perox. B	Organic peroxides type B
Org. Perox. CD	Organic peroxides type C and D
Org. Perox. EF	Organic peroxides type E and F
Org. Perox. G	Organic peroxides type G
Met. Corr. 1	Corrosive to metals category 1
Acute Tox. 1	Acute toxicity category 1
Acute Tox. 2	Acute toxicity category 2
Acute Tox. 3	Acute toxicity category 3
Acute Tox. 4	Acute toxicity category 4
Skin Corr. 1A	Skin corrosion or irritation category 1A
Skin Corr. 1B	Skin corrosion or irritation category 1B
Skin Corr. 1C	Skin corrosion or irritation category 1C
Skin Irrit. 2	Skin corrosion or irritation category 2
Eye Dam. 1	Serious eye damage or eye irritation category 1
Eye Irrit. 2	Serious eye damage or eye irritation category 2
Resp. Sens. 1	Respiratory sensitization category 1
Skin Sens. 1	Skin sensitization category 1
Muta. 1A	Germ cell mutagenicity category 1A
Muta. 1B	Germ cell mutagenicity category 1B
Muta. 2	Germ cell mutagenicity category 2
Carc. 1A	Carcinogenicity category 1A
Carc. 1B	Carcinogenicity category 1B
Carc. 2	Carcinogenicity category 2
Repr. 1A	Reproductive toxicity category 1A
Repr. 1B	Reproductive toxicity category 1B
Repr. 2	Reproductive toxicity category 2
Lact.	Effect on or via lactation
STOT SE 1	Specific target organ toxicity – single exposure category 1
STOT SE 2	Specific target organ toxicity – single exposure category 2
STOT SE 3	Specific target organ toxicity – single exposure category 3
STOT RE 1	Specific target organ toxicity – repeated exposure category 1
STOT RE 2	Specific target organ toxicity – repeated exposure category 2
Asp. Haz.	Aspiration hazard category 1
Aquatic Acute 1	Hazardous to the aquatic environment – acute hazard category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – chronic hazard category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – chronic hazard category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – chronic hazard category 3
Aquatic Chronic 4	Hazardous to the aquatic environment – chronic hazard category 4
Ozone	Hazardous to the ozone layer category 1

Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.