We create chemistry

Safety data sheet

BASF safety data sheet. This document has been drafted following generic rules for safety data sheets. It does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 14.02.2025 Version: 2.1
Date / Previous version: 09.12.2022 Previous version: 2.0
Product: **DisPlus 39L**

(ID no. 30735595/SDS_GEN_EU/EN)
Date of print 27.06.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DisPlus 39L

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Performance Chemicals for Oilfield Applications

For the detailed identified uses of the product see appendix of the safety data sheet.

1.3. Details of the supplier of the safety data sheet

Company:
BASF SE
67056 Ludwigshafen
GERMANY
Global Oilfield Chemicals

Telephone: +49 621 60-0
E-mail address: RegXcellenceOilfieldChemicals@basf.com

1.4. Emergency telephone number

International emergency number:
Telephone: +49 180 2273-112

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

According to Regulation (EC) No 1272/2008 [CLP]

Acute Tox. 4 (oral)	H302 Harmful if swallowed.
Acute Tox. 4 (dermal)	H312 Harmful in contact with skin.
Skin Corr./Irrit. 2	H315 Causes skin irritation.
Eye Dam./Irrit. 1	H318 Causes serious eye damage.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to Regulation (EC) No 1272/2008 [CLP]

Pictogram:

Signal Word:

Danger

Hazard Statement:

H318	Causes serious eye damage.
H315	Causes skin irritation.
H302 + H312	Harmful if swallowed or in contact with skin.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P273	Avoid release to the environment.

Precautionary Statements (Response):

P310	Immediately call a POISON CENTER or physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303 + P352	IF ON SKIN (or hair): Wash with plenty of soap and water.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.

Hazard determining component(s) for labelling: (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO), Alcohols, C13-15, branched and linear, ethoxylated, 2-butoxyethanol

2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.
The product does not contain a substance above legal limits fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.
Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Chemical nature

Preparation based on:anionic and non-ionic surfactants

Regulatory relevant ingredients

(OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)

Content (W/W): >= 25 % - < 50 %	Skin Irrit. 2
CAS Number: 68891-38-3	Eye Dam. 1
REACH registration number: 01-2119488639-16	H318, H315
	Specific concentration limit:
	Eye Irrit. 2A: 5 - 10 %
	Eye Dam. 1: > 10 %

Alcohols, C13-15, branched and linear, ethoxylated

Content (W/W): >= 25 % - < 50 %	Acute Tox. 4 (oral)
CAS Number: 157627-86-6	Eye Dam./Irrit. 1
	Aquatic Chronic 3
	H318, H302, H412

2-butoxyethanol

Content (W/W): >= 20 % - < 25 % CAS Number: 111-76-2 EC-Number: 203-905-0 REACH registration number: 01-2119475108-36 INDEX-Number: 603-014-00-0 Substance with EU occupational exposure limit	Acute Tox. 4 (oral) Skin Irrit. 2 Eye Irrit. 2 Acute Tox. 3 (Inhalation - vapour) H319, H315, H331, H302 Acute toxicity estimate: oral: 1,200 mg/kg Inhalation: 3 mg/l (vapour)

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

Immediately remove contaminated clothing.

If inhaled:
Keep patient calm, remove to fresh air, seek medical attention. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

On skin contact:
Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

On contact with eyes:
Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:
Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media:
water spray, dry powder, foam

5.2. Special hazards arising from the substance or mixture

Endangering substances: harmful vapours, carbon oxides
Advice: Generation of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

5.3. Advice for fire-fighters

Further information:
The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

SECTION 6: Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

6.3. Methods and material for containment and cleaning up

For large amounts: Pump off product.
For residues: Pick up with suitable absorbent material. Dispose of absorbed material in accordance with regulations.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Wear chemically resistant gloves in combination with intensive management supervision control. Use suitable eye protection. Local exhaust ventilation Wear suitable respiratory protection.

No eating, drinking, smoking or tobacco use at the place of work. Hands and/or face should be washed before breaks and at the end of the shift. Remove contaminated clothing and protective equipment before entering eating areas.

7.2. Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds. Segregate from strong acids. Segregate from strong bases.

Suitable materials for containers: High density polyethylene (HDPE)
Further information on storage conditions: Keep container tightly closed and dry; store in a cool place.

7.3. Specific end use(s)

See exposure scenario(s) in the attachment to this safety data sheet.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

111-76-2: 2-butoxyethanol
144-55-8: Sodium hydrogencarbonate

PNEC

Data refer to the lead substance

Components with PNEC

68891-38-3: (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
freshwater: 0.129 mg/l
marine water: 0.0129 mg/l
intermittent release: 0.71 mg/l
STP: 10000 mg/l
sediment (freshwater): 4.835 mg/kg
sediment (marine water): 0.4835 mg/kg
soil: 7.5 mg/kg
oral (secondary poisoning):
No PNEC oral derived, as accumulation in organisms is not to be expected.

DNEL

Data refer to the lead substance

Components with DNEL

111-76-2: 2-butoxyethanol
worker: Long-term exposure- systemic effects, Inhalation: 98 mg/m3, 20 ppm
worker: Short-term exposure - systemic effects, Inhalation: 1091 mg/m3
worker: Short-term exposure - local effects, Inhalation: 246 mg/m3
consumer: Long-term exposure- systemic effects, oral: 6.3 mg/kg
consumer: Short-term exposure - systemic effects, oral: 26.7 mg/kg
consumer: Long-term exposure- systemic effects, Inhalation: 59 mg/m3

consumer: Short-term exposure - systemic effects, Inhalation: 426 mg/m3
consumer: Short-term exposure - local effects, Inhalation: 147 mg/m3

8.2. Exposure controls

Personal protective equipment

Respiratory protection:
Wear respiratory protection if ventilation is inadequate. Combination filter for gases/vapours of organic compounds and solid and liquid particles (f.e. EN 14387 Type A-P2)

Eye protection:
Tightly fitting safety goggles (cage goggles) (e.g. EN 166) and face shield.

Body protection:
Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls

Do not discharge product into the environment without control.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

State of matter:	liquid	
Form:	liquid	
Colour:	clear	
Odour:	product specific	
Odour threshold:	not determined	
freezing range:	not determined	
boiling temperature:	100 - 101 °C (1,013 hPa)	(OECD Guideline 103)
Flammability:	hardly combustible	(derived from flash point)
Lower explosion limit:	For liquids not relevant for classification and labelling., The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:		(DIN 51649-1)

	For liquids not relevant for classification and labelling.	
Flash point:	100 - 101 °C	(ISO 2719)
Auto-ignition temperature:	232 °C	
	The product has not been tested. The statement has been derived from the properties of the individual components.	
Information on: 2-butoxyethanol		
Auto-ignition temperature:	*232 °C*	*(DIN EN 14522)*

Thermal decomposition:	not determined	
pH value:	> 5.5 (100 %(m))	(DIN 19268)
Viscosity, kinematic:	approx. 59 mm2/s (23 °C)	(calculated (from dynamic viscosity))
Viscosity, dynamic:	60 mPa.s (23 °C)	
Solubility in water:	soluble	
Solubility (qualitative) solvent(s):	alcohols soluble	
Partitioning coefficient n-octanol/water (log Kow):	not applicable for mixtures	
Vapour pressure:	62.74 hPa (20 °C)	(OECD Guideline 104)
	71.71 hPa (50 °C)	(OECD Guideline 104)
	155.82 hPa (55 °C)	(OECD Guideline 104)
Density:	1.02 g/cm3 (15 °C)	(ISO 2811-3)
	1.02 g/cm3 (20 °C)	(ISO 2811-3)
	1.00 g/cm3 (50 °C)	
Relative vapour density (air):	not determined	

Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular form. -

9.2. Other information

Information with regard to physical hazard classes

Explosives

Explosion hazard: not explosive

Oxidizing properties

Fire promoting properties: not fire-propagating

Self-heating substances and mixtures

Self heating ability: It is not a substance capable of spontaneous heating.

Corrosion to metals

No corrosive effect on metal.

Other safety characteristics

Hygroscopy: hygroscopic
Evaporation rate:
not determined

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals: No corrosive effect on metal.

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

10.3. Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

10.4. Conditions to avoid

Avoid open flames.

10.5. Incompatible materials

Substances to avoid:
strong acids, strong bases, strong oxidizing agents

10.6. Hazardous decomposition products

Hazardous decomposition products:
No hazardous decomposition products known.

SECTION 11: Toxicological Information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Assessment of acute toxicity:

Of moderate toxicity after short-term skin contact. Of moderate toxicity after single ingestion.

Experimental/calculated data:

ATE (oral): > 300 - < 2,000 mg/kg (calculated)
ATE (by inhalation): 50 mg/l
ATE (dermal): 2,000 mg/kg

Information on: 2-butoxyethanol
Assessment of acute toxicity:
Of moderate toxicity after single ingestion. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard. Virtually nontoxic after a single skin contact.

Information on: (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)

Experimental/calculated data:
LD50 rat (oral): > 2,000 mg/kg (BASF-Test)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

LD50 rat (oral): > 2,000 mg/kg (BASF-Test)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: Alcohols, C13-15, branched and linear, ethoxylated

Experimental/calculated data:
LD50 rat (oral): > 300 - 2,000 mg/kg (OECD Guideline 401)
Literature data.

Information on: 2-butoxyethanol

Experimental/calculated data:
LD50 guinea pig (oral): 1,200 mg/kg (similar to OECD guideline 401)

ATE (oral): 1,200 mg/kg

Information on: (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Experimental/calculated data:
LD50 rat (dermal): 2,000 mg/kg (OECD Guideline 402)

Irritation

Assessment of irritating effects:

Skin contact causes irritation. May cause severe damage to the eyes.

Information on: (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Experimental/calculated data:
Skin corrosion/irritation
In vitro assay: Irritant. (OECD Guideline 439)

Skin corrosion/irritation
rabbit: Irritant. (OECD Guideline 404)

Information on: Alcohols, C13-15, branched and linear, ethoxylated
Experimental/calculated data:
Skin corrosion/irritation
rabbit: non-irritant (OECD Guideline 404)
Literature data.

Information on: 2-butoxyethanol
Experimental/calculated data:
Skin corrosion/irritation
rabbit: Irritant. (BASF-Test)

Information on: (OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Experimental/calculated data:
Serious eye damage/irritation
In vitro assay: no irreversible damage (BCOP)

Serious eye damage/irritation
rabbit: irreversible damage (OECD Guideline 405)

Information on: Alcohols, C13-15, branched and linear, ethoxylated
Experimental/calculated data:
Serious eye damage/irritation
rabbit: irreversible damage (Draize test)
Literature data.

Information on: 2-butoxyethanol
Experimental/calculated data:
Serious eye damage/irritation
rabbit: Irritant. (OECD Guideline 405)

Respiratory/Skin sensitization

Assessment of sensitization:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Assessment of mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:
Based on available data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity:
Based on available data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity:

Based on the ingredients, there is no suspicion of a teratogenic effect.

Specific target organ toxicity (single exposure)

Assessment of STOT single:
Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Aspiration hazard

No aspiration hazard expected.

Interactive effects

No data available.

11.2. Information on other hazards

Endocrine disrupting properties

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting

properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

Other information

Other relevant toxicity information

The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:
Acutely toxic for aquatic organisms. Harmful to aquatic life with long lasting effects.

Information on:(OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Toxicity to fish:
LC50 (96 h) 7.1 mg/l, Brachydanio rerio (OECD Guideline 203, Flow through.)
The details of the toxic effect relate to the nominal concentration.

Information on:Alcohols, C13-15, branched and linear, ethoxylated
Toxicity to fish:
LC50 (96 h) > 1 - 10 mg/l, Brachydanio rerio (OECD 203; ISO 7346; 84/449/EWG, C.1, static)
Literature data.

Information on:(OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Aquatic invertebrates:
EC50 (48 h) 7.4 mg/l, Daphnia magna (OECD Guideline 202, part 1, static)
The details of the toxic effect relate to the nominal concentration.

Information on:Alcohols, C13-15, branched and linear, ethoxylated
Aquatic invertebrates:
EC50 (48 h) > 1 - 10 mg/l, Daphnia magna (Directive 79/831/EEC)
Literature data.

Information on:(OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Aquatic plants:
No observed effect concentration (72 h) 0.95 mg/l (growth rate), Scenedesmus subspicatus (Algal growth inhibition test)
The statement of the toxic effect relates to the analytically determined concentration.

EC50 (72 h) 27.7 mg/l (growth rate), Desmodesmus subspicatus (OECD Guideline 201)

The statement of the toxic effect relates to the analytically determined concentration.

EC10 (72 h) 4.4 mg/l (growth rate), Pseudokirchneriella subcapitata (OECD Guideline 201)
The statement of the toxic effect relates to the analytically determined concentration.

Information on:Alcohols, C13-15, branched and linear, ethoxylated
Aquatic plants:
EC50 (72 h) > 1 - 10 mg/l (growth rate), Scenedesmus subspicatus (OECD Guideline 201, static)
Literature data.

Information on:(OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Chronic toxicity to fish:
EC10 (28 d) 1.7 mg/l, Pimephales promelas (OECD Guideline 210, Flow through.)
The statement of the toxic effect relates to the analytically determined concentration. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on:(OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Chronic toxicity to aquatic invertebrates:
No observed effect concentration (21 d) > 1.19 mg/l, Daphnia magna (OECD Guideline 211, other)
The statement of the toxic effect relates to the analytically determined concentration.

Information on:Alcohols, C13-15, branched and linear, ethoxylated
Chronic toxicity to aquatic invertebrates:
No observed effect concentration > 0.1 - 1 mg/l, Daphnia magna
Literature data.

12.2. Persistence and degradability

Information on:(OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Assessment biodegradation and elimination (H2O):
Readily biodegradable (according to OECD criteria).

Information on:2-butoxyethanol
Assessment biodegradation and elimination (H2O):
Readily biodegradable (according to OECD criteria).

12.3. Bioaccumulative potential

Information on:(OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Assessment bioaccumulation potential:
Significant accumulation in organisms is not to be expected.

Information on:Alcohols, C13-15, branched and linear, ethoxylated
Assessment bioaccumulation potential:
Accumulation in organisms is not to be expected.

Information on:2-butoxyethanol
Assessment bioaccumulation potential:
Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

12.4. Mobility in soil

Information on:(OLIGOMER) Alcohols, C12-14, ethoxylated, sulfates, sodium salts (> 1 < 2.5 mol EO)
Assessment transport between environmental compartments:
Volatility: The substance will not evaporate into the atmosphere from the water surface.
Adsorption in soil: Following exposure to soil, the product trickles away and can - dependant on degradation - be transported to deeper soil areas with larger water loads.Study scientifically not justified.

Information on:2-butoxyethanol
Assessment transport between environmental compartments:
Volatility: The substance will not evaporate into the atmosphere from the water surface.
Adsorption in soil: Adsorption to solid soil phase is not expected.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

12.6. Endocrine disrupting properties

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

Additional information

Other ecotoxicological advice:
The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Must be disposed of or incinerated in accordance with local regulations.

Contaminated packaging:
Uncontaminated packaging can be re-used.Packs that cannot be cleaned should be disposed of in the same manner as the contents.

SECTION 14: Transport Information

Land transport

ADR

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

RID

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

Inland waterway transport
ADN

Not classified as a dangerous good under transport regulations

UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	None known

Transport in inland waterway vessel
Not evaluated

Sea transport

IMDG

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

Air transport

IATA/ICAO

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

14.1. UN number or ID number
See corresponding entries for “UN number or ID number” for the respective regulations in the tables above.

14.2. UN proper shipping name
See corresponding entries for “UN proper shipping name” for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for “Transport hazard class(es)” for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for “Packing group” for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for “Environmental hazards” for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for “Special precautions for user” for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 3, 75, 54, 55

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):
Listed in above regulation: no
Classification applies for standard conditions of temperature and pressure.

15.2. Chemical Safety Assessment

Assessment of safe use has been performed for the mixture. Results and measures for human health are documented in sections 7 and 8, those for environment are attached as an annex of the safety data sheet.

SECTION 16: Other Information

Assessment of the hazard classes according to UN GHS criteria (most recent version)

Acute Tox. 4 (oral)
Acute Tox. 4 (dermal)
Acute Tox. 5 (Inhalation - vapour)
Eye Dam./Irrit. 1

Skin Corr./Irrit. 2
Aquatic Acute 2
Aquatic Chronic 3

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Acute Tox.	Acute toxicity
Skin Corr./Irrit.	Skin corrosion/irritation
Eye Dam./Irrit.	Serious eye damage/eye irritation
Aquatic Chronic	Hazardous to the aquatic environment - chronic
Skin Irrit.	Skin irritation
Eye Dam.	Serious eye damage
Eye Irrit.	Eye irritation
H318	Causes serious eye damage.
H315	Causes skin irritation.
H302 + H312	Harmful if swallowed or in contact with skin.
H412	Harmful to aquatic life with long lasting effects.
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.

Abbreviations
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Annex: Exposure Scenarios

Index

1. Formulation of mixtures (industrial, professional, consumer)
SU0-1; ERC2

2. End use (industrial, professional)
SU5, SU12, SU13, SU15; ERC4

3. End use (industrial, professional)
SU0-1, SU8, SU9; ERC6a

4. End use (industrial, professional)
SU5, SU12, SU13, SU15; ERC6b

5. End use (industrial, professional)
SU5, SU11, SU12, SU13, SU15; ERC8a

6. End use (industrial, professional)
SU5, SU11, SU12, SU13, SU15; ERC8b

7. End use (industrial, professional)
SU5, SU11, SU12, SU13, SU15; ERC8d

8. End use (industrial, professional)
SU5, SU11, SU12, SU13, SU15; ERC8e

****

1. Short title of exposure scenario

Formulation of mixtures (industrial, professional, consumer)
SU0-1; ERC2
A consolidation approach has been used to limit the number of exposure scenarios. Parameters provided in the scenario cover all mentioned spERCs.

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	AISE SPERC 2.1.a.v2: AISE SPERC 2.1.a.v2
Operational conditions	
Minimum emission days per year	250
Emission factor air	0 %
Emission factor water	0.01 %

Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Wastewater treatment measures considered suitable are, e.g.	Precipitation, Coagulation, Must be eliminated from water by chemical flocculation.
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	99,810 kg/d
Data refer to the product	

Contributing exposure scenario	
Use descriptors covered	CEPE SPERC 2.1a.v1: CEPE SPERC 2.1a.v1
Operational conditions	
Minimum emission days per year	225
Emission factor air	0.6 %
Emission factor water	0 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	273,665

	kg/d
Data refer to the product	

Contributing exposure scenario	
Use descriptors covered	COLIPA SPERC 2.1.a.v2
Operational conditions	
Minimum emission days per year	250
Emission factor air	0 %
Emission factor water	0.1 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Wastewater treatment measures considered suitable are, e.g.	Sedimentation, Precipitation, pH adjustment
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	78,947 kg/d
Data refer to the product	

Contributing exposure scenario	
Use descriptors covered	EFCC SPERC 2.1a.v1: EFCC SPERC 2.1a.v1 ; covers also: EFCC SPERC 2.1b.v1: EFCC SPERC 2.1b.v1
Operational conditions	
Minimum emission days per year	220
Emission factor air	1 %
Emission factor water	0.5 %
Emission factor soil	0 %

Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	43,802 kg/d
Data refer to the product	

Contributing exposure scenario	
Use descriptors covered	ERC2: Formulation into mixture
Operational conditions	
Minimum emission days per year	100
Emission factor air	0.25 %
Emission factor water	0.3 %
Emission factor soil	0.01 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	52,076 kg/d
Data refer to the product	

Contributing exposure scenario

Use descriptors covered	ESVOC SpERC 2.2.v1: ESVOC SpERC 2.2.v1 ; covers also: ESVOC SpERC 1.1b.v1: ESVOC SpERC 1.1b.v1
Operational conditions	
Minimum emission days per year	300
Emission factor air	0.25 %
Emission factor water	0.5 %
Emission factor soil	0.01 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Air treatment measures considered suitable are, e.g.	Wet scrubber - for dusts, Filtration, Waste gas treatment by thermal oxidation, Adsorption
Wastewater treatment measures considered suitable are, e.g.	Acclimated biological treatment, Distillation
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	157,188 kg/d
Data refer to the product	

Contributing exposure scenario	
Use descriptors covered	FEICA SPERC 2.1a.v2
Operational conditions	
Minimum emission days per year	220
Emission factor air	1 %
Emission factor water	0.005 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d

Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	179,837 kg/d
Data refer to the product	

*** * * * * * * * * * * * * * * * ****

2. Short title of exposure scenario

End use (industrial, professional)
SU5, SU12, SU13, SU15; ERC4
A consolidation approach has been used to limit the number of exposure scenarios. Parameters provided in the scenario cover all mentioned spERCs.

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	AISE SPERC 4.1.v2: AISE SPERC 4.1.v2 ; covers also: AISE SPERC 5.1b.v2: AISE SPERC 5.1b.v2 AISE SPERC 5.1a.v2: AISE SPERC 5.1a.v2
Operational conditions	
Minimum emission days per year	220
Emission factor air	0 %
Emission factor water	100 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	

Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	161 kg/d
Data refer to the product	

Contributing exposure scenario	
Use descriptors covered	CEPE SPERC 4.1a.v1: CEPE SPERC 4.1a.v1
Operational conditions	
Minimum emission days per year	225
Emission factor air	0.8 %
Emission factor water	2 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Air treatment measures considered suitable are, e.g.	Waste gas treatment by thermal oxidation
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	4,520 kg/d
Data refer to the product	

Contributing exposure scenario	
Use descriptors covered	EFCC SPERC 4.1a.v1: EFCC SPERC 4.1a.v1
Operational conditions	
Minimum emission days per year	220

Emission factor air	98.5 %
Emission factor water	0 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	12,315 kg/d
Data refer to the product	

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 4.20.v1: ESVOC SpERC 4.20.v1
Operational conditions	
Minimum emission days per year	300
Emission factor air	0.2 %
Emission factor water	1 %
Emission factor soil	0.01 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.

Maximum amount of safe use	12,797 kg/d
Data refer to the product	

Contributing exposure scenario	
Use descriptors covered	FEICA SPERC 4.2a.v2
Operational conditions	
Minimum emission days per year	220
Emission factor air	98.5 %
Emission factor water	0 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	3,694 kg/d
Data refer to the product	

Contributing exposure scenario	
Use descriptors covered	TEGEWA SPERC 4.1.v1: TEGEWA SPERC 4.1.v1
Operational conditions	
Minimum emission days per year	220
Emission factor air	0 %
Emission factor water	100 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d

Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	161 kg/d
Data refer to the product	

*** * * * * * * * * * * * * * * * ****

3. Short title of exposure scenario

End use (industrial, professional)
SU0-1, SU8, SU9; ERC6a

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC6a: Use of intermediate
Operational conditions	
Minimum emission days per year	300
Emission factor air	0.025 %
Emission factor water	0.05 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine

	sediment.
Maximum amount of safe use	4,080 kg/d
Data refer to the product	

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 6.1a.v1: ESVOC SpERC 6.1a.v1
Operational conditions	
Minimum emission days per year	300
Emission factor air	2 ppm
Emission factor water	1 %
Emission factor soil	0.1 %
	Values provided in per mill
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Air treatment measures considered suitable are, e.g.	Wet scrubber - for dusts, Adsorption
Wastewater treatment measures considered suitable are, e.g.	Acclimated biological treatment
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	24,039 kg/d
Data refer to the product	

****

4. Short title of exposure scenario

End use (industrial, professional)
SU5, SU12, SU13, SU15; ERC6b

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	TEGEWA SPERC 6b.1.v1: TEGEWA SPERC 6b.1.v1
Operational conditions	
Minimum emission days per year	220
Emission factor air	0 %
Emission factor water	2 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	10,574 kg/d
Data refer to the product	

****

5. Short title of exposure scenario

End use (industrial, professional)
SU5, SU11, SU12, SU13, SU15; ERC8a

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	AISE SPERC 8a.1.b.v2: AISE SPERC 8a.1.b.v2 ; covers also: AISE SPERC 8a.1.a.v2: AISE SPERC 8a.1.a.v2 AISE SPERC 8a.1.c.v2: AISE SPERC 8a.1.c.v2
Operational conditions	
Minimum emission days per year	365
Emission factor air	0 %

Emission factor water	100 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	216 kg/d
Data refer to the product	

Contributing exposure scenario	
Use descriptors covered	CEPE SPERC 8a.2a.v1: CEPE SPERC 8a.2a.v1 ; covers also: CEPE SPERC 8a.1a.v1: CEPE SPERC 8a.1a.v1
Operational conditions	
Minimum emission days per year	225
Emission factor air	99 %
Emission factor water	1 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Wastewater treatment measures considered suitable are, e.g.	STP
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine

	sediment.
Maximum amount of safe use	153 kg/d
Data refer to the product	

Contributing exposure scenario	
Use descriptors covered	ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)
Operational conditions	
Minimum emission days per year	365
Emission factor air	100 %
Emission factor water	100 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	113 kg/d
Data refer to the product	

Contributing exposure scenario	
Use descriptors covered	COLIPA SPERC 8a.1.a.v2
Operational conditions	
Minimum emission days per year	365
Emission factor air	0 %
Emission factor water	100 %
Emission factor soil	0 %

Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	6.5 kg/d
Data refer to the product	

Contributing exposure scenario	
Use descriptors covered	EFCC SPERC 8A.1a.v1: EFCC SPERC 8A.1a.v1
Operational conditions	
Minimum emission days per year	365
Emission factor air	98 %
Emission factor water	1 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	67 kg/d
Data refer to the product	

****

6. Short title of exposure scenario

End use (industrial, professional)
SU5, SU11, SU12, SU13, SU15; ERC8b

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC8b: Widespread use of reactive processing aid (no inclusion into or onto article, indoor)
Operational conditions	
Minimum emission days per year	365
Emission factor air	0.1 %
Emission factor water	2 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	167 kg/d
Data refer to the product	

Contributing exposure scenario	
Use descriptors covered	AISE SPERC 8a.1.a.v2: AISE SPERC 8a.1.a.v2
Operational conditions	
Minimum emission days per year	365
Emission factor air	0 %
Emission factor water	100 %

Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	9.9 kg/d
Data refer to the product	

****

7. Short title of exposure scenario

End use (industrial, professional)
SU5, SU11, SU12, SU13, SU15; ERC8d

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	AISE SPERC 8a.1.a.v2: AISE SPERC 8a.1.a.v2
Operational conditions	
Minimum emission days per year	365
Emission factor air	0 %
Emission factor water	100 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP

Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	19 kg/d
Data refer to the product	

Contributing exposure scenario	
Use descriptors covered	ERC8d: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)
Operational conditions	
Minimum emission days per year	365
Emission factor air	100 %
Emission factor water	100 %
Emission factor soil	20 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	97 kg/d
Data refer to the product	

Contributing exposure scenario	
Use descriptors covered	ECPA SPERC 8d.2.v2
Operational conditions	
Minimum emission days per year	365
Emission factor air	100 %

Emission factor water	0 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	no STP
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	9.2 kg/d
Data refer to the product	

Contributing exposure scenario	
Use descriptors covered	ECPA SPERC 8d.1.v1: ECPA SPERC 8d.1.v1
Operational conditions	
Minimum emission days per year	365
Emission factor air	0 %
Emission factor water	0 %
Emission factor soil	100 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	no STP
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	9.2 kg/d
Data refer to the product	

Contributing exposure scenario	
Use descriptors covered	ECPA SPERC 8d.2.v2
Operational conditions	
Minimum emission days per year	365
Emission factor air	100 %
Emission factor water	0 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	no STP
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	9.2 kg/d
Data refer to the product	

Contributing exposure scenario	
Use descriptors covered	ECPA SPERC 8d.1.v1: ECPA SPERC 8d.1.v1
Operational conditions	
Minimum emission days per year	365
Emission factor air	0 %
Emission factor water	0 %
Emission factor soil	100 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	

Type of STP	no STP
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	9.2 kg/d
Data refer to the product	

Contributing exposure scenario	
Use descriptors covered	EFCC SPERC 8D.1a.v1: EFCC SPERC 8D.1a.v1
Operational conditions	
Minimum emission days per year	365
Emission factor air	98 %
Emission factor water	1 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	101 kg/d
Data refer to the product	

****

8. Short title of exposure scenario

End use (industrial, professional)
SU5, SU11, SU12, SU13, SU15; ERC8e

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC8e: Widespread use of reactive processing aid (no inclusion into or onto article, outdoor)
Operational conditions	
Minimum emission days per year	365
Emission factor air	0.1 %
Emission factor water	2 %
Emission factor soil	1 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
	Risk from environmental exposure is driven by marine sediment.
Maximum amount of safe use	67 kg/d
Data refer to the product	

* * * * * * * * * * * * * * * *