We create chemistry

Safety data sheet

1. Substance/preparation and manufacturer/supplier identification

Product name:
Xylol-Mix

Use: Chemical, Intermediate for the chemical industry, chemical for the petroleum industry, Chemical used in synthesis and/or formulation of industrial products

Recommended use: Chemical

Manufacturer/supplier:
BASF South East Asia Pte Ltd.
128 Beach Road #18-01
Guoco Midtown, 189773, Singapore
Telephone: +65 8322 4420
Telefax number: +65 6 334-0330
E-mail address: benny.zou@basf.com

Emergency information:
Singapore Emergency Toll-Free Number:
Telephone: 1800-723-1361
International emergency number:
Telephone: +49 180 2273-112

2. Hazard identification

Classification of the substance and mixture:
Aspiration hazard: Cat.1
Flammable liquids: Cat.3
Acute toxicity: Cat.4 (Inhalation - vapour)
Acute toxicity: Cat.5 (oral)
Skin irritation: Cat.2
Eye irritation: Cat.2A
Germ cell mutagenicity: Cat.1B

Carcinogenicity: Cat.1A
Reproductive toxicity: Cat.2 (fertility)
Reproductive toxicity: Cat.2 (unborn child)
Specific target organ toxicity — single exposure: Cat.3 (May cause drowsiness and dizziness.)
Specific target organ toxicity — single exposure: Cat.3 (irritating to respiratory system)
Specific target organ toxicity — repeated exposure (Auditory organ, Central nervous system, Liver, Kidney): Cat.2
Hazardous to the aquatic environment - acute: Cat.2
Hazardous to the aquatic environment - chronic: Cat.2

Label elements and precautionary statement:

Pictogram:

Signal Word:
Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H303	May be harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H335	May cause respiratory irritation.
H350	May cause cancer.
H340	May cause genetic defects.
H361	Suspected of damaging fertility. Suspected of damaging the unborn child.
H373	May cause damage to organs (Auditory organ, Central nervous system, Liver, Kidney) through prolonged or repeated exposure.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P271	Use only outdoors or in a well-ventilated area.
P201	Obtain special instructions before use.
P273	Avoid release to the environment.
P280	Wear eye protection.
P260	Do not breathe dust/gas/mist/vapours.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P202	Do not handle until all safety precautions have been read and understood.
P243	Take action to prevent static discharges.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P264	Wash contaminated body parts thoroughly after handling.
P242	Use non-sparking tools.
P240	Ground and bond container and receiving equipment.

Precautionary Statements (Response):

P312	Call a POISON CENTER or physician if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308 + P313	IF exposed or concerned: Get medical attention.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or physician.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P332 + P313	If skin irritation occurs: Get medical attention.
P391	Collect spillage.
P331	Do NOT induce vomiting.
P337 + P313	If eye irritation persists: Get medical attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use water spray, dry powder, foam or carbon dioxide for extinction.

Precautionary Statements (Storage):

P403 + P235	Store in a well-ventilated place. Keep cool.
P233	Keep container tightly closed.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.

Other hazards which do not result in classification:
If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 20 - 47 %, dermal The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 19 - 39 %, oral The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 19 - 39 %, Inhalation - vapour May form explosive peroxides.

3. Composition/information on ingredients

Chemical nature

Substance nature: Substance

Aromatic hydrocarbons, C7-8, ethylene-manuf.-by-product (Content (W/W): 100 %)
CAS Number: 90989-43-8

Hazardous ingredients

ethylbenzene

Content (W/W): >= 10 % - <= 40 % CAS Number: 100-41-4	Asp. Tox.: Cat. 1 Flam. Liq.: Cat. 2 Acute Tox.: Cat. 4 (Inhalation - vapour) Acute Tox.: Cat. 5 (oral) STOT RE (Auditory organ): Cat. 2 Aquatic Acute: Cat. 2 Aquatic Chronic: Cat. 3

xylene

Content (W/W): >= 10 % - <= 30 % CAS Number: 1330-20-7	Asp. Tox.: Cat. 1 Flam. Liq.: Cat. 3 Acute Tox.: Cat. 5 (Inhalation - vapour) Acute Tox.: Cat. 5 (oral) Skin Irrit.: Cat. 2 Eye Irrit.: Cat. 2B STOT SE: Cat. 3 (irr. to respiratory syst.) Aquatic Chronic: Cat. 3 STOT RE (Central nervous system, Liver, Kidney): Cat. 2 Aquatic Acute: Cat. 2

toluene

Content (W/W): >= 0.01 % - <= 25 % CAS Number: 108-88-3	Asp. Tox.: Cat. 1 Flam. Liq.: Cat. 2 Skin Corr./Irrit.: Cat. 2 Repr.: Cat. 2 (unborn child) STOT SE: Cat. 3 (drowsiness and dizziness) STOT RE (Central nervous system): Cat. 2 Aquatic Acute: Cat. 2 Aquatic Chronic: Cat. 3

ethyltoluene

Content (W/W): >= 4 % - <= 12 % CAS Number: 25550-14-5	Flam. Liq.: Cat. 3 Acute Tox.: Cat. 5 (oral) Skin Corr./Irrit.: Cat. 3 Eye Dam./Irrit.: Cat. 2A Repr.: Cat. 2 (fertility) Aquatic Acute: Cat. 2 Aquatic Chronic: Cat. 2

propylbenzene

Content (W/W): >= 1 % - <= 6 % CAS Number: 103-65-1	Asp. Tox.: Cat. 1 Flam. Liq.: Cat. 3 STOT SE: Cat. 3 (irr. to respiratory syst.) Aquatic Acute: Cat. 2 Aquatic Chronic: Cat. 2

Naphthalene, 1,2,3,4-tetrahydro-

Content (W/W): >= 0.1 % - <= 4 % CAS Number: 119-64-2	Asp. Tox.: Cat. 1 Flam. Liq.: Cat. 4 Acute Tox.: Cat. 5 (oral) Skin Corr./Irrit.: Cat. 2 Eye Dam./Irrit.: Cat. 2A Carc.: Cat. 2 Aquatic Acute: Cat. 2 Aquatic Chronic: Cat. 2

Benzene, trimethyl-

Content (W/W): >= 0.5 % - <= 4 % CAS Number: 25551-13-7	Asp. Tox.: Cat. 1 Flam. Liq.: Cat. 3 Acute Tox.: Cat. 4 (Inhalation - vapour) Skin Corr./Irrit.: Cat. 2 Eye Dam./Irrit.: Cat. 2B STOT SE: Cat. 3 (irr. to respiratory syst.) Aquatic Acute: Cat. 2 Aquatic Chronic: Cat. 2

naphthalene

Content (W/W): >= 0.1 % - <= 2 % CAS Number: 91-20-3	Flam. Sol.: Cat. 2 Acute Tox.: Cat. 4 (oral) Carc.: Cat. 2 Aquatic Acute: Cat. 1 Aquatic Chronic: Cat. 1 M-factor acute: 1 M-factor chronic: 1

cumene

Content (W/W): >= 0.5 % - <= 2 % CAS Number: 98-82-8	Asp. Tox.: Cat. 1 Flam. Liq.: Cat. 3 Acute Tox.: Cat. 5 (oral) Carc.: Cat. 2 STOT SE: Cat. 3 (irr. to respiratory syst.) Aquatic Acute: Cat. 2 Aquatic Chronic: Cat. 2

4,7-Methano-1H-indene, 3a,4,7,7a-tetrahydrodimethyl-

Content (W/W): >= 0.1 % - <= 1.5 % CAS Number: 26472-00-4	Asp. Tox.: Cat. 1 Flam. Liq.: Cat. 3 Aquatic Acute: Cat. 1 Aquatic Chronic: Cat. 1 M-factor acute: 1 M-factor chronic: 1

octane

Content (W/W): >= 0.01 % - <= 1 % CAS Number: 111-65-9	Asp. Tox.: Cat. 1 Flam. Liq.: Cat. 2 Skin Corr./Irrit.: Cat. 2 STOT SE: Cat. 3 (drowsiness and dizziness) Aquatic Acute: Cat. 1 Aquatic Chronic: Cat. 1 M-factor acute: 1 M-factor chronic: 1

Benzene, 1,3-diethyl-

Content (W/W): >= 0.1 % - <= 1 % CAS Number: 141-93-5	Asp. Tox.: Cat. 1 Flam. Liq.: Cat. 3 Acute Tox.: Cat. 5 (oral) Skin Corr./Irrit.: Cat. 2 Eye Dam./Irrit.: Cat. 2A STOT SE: Cat. 3 (irr. to respiratory syst.) Aquatic Acute: Cat. 2 Aquatic Chronic: Cat. 2

benzene

Content (W/W): >= 0.003 % - <= 0.6 % CAS Number: 71-43-2	Asp. Tox.: Cat. 1 Flam. Liq.: Cat. 2 Skin Irrit.: Cat. 2 Eye Irrit.: Cat. 2A Muta.: Cat. 1B Carc.: Cat. 1A Aquatic Chronic: Cat. 3 STOT RE (Blood): Cat. 1 Aquatic Acute: Cat. 2

Benzene, 1,4-diethyl-

Content (W/W): >= 0.1 % - <= 0.5 %	Asp. Tox.: Cat. 1
CAS Number: 105-05-5	Flam. Liq.: Cat. 3
	Skin Corr./Irrit.: Cat. 2
	Eye Dam./Irrit.: Cat. 1
	Aquatic Acute: Cat. 2
	Aquatic Chronic: Cat. 2

Benzene, (2-methylpropyl)-

Content (W/W): >= 0.1 % - <= 0.5 %	Flam. Liq.: Cat. 3
CAS Number: 538-93-2	Skin Corr./Irrit.: Cat. 3
	Aquatic Acute: Cat. 1
	Aquatic Chronic: Cat. 1
	M-factor acute: 1
	M-factor chronic: 1

Benzene, butyl-

Content (W/W): >= 0.1 % - <= 0.1 %	Asp. Tox.: Cat. 1
CAS Number: 104-51-8	Flam. Liq.: Cat. 3
	Aquatic Acute: Cat. 1
	Aquatic Chronic: Cat. 1
	M-factor acute: 1
	M-factor chronic: 1

4. First-Aid Measures

General advice:
First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:
Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:
Immediately wash thoroughly with soap and water, seek medical attention.

On contact with eyes:
Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:
Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Note to physician:
Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.
Hazards: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. (Further) symptoms and / or effects are not known so far

When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.
Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote. The presence of benzene in the body can be detected by determining the amount of this substance in the blood and/or urine.

5. Fire-Fighting Measures

Suitable extinguishing media:
dry powder, water spray, carbon dioxide, foam

Unsuitable extinguishing media for safety reasons:
water jet

Additional information:
Use extinguishing measures to suit surroundings.

Specific hazards:
Flammable liquid Cool endangered containers with water-spray. See SDS section 7 - Handling and storage.

Special protective equipment:
Wear a self-contained breathing apparatus. Special protective equipment for firefighters

Further information:
Evacuate area of all unnecessary personnel. Fight fire from maximum distance.

Further information:
Extend fire extinguishing measures to the surroundings. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental Release Measures

Personal precautions:
Handle in accordance with good industrial hygiene and safety practice.

Avoid all sources of ignition: heat, sparks, open flame.Use antistatic tools.Avoid contact with the skin, eyes and clothing.

Take off immediately all contaminated clothing.

Environmental precautions:
Discharge into the environment must be avoided.

Methods for cleaning up or taking up:
Pick up with suitable appliance and dispose of. Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations.

Additional information: High risk of slipping due to leakage/spillage of product.

Release of substance/product can cause fire or explosion. Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

7. Handling and Storage

Handling

Handle in accordance with good industrial hygiene and safety practice. Avoid all direct contact with the substance/product. Ensure thorough ventilation of stores and work areas. Change clothes immediately after contamination. Refill and handle product only in closed system.

Protection against fire and explosion:
Avoid all sources of ignition: heat, sparks, open flame. Ground all transfer equipment properly to prevent electrostatic discharge.

Storage

No applicable information available.
Further information on storage conditions: Keep container tightly closed in a cool, well-ventilated place. Protect from direct sunlight. Protect against heat.

8. Exposure controls and personal protection

Components with occupational exposure limits

benzene, 71-43-2;
TWA value 3.18 mg/m3 ; 1 ppm (OEL (SG))
Skin Designation (ACGIHTLV)
Danger of cutaneous absorption
Skin Designation (ACGIHTLV)
Danger of cutaneous absorption
TWA value 0.02 ppm (ACGIHTLV)

naphthalene, 91-20-3;
TWA value 10 ppm (ACGIHTLV)
Skin Designation (ACGIHTLV)
Danger of cutaneous absorption
TWA value 52 mg/m3 ; 10 ppm (OEL (SG))
STEL value 79 mg/m3 ; 15 ppm (OEL (SG))

cumene, 98-82-8;
TWA value 246 mg/m3 ; 50 ppm (OEL (SG))
TWA value 5 ppm (ACGIHTLV)

ethylbenzene, 100-41-4;
TWA value 20 ppm (ACGIHTLV)
TWA value 434 mg/m3 ; 100 ppm (OEL (SG))
STEL value 543 mg/m3 ; 125 ppm (OEL (SG))

toluene, 108-88-3;
TWA value 20 ppm (ACGIHTLV)
TWA value 188 mg/m3 ; 50 ppm (OEL (SG))

octane, 111-65-9;
TWA value 300 ppm (ACGIHTLV)
TWA value 1,400 mg/m3 ; 300 ppm (OEL (SG))
STEL value 1,750 mg/m3 ; 375 ppm (OEL (SG))

xylene, 1330-20-7;
TWA value 434 mg/m3 ; 100 ppm (OEL (SG))
STEL value 651 mg/m3 ; 150 ppm (OEL (SG))
TWA value 20 ppm (ACGIHTLV)

Benzene, trimethyl-, 25551-13-7;
TWA value 25 ppm (ACGIHTLV)
TWA value 123 mg/m3 ; 25 ppm (OEL (SG))
TWA value 10 ppm (ACGIHTLV)

Personal protective equipment

Respiratory protection:
Wear respiratory protection if ventilation is inadequate. Suitable respiratory protection for lower concentrations or short-term effect: Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A) Suitable respiratory protection for higher concentrations or long-term effect: Self-contained breathing apparatus.

Hand protection:
Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):
fluoroelastomer (FKM) - 0.7 mm coating thickness
nitrile rubber (NBR) - 0.4 mm coating thickness

Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)
butyl rubber (butyl) - 0.7 mm coating thickness
chloroprene rubber (CR) - 0.5 mm coating thickness

Manufacturer's directions for use should be observed because of great diversity of types.
Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Eye protection:
Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:
Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures:
Ensure adequate ventilation. Avoid inhalation of vapour. Avoid contact with the skin, eyes and clothing. Wearing of closed work clothing is required additionally to the stated personal protection equipment. Handle in accordance with good industrial hygiene and safety practice. At the end of the shift the skin should be cleaned and skin-care agents applied.

9. Physical and Chemical Properties

Form:	liquid	
Colour:	colourless, clear	
Odour:	benzene-like	
Odour threshold:	not determined	
pH value:	not applicable	
Melting point:	< -100 °C	(OECD Guideline 102)
Boiling point:	151.38 °C (1,013.25 hPa)	(measured)
Flash point:	35 °C	(DIN 51755, closed cup)
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.	
Flammability (solid/gas):	Flammable.	(derived from flash point)
Lower explosion limit:	1.6 %(V) For liquids not relevant for classification and labelling.	
Upper explosion limit:	7.8 %(V) For liquids not relevant for classification and labelling.	
Ignition temperature:	421 °C	(DIN EN 14522)
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Self ignition:	Based on its structural properties the product is not classified as self-igniting.	Test type: Spontaneous self-ignition at room-temperature.
Self heating ability:	not applicable, the product is a liquid	
SADT:	No data available.	
Explosion hazard:	Based on the chemical structure there is no indication of explosive properties.	
Fire promoting properties:	Based on its structural properties the product is not classified as oxidizing.	

Radioactivity:		not radioactive for transport purposes
Vapour pressure:	7.0 hPa (15 °C)	(OECD Guideline 104)
	9.04 hPa (20 °C)	(OECD Guideline 104)
	11.58 hPa (25 °C)	(OECD Guideline 104)
	35.94 hPa (50 °C)	(OECD Guideline 104)
Density:	0.8871 g/cm3 (20 °C)	(OECD Guideline 109)
Relative density:	0.8871 (20 °C)	(OECD Guideline 109)
Relative vapour density (air):	> 1 (20 °C) Heavier than air.	(estimated)
Solubility in water:	1 - 10 g/l (20 °C)	
Partitioning coefficient n-octanol/water (log Pow):	2.8 - 6.5 (23 °C)	(OECD Guideline 117)
Adsorption/water - soil:	log KOC: 1.46 - 4.71	(calculated)
Surface tension:	71.6 mN/m (20 °C) Based on chemical structure, surface activity is not to be expected.	(OECD Guideline 115, OECD harmonized ring method)
Viscosity, dynamic:	0.95 mPa.s (20 °C) The value was determined by calculation from the detected kinematic viscosity.	(OECD Guideline 114)
	0.73 mPa.s (40 °C) The value was determined by calculation from the detected kinematic viscosity.	(OECD Guideline 114)
Viscosity, kinematic:	1.07 mm2/s (20 °C)	(OECD Guideline 114)
	0.83 mm2/s (40 °C)	(OECD Guideline 114)

Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular form. -

Specific Surface Area:

No data available.

Particle Shape:

No data available.

Dustiness:

No data available.

10. Stability and Reactivity

Conditions to avoid:
Avoid all sources of ignition: heat, sparks, open flame.

Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

Substances to avoid:
strong oxidizing agents

Corrosion to metals: Corrosive effects to metal are not anticipated.

Hazardous reactions:
No hazardous reactions if stored and handled as prescribed/indicated.

No hazardous decomposition products if stored and handled as prescribed/indicated.

Chemical stability:
The product is stable if stored and handled as prescribed/indicated.

Reactivity:
No hazardous reactions if stored and handled as prescribed/indicated. When heated can give off ignitable vapours. Vapours may form explosive mixture with air.

11. Toxicological Information

Routes of exposure

Acute oral toxicity

Experimental/calculated data:
LD50rat (oral): 2,980 mg/kg (calculated)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. Analogous: Assessment derived from products with similar chemical character.

Acute inhalation toxicity

LC50 rat (by inhalation): > 5.14 mg/l 4 h (other)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The vapour was tested.

Acute dermal toxicity

LD50 rabbit (dermal): > 2,000 mg/kg (other)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. Analogous: Assessment derived from products with similar chemical character.

Assessment of acute toxicity

Of low toxicity after single ingestion. Of moderate toxicity after short-term inhalation. The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: xylene

Assessment of acute toxicity

Of low toxicity after single ingestion. Of low toxicity after short-term inhalation. Virtually nontoxic after a single skin contact. The European Union (EU) has classified this substance as 'harmful' after inhalation. The European Union (EU) has classified this substance as 'harmful' after dermal exposure. High concentrations in the air may cause narcosis.

Symptoms

Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 20 - 47 %, dermal

The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 19 - 39 %, oral

The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 19 - 39 %, Inhalation - vapour

Irritation

Assessment of irritating effects:
Skin contact causes irritation. Eye contact causes irritation. The product has not been tested. The statement has been derived from the properties of the individual components.

Experimental/calculated data:
Skin corrosion/irritation rabbit: Irritant. (OECD Guideline 404)

Serious eye damage/irritation rabbit: Irritant. (OECD Guideline 405)

Information on: xylene
Assessment of irritating effects:
Skin contact causes irritation. Eye contact causes irritation.

Respiratory/Skin sensitization

Assessment of sensitization:
Skin sensitizing effects were not observed in animal studies. The product has not been tested. The statement has been derived from the properties of the individual components.

Experimental/calculated data:
other other: Non-sensitizing. (other)
The product has not been tested. The statement has been derived from the properties of the individual components.

Germ cell mutagenicity

Assessment of mutagenicity:

Capable of causing genetic defects. The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: benzene
Assessment of mutagenicity:
Capable of causing genetic defects.

Carcinogenicity

Assessment of carcinogenicity:
Based on the ingredients there is a suspicion of a carcinogenic effect in humans. The product has not been tested. The statement has been derived from the properties of the individual components.

Experimental/calculated data:
No data available.

Information on: benzene
Assessment of carcinogenicity:
The substance caused cancer in animal studies.

Reproductive toxicity

Assessment of reproduction toxicity:
The results of animal studies suggest a fertility impairing effect. The product has not been tested. The statement has been derived from the properties of the individual components.

Experimental/calculated data:
No data available.

Developmental toxicity

Assessment of teratogenicity:
Indications of possible developmental toxicity/teratogenicity were seen in animal studies. The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: toluene
Assessment of teratogenicity:
Indications of possible developmental toxicity/teratogenicity were seen in animal studies.

Specific target organ toxicity (single exposure)

Possible narcotic effects (drowsiness or dizziness).

Causes temporary irritation of the respiratory tract.

Remarks: The product has not been tested. The statement has been derived from the properties of the individual components.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:
Repeated exposure may affect certain organs. The product has not been tested. The statement has been derived from the properties of the individual components.

Experimental/calculated data:
No data available.

Information on: benzene
Assessment of repeated dose toxicity:
Repeated exposure to small quantities may affect certain organs. Damages blood cells.

Aspiration hazard

May also damage the lung at swallowing (aspiration hazard).

12. Ecological Information

Ecotoxicity

Assessment of aquatic toxicity:
Acutely toxic for aquatic organisms. Depending on local conditions and existing concentrations, disturbances in the biodegradation process of activated sludge are possible.

Toxicity to fish:
LL50 (96 h) 1.1 mg/l, Oncorhynchus mykiss (OECD 203; ISO 7346; 84/449/EWG, C.1, semistatic)
The product has low solubility in the test medium. An eluate has been tested. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aquatic invertebrates:
EL50 (48 h) 1.2 mg/l, Daphnia magna (OECD Guideline 202, part 1, static)
The product has low solubility in the test medium. An eluate has been tested. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aquatic plants:
EL50 (72 h) 2.3 mg/l (growth rate), Pseudokirchneriella subcapitata (OECD Guideline 201)
The product has low solubility in the test medium. An eluate has been tested. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Microorganisms/Effect on activated sludge:
EC0 (72 h) 3.75 mg/l, Tetrahymena pyriformis (other)
The product has not been tested. The statement has been derived from the structure of the product.

Chronic toxicity to fish:
No data available.

Chronic toxicity to aquatic invertebrates:
No data available.

Assessment of terrestrial toxicity:

Mobility

Assessment transport between environmental compartments:
No data available.
Adsorption to solid soil phase is expected.

Persistence and degradability

Elimination information:
29 % BOD of the ThOD (28 d) (OECD 301F; ISO 9408; 92/69/EWG, C.4-D) (aerobic, activated sludge, domestic, non-adapted)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

7.3 % BOD of the ThOD (28 d) (OECD 301F; ISO 9408; 92/69/EWG, C.4-D) (aerobic, activated sludge, domestic, non-adapted)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Assessment of stability in water:
According to structural properties, hydrolysis is not expected/probable.

Information on Stability in Water (Hydrolysis):
No data available.

Bioaccumulation potential

Assessment bioaccumulation potential:
The product contains components with potential for bioaccumulation

Bioaccumulation potential:
May be accumulated in organisms. The product has not been tested. The statement has been derived from the properties of the individual components.

Other adverse effects

Adsorbable organically-bound halogen (AOX):
This product contains no organically-bound halogen.

Additional information

Other ecotoxicological advice:
Do not release untreated into natural waters. Do not allow to enter soil, waterways or waste water channels.

13. Disposal Considerations

Dispose of in accordance with national, state and local regulations.

Contaminated packaging:
Disposal must be made according to official regulations.

14. Transport Information

Domestic transport:

UN number or ID number:	UN 3295
UN proper shipping name:	HYDROCARBONS, LIQUID, N.O.S. (ORTHO-, META-, PARA-XYLENE, NAPHTHALENE, BENZENE)
Transport hazard class(es):	3, EHSM
Packing group:	III
Environmental hazards:	yes
Special precautions for user:	None known

Sea transport
IMDG

UN number or ID number:	UN 3295
UN proper shipping name:	HYDROCARBONS, LIQUID, N.O.S. (ORTHO-, META-, PARA-XYLENE, NAPHTHALENE, BENZENE)
Transport hazard class(es):	3, EHSM
Packing group:	III
Environmental hazards:	yes Marine pollutant: YES
Special precautions for user:	EmS: F - E; S - D

Air transport
IATA/ICAO

UN number or ID number:	UN 3295
UN proper shipping name:	HYDROCARBONS, LIQUID, N.O.S.
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	No Mark as dangerous for the environment is needed
Special precautions for user:	None known

Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

15. Regulatory Information

Other regulations

16. Other Information

Vertical lines in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.