Safety Data Sheet
ULTRADUR® B 4406 G6 UNCOLORED POLYBUTYLENE TEREPHTHALATE

1. Identification

Product identifier used on the label

ULTRADUR® B 4406 G6 UNCOLORED POLYBUTYLENE TEREPHTHALATE

Recommended use of the chemical and restriction on use

Recommended use*: Polymer
Recommended use*: Polymer; for industrial processing only
Suitable for use in industrial sector: Polymers industry

* The “Recommended use” identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
BASF Canada Inc.
5025 Creekbank Road
Building A, Floor 2
Mississauga, ON, L4W 0B6, CANADA

Telephone: +1 289 360-1300

Emergency telephone number

24 Hour Emergency Response Information
CHEMTREC: 1-800-424-9300
BASF HOTLINE: (800) 454-COPE (2673)

Other means of identification

Molecular formula:	(C12H12O4)N
Synonyms:	Poly(butylene terephthalate) ULTRADUR

2. Hazards Identification

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

Classification of the product

Carc.	2 (by inhalation)	Carcinogenicity
STOT RE	2	Specific target organ toxicity — repeated exposure

Label elements

Pictogram:

Signal Word:
Warning

Hazard Statement:

H351	Suspected of causing cancer by inhalation.
H373	May cause damage to organs (Lung) through prolonged or repeated exposure.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P201	Obtain special instructions before use.
P260	Do not breathe dust.
P202	Do not handle until all safety precautions have been read and understood.

Precautionary Statements (Response):

P308 + P313	IF exposed or concerned: Get medical attention.

Precautionary Statements (Storage):

P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents/container in accordance with local regulations.

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

3. Composition / Information on Ingredients

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

diantimony trioxide
CAS Number: 1309-64-4
Content (W/W): >= 5.0 - < 7.0%
Synonym: ANTIMONY TRIOXIDE

4. First-Aid Measures

Description of first aid measures

General advice:
Avoid contact with the skin, eyes and clothing. Remove contaminated clothing.

If inhaled:
If difficulties occur after dust has been inhaled, remove to fresh air and seek medical attention.

If on skin:
Burns caused by molten material require hospital treatment.

If in eyes:
In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

If swallowed:
Rinse mouth and then drink 200-300 ml of water. Ingestion is not likely in the available physical form. If ingested, seek medical attention. Do not induce vomiting.

Most important symptoms and effects, both acute and delayed

Symptoms: (Further) symptoms and / or effects are not known so far

Information on: diantimony trioxide
Symptoms: Overexposure may cause:, vomiting, abdominal cramps, metallic taste in mouth, pneumonitis, dyspnea, nausea, diarrhea
---

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:	Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Suitable extinguishing media:
water spray, foam, dry powder

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
carbon monoxide, tetrahydrofuran, hydrogen halides, brominated dibenzodioxins can be emitted at > 290 °C

Under special fire conditions traces of other toxic substances are possible. Formation of further decomposition and oxidation products depends upon the fire conditions.

Advice for fire-fighters
Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:
Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Further accidental release measures:
High risk of slipping due to leakage/spillage of product.

Personal precautions, protective equipment and emergency procedures
No special precautions necessary.

Environmental precautions
No special precautions necessary.

Methods and material for containment and cleaning up
For small amounts: Pick up with suitable appliance and dispose of.
For large amounts: Pick up with suitable appliance and dispose of.
For residues: Sweep/shovel up.
Dispose of absorbed material in accordance with regulations.

7. Handling and Storage

Precautions for safe handling
Avoid dust formation.

Exhaust ventilation at processing machines is required during thermal processing and/or machining. However, if dust formulation occurs at processing / finishing processing steps like regranulation, mechanical machining (for example drilling, grinding etc.) provide suitable exhaust ventilation.

Cleaning of product-contaminated machine parts with open flames should be avoided. If task are carried out with open flames, ventilation measures are mandatory.

Protection against fire and explosion:
Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities
Segregate from foods and animal feeds.

Suitable materials for containers: Low density polyethylene (LDPE), High density polyethylene (HDPE), Aluminium, Carbon steel (Iron)

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place. Avoid dust formation, product dust can form an explosive mixture with air.

Storage stability:
Protect against moisture.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

diantimony trioxide	OSHA Z1:	PEL 0.5 mg/m3 (antimony (Sb));
	ACGIH, US:	TWA value 0.02 mg/m3 Inhalable fraction ;

Advice on system design:
Ensure adequate ventilation.

Personal protective equipment

Respiratory protection:
Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection:
Wear gloves to prevent contact during mechanical processing and/or hot melt conditions.

Eye protection:
Tightly fitting safety goggles (chemical goggles).

Body protection:
Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:
Wear protective clothing to prevent contact during mechanical processing and/or hot melt conditions. When using do not eat or drink. Hands and/or face should be washed before breaks and at the end of the shift. Wash soiled clothing immediately.

9. Physical and Chemical Properties

Form:	pellets	
Odour:	odourless	
Odour threshold:	not applicable	
Colour:	various, depending on the colourant	
pH value:	not applicable	
melting range:	220 - 230 °C (1,013 hPa)	(DIN 53736)
Boiling range:	The substance / product decomposes therefore not determined.	
Sublimation point:	No applicable information available.	
Flash point:	not applicable	
Flammability:	not self-igniting	(derived from flash point)
Flammability of Aerosol Products:	not applicable, the product does not form flammable aerosoles	

Lower explosion limit:	For solids not relevant for classification and labelling.	
Upper explosion limit:	For solids not relevant for classification and labelling.	
Autoignition:	> 350 °C	(ASTM D1929)
Vapour pressure:	not applicable	
Density:	1.60 - 1.70 g/cm3 (20 °C, 1,013 hPa)	(EN ISO 1183-1)
Relative density:	Study does not need to be conducted.	
Bulk density:	600 - 900 kg/m3 (20 °C, 1,013 hPa)	(DIN 53466)
Vapour density:	not applicable	
Partitioning coefficient n-octanol/water (log Pow):	not applicable	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	> 290 °C (TGA) To avoid thermal decomposition, do not overheat.	
Viscosity, dynamic:	not applicable, the product is a solid	
Viscosity, kinematic:	not applicable, the product is a solid	
Particle size:	spheroidal	
Solubility in water:	(20 °C, 1,013 hPa) insoluble	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Evaporation rate:	The product is a non-volatile solid.	

10. Stability and Reactivity

Reactivity
No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:
No corrosive effect on metal.

Oxidizing properties:
not fire-propagating

Chemical stability
The product is stable if stored and handled as prescribed/indicated.
The product is chemically stable.

Possibility of hazardous reactions
The product is chemically stable.
No hazardous reactions known.

Conditions to avoid
Temperature: > 290 degrees Celsius

Incompatible materials
No substances known that should be avoided.

Hazardous decomposition products

Decomposition products:
Hazardous decomposition products: carbon monoxide, tetrahydrofuran, terephthalic acid, carbon dioxide, Water, Danger by forming of toxic pyrolytic products.

Thermal decomposition:
> 290 °C (TGA)
To avoid thermal decomposition, do not overheat.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity
Assessment of acute toxicity: Contact with molten product may cause thermal burns. The resin in pelleted form poses a low hazard.

Oral
Type of value: ATE
Value: > 5,000 mg/kg

Inhalation
Not inhalable due to the physico-chemical properties of the product.

Dermal
Type of value: ATE
Value: > 5,000 mg/kg

Assessment other acute effects
No applicable information available.

Irritation / corrosion
Assessment of irritating effects: Thermal decomposition products of the substance can irritate the eyes, skin, and respiratory tract.

Information on: diantimony trioxide
Assessment of irritating effects: Not irritating to eyes and skin.

Sensitization
Assessment of sensitization: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Aspiration Hazard
May be harmful if swallowed and enters airways.

Chronic Toxicity/Effects

Repeated dose toxicity
Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.

Information on: diantimony trioxide
Assessment of repeated dose toxicity: Repeated oral uptake of the substance did not cause substance-related effects. The substance may cause damage to the lung even after repeated inhalation of low doses, as shown in animal studies.

Genetic toxicity
Assessment of mutagenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Carcinogenicity
Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests.

Information on: diantimony trioxide
Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).

Reproductive toxicity
Assessment of reproduction toxicity: No applicable information available.

Teratogenicity
Assessment of teratogenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Other Information
Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

12. Ecological Information

Toxicity

Aquatic toxicity
Assessment of aquatic toxicity:
The product has not been tested. The statement has been derived from the structure of the product. There is a high probability that the product is not acutely harmful to aquatic organisms.

Persistence and degradability

Assessment biodegradation and elimination (H2O)
Experience shows this product to be inert and non-degradable.
The product is virtually insoluble in water and can thus be separated from water mechanically in suitable effluent treatment plants.

Elimination information

Poorly biodegradable.

Assessment of stability in water
According to structural properties, hydrolysis is not expected/probable.

Bioaccumulative potential

Assessment bioaccumulation potential
Does not significantly accumulate in organisms.

Bioaccumulation potential
The product will not be readily bioavailable due to its consistency and insolubility in water.

Mobility in soil

Assessment transport between environmental compartments
Adsorption to solid soil phase is not expected.

Additional information

Adsorbable organically-bound halogen(AOX):
The product contains according to the formulation, organically bound halogen. It can increase the AOX-value in the water purification plants overflow or if it reaches waters.

Other ecotoxicological advice:
The product is a polymeric compound.

13. Disposal considerations

Waste disposal of substance:
Check for possible recycling. Observe national and local legal requirements. Dispose of as hazardous waste in compliance with national waste legislation requirements and local regulations.

Container disposal:
Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport
TDG

Not classified as a dangerous good under transport regulations

Sea transport
IMDG

Not classified as a dangerous good under transport regulations

Air transport
IATA/ICAO
Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:
Chemical DSL, CA released; restriction on quantity / not listed

NFPA Hazard codes:
Health: 1 Fire: 1 Reactivity: 0 Special:

16. Other Information

SDS Prepared by:
BASF NA Product Regulations
SDS Prepared on: 2025/01/07

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

ULTRADUR® B 4406 G6 UNCOLORED POLYBUTYLENE TEREPHTHALATE is a registered trademark of BASF Canada or BASF SE
END OF DATA SHEET