Safety Data Sheet
PVP-Iodine 30/06

1. Identification

Product identifier used on the label

PVP-Iodine 30/06

Recommended use of the chemical and restriction on use

Recommended use*: Pharmaceutical agent
Unsuitable for use: Not intended for sale to or use by the general public.

* The “Recommended use” identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
BASF Canada Inc.
5025 Creekbank Road
Building A, Floor 2
Mississauga, ON, L4W 0B6, CANADA

Telephone: +1 289 360-1300

Emergency telephone number

24 Hour Emergency Response Information
CHEMTREC: 1-800-424-9300
BASF HOTLINE: (800) 454-COPE (2673)

Other means of identification

Synonyms: 2-Pyrrolidinone, 1-ethenyl-, homopolymer, compd. with iodine

2. Hazards Identification

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

Classification of the product

STOT RE	2	Specific target organ toxicity — repeated exposure
Aquatic Acute	2	Hazardous to the aquatic environment - acute

Aquatic Chronic	2	Hazardous to the aquatic environment - chronic
Eye Dam.	1	Serious eye damage
Skin Irrit.	2	Skin irritation
Combustible Dust	Combustible Dust (1)	Combustible Dust

Label elements

Pictogram:

Signal Word:
Danger

Hazard Statement:

	May form combustible dust concentration in air.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H373	May cause damage to organs (Thyroid gland) through prolonged or repeated exposure.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves and eye protection or face protection.
P273	Avoid release to the environment.
P260	Do not breathe dust.
P264	Wash contaminated body parts thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P391	Collect spillage.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Disposal):

P501	Dispose of contents/container in accordance with local regulations.

Hazards not otherwise classified

The product is under certain conditions capable of dust explosion.

3. Composition / Information on Ingredients

According to Hazardous Products Regulations (HPR) (SOR/2015-17)

2-Pyrrolidinone, 1-ethenyl-, homopolymer, compd. with iodine
CAS Number: 25655-41-8
Content (W/W): 75.0 - 100.0%
Synonym: No data available.

4. First-Aid Measures

Description of first aid measures

General advice:
Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.

If inhaled:
Keep patient calm, remove to fresh air, seek medical attention. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

If on skin:
Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Seek medical attention.

If in eyes:
Hold eyes open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing. If irritation develops, seek medical attention.

If swallowed:
Rinse mouth and then drink 200-300 ml of water. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: itching, eczema, erythema, skin irritation, Eye irritation, conjunctivitis, lacrimation, visual disturbances

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:	Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Suitable extinguishing media:
water spray, carbon dioxide, dry powder, Dry sand, foam

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
hydrogen cyanide, iodine, carbon dioxide, nitrogen oxides
The substances/groups of substances mentioned can be released in case of fire. Dust explosion hazard.

Advice for fire-fighters

Protective equipment for fire-fighting:
Wear self-contained breathing apparatus and chemical-protective clothing.

Further information:
Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Dusty conditions may ignite explosively in the presence of an ignition source causing flash fire.

6. Accidental release measures

Further accidental release measures:
Avoid dispersal of dust in the air (e.g. by clearing dusty surfaces with compressed air). Avoid the formation and build-up of dust - danger of dust explosion. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition.

Personal precautions, protective equipment and emergency procedures
Use personal protective clothing. Information regarding personal protective measures, see section 8. Avoid dust formation. Ensure adequate ventilation. Do not breathe dust. Avoid contact with the skin, eyes and clothing.

Environmental precautions
May be harmful to the aquatic environment. Prevent entry into drains and surface waters.

Methods and material for containment and cleaning up
For small amounts: Contain with dust binding material and dispose of.
For large amounts: Sweep/shovel up.
Dispose of absorbed material in accordance with regulations. Avoid raising dust. Cleaning operations should be carried out only while wearing breathing apparatus.

For small amounts: Sweep/shovel up.
For large amounts: Sweep/shovel up.
Avoid raising dust. Nonsparking tools should be used.

7. Handling and Storage

Precautions for safe handling
Avoid dust formation. Ensure thorough ventilation of stores and work areas. Wear suitable protective clothing and eye/face protection. Avoid contact with the skin, eyes and clothing. Keep container tightly sealed.

Protection against fire and explosion:
Avoid dust formation. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids (2013 Edition) for safe handling.

Dust explosion class: Dust explosion class 1 (Kst-value >0 up to 200 bar m s-1).

Conditions for safe storage, including any incompatibilities
No applicable information available.

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place.

8. Exposure Controls/Personal Protection

No substance specific occupational exposure limits known.

Advice on system design:
Provide local exhaust ventilation to control dust. It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen deficient environment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Use only appropriately classified electrical equipment and powered industrial trucks.

Personal protective equipment

Respiratory protection:
Breathing protection if breathable aerosols/dust are formed. Wear a NIOSH-certified (or equivalent) particulate respirator.

Hand protection:
Wear chemical resistant protective gloves., Consult with glove manufacturer for testing data.

Eye protection:
Wear safety goggles (chemical goggles) if there is potential for airborne dust exposures.

Body protection:
Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

General safety and hygiene measures:
Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is required additionally to the stated personal protection equipment. Do not breathe dust. Avoid contact with the skin, eyes and clothing. No eating, drinking, smoking or tobacco use at the place of work. Hands and/or face should be washed before breaks and at the end of the shift. Store work clothing separately.

9. Physical and Chemical Properties

Form:	amorphous powder	
Odour:	almost odourless	
Colour:	brown	
pH value:	1.8 (approx. 101.5 g/kg, 20 °C)	(pH Meter)
Melting point:	> 180 °C slow decomposition	(OECD Guideline 102)
Freezing point:	No data available.	

Boiling point:	(1,013 hPa) The substance / product decomposes therefore not determined.	
Sublimation point:	No applicable information available.	
Flash point:	not applicable, the product is a solid	
Flammability:	not highly flammable	(VDI 2263, sheet 1, 1.2)
Lower explosion limit:	For solids not relevant for classification and labelling.	
Upper explosion limit:	For solids not relevant for classification and labelling.	
Vapour pressure:	< 0.1 hPa (approx. 20 °C)	
Relative density:	1.365 (20 °C)	(OECD Guideline 109)
Bulk density:	450 kg/m3	
Vapour density:	not relevant	
Partitioning coefficient n-octanol/water (log Pow):	< -3.1 (23 °C)	(internal method)
Self-ignition temperature:	Based on its structural properties the product is not classified as self-igniting.	
Thermal decomposition:	> 180 °C, 20 J/g	
Viscosity, dynamic:	not applicable, the product is a solid	
Viscosity, kinematic:	No data available.	
Particle size:	typically D50 > 100 µm	(ISO 13320-1)
Solubility in water:	approx. 700 g/l (20 °C)	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	soluble solvent(s): alcohols, Ethanol	
Molar mass:	No data available.	
Evaporation rate:	The product is a non-volatile solid.	

10. Stability and Reactivity

Reactivity
No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:
In the presence of water or moisture metal corrosion cannot be excluded.

Oxidizing properties:
not fire-propagating

Dust explosivity characteristics:
Kst: 93 m.bar/s

Dust explosion class:
Dust explosion class 1 (Kst-value >0 up to 200 bar m s-1) (St 1)

Minimum ignition energy:

The product is capable of dust explosion.

Formation of flammable gases:	Remarks:	Study scientifically not justified.

Chemical stability
The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions
Dust explosion hazard.

Conditions to avoid
Avoid dust formation. Avoid electro-static charge. Avoid all sources of ignition: heat, sparks, open flame.

Incompatible materials
reducing agents, metal

Hazardous decomposition products

Decomposition products:
Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:
> 180 °C

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity
Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic after a single skin contact.

Oral
Type of value: LD50
Species: rat (male/female)
Value: > 4,640 mg/kg

Inhalation
No applicable information available.

Dermal
Type of value: LD50
Species: rat
Value: > 2,500 mg/kg
No mortality was observed.

Assessment other acute effects
Assessment of STOT single:
Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Irritation / corrosion
Assessment of irritating effects: Irritating to skin. Risk of serious damage to eyes.

Skin
Species: rabbit
Result: Irritant.
Method: OECD Guideline 404

Eye
Species: rabbit
Result: Corrosive.
Method: OECD Guideline 405

Sensitization
Assessment of sensitization: Skin sensitizing effects were not observed in animal studies.

Guinea pig maximization test
Species: guinea pig
Result: Non-sensitizing.
Method: OECD Guideline 406

Aspiration Hazard
not applicable

Chronic Toxicity/Effects

Repeated dose toxicity
Assessment of repeated dose toxicity: Danger of serious damage to health by prolonged exposure. Damages the thyroid.
Experimental/calculated data: No data available.

Genetic toxicity
Assessment of mutagenicity: No mutagenic effect was found in various tests with bacteria and mammals.
Genetic toxicity in vitro: DNA damage and repair assay positive

Carcinogenicity
Assessment of carcinogenicity: No data available.
Experimental/calculated data: No data available.

Reproductive toxicity
Assessment of reproduction toxicity: No data available.

Reproduction
Experimental/calculated data: No data available.

Teratogenicity
Assessment of teratogenicity: In animal studies the substance did not cause malformations.

12. Ecological Information

Toxicity

Aquatic toxicity
Assessment of aquatic toxicity:
Acutely toxic for aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish
LC50 (96 h) 6.78 mg/l, Leuciscus idus (DIN 38412 Part 15, static)

Aquatic invertebrates
EC50 (48 h) 3.23 mg/l, Daphnia magna (OECD Guideline 202, part 1, static)
The statement of the toxic effect relates to the analytically determined concentration.

Aquatic plants
EC50 (72 h) 4.91 mg/l (growth rate), Desmodesmus subspicatus (OECD Guideline 201, static)
The statement of the toxic effect relates to the analytically determined concentration.

Chronic toxicity to fish
No data available regarding toxicity to fish.

Chronic toxicity to aquatic invertebrates
No data available regarding toxicity to daphnids.

Assessment of terrestrial toxicity
No data available.

Microorganisms/Effect on activated sludge

Toxicity to microorganisms
DIN 38412 Part 8 aerobic
bacterium/EC10 (17 h): 270 mg/l

Persistence and degradability

Assessment biodegradation and elimination (H2O)
Not readily biodegradable (by OECD criteria). Poorly biodegradable. Poorly eliminated from water.

Elimination information

< 20 % DOC reduction (3 h) (OECD Guideline 302 B) (aerobic, activated sludge, domestic, adapted)

< 10 % (28 d) (ISO 14593) (aerobic, activated sludge, domestic)

Assessment of stability in water
No data available.

Bioaccumulative potential

Assessment bioaccumulation potential

Based on its structural properties, the polymer is not biologically available. Accumulation in organisms is not to be expected.

Bioaccumulation potential
No data available.

Mobility in soil

Assessment transport between environmental compartments
Adsorption to solid soil phase is not expected.

Additional information

Other ecotoxicological advice:
No data available.

13. Disposal considerations

Waste disposal of substance:
Do not discharge into waterways or sewer systems without proper authorization. Dispose of in accordance with national, state and local regulations.

Container disposal:
Dispose of container and any rinsate in an environmentally safe manner. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

14. Transport Information

Land transport
TDG

Hazard class:	9
Packing group:	III
ID number:	UN 3077
Hazard label:	9, EHSM
Proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (contains POLYVINYLPYRROLIDONE IODINE COMPLEX)

Sea transport
IMDG

Hazard class:	9
Packing group:	III
ID number:	UN 3077
Hazard label:	9, EHSM
Marine pollutant:	YES
Proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (contains POLYVINYLPYRROLIDONE IODINE COMPLEX)

Air transport
IATA/ICAO

Hazard class:	9
Packing group:	III
ID number:	UN 3077
Hazard label:	9, EHSM

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (contains POLYVINYLPYRROLIDONE IODINE COMPLEX)

Further information
Product may be shipped as non-hazardous in suitable packages containing a net quantity of 5 kg or less under the provisions of various regulatory agencies: ADR, RID, ADN: Special Provision 375; IMDG: 2:10.2.7; IATA: A197; TDS: Special Provision 99(2); 49CFR: §171.4 (c) (2) and also the Special Provision 375 in Appendix B which is regulated in China "Regulations Concerning Road Transportation of Dangerous Goods Part 3: Index of dangerous goods name and transportation requirements" (JT/T 617.3)

15. Regulatory Information

Federal Regulations

Registration status:

Pharma	DSL, CA	released / listed
Chemical	DSL, CA	released / listed

NFPA Hazard codes:
Health: 2 Fire: 1 Reactivity: 0 Special:

Assessment of the hazard classes according to UN GHS criteria (most recent version):

Eye Dam.	1	Serious eye damage
Skin Irrit.	2	Skin irritation
Aquatic Acute	2	Hazardous to the aquatic environment - acute
Aquatic Chronic	2	Hazardous to the aquatic environment - chronic
STOT RE	2	Specific target organ toxicity — repeated exposure

16. Other Information

SDS Prepared by:
BASF NA Product Regulations
SDS Prepared on: 2023/03/30

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

END OF DATA SHEET