Safety Data Sheet
n-HEXYL GLYCOL

1. Identification

Product identifier used on the label

n-HEXYL GLYCOL

Recommended use of the chemical and restriction on use

Recommended use*: Chemical
Recommended use*: for industrial use only; Chemical; solvent(s); process chemical
Unsuitable for use: Not intended for sale to or use by the general public.

* The “Recommended use” identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

24 Hour Emergency Response Information
CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: Preparation based on: alcohols

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Flam. Liq.	4	Flammable liquids
Acute Tox.	4 (oral)	Acute toxicity
Acute Tox.	3 (dermal)	Acute toxicity
Skin Corr./Irrit.	1B	Skin corrosion/irritation

Eye Dam./Irrit.	1	Serious eye damage/eye irritation

Label elements

Pictogram:

Signal Word:
Danger

Hazard Statement:

H227	Combustible liquid.
H311	Toxic in contact with skin.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist or vapour.
P270	Do not eat, drink or smoke when using this product.
P264	Wash contaminated body parts thoroughly after handling.

Precautionary Statements (Response):

P310	Immediately call a POISON CENTER or physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P361 + P364	Take off immediately all contaminated clothing and wash it before reuse.
P301 + P330 + P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P370 + P378	In case of fire: Use water spray, dry powder, foam or carbon dioxide for extinction.

Precautionary Statements (Storage):

P405	Store locked up.
P403	Store in a well-ventilated place.

Precautionary Statements (Disposal):

P501	Dispose of contents/container in accordance with local regulations.

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.
See section 12 - Results of PBT and vPvB assessment.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

2-hexyloxyethanol
CAS Number: 112-25-4
Content (W/W): > 98.5 - < 99.1%
Synonym: Ethylene glycol monohexyl ether

2-(2-hexyloxyethoxy)ethanol
CAS Number: 112-59-4
Content (W/W): >= 0.03 - <= 0.28%
Synonym: Diethylene glycol monohexyl ether

4. First-Aid Measures

Description of first aid measures

General advice:
If not breathing, give artificial respiration.

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:
Keep patient calm, remove to fresh air, seek medical attention. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

If on skin:
Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

If in eyes:
Hold eyes open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing. Seek medical attention.

If swallowed:
Do not induce vomiting. Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: Overexposure may cause:, corneal injury, skin corrosion, severe pain, coughing, respiratory disorders, dyspnea, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps
Hazards: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. (Further) symptoms and / or effects are not known so far

Indication of any immediate medical attention and special treatment needed

Note to physician
Treatment: Treat according to symptoms (decontamination, vital functions), no

known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
dry powder, water spray, carbon dioxide, foam

Unsuitable extinguishing media for safety reasons:
water jet

Additional information:
Use extinguishing measures to suit surroundings.

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
Flammable liquid Cool endangered containers with water-spray. See SDS section 7 - Handling and storage.

Advice for fire-fighters

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear. Special protective equipment for firefighters

Further information:
Evacuate area of all unnecessary personnel. Fight fire from maximum distance.

Extend fire extinguishing measures to the surroundings. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Impact Sensitivity:
Remarks: Based on the chemical structure there is no shock-sensitivity.

6. Accidental release measures

Further accidental release measures:
High risk of slipping due to leakage/spillage of product.

Release of substance/product can cause fire or explosion. Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

Personal precautions, protective equipment and emergency procedures

Handle in accordance with good industrial hygiene and safety practice.

Avoid all sources of ignition: heat, sparks, open flame. Use antistatic tools.

Environmental precautions

Discharge into the environment must be avoided.

Methods and material for containment and cleaning up
Pick up with suitable appliance and dispose of. Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations.

7. Handling and Storage

Precautions for safe handling
Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:
Avoid all sources of ignition: heat, sparks, open flame. Ground all transfer equipment properly to prevent electrostatic discharge.

Conditions for safe storage, including any incompatibilities
No applicable information available.

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

8. Exposure Controls/Personal Protection

No substance specific occupational exposure limits known.

Advice on system design:
No applicable information available.

Personal protective equipment

Respiratory protection:
Wear respiratory protection if ventilation is inadequate. Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:
Chemical resistant protective gloves (EN ISO 374-1), Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):, butyl rubber (butyl) - 0.7 mm coating thickness, Manufacturer's directions for use should be observed because of great diversity of types., Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Eye protection:
Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:
Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures:
Avoid contact with the skin, eyes and clothing. Wearing of closed work clothing is required additionally to the stated personal protection equipment.

9. Physical and Chemical Properties

Form:	liquid	
Odour:	ether-like	
Odour threshold:	not determined	
Colour:	colourless, clear	
pH value:	neutral	
Melting point:	-42 °C (1,013 hPa)	
Freezing point:	No data available.	
Boiling point:	208.5 °C (1,013.3 hPa)	
Boiling range:	200 - 212 °C (1,013.3 hPa)	
Sublimation point:	No applicable information available.	
Flash point:	91.5 °C	(ISO 2719, closed cup)
Flammability:	Combustible liquid.	(derived from flash point)
Lower explosion limit:	0.9 %(V) (82.85 °C) The lower explosion point of the substance/mixture has been determined. The explosion point describes the temperature of a flammable liquid at which the concentration of the saturated vapour mixed with air equals the lower explosion limit. Literature data.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Autoignition:	225 °C	(DIN 51794)
Vapour pressure:	0.1 hPa (22.9 °C) dynamic	(OECD Guideline 104)
Density:	0.8875 g/cm3 (20 °C) Literature data.	
Relative density:	0.8875 (20 °C)	
Vapour density:	5.04 (20 °C) Heavier than air.	(calculated)
Partitioning coefficient n-octanol/water (log Pow):	1.97 (25 °C)	
Refractive index:	1.429 (20 °C)	(DIN 51423-1)
Self-ignition temperature:	Based on its structural properties the product is not classified as self-igniting.	
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Viscosity, dynamic:	4.4 mPa.s (20 °C)	
Viscosity, kinematic:	No applicable information available.	

Particle size:	The substance / product is marketed or used in a non solid or granular form.
Solubility in water:	9.460 g/l (20 °C)
Miscibility with water:	partly miscible
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	soluble solvent(s): organic solvents,
Molar mass:	146.23 g/mol
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.

10. Stability and Reactivity

Reactivity
When heated can give off ignitable vapours.

Corrosion to metals:
No corrosive effect on metal.

Oxidizing properties:
Based on its structural properties the product is not classified as oxidizing.

Formation of flammable gases:	Remarks:	Forms no flammable gases in the presence of water.

Chemical stability
The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions
Reacts with light metals, with evolution of hydrogen. Reacts with strong oxidizing agents.

Conditions to avoid
No special precautions other than good housekeeping of chemicals.

Incompatible materials
strong oxidizing agents

Hazardous decomposition products

Decomposition products:
Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:
No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity
Assessment of acute toxicity: Of moderate toxicity after single ingestion. Of pronounced toxicity after short-term skin contact. Virtually nontoxic by inhalation.

Oral
Type of value: LD50
Species: rat
Value: 738 mg/kg (other)

Inhalation
Type of value: LC0
Species: rat
Value: (other)
Exposure time: 6 h
The vapour was tested.
No mortality within the stated exposition time as shown in animal studies.

Dermal
Type of value: LD50
Species: rabbit
Value: 757.35 mg/kg (other)

Assessment other acute effects
Assessment of STOT single:
not applicable

Irritation / corrosion
Assessment of irritating effects: Corrosive! Damages skin and eyes.

Skin
Species: rabbit
Result: Corrosive.
Method: other
The European Union (EU) has classified this substance with 'Causes burns.'

Eye
Species: rabbit
Result: Risk of serious damage to eyes.
Method: OECD Guideline 405

Sensitization
Assessment of sensitization: As the substance is corrosive, conducting sensitization studies is not feasible.

Aspiration Hazard
not applicable

Chronic Toxicity/Effects

Repeated dose toxicity
Assessment of repeated dose toxicity: After repeated exposure the prominent effect is local irritation. The substance may cause damage to the liver after repeated inhalation of high doses.

Genetic toxicity
Assessment of mutagenicity: The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture.

Carcinogenicity
Assessment of carcinogenicity: The whole of the information assessable provides no indication of a carcinogenic effect.

Reproductive toxicity
Assessment of reproduction toxicity: The results of animal studies gave no indication of a fertility impairing effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Teratogenicity
Assessment of teratogenicity: No indications of a developmental toxic / teratogenic effect were seen in animal studies.

12. Ecological Information

Toxicity

Aquatic toxicity
Assessment of aquatic toxicity:
There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish
LC50 (96 h) 140 mg/l, Pimephales promelas (OECD Guideline 203, static)
Nominal concentration.

Aquatic invertebrates
EC50 (48 h) 145 mg/l, Daphnia magna (DIN 38412 Part 11, static)
Nominal concentration.

Aquatic plants
EC50 (72 h) 198 mg/l (growth rate), Scenedesmus subspicatus (DIN 38412 Part 9, static)
Nominal concentration.

Chronic toxicity to fish
Study scientifically not justified.

Chronic toxicity to aquatic invertebrates
Study scientifically not justified.

Assessment of terrestrial toxicity
No data available concerning terrestrial toxicity.

Microorganisms/Effect on activated sludge

Toxicity to microorganisms
DIN EN ISO 8192-OECD 209-88/302/EEC,P. C aquatic
activated sludge, domestic, non-adapted/EC20 (30 min): 750 mg/l
Nominal concentration.

Persistence and degradability

Assessment biodegradation and elimination (H2O)
Readily biodegradable (according to OECD criteria).

Elimination information

97 % CO2 formation relative to the theoretical value (20 d) (OECD 301B; ISO 9439; 92/69/EWG, C.4-C) (aerobic)

Assessment of stability in water
Substance is readily biodegradable, therefore hydrolysis is not expected to be relevant.

Bioaccumulative potential

Assessment bioaccumulation potential
No significant accumulation in organisms is expected as a result of the distribution coefficient of n-octanol/water (log Pow).

Bioaccumulation potential
No data available.

Mobility in soil

Assessment transport between environmental compartments
The substance will not evaporate into the atmosphere from the water surface.
Adsorption to solid soil phase is not expected.

Additional information

Adsorbable organically-bound halogen(AOX):
This product contains no organically-bound halogen.

Other ecotoxicological advice:
Do not release untreated into natural waters.

13. Disposal considerations

Waste disposal of substance:
Dispose of in accordance with national, state and local regulations.

Container disposal:
Flammable vapors may exist in containers in which residues of this product remain. Packs that cannot be cleaned should be disposed of in the same manner as the contents.

14. Transport Information

Land transport
USDOT
Hazard class: 8

Packing group:	II
ID number:	UN 2922
Hazard label:	8, 6.1
Proper shipping name:	CORROSIVE LIQUID, TOXIC, N.O.S. (contains ETHYLENEGLYCOL MONOHEXYLETHER)

Sea transport
IMDG

Hazard class:	8
Packing group:	II
ID number:	UN 2922
Hazard label:	8, 6.1
Marine pollutant:	NO
Proper shipping name:	CORROSIVE LIQUID, TOXIC, N.O.S. (contains ETHYLENEGLYCOL MONOHEXYLETHER)

Air transport
IATA/ICAO

Hazard class:	8
Packing group:	II
ID number:	UN 2922
Hazard label:	8, 6.1
Proper shipping name:	CORROSIVE LIQUID, TOXIC, N.O.S. (contains ETHYLENEGLYCOL MONOHEXYLETHER)

15. Regulatory Information

Federal Regulations

Registration status:
Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

EPCRA 313:

CAS Number	Chemical name
112-25-4	2-hexyloxyethanol

State regulations

State RTK	CAS Number	Chemical name
PA	112-25-4	2-hexyloxyethanol

NFPA Hazard codes:
Health: 3 Fire: 2 Reactivity: 0 Special:

HMIS III rating
Health: 3 Flammability: 2 Physical hazard: 0

Assessment of the hazard classes according to UN GHS criteria (most recent version):

Acute Tox.	4 (oral)	Acute toxicity
Skin Corr./Irrit.	1B	Skin corrosion/irritation

Flam. Liq.	4	Flammable liquids
Eye Dam./Irrit.	1	Serious eye damage/eye irritation
Acute Tox.	3 (dermal)	Acute toxicity

16. Other Information

SDS Prepared by:
BASF NA Product Regulations
SDS Prepared on: 2023/12/05

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET