We create chemistry

Safety Data Sheet
ULTRAMID®B3GM35 BLACK 23335 POLYAMIDE

1. Identification

Product identifier used on the label

ULTRAMID®B3GM35 BLACK 23335 POLYAMIDE

Recommended use of the chemical and restriction on use

Recommended use*: Polymer; for industrial processing only
Suitable for use in industrial sector: Polymers industry
Unsuitable for use: Uses other than recommended

* The “Recommended use” identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

24 Hour Emergency Response Information
CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family:	polyamide
Synonyms:	Polyamide (PA6)

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Carc.	1A	Carcinogenicity

Label elements

Pictogram:

Signal Word:
Danger

Hazard Statement:

H350	May cause cancer.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.

Precautionary Statements (Response):

P308 + P311	IF exposed or concerned: Call a POISON CENTER or physician.

Precautionary Statements (Storage):

P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

Labeling of special preparations (GHS):
UNDER HOT MELT PROCESSING CONDITIONS, WEAR PERSONAL PROTECTIVE EQUIPMENT TO PREVENT THERMAL BURNS.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

carbon black
CAS Number: 1333-86-4
Content (W/W): >= 0.3 - < 1.0%
Synonym: C.I. 77266

crystalline silica
CAS Number: 14808-60-7
Content (W/W): > 0.0 - < 1.0%
Synonym: No data available.

copper iodide
CAS Number: 7681-65-4
Content (W/W): > 0.0 - < 0.1%
Synonym: Copper monoiodide

Wollastonite (Ca(SiO3))
CAS Number: 13983-17-0
Content (W/W): >= 15.0 - <= 25.0%
Synonym: Wollastonite

4. First-Aid Measures

Description of first aid measures

General advice:
Remove contaminated clothing.

If inhaled:
Keep patient calm, remove to fresh air.

If on skin:
Wash thoroughly with soap and water

If in eyes:
Wash affected eyes for at least 15 minutes under running water with eyelids held open.

If swallowed:
Rinse mouth and then drink 200-300 ml of water.

Most important symptoms and effects, both acute and delayed

Symptoms: (Further) symptoms and / or effects are not known so far
No data available.
Hazards: No hazard is expected under intended use and appropriate handling.

Indication of any immediate medical attention and special treatment needed

Note to physician
Treatment: Symptomatic treatment (decontamination, vital functions).

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
water spray, foam, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
Ammonium hydroxide, carbon monoxide, carbon dioxide, caprolactam, hydrogen cyanide, nitriles can be emitted at > 320 °C

Under special fire conditions traces of other toxic substances are possible. Formation of further decomposition and oxidation products depends upon the fire conditions.

Advice for fire-fighters
Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:
Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Further accidental release measures:
High risk of slipping due to leakage/spillage of product.

Personal precautions, protective equipment and emergency procedures
No special precautions necessary.

Environmental precautions
No special precautions necessary.

Methods and material for containment and cleaning up
Reclaim for processing if possible. Sweep/shovel up. Place into suitable containers for reuse or disposal in a licensed facility.

7. Handling and Storage

Precautions for safe handling
Avoid inhalation of dusts/mists/vapours.

Protection against fire and explosion:
No explosion proofing necessary.

Conditions for safe storage, including any incompatibilities
The product in undamaged packing need not be stored separately.

Suitable materials for containers: Low density polyethylene (LDPE), High density polyethylene (HDPE), Aluminium, Carbon steel (Iron)

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place. Avoid dust formation, product dust can form an explosive mixture with air.

Storage stability:
Protect against moisture.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

carbon black	ACGIH, US:	TWA value 3 mg/m3 Inhalable fraction ;
	OSHA Z1:	PEL 3.5 mg/m3 ;
copper iodide	ACGIH, US:	TWA value 0.2 mg/m3 fumes/smoke (copper (Cu));
	ACGIH, US:	TWA value 1 mg/m3 Dust and mist (copper (Cu));
	ACGIH, US:	Skin Designation Inhalable fraction (iodine (I)); Danger of cutaneous absorption
	ACGIH, US:	TWA value 0.01 mg/m3 Inhalable fraction (iodine (I));
Wollastonite (Ca(SiO3))	ACGIH, US:	TWA value 1 mg/m3 Inhalable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.
	ACGIH, US:	TWA value 1 mg/m3 Inhalable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.
crystalline silica	OSHA Z1:	PEL 0.05 mg/m3 Respirable dust ;
	OSHA Z3:	TWA value 2.4 millions of particles per cubic foot of air Respirable ; The exposure limit is calculated from the equation, 250/(%SiO2+5), using a value of 100% SiO2. Lower percentages of SiO2 will yield higher exposure limits.
	OSHA Z3:	TWA value 0.1 mg/m3 Respirable ; The exposure limit is calculated from the equation, 10mg/m3)/(%SiO2+2), using a value of 100% SiO2. Lower percentages of SiO2 will yield higher exposure limits.
	OSHA, US:	TWA value 0.05 mg/m3 (Respirable dust);
	OSHA, US:	OSHA Action level 0.025 mg/m3 (Respirable dust);

Advice on system design:
Provide local exhaust ventilation to control dusts/vapours.

Personal protective equipment

Respiratory protection:
Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) particulate respirator.

Hand protection:
Wear gloves to prevent contact during mechanical processing and/or hot melt conditions.

Eye protection:
Tightly fitting safety goggles (chemical goggles).

Body protection:
Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:
Wear protective clothing to prevent contact during mechanical processing and/or hot melt conditions. Avoid inhalation of dust. Wash soiled clothing immediately.

9. Physical and Chemical Properties

Form:	pellets	
Odour:	odourless	
Odour threshold:	not applicable	
Colour:	black	
pH value:	not applicable	
Freezing point:	not applicable	
Melting point:	No data available.	
Boiling point:	The substance / product decomposes therefore not determined.	
Sublimation point:	No applicable information available.	
Flash point:	> 400 °C	
Flammability:	not self-igniting	(derived from flash point)
Flammability of Aerosol Products:	not applicable, the product does not form flammable aerosoles	
Lower explosion limit:	For solids not relevant for classification and labelling.	
Upper explosion limit:	For solids not relevant for classification and labelling.	
Autoignition:	> 400 °C	(ASTM D1929)
Vapour pressure:	not applicable	
Density:	18.4 g/cm3 (20 °C)	(EN ISO 1183-1)
Relative density:	Study does not need to be conducted.	
Bulk density:	600 kg/m3	
Vapour density:	not applicable	
Partitioning coefficient n-octanol/water (log Pow):	not applicable	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	> 320 °C (TGA)	
Viscosity, dynamic:	not applicable, the product is a solid	
Viscosity, kinematic:	not applicable, the product is a solid	
Particle size:	spheroidal	
Solubility in water:	(20 °C, 1,013 hPa) insoluble	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	No applicable information available.	
Evaporation rate:	The product is a non-volatile solid.	

10. Stability and Reactivity

Reactivity
No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:
No corrosive effect on metal.

Oxidizing properties:
not fire-propagating

Chemical stability
The product is stable if stored and handled as prescribed/indicated.
The product is chemically stable.

Possibility of hazardous reactions
The product is chemically stable.
No hazardous reactions known.

Conditions to avoid
Temperature: > 320 degrees Celsius
See SDS section 7 - Handling and storage.

Incompatible materials
No substances known that should be avoided.

Hazardous decomposition products

Decomposition products:
Possible decomposition products: Ammonium hydroxide, carbon monoxide, carbon dioxide, caprolactam, hydrogen cyanide, nitriles

Thermal decomposition:
> 320 °C (TGA)

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity
Assessment of acute toxicity: Contact with molten product may cause thermal burns. The resin in pelleted form poses a low hazard.

Inhalation
Not inhalable due to the physico-chemical properties of the product.

Assessment other acute effects
No applicable information available.

Irritation / corrosion
Assessment of irritating effects: Thermal decomposition products of the substance can irritate the eyes, skin, and respiratory tract.

Sensitization

Assessment of sensitization: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Aspiration Hazard
No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity
Assessment of repeated dose toxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Genetic toxicity
Assessment of mutagenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Carcinogenicity
Assessment of carcinogenicity: The substance caused cancer in animal studies.

Information on: carbon black
Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term animal studies in which the substance was given by inhalation in high concentrations, a carcinogenic effect was observed. A clear indication of an increased risk of cancer in humans has so far not been shown. No carcinogenic potential can be deduced from other studies with rats and mice.

Information on: crystalline silica
Assessment of carcinogenicity: May cause cancer by inhalation. The substance was found to cause cancer in animal experiments. Epidemiological studies stated a carcinogenic activity also in humans. The substance and its compounds in the form of respirable dusts/aerosolsis classified by the German MAK commision as a category 1 carcinogen (substances that cause cancer to humans). The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen.
NTP listed carcinogen
OSHA (Occupational Safety and Health Administration) has classified this substance as carcinogenic.

Reproductive toxicity
Assessment of reproduction toxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Teratogenicity
Assessment of teratogenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Other Information
The product has not been tested. The statement has been derived from the properties of the individual components.

12. Ecological Information

Toxicity

Aquatic toxicity
Assessment of aquatic toxicity:
The product has not been tested. The statement has been derived from the structure of the product. There is a high probability that the product is not acutely harmful to aquatic organisms.

Persistence and degradability

Assessment biodegradation and elimination (H2O)
Experience shows this product to be inert and non-degradable.
The product is virtually insoluble in water and can thus be separated from water mechanically in suitable effluent treatment plants.

Elimination information

Poorly biodegradable.

Assessment of stability in water
According to structural properties, hydrolysis is not expected/probable.

Bioaccumulative potential

Assessment bioaccumulation potential
Does not significantly accumulate in organisms.

Bioaccumulation potential
The product will not be readily bioavailable due to its consistency and insolubility in water.

Mobility in soil

Assessment transport between environmental compartments
Adsorption to solid soil phase is not expected.

Additional information

Adsorbable organically-bound halogen(AOX):
This product contains no organically-bound halogen.

Other ecotoxicological advice:
The product is a polymeric compound.

13. Disposal considerations

Waste disposal of substance:
Check for possible recycling. Dispose of in a licensed facility. Observe all local regulations.

Container disposal:
Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport
USDOT

Not classified as a dangerous good under transport regulations

Sea transport
IMDG

Not classified as a dangerous good under transport regulations

Air transport
IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:
Chemical TSCA, US

Contains exempted, non-listed substance (e.g. polymer exemption rule under TSCA 40 CFR 723.250) (commercial status of other substances is active).
For polymers, individual legal entity registration required to import.

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

State regulations

State RTK	CAS Number	Chemical name
NJ	1333-86-4	carbon black
	14808-60-7	crystalline silica
PA	1333-86-4	carbon black
	68187-11-1	Cobalt chromite blue green spinel

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including SILICA, CRYSTALLINE (AIRBORNE PARTICLES OF RESPIRABLE SIZE), which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:
Health: 2 Fire: 1 Reactivity: 0 Special:

HMIS III rating
Health: 2¤ Flammability: 1 Physical hazard: 0

16. Other Information

SDS Prepared by:
BASF NA Product Regulations
SDS Prepared on: 2024/08/22

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

ULTRAMID®B3GM35 BLACK 23335 POLYAMIDE is a registered trademark of BASF Corporation or BASF SE
IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET