We create chemistry

Safety Data Sheet
Na-Methylate sol. 25 %

1. Identification

Product identifier used on the label

Na-Methylate sol. 25 %

Recommended use of the chemical and restriction on use

Recommended use*: Chemical
Recommended use*: Intermediate; process chemical; catalyst
Unsuitable for use: Not intended for sale to or use by the general public.

* The “Recommended use” identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

24 Hour Emergency Response Information
CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family:	alcohol
Synonyms:	Sodium Methylate Solution 25% Sodium Methoxide Solution 25%

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Flam. Liq.	3	Flammable liquids
Met. Corr.	1	Corrosive to metals

Acute Tox.	3 (Inhalation - vapour)	Acute toxicity
Acute Tox.	3 (oral)	Acute toxicity
Acute Tox.	3 (dermal)	Acute toxicity
Skin Corr.	1A	Skin corrosion
Eye Dam./Irrit.	1	Serious eye damage/eye irritation
STOT SE	1	Specific target organ toxicity — single exposure

Label elements

Pictogram:

Signal Word:
Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H301 + H311 + H331	Toxic if swallowed, in contact with skin or if inhaled.
H370	Causes damage to organs (Central nervous system, Optic nerve).

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P271	Use only outdoors or in a well-ventilated area.
P260	Do not breathe mist or vapour or spray.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take action to prevent static discharges.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P264	Wash contaminated body parts thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P234	Keep only in original packaging.
P242	Use non-sparking tools.
P240	Ground and bond container and receiving equipment.

Precautionary Statements (Response):

P310	Immediately call a POISON CENTER or physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P361 + P364	Take off immediately all contaminated clothing and wash it before reuse.
P301 + P330 + P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P390	Absorb spillage to prevent material damage.
P370 + P378	In case of fire: Use … to extinguish.

Precautionary Statements (Storage):

P233	Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P406	Store in a corrosion-resistant container with a resistant inner liner.

Precautionary Statements (Disposal):

P501	Dispose of contents/container in accordance with local regulations.

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered. If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Methanol
CAS Number: 67-56-1
Content (W/W): >= 50.0 - <= 100.0%
Synonym: Methanol; Methyl alcohol

sodium methanolate
CAS Number: 124-41-4
Content (W/W): >= 20.0 - < 50.0%
Synonym: Methanol, sodium salt; Sodium methanolate

Sodium Hydroxide
CAS Number: 1310-73-2
Content (W/W): > 0.0 - < 1.0%
Synonym: Sodium hydroxide; Caustic soda

4. First-Aid Measures

Description of first aid measures

General advice:
First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:
Keep patient calm, remove to fresh air, seek medical attention. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

If on skin:
Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

If in eyes:
Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:
Do not induce vomiting. Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: skin corrosion, irritates the eyes and respiratory tract, blindness, Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

Information on: Methanol
Symptoms: Overexposure may cause:, headache, dizziness, respiratory disorders, nausea, acidosis, coma, blindness

Information on: sodium methanolate
Symptoms: Overexposure may cause:, corneal injury, skin corrosion, severe pain, coughing, respiratory disorders, dyspnea, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps
---
Hazards: No data available.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:	Adminstration of ethanol resp. 4-methylpyrazole. Symptomatic treatment (decontamination, vital functions). The contamination by the substance may be ascertained by determining the content in the blood and/or urine.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
dry powder, Dry sand, alcohol-resistant foam

Unsuitable extinguishing media for safety reasons:
water, carbon dioxide

Special hazards arising from the substance or mixture
Hazards during fire-fighting:
Risk of exothermic reaction. May release highly flammable and/or corrosive gases/vapours.

Advice for fire-fighters
Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:
Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

6. Accidental release measures

Further accidental release measures:
Release of substance/product can cause fire or explosion.

Personal precautions, protective equipment and emergency procedures
Sources of ignition should be kept well clear. Use personal protective clothing. Avoid inhalation. Avoid contact with skin and eyes.

Environmental precautions
Substance/product is RCRA hazardous due to its properties.

Methods and material for containment and cleaning up
Spills should be contained and placed in suitable containers for disposal.

7. Handling and Storage

Precautions for safe handling
Ensure thorough ventilation of stores and work areas. Protect against moisture. Protect against heat.

Protection against fire and explosion:
Avoid all sources of ignition: heat, sparks, open flame. Take precautionary measures against static discharges. Use antistatic tools. Render equipment and apparatus inert (nitrogen, inert gases) and ground before putting into operation. Fire extinguishers should be kept handy.

Conditions for safe storage, including any incompatibilities
Segregate from acids and acid forming substances. Keep away from water.

Suitable materials for containers: Carbon steel (Iron), Stainless steel 1.4401, Stainless steel 1.4301 (V2), High density polyethylene (HDPE), glass, Low density polyethylene (LDPE), Stainless steel 1.4541, Stainless steel 1.4571
Unsuitable materials for containers: Aluminium, Galvanized carbon steel (Zinc), Paper/Fibreboard

Further information on storage conditions: Keep container tightly closed in a cool, well-ventilated place. Keep under dry nitrogen. Protect against moisture. Protect against heat. Keep away from sources of ignition - No smoking.

Storage stability:
Protect against moisture.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Methanol	ACGIH, US:	TWA value 200 ppm ;
	ACGIH, US:	STEL value 250 ppm ;
	OSHA Z1:	PEL 200 ppm 260 mg/m3 ;
	ACGIH, US:	Skin Designation ; Danger of cutaneous absorption
	ACGIH, US:	Skin Designation ; Danger of cutaneous absorption
	NIO ID, US:	IDLH 6,000 ppm ; IDLH values based on the 1994 Revised Criteria
	NIO ID, US:	LEL 6.0 % ;
Sodium Hydroxide	ACGIH, US:	CLV 2 mg/m3 ;
	OSHA Z1:	PEL 2 mg/m3 ;
	NIO ID, US:	IDLH 10 mg/m3 ; IDLH values based on the 1994 Revised Criteria

Advice on system design:
Provide local exhaust ventilation to control vapours/mists.

Personal protective equipment

Respiratory protection:
Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator. Do not exceed the maximum use concentration for the respirator facepiece/cartridge combination. For emergency or non-routine, high exposure situations, use a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.

Observe OSHA regulations for respirator use (29 CFR 1910.134).

Hand protection:
Chemical resistant protective gloves should be worn to prevent all skin contact., Suitable materials may include, butyl rubber, fluoroelastomer (Viton), nitrile rubber (Buna N), chloroprene rubber (Neoprene), polyvinylchloride (Pylox), Consult with glove manufacturer for testing data., Protective glove selection must be based on the user's assessment of the workplace hazards.

Eye protection:
Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.

Body protection:
Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

General safety and hygiene measures:
Eye wash fountains and safety showers must be easily accessible. Wear protective clothing as necessary to prevent contact.

9. Physical and Chemical Properties

Form:	liquid
Odour:	alcohol-like
Odour threshold:	Not determined due to potential health hazard by inhalation.

Colour:	colourless to yellowish	
pH value:	approx. 11	(ISO 1148)
crystallization temperature:	-2 °C	
Melting point:	No data available.	
Freezing point:	No data available.	
Boiling point:	85 °C (1,013 mbar)	
Flash point:	29 °C	(DIN 51755)
Flammability:	Flammable liquid and vapour.	(derived from flash - and boiling point)
Lower explosion limit:	For liquids not relevant for classification and labelling.	
Information on: Methanol		
Lower explosion limit:	5.5 %(V)	

Upper explosion limit:	For liquids not relevant for classification and labelling.	
Information on: Methanol		
Upper explosion limit:	36.5 %(V)	

Autoignition:	not determined	
Information on: Methanol		
Autoignition:	455 °C	

Vapour pressure:	approx. 46 mbar (20 °C) approx. 220 mbar (50 °C)	
Density:	0.944 g/cm3 (20 °C)	(ISO 2811-3)
	0.918 g/cm3 (50 °C)	(ISO 2811-3)
Relative density:	not determined	
Bulk density:	not applicable	
Vapour density:	not determined	
Partitioning coefficient n-octanol/water (log Pow):	not applicable for mixtures	
Information on: Methanol		
Partitioning coefficient n-octanol/water (log Pow):	-0.77 (20 °C) Literature data.	(measured)

Self-ignition temperature:	not self-igniting	
Thermal decomposition:	It is not a self-decompositionable substance.	
Viscosity, dynamic:	27 mPa.s (20 °C)	
Viscosity, kinematic:	not determined	
Solubility in water:	(20 °C) hydrolyzes	
Miscibility with water:	(15 °C) Reacts with water.	
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.	

10. Stability and Reactivity

Reactivity

Corrosion to metals:
Corrosive effect on: Aluminium

Oxidizing properties:
not fire-propagating

Formation of flammable gases:	Remarks:	The product liberates flammable gases in contact with water.

Chemical stability
The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions
The product is chemically stable.
Violent reaction under influence of oxidizing agents. Reacts with water and acids.

Conditions to avoid
Avoid all sources of ignition: heat, sparks, open flame. Avoid contact with air. Avoid moisture.

Incompatible materials
carbon dioxide, water, acids, substances with an acid reaction, light metals

Hazardous decomposition products

Decomposition products:
Hazardous decomposition products: Sodium Hydroxide, Methanol

Thermal decomposition:
It is not a self-decompositionable substance.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity
Assessment of acute toxicity: Of pronounced toxicity after single ingestion. Of pronounced toxicity after short-term skin contact. Of pronounced toxicity after short-term inhalation. The toxicity of the product is based on its corrosivity.

Information on: Methanol
Assessment of acute toxicity:Of high toxicity after single ingestion. Of high toxicity after short-term inhalation. Of high toxicity after short-term skin contact.

Oral

Information on: sodium methanolate
Type of value: LD50
Species: rat (male/female)
Value: 1,687 mg/kg (OECD Guideline 401)
An aqueous solution was tested.

Information on: Methanol
Type of value: LD50
Species: rat
Value: > 1187 - 2769 mg/kg (BASF-Test)

Inhalation
Species: rat
Value: (IRT)
Exposure time: 8 h
No mortality within the stated exposition time as shown in animal studies. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: Methanol
Type of value: LC50
Species: rat (male/female)
Value: 128 mg/l (BASF-Test)
Exposure time: 4 h
The vapour was tested.

Dermal

Information on: Methanol
Type of value: LD50
Species: rabbit
Value: 17100 mg/kg (other)

Assessment other acute effects
Assessment of STOT single:
A single exposure to small quantities may have toxic effects on specific organs.

Irritation / corrosion
Assessment of irritating effects: Highly corrosive! Damages skin and eyes.

Information on: sodium methanolate
Assessment of irritating effects: Corrosive! Damages skin and eyes.

Skin
Species: rabbit
Result: Corrosive.
Method: BASF-Test

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Eye
Species: rabbit
Result: irreversible damage
Method: BASF-Test
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Sensitization
Assessment of sensitization: As the substance is corrosive, conducting sensitization studies is not feasible.

Information on: sodium methanolate
Assessment of sensitization:
As the substance is corrosive, conducting sensitization studies is not feasible. The chemical structure does not suggest a sensitizing effect.

Information on: Methanol
Assessment of sensitization:
Skin sensitizing effects were not observed in animal studies.

Aspiration Hazard
Toxic if swallowed.

Chronic Toxicity/Effects

Repeated dose toxicity
Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.

Information on: Methanol
Assessment of repeated dose toxicity: The substance may cause blindness after repeated ingestion. The substance may cause blindness after repeated inhalation.

Genetic toxicity
Assessment of mutagenicity: Based on the ingredients, there is no suspicion of a mutagenic effect.

Carcinogenicity
Assessment of carcinogenicity: Based on the ingredients there is no suspicion of a carcinogenic effect in humans.
Not classified, due to lack of data.

Reproductive toxicity
Assessment of reproduction toxicity: Based on the ingredients, there is no suspicion of a toxic effect on reproduction.
Not classified, due to lack of data.

Teratogenicity
Assessment of teratogenicity: Based on the ingredients, there is no suspicion of a teratogenic effect.
Not classified, due to lack of data.

Experiences in humans

Information on: Methanol
---

12. Ecological Information

Toxicity

Aquatic toxicity
Assessment of aquatic toxicity:
The product has not been tested. The statement has been derived from the properties of the hydrolysis products.

Toxicity to fish

Information on: Sodium Hydroxide
LC50 (96 h) 125 mg/l, Gambusia affinis (other, static)
The product will cause changes in the pH value of the test system. The result refers to an unneutralized sample. Literature data.

Information on: Methanol
LC50 (96 h) 15,400 mg/l, Lepomis macrochirus (other, Flow through.)

Persistence and degradability

Assessment biodegradation and elimination (H2O)
The product is unstable in water. The elimination data also refer to products of hydrolysis.

Elimination information

Information on: Methanol
95 % BOD of the ThOD (20 d) (OECD 301D; 92/69/EWG, C.4-E) (aerobic, activated sludge, domestic, non-adapted) Readily biodegradable (according to OECD criteria).

Mobility in soil

Assessment transport between environmental compartments
Adsorption to solid soil phase is not expected.

Additional information

Other ecotoxicological advice:
Due to the pH-value of the product, neutralization is generally required before discharging sewage into treatment plants. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations. Do not release untreated into natural waters.

13. Disposal considerations

Waste disposal of substance:
Incinerate or dispose of in a RCRA-licensed facility. Do not discharge into waterways or sewer systems without proper authorization.

Container disposal:
Empty containers with less than 1 inch of residue may be landfilled at a licensed facility. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers. If containers are not empty, they must be disposed of in a RCRA-licensed facility.

14. Transport Information

Land transport
USDOT

Hazard class:	3
Packing group:	III
ID number:	UN 1289
Hazard label:	3, 8
Proper shipping name:	SODIUM METHYLATE SOLUTION

Sea transport
IMDG

Hazard class:	3
Packing group:	III
ID number:	UN 1289
Hazard label:	3, 8
Marine pollutant:	NO
Proper shipping name:	SODIUM METHYLATE SOLUTION

Air transport
IATA/ICAO

Hazard class:	3
Packing group:	III
ID number:	UN 1289
Hazard label:	3, 8
Proper shipping name:	SODIUM METHYLATE SOLUTION

15. Regulatory Information

Federal Regulations

Registration status:
Chemical TSCA, US

All substances are TSCA listed and active.

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

EPCRA 313:

CAS Number	Chemical name
67-56-1	Methanol
7439-97-6	mercury

CERCLA RQ	CAS Number	Chemical name
5000 LBS	67-56-1	Methanol
1000 LBS	124-41-4	sodium methanolate

Reportable Quantity for release: 100 lb

State regulations

State RTK	CAS Number	Chemical name
NJ	124-41-4	sodium methanolate
	67-56-1	Methanol
PA	67-56-1	Methanol
	124-41-4	sodium methanolate

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including METHANOL, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:
Health: 3 Fire: 3 Reactivity: 1 Special:

16. Other Information

SDS Prepared by:
BASF NA Product Regulations
SDS Prepared on: 2025/03/07

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET