Safety Data Sheet
Neopor® F 5300 Plus BMB

1. Identification

Product identifier used on the label

Neopor® F 5300 Plus BMB

Recommended use of the chemical and restriction on use

Recommended use*: Expanding-agent containing plastic for the production of foam plastics
Recommended use*: for industrial use only; Expanding-agent containing plastic for the production of foam plastics
Unsuitable for use: Uses other than recommended; Not intended for sale to or use by the general public.

* The “Recommended use” identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

24 Hour Emergency Response Information
CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: Preparation based on: polystyrene, propellant, flame retardant

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

No need for classification according to GHS criteria for this product.

Label elements

The product does not require a hazard warning label in accordance with GHS criteria.

Hazards not otherwise classified

May cause some eye irritation which should cease after removal of the product. In use may form flammable/explosive vapour-air mixture.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Pentane
CAS Number: 109-66-0
Content (W/W): 3.0 - < 7.0%
Synonym: n-Pentan

Graphite
CAS Number: 7782-42-5
Content (W/W): 3.0 - < 7.0%
Synonym: No data available.

isopentane
CAS Number: 78-78-4
Content (W/W): 0.3 - < 3.0%
Synonym: 2-Methylbutane

Styrene
CAS Number: 100-42-5
Content (W/W): 0.0 - < 0.2%
Synonym: Vinylbenzene; Styrene, Ethenylbenzene

4. First-Aid Measures

Description of first aid measures

General advice:
If adverse health effects develop seek medical attention.

If inhaled:
Keep patient calm, remove to fresh air. If difficulties occur: Seek medical attention.

If on skin:
Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

If in eyes:
In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

If swallowed:
No hazards anticipated. Rinse mouth and then drink 200-300 ml of water. If difficulties occur: Seek medical attention.

Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions.

Most important symptoms and effects, both acute and delayed

Symptoms: headache, dizziness, coordination disorder, dazed state, Eye irritation, skin irritation
(Further) symptoms and / or effects are not known so far

Information on: Pentane
Symptoms: Overexposure may cause:, unconsciousness

Information on: isopentane
Symptoms: Overexposure may cause:, unconsciousness, death, weakness, coordination disorder, nausea, headache, dizziness
---

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:	Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
water spray, foam, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:
water jet

Additional information:
Use extinguishing measures to suit surroundings.

Special hazards arising from the substance or mixture
Hazards during fire-fighting:
carbon monoxide, carbon dioxide, Styrene, aliphatic hydrocarbons
The substances/groups of substances mentioned can be released in case of fire.

Advice for fire-fighters
Protective equipment for fire-fighting:
Wear self-contained breathing apparatus and chemical-protective clothing.

Further information:
Burns with dense emission of soot. Containers/tanks should be cooled with water spray. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Flammable concentrations of propellant may accumulate on storage in closed containers. Product will burn on contact with flame or exposure to high temperature.

6. Accidental release measures

Further accidental release measures:
High risk of slipping due to leakage/spillage of product. Shut off or stop source of leak. Substance/product can form explosive mixture with air.

Personal precautions, protective equipment and emergency procedures

Sources of ignition should be kept well clear. Ensure adequate ventilation. Note that this gas is heavier than air and can spread along the ground in the direction of the wind. Beware of pits and confined spaces. Use antistatic tools.

Environmental precautions

Do not allow to enter drains or waterways. Discharge into the environment must be avoided.

Methods and material for containment and cleaning up

For small amounts: Pick up with suitable appliance and dispose of.
For large amounts: Pick up with suitable appliance and dispose of.
Ensure adequate ventilation. Use spark-proof tools and explosion-proof equipment. Avoid sources of ignition. Dispose of in accordance with national, state and local regulations.

7. Handling and Storage

Precautions for safe handling

Upon delivery, trailer and/or container should be opened and allowed to vent for a minimum of one (1) hour before unloading. Keep away from sources of ignition - No smoking. Protect against heat. Protect from direct sunlight. Ensure adequate ventilation. Provide good room ventilation even at ground level (vapours are heavier than air). The substance/product in bead or expanded form generates static charges during handling which are difficult to dissipate due to the insulating properties. Take precautionary measures against static discharges. Use antistatic tools. Containers should be opened carefully in well-ventilated areas to avoid static discharge. Maintain air circulation and ventilation at a minimum rate of six air changes per hour to prevent the formation of flammable concentrations. The substance/ product may be handled only by appropriately trained personnel.

Protection against fire and explosion:
The product is combustible. Vapours may form ignitable mixture with air. Keep away from heat. Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy. Avoid all sources of ignition: heat, sparks, open flame. Containers should be earthed during decanting operations. It is recommended that all conductive parts of the machinery are grounded. All parts of the plant and equipment should be electrically bonded together and grounded. Electrical continuity should be checked at regular intervals. Higher line velocity can increase the build-up of static electric charge. Avoid flammable gas mixtures. Ensure an efficient ventilation (at least one air change per hour). Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition. Because of danger of explosion, avoid vapours reaching the cellar, sewage water and pits. Empty containers may contain flammable residue.

Conditions for safe storage, including any incompatibilities

Segregate from strong oxidizing agents.

Suitable materials for containers: High density polyethylene (HDPE), Low density polyethylene (LDPE), Paper/Fibreboard, Stove-lacquer RDL 50, Stove-lacquer R 78433, Carbon steel (Iron),

Stainless steel 1.4301 (V2), Stainless steel 1.4361, Stainless steel 1.4401, Stainless steel 1.4439, Stainless steel 1.4539, Stainless steel 1.4541, Stainless steel 1.4571, Stainless steel 1.4306 (V2A), Stainless steel 1.4307, Stainless steel 1.4311, Stainless steel 1.4404, Polyamide (PA)

Further information on storage conditions: Protect against heat. Keep away from sources of ignition - No smoking. Keep only in the original container. Keep container tightly closed. Protect against moisture. Avoid direct sunlight. Protect containers from physical damage. The authority permits and storage regulations must be observed. Store protected against freezing. Keep tanks under inert gas. Air monitoring should be used to alert any build up of explosive mixtures. Ventilate freight container with open door for 30 minutes before unloading.

Storage stability:
Keep container tightly closed and dry.
Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

isopentane	ACGIH, US:	TWA value 1,000 ppm ;
Pentane	ACGIH, US:	TWA value 1,000 ppm ;
	OSHA Z1:	PEL 1,000 ppm 2,950 mg/m3 ;
Graphite	ACGIH, US:	TWA value 2 mg/m3 Respirable fraction ;
	OSHA Z3:	TWA value 15 millions of particles per cubic foot of air ;
	OSHA Z1:	PEL 5 mg/m3 Respirable fraction ;
	OSHA Z1:	PEL 15 mg/m3 Total dust ;

Advice on system design:
Provide local exhaust ventilation to maintain recommended P.E.L.

Personal protective equipment

Respiratory protection:
Respiratory protection may not be required under normal operating conditions if adequate ventilation is provided. Wear respiratory protection if ventilation is inadequate.

Hand protection:
Chemical resistant protective gloves, non-static gloves (e.g. of leather)

Eye protection:
Safety glasses with side-shields. Tightly fitting safety goggles (chemical goggles).

Body protection:
Anti-static protective clothing, Antistatic safety shoes

General safety and hygiene measures:
Avoid inhalation of dusts/mists/vapours. Ensure adequate ventilation. When using do not eat or drink. When using do not smoke.

9. Physical and Chemical Properties

Form:	beads	
Odour:	of pentane	
Odour threshold:	No applicable information available.	
Colour:	black	
pH value:	not soluble	
softening temperature:	approx. 160 °F	
Melting point:	No applicable information available.	
Freezing point:	No applicable information available.	
Boiling point:	not applicable	
Sublimation point:	not applicable	
Flash point:	Vapours are flammable.	
Flammability:	not highly flammable	(UN Test N.1 (ready combustible solids))
Lower explosion limit:	Product not examined: Value is calculated from the data of the components.	
Upper explosion limit:	Product not examined: Value is calculated from the data of the components.	
Autoignition:	285 °C	(DIN 51794)
Vapour pressure:	not applicable	
Density:	approx. 1.02 - 1.05 g/cm3 (20 °C)	
Relative density:	1.02 - 1.05 (20 °C)	
Bulk density:	approx. 650 kg/m3 (20 °C)	
Vapour density:	2.5 Heavier than air.	
Partitioning coefficient n-octanol/water (log Pow):	not applicable	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	approx. 220 °C No decomposition if used as directed.	
Viscosity, dynamic:	not applicable, the product is a solid	
Viscosity, kinematic:	not applicable, the product is a solid	
Solubility in water:	not soluble	
Miscibility with water:	immiscible	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	soluble solvent(s): aromatic hydrocarbons, ketones, organic solvents,	
Molar mass:	No data available.	
Evaporation rate:	The product is a non-volatile solid.	

10. Stability and Reactivity

Reactivity
No hazardous reactions if stored and handled as prescribed/indicated., Vapours may form explosive mixture with air.

Corrosion to metals:

No corrosive effect on metal.

Oxidizing properties:
not fire-propagating

Minimum ignition energy:
0.28 mJ
The product is not capable of a dust explosion.

Chemical stability
The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions
Formation of explosive gas/air mixtures.

Conditions to avoid
> 70 degrees Celsius
Avoid all sources of ignition: heat, sparks, open flame. Avoid direct sunlight. Avoid electro-static discharge.

Incompatible materials
explosive substances according UN transport regulations class 1, Propellant release will be boosted with increasing temperature.

Hazardous decomposition products

Decomposition products:
Possible thermal decomposition products: Pentane, styrene monomers, Heated product evolves combustible vapours.

Thermal decomposition:
approx. 220 °C
No decomposition if used as directed.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity
Assessment of acute toxicity: Not expected to be acutely toxic. Inhalation of vapors may result in headache, dizziness, or other central nervous system effects. The product has not been tested. The statement has been derived from the properties of the individual components.

Oral
Type of value: ATE
Value: > 2,000 mg/kg
The product has not been tested. The statement has been derived from the properties of the individual components.

Inhalation
Type of value: ATE
Value: > 5 mg/l
The product has not been tested. The statement has been derived from the properties of the individual components.

Dermal
Type of value: ATE
Value: > 2,000 mg/kg
The product has not been tested. The statement has been derived from the properties of the individual components.

Assessment other acute effects
No applicable information available.

Irritation / corrosion
Assessment of irritating effects: Irritation is possible when the product comes in contact with the skin, respiratory tract or the eyes.

Information on: isopentane
Assessment of irritating effects: Not irritating to eyes and skin. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Skin
Prolonged contact with the product can result in skin irritation.

Eye
Similar findings as for skin apply to eyes.

Sensitization
Assessment of sensitization: There is no evidence of a skin-sensitizing potential.

Chronic Toxicity/Effects

Repeated dose toxicity
Assessment of repeated dose toxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Genetic toxicity
Assessment of mutagenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Carcinogenicity
Assessment of carcinogenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Reproductive toxicity
Assessment of reproduction toxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Teratogenicity

Assessment of teratogenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Other Information
No reports of ill effects provided product was correctly handled and processed.

12. Ecological Information

Toxicity

Aquatic toxicity
Assessment of aquatic toxicity:
There is a high probability that the product is not acutely harmful to aquatic organisms. No toxic effects occur within the range of solubility.

Aquatic invertebrates
EC50 (48 h) > 100 mg/l, Daphnia magna (OECD Guideline 202, part 1, static)
Nominal concentration. The product has low solubility in the test medium. An eluate has been tested. No toxic effects occur within the range of solubility. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aquatic plants
EC50 (72 h) > 100 mg/l (growth rate), Desmodesmus subspicatus (OECD Guideline 201, static)
Nominal concentration. The product has low solubility in the test medium. An eluate has been tested. No toxic effects occur within the range of solubility. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Persistence and degradability

Assessment biodegradation and elimination (H2O)
On the basis of the data available concerning eliminability/degradation and bioaccumulation potential, longer-term harm to the environment is improbable. No data available concerning biodegradation and elimination.

In accordance with the required stability the product is not readily biodegradable. The product has not been tested. The statement has been derived from the structure of the product. The product is virtually insoluble in water and can thus be separated from water mechanically in suitable effluent treatment plants.

Elimination information

Non-biodegradable.

Bioaccumulative potential

Bioaccumulation potential
The product will not be readily bioavailable due to its consistency and insolubility in water.

Mobility in soil

Assessment transport between environmental compartments
Study scientifically not justified.

Additional information

Add. remarks environm. fate & pathway:
Because of the product's consistency and low water solubility, bioavailability is improbable.

Other ecotoxicological advice:
At the present state of knowledge, no negative ecological effects are expected. No toxic effects occur within the range of solubility.

Information on: Pentane
Other ecotoxicological advice:
The substance has a very low Global Warming Potential and no Ozone Depleting Potential.
---

13. Disposal considerations

Waste disposal of substance:
This product is not regulated by RCRA. This product is not regulated by CERCLA ('Superfund'). Dispose of in accordance with national, state and local regulations. Do not discharge into waterways or sewer systems without proper authorization.

Container disposal:
Remove all packaging for recovery or disposal

14. Transport Information

Land transport
USDOT

Hazard class:	9
Packing group:	III
ID number:	UN 2211
Hazard label:	9
Proper shipping name:	POLYMERIC BEADS, EXPANDABLE

Sea transport
IMDG

Hazard class:	9
Packing group:	III
ID number:	UN 2211
Hazard label:	9
Marine pollutant:	NO
Proper shipping name:	POLYMERIC BEADS, EXPANDABLE

Air transport
IATA/ICAO

Hazard class:	9
Packing group:	III
ID number:	UN 2211
Hazard label:	9
Proper shipping name:	POLYMERIC BEADS, EXPANDABLE

Further information
DOT: This product is regulated if the amount in a single receptacle exceeds the Reportable Quantity (RQ). Please refer to Section 15 of this SDS for the RQ for this product.

15. Regulatory Information

Federal Regulations

Registration status:
Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

CERCLA RQ	CAS Number	Chemical name
5000 LBS	98-82-8	cumene
1000 LBS	100-42-5; 100-41-4	Styrene; ethylbenzene
100 LBS	74-85-1; 109-66-0; 78-78-4	ethene; Pentane; isopentane
100 LBS	78-78-4; 109-66-0	isopentane; Pentane
10 LBS	71-43-2	Benzene

State regulations

State RTK	CAS Number	Chemical name
PA	78-78-4	isopentane
	109-66-0	Pentane
NJ	78-78-4	isopentane
	100-42-5	Styrene
	109-66-0	Pentane

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including BENZENE, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:
Health: 1 Fire: 2 Reactivity: 0 Special:

HMIS III rating
Health: 1 Flammability: 2 Physical hazard: 0

16. Other Information

SDS Prepared by:
BASF NA Product Regulations
SDS Prepared on: 2022/12/15

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our

operations on society and the environment during production, storage, transport, use and disposal of our products.

Neopor® F 5300 Plus BMB is a registered trademark of BASF Corporation or BASF SE
IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. BASF CORPORATION WILL NOT MAKE ITS PRODUCTS AVAILABLE TO CUSTOMERS FOR USE IN THE MANUFACTURE OF MEDICAL DEVICES WHICH ARE INTENDED FOR PERMANENT IMPLANTATION IN THE HUMAN BODY OR IN PERMANENT CONTACT WITH INTERNAL BODILY TISSUES OR FLUIDS.
This product is of industrial quality and unless otherwise specified or agreed intended exclusively for industrial use.

END OF DATA SHEET