We create chemistry

# Safety Data Sheet
## BUTYL ACRYLATE BMB



## 1. Identification

### Product identifier used on the label

# BUTYL ACRYLATE BMB

### Recommended use of the chemical and restriction on use

Recommended use*: Monomer for manufacturing of polymers
Recommended use*: Monomer.; Intermediate
Unsuitable for use: cosmetics; Pharmaceutical

* The “Recommended use” identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

### Details of the supplier of the safety data sheet

Company:
BASF Mexicana S.A. de C.V.
Av. Insurgentes Sur 975
Col. CD. De Los Deportes,
C.P. 03710 Ciudad de México
MÉXICO

Telephone: +52 55 5325 2600

### Emergency telephone number

24 Hour Emergency Response Information
SETIQ: 1800-00-214-(Rep. Mexicana) or 55-59-15-88 (CDMX)
Telephone: +1-800-849-5204 or +1-833-229-1000

### Other means of identification

| | |
|---|---|
| Registration number: | Biomass balanced product certified according to REDcert² scheme for the chemical industry, certificate number: 929-35244206 |
| Molecular formula: | C7 H12 O2 |
| Chemical family: | acrylates |
| Synonyms: | Acrylic acid, butyl ester<br>Butyl 2-propenoate; 2-Propenoic acid, butyl ester |

## 2. Hazards Identification

**According to Regulation NOM-018-STPS-2015**

### Classification of the product

| | | |
|---|---|---|
| Flam. Liq. | 3 | Flammable liquids |
| Acute Tox. | 4 (Inhalation - vapour) | Acute toxicity |
| Skin Irrit. | 2 | Skin irritation |
| Eye Irrit. | 2A | Eye irritation |
| Skin Sens. | 1B | Skin sensitization |
| STOT SE | 3 (irritating to respiratory system) | Specific target organ toxicity — single exposure |
| Aquatic Acute | 2 | Hazardous to the aquatic environment - acute |
| Aquatic Chronic | 3 | Hazardous to the aquatic environment - chronic |

### Label elements

Pictogram:

Signal Word:
Warning

Hazard Statement:

| | |
|---|---|
| H226 | Flammable liquid and vapour. |
| H319 | Causes serious eye irritation. |
| H315 | Causes skin irritation. |
| H332 | Harmful if inhaled. |
| H317 | May cause an allergic skin reaction. |
| H335 | May cause respiratory irritation. |
| H412 | Harmful to aquatic life with long lasting effects. |
| H401 | Toxic to aquatic life. |

Precautionary Statements (Prevention):

| | |
|---|---|
| P280 | Wear protective gloves and eye protection or face protection. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P260 | Do not breathe mist or vapour. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P280 | Wear eye protection. |
| P273 | Avoid release to the environment. |
| P243 | Take action to prevent static discharges. |
| P241 | Use explosion-proof electrical, ventilating and lighting equipment. |
| P272 | Contaminated work clothing should not be allowed out of the workplace. |
| P264 | Wash contaminated body parts thoroughly after handling. |
| P242 | Use non-sparking tools. |
| P240 | Ground and bond container and receiving equipment. |

Precautionary Statements (Response):

| | |
|---|---|
| P312 | Call a POISON CENTER or physician if you feel unwell. |
| P305 + P351 + P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P304 + P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| P303 + P361 + P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. |
| P333 + P313 | If skin irritation or rash occurs: Get medical attention. |
| P362 + P364 | Take off contaminated clothing and wash it before reuse. |
| P332 + P313 | If skin irritation occurs: Get medical attention. |
| P337 + P313 | If eye irritation persists: Get medical attention. |
| P370 + P378 | In case of fire: Use water spray, dry powder, foam or carbon dioxide for extinction. |

Precautionary Statements (Storage):

| | |
|---|---|
| P403 + P235 | Store in a well-ventilated place. Keep cool. |
| P233 | Keep container tightly closed. |
| P405 | Store locked up. |

Precautionary Statements (Disposal):

| | |
|---|---|
| P501 | Dispose of contents/container in accordance with local regulations. |

### Hazards not otherwise classified

No applicable information available.

Labeling of special preparations (GHS):
Risk of hazardous polymerization under certain conditions (e.g. elevated temperatures, low inhibitor and oxygen concentration). Do not blanket with nitrogen.

## 3. Composition / Information on Ingredients

**According to Regulation NOM-018-STPS-2015**

n-butyl acrylate
CAS Number: 141-32-2
Content (W/W): >= 99.5 - <= 100.0%
Synonym: 2-Propenoic acid butyl ester; Butyl acrylate

## 4. First-Aid Measures

### Description of first aid measures

**General advice:**
First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

**If inhaled:**
Keep patient calm, remove to fresh air, seek medical attention.

**If on skin:**
Wash thoroughly with soap and water

**If in eyes:**
Hold eyes open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing.

**If swallowed:**
Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

### Most important symptoms and effects, both acute and delayed

Symptoms: Overexposure may cause:, Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps

### Indication of any immediate medical attention and special treatment needed

Note to physician

| | |
|---|---|
| Treatment: | Treat according to symptoms (decontamination, vital functions), no known specific antidote. |

## 5. Fire-Fighting Measures

### Extinguishing media

Suitable extinguishing media:
dry powder, water spray, carbon dioxide, foam

Unsuitable extinguishing media for safety reasons:
water jet

Additional information:
Use extinguishing measures to suit surroundings.

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:
Risk of violent self-polymerization if overheated in a container. Cool endangered containers with water-spray.

The product is combustible. See SDS section 7 - Handling and storage.

### Advice for fire-fighters

Protective equipment for fire-fighting:
Wear a self-contained breathing apparatus. Special protective equipment for firefighters

**Further information:**
Extend fire extinguishing measures to the surroundings. Fight fire from maximum distance. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

In case of a fire in the vicinity a restabilization system should be used if the temperature in the bulk storage-tank reaches 45°C. Evacuate area of all unnecessary personnel. In case of a fire in the vicinity evacuate all personnel in a greater area if the temperature in the bulk storage-tank reaches 60°C.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

**Impact Sensitivity:**
Remarks: Based on the chemical structure there is no shock-sensitivity.

## 6. Accidental release measures

Further accidental release measures:
High risk of slipping due to leakage/spillage of product.

Release of substance/product can cause fire or explosion. Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

### Personal precautions, protective equipment and emergency procedures
Handle in accordance with good industrial hygiene and safety practice.

Avoid all sources of ignition: heat, sparks, open flame. Use antistatic tools.

### Environmental precautions
Discharge into the environment must be avoided.

### Methods and material for containment and cleaning up
For large amounts: Pump off product.
Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations. Ensure adequate ventilation. Suppress gases/vapours/mists with water spray jet. Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Cleaning operations should be carried out only while wearing breathing apparatus. Pick up with suitable appliance and dispose of.

## 7. Handling and Storage

### Precautions for safe handling
The substance/ product may be handled only by appropriately trained personnel. Facility parts must be checked for polymer residues and cleaned on regular basis in order to avoid hazardous reactions.

Ensure thorough ventilation of stores and work areas. Encapsulation or exhaust ventilation required. When filling, transferring, or emptying of containers, adequate local exhaust ventilation is necessary. Vent waste air to atmosphere only through suitable separators. Check the condition of seals and connector screw threads.

The temperatures which must be avoided are to be considered. Protect against heat. Protect from direct sunlight. Protect contents from the effects of light. Do not open warm or swollen product containers. Remove persons to safety and alert fire brigade.

Ensure adequate inhibitor and dissolved oxygen level.

Avoid inhalation of dusts/mists/vapours. Avoid aerosol formation. Avoid all direct contact with the substance/product.

Protection against fire and explosion:
Avoid all sources of ignition: heat, sparks, open flame. Substance/product can form explosive mixture with air. Ground all transfer equipment properly to prevent electrostatic discharge. It is recommended that all conductive parts of the machinery are grounded. Explosion-proof equipment is not necessary when loading and processing of the product takes place at a minimum of 5 °C below the flash point.

Heated containers should be cooled to prevent polymerization. If exposed to fire, keep containers cool by spraying with water. Emergency cooling must be provided for the eventuality of a fire in the vicinity.

Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

### Conditions for safe storage, including any incompatibilities
No applicable information available.

Further information on storage conditions: Prior to storage ensure that the transfer equipment used and the intended storage containers do not contain other substances/products. Before transfer to stock the identity of the product must be proved to be without doubt. The entrance to storage rooms is to be granted only to appropriately trained personnel.
The stabilizer is only effective in the presence of oxygen. Maintain contact with atmosphere containing 5 - 21% oxygen. Never use tanks with inert-gas installation for storage.
Risk of polymerization. Protect against heat. Protect from direct sunlight. Avoid UV-light and other radiation with high energy. Protect against contamination.
In case of bulk storage, the storage-tanks should at least be equipped with two high temperature alert devices.
Even if the product is stored and handled as prescribed/indicated it should be used up within the indicated duration of storage.

Storage stability:
Storage temperature: < 35 °C
Storage duration: 12 Months
The stated storage temperature should be noted.
Avoid prolonged storage.
This product should be processed as soon as possible.
Ensure adequate inhibitor and dissolved oxygen level.
Do not store with less than 10 % headspace above liquid.
Storage stability is based upon ambient temperatures and conditions described.
It is recommended to keep a safe distance of +2 degrees above the crystallization range.
The product is stabilized, the shelf life should be noted.
Storage temperature: 45 °C
A restabilization system should be used if the temperature in the bulk storage-tank reaches the indicated value.
Storage temperature: 60 °C
All personnel in a greater area should be evacuated if the temperature in the bulk storage-tank reaches the indicated value.

## 8. Exposure Controls/Personal Protection

**Components with occupational exposure limits**

| | | |
|---|---|---|
| n-butyl acrylate | OEL, MX: | TWA value 2 ppm ; |

**Advice on system design:**
Provide local exhaust ventilation to maintain recommended P.E.L.

**Personal protective equipment**

**Respiratory protection:**
Suitable respiratory protection for lower concentrations or short-term effect: Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

**Hand protection:**
Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):, butyl rubber (butyl) - 0.7 mm coating thickness, nitrile rubber (NBR) - 0.4 mm coating thickness, Manufacturer's directions for use should be observed because of great diversity of types., Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

**Eye protection:**
Safety glasses with side-shields (frame goggles) (e.g. EN 166)

**Body protection:**
Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

**General safety and hygiene measures:**
Avoid contact with the skin, eyes and clothing. Avoid inhalation of vapour. Wearing of closed work clothing is required additionally to the stated personal protection equipment.

## 9. Physical and Chemical Properties

| | | |
|---|---|---|
| Form: | liquid | |
| Odour: | acrylic-like<br>ester-like | |
| Odour threshold: | not determined | |
| Colour: | colourless | |
| pH value: | not applicable | |
| Melting point: | -64.6 °C The substance / product does not decompose.<br>Literature data. | |
| Freezing point: | No data available. | |
| Boiling point: | 147 °C<br>( 1,013 hPa) | |
| Boiling range: | No data available. | |
| Sublimation point: | No applicable information available. | |
| Flash point: | 38 °C | (DIN 51755, closed cup) |
| Flammability: | Flammable liquid and vapour. | (derived from flash point) |

| | | |
|---|---|---|
| Lower explosion limit: | For liquids not relevant for classification and labelling. The lower explosion point may be 5 - 15 °C below the flash point. | |
| Upper explosion limit: | For liquids not relevant for classification and labelling. | |
| Autoignition: | 275 °C | (DIN 51794) |
| SADT: | Not a substance/mixture liable to self-decomposition according to GHS. | |
| Vapour pressure: | 5 hPa<br>( 22.2 °C) | |
| Density: | 0.899 g/cm3<br>( 20 °C)<br>0.8689 g/cm3<br>( 50 °C)<br>0.8639 g/cm3<br>( 55 °C) | <br><br><br><br>(calculated) |
| Relative density: | 0.9<br>( 20 °C) | |
| Vapour density: | 4.41<br>( 20 °C)<br>Heavier than air. | (calculated) |
| Partitioning coefficient n-octanol/water (log Pow): | 2.38<br>( 25 °C) | (measured) |
| Self-ignition temperature: | Based on its structural properties the product is not classified as self-igniting. | |
| Thermal decomposition: | No decomposition if stored and handled as prescribed/indicated. | |
| Viscosity, dynamic: | 0.88 mPa.s<br>( 20 °C)<br>0.66 mPa.s<br>( 40 °C) | |
| Viscosity, kinematic: | ( 20 °C)<br>not determined | |
| Particle size: | The substance / product is marketed or used in a non solid or granular form. | |
| Solubility in water: | 1.7 g/l<br>( 20 °C) | |
| Solubility (quantitative): | No applicable information available. | |
| Solubility (qualitative): | miscible<br>solvent(s): organic solvents, | |
| Molar mass: | 128.17 g/mol | |
| Evaporation rate: | No data available. | |

## 10. Stability and Reactivity

### Reactivity
No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:
No corrosive effect on metal.

Oxidizing properties:
Based on its structural properties the product is not classified as oxidizing.

| | | |
|---|---|---|
| Formation of flammable gases: | Remarks: | Forms no flammable gases in the presence of water. |

### Chemical stability
The product is stable if stored and handled as prescribed/indicated.

### Possibility of hazardous reactions
Explosion and fire hazard exists under confined conditions. Ignitable air mixtures can form when the product is heated above the flash point and/or when sprayed or atomized. Formation of explosive gas/air mixtures.
Polymerization coupled with heat formation.
Risk of spontaneous polymerization by oxygen depletion of the liquid phase. Risk of spontaneous polymerization when heated or in the presence of UV radiation. Risk of spontaneous and violent self-polymerization if inhibitor is lost or product is exposed to excessive heat. Polymerization produces gases which may burst closed or confined containers. Reactions may cause ignition.
Risk of spontaneous polymerization in the presence of starters for radical chain reactions (e.g. peroxides). Reacts with nitric acid. Risk of spontaneous polymerization in the presence of oxidizing agents.
Hazardous reactions in presence of mentioned substances to avoid.
The product is stabilized against spontaneous polymerization prior to despatch. The product is stable if stored and handled as prescribed/indicated.

### Conditions to avoid
Avoid heat. Avoid oxygen content above the product of less than 5 %. Avoid UV-light and other radiation with high energy. Avoid direct sunlight. Avoid prolonged storage. Avoid inhibitor loss. Avoid excessive temperatures. Avoid all sources of ignition: heat, sparks, open flame. Avoid freezing. Avoid moisture.

### Incompatible materials
radical formers, free radical initiators, peroxides, mercaptans, nitro-compounds, perborates, azides, ether, ketones, aldehydes, amines, nitrates, nitrites, oxidizing agents, reducing agents, strong bases, alkaline reactive substances, acid anhydrides, acid chlorides, concentrated mineral acids, metal salts Inert gas

### Hazardous decomposition products

Decomposition products:
Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:
No decomposition if stored and handled as prescribed/indicated.

## 11. Toxicological information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

### Acute Toxicity/Effects

Acute toxicity
Assessment of acute toxicity: Of moderate toxicity after short-term inhalation. Of low toxicity after single ingestion. Of low toxicity after short-term skin contact.

Oral
Type of value: LD50
Species: rat
Value: 3,150 mg/kg (BASF-Test)

Inhalation
Type of value: LC50
Species: rat
Value: 10.3 mg/l (OECD Guideline 403)
Exposure time: 4 h
The vapour was tested.

Dermal
Type of value: LD50
Species: rabbit
Value: 2,000 - 3,024 mg/kg (other)

Assessment other acute effects
Assessment of STOT single:
Causes temporary irritation of the respiratory tract.

Irritation / corrosion
Assessment of irritating effects: Eye contact causes irritation. Skin contact causes irritation.

Skin
Species: rabbit
Result: Irritant.
Method: BASF-Test

Eye
Species: rabbit
Result: Irritant.
Method: other

Sensitization
Assessment of sensitization: Sensitization after skin contact possible.

Mouse Local Lymph Node Assay (LLNA)
Species: mouse
Result: sensitizing
Method: OECD Guideline 429

Aspiration Hazard
not applicable

### Chronic Toxicity/Effects

Repeated dose toxicity
Assessment of repeated dose toxicity: After repeated exposure the prominent effect is local irritation. The substance may cause damage to the olfactory epithelium after repeated inhalation.

Genetic toxicity
Assessment of mutagenicity: The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture. The substance was not mutagenic in a test with mammals. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Carcinogenicity
Assessment of carcinogenicity: In long-term animal studies in which the substance was given by inhalation, a carcinogenic effect was not observed. The substance showed no carcinogenic activity in animals after chronic administration to the skin. IARC Group 3 (not classifiable as to human carcinogenicity).

Reproductive toxicity
Assessment of reproduction toxicity: The results of animal studies gave no indication of a fertility impairing effect.

Teratogenicity
Assessment of teratogenicity: No indications of a developmental toxic / teratogenic effect were seen in animal studies.

## 12. Ecological Information

### Toxicity

Aquatic toxicity
Assessment of aquatic toxicity:
Acutely toxic for aquatic organisms. Harmful to aquatic organisms based on long-term (chronic) toxicity study data. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish
LC50 (96 h) 2.1 mg/l, Cyprinodon variegatus (OECD Guideline 203, Flow through.)
The statement of the toxic effect relates to the analytically determined concentration.

Aquatic invertebrates
EC50 (48 h) 8.2 mg/l, Daphnia magna (OECD Guideline 202, part 1, Flow through.)
The statement of the toxic effect relates to the analytically determined concentration.

Aquatic plants
EC50 (96 h) 2.65 mg/l, Selenastrum capricornutum (OECD Guideline 201, static)
The statement of the toxic effect relates to the analytically determined concentration.

Chronic toxicity to fish
No data available.

Chronic toxicity to aquatic invertebrates
No observed effect concentration (21 d) 0.136 mg/l, Daphnia magna (OECD Guideline 211, semistatic)
The statement of the toxic effect relates to the analytically determined concentration.

Assessment of terrestrial toxicity
No effects at the highest test concentration.
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Soil living organisms

Toxicity to soil dwelling organisms:
EC50 (28 d) > 1,000 mg/kg, soil dwelling microorganisms (OECD Guideline 217)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The details of the toxic effect relate to the nominal concentration.

Toxicity to terrestrial plants

No data available.

Other terrestrial non-mammals
No data available.

### Microorganisms/Effect on activated sludge

Toxicity to microorganisms
other aerobic
activated sludge, industrial/EC0 (3 d): > 150 mg/l
Nominal concentration.

### Persistence and degradability

Assessment biodegradation and elimination (H2O)
Readily biodegradable (according to OECD criteria).

Elimination information

80 - 90 % TIC of the ThIC (28 d) (ISO 14593) (aerobic, activated sludge, domestic)

Assessment of stability in water
In contact with water the substance will hydrolyse slowly.

Information on Stability in Water (Hydrolysis)
$t_{1/2}$ 1,100 d (25 °C, pH value 7), (OECD Guideline 111, pH 7)
In contact with water the substance will hydrolyse slowly.

### Bioaccumulative potential

Assessment bioaccumulation potential
Accumulation in organisms is not to be expected.

Bioaccumulation potential
Bioconcentration factor: 17.3 (calculated)
Accumulation in organisms is not to be expected.

### Mobility in soil

Assessment transport between environmental compartments
The substance will not evaporate into the atmosphere from the water surface.
Adsorption to solid soil phase is not expected.

### Additional information

Other ecotoxicological advice:

Do not release untreated into natural waters. Acutely toxic for aquatic organisms.

## 13. Disposal considerations

**Waste disposal of substance:**
Do not discharge into drains/surface waters/groundwater. Dispose of in accordance with national, state and local regulations.

**Container disposal:**
WARNING: Empty containers may still contain hazardous residue. Flammable vapors may exist in containers in which residues of this product remain. Dispose of in accordance with national, state and local regulations.

## 14. Transport Information

**Land transport**
TDG

| | |
|---|---|
| Hazard class: | 3 |
| Packing group: | III |
| ID number: | UN 2348 |
| Hazard label: | 3 |
| Proper shipping name: | BUTYL ACRYLATES, STABILIZED |

**Sea transport**
IMDG

| | |
|---|---|
| Hazard class: | 3 |
| Packing group: | III |
| ID number: | UN 2348 |
| Hazard label: | 3 |
| Marine pollutant: | NO |
| Proper shipping name: | BUTYL ACRYLATES, STABILIZED |

**Air transport**
IATA/ICAO

| | |
|---|---|
| Hazard class: | 3 |
| Packing group: | III |
| ID number: | UN 2348 |
| Hazard label: | 3 |
| Proper shipping name: | BUTYL ACRYLATES, STABILIZED |

## 15. Regulatory Information

**Federal Regulations**

Not applicable

**NFPA Hazard codes:**
Health: 2 Fire: 2 Reactivity: 2 Special:

**HMIS III rating**

Health: 2¤ Flammability: 2 Physical hazard: 2

**Assessment of the hazard classes according to UN GHS criteria (most recent version):**

| | | |
|---|---|---|
| Aquatic Acute | 2 | Hazardous to the aquatic environment - acute |
| Aquatic Chronic | 3 | Hazardous to the aquatic environment - chronic |
| Acute Tox. | 5 (oral) | Acute toxicity |
| Acute Tox. | 4 (Inhalation - vapour) | Acute toxicity |
| Acute Tox. | 5 (dermal) | Acute toxicity |
| Skin Corr./Irrit. | 2 | Skin corrosion/irritation |
| Eye Dam./Irrit. | 2A | Serious eye damage/eye irritation |
| STOT SE | 3 (irritating to respiratory system) | Specific target organ toxicity — single exposure |
| Flam. Liq. | 3 | Flammable liquids |
| Skin Sens. | 1B | Skin sensitization |

## 16. Other Information

**SDS Prepared by:**
BASF NA Product Regulations
SDS Prepared on: 2024/06/18

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.


This information is considered accurate but is not exhaustive and shall only be used as a guideline based on current knowledge of the chemical substance or mixture. Safety precautions suitable for the product must be applied.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET