BASF
We create chemistry

# Declaration of Performance

(Construction Products Regulation No. 305/2011)

## No. NL17-0027-01-CPR-20

EN

| | | |
|---|---|---|
| 1. | Unique identification code of the product type: | **In-situ formed dispensed rigid polyurethane foam system (PU):**<br>- **Elastopor H 1701/21 : IsoPMDI 92140**<br>Designation Code: **PU EN 14318-1-CCC1-CT57(20)-GT208(20)-TFT610(20)-FRB44(20)-MU10-W2,5** |
| 2. | Intended use/es: | **ThIB - Thermal Insulation for Buildings** |
| 3. | Manufacturer: | **BASF Nederland B.V.**<br>**Hemelrijk 11-13**<br>**5281 PS Boxtel**<br>**NETHERLANDS** |
| 4. | Authorised representative: | **Not relevant.** |
| 5. | System/s of AVCP: | **System AVCP 4 for Reaction to Fire.**<br>**System AVCP 3 for the rest of essential characteristics.** |
| 6a. | Harmonised standard:<br>Notified body/ies: | **EN 14318-1:2013**<br>**The notified testing laboratory Wetenschappelijk en Technisch Centrum voor het Bouwbedrijf (WTCB) (1136) performed the test reports on Thermal resistance declared under system AVCP 3.**<br>**The notified testing laboratory IKOB BKB BV (0957) performed the test reports on Water vapour permeability declared under system AVCP 3.**<br>**The notified testing laboratory IKOB BKB BV (0957) performed the test reports on Water permeability declared under system AVCP 3.** |
| 6b. | European Assessment Document:<br>European Technical Asessment:<br>Technical Assessment Body:<br>Notified body/ies: | **Not relevant.** |

7. Declared performance/s:

| *Essential characteristics* | *Performance* | *Harmonized technical specification* |
|---|---|---|
| Reaction to fire | F | EN 13501-1 |
| Water permeability | Short term water absorption by partial immersion: ≤ 2,5 kg/m2 | EN 1609 Method B |
| Release of dangerous substances to the indoor environment | No harmonized test method available | EN 14318-1:2013 |
| Thermal resistance | See performance chart | EN 14318-1:2013 |
| Water vapour permeability | Water vapour resistance factor: 10 | EN 12086 Method A |
| Durability of reaction to fire against ageing/degradation | Reaction to fire does not decrease with time | EN 14318-1:2013 |
| Durability of thermal resistance against ageing/degradation | See performance chart | EN 14318-1:2013 |
| Continuous glowing combustion | No harmonized test method available | EN 14318-1:2013 |
| | | |
| | | |
| | | |

Performance chart

| Type of facing: Cut foam without facings | | |
|---|---|---|
| **Thickness** | **Declared aged thermal conductivity** ($\lambda_D$) W/(m·K) | **Thermal resistance level** ($R_D$) $m^2 \cdot K/W$ |
| 30 mm | 0,039 | 0,75 |
| 35 mm | 0,039 | 0,90 |
| 40 mm | 0,039 | 1,00 |
| 45 mm | 0,039 | 1,15 |
| 50 mm | 0,039 | 1,30 |
| 55 mm | 0,039 | 1,40 |
| 60 mm | 0,039 | 1,55 |
| 65 mm | 0,039 | 1,70 |
| 70 mm | 0,039 | 1,80 |
| 75 mm | 0,039 | 1,95 |
| 80 mm | 0,039 | 2,05 |
| 85 mm | 0,039 | 2,20 |
| 90 mm | 0,039 | 2,35 |
| 95 mm | 0,039 | 2,45 |
| 100 mm | 0,039 | 2,60 |
| 105 mm | 0,039 | 2,75 |
| 110 mm | 0,039 | 2,85 |
| 115 mm | 0,039 | 3,00 |
| 120 mm | 0,039 | 3,10 |
| 125 mm | 0,039 | 3,25 |
| 130 mm | 0,039 | 3,40 |
| 135 mm | 0,039 | 3,50 |
| 140 mm | 0,039 | 3,65 |
| 145 mm | 0,039 | 3,80 |
| 150 mm | 0,039 | 3,90 |
| 155 mm | 0,039 | 4,05 |
| 160 mm | 0,039 | 4,15 |
| 165 mm | 0,039 | 4,30 |
| 170 mm | 0,039 | 4,45 |
| 175 mm | 0,039 | 4,55 |
| 180 mm | 0,039 | 4,70 |
| 185 mm | 0,039 | 4,85 |
| 190 mm | 0,039 | 4,95 |
| 195 mm | 0,039 | 5,10 |
| 200 mm | 0,039 | 5,20 |

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

**Not relevant.**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

| Name and function | Place and date of issue | Signature |
|---|---|---|
| **Cees MOORMAN**<br>**Sales Construction BeNeLux & Greece** | **Boxtel (Netherlands)**<br>**24-9-2020** | |
| **Marno DINGENOUTS**<br>**Operations PU Boxtel** | **Boxtel (Netherlands)**<br>**24-9-2020** | |