We create chemistry

Safety data sheet

BASF Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.
Date / Revised: 14.09.2023 Version: 12.0
Date previous version: 08.11.2022 Previous version: 11.0
Date / First version: 17.06.2002
Product: **2-ETHYLHEXYL ACETATE**
(ID no. 30034747/SDS_GEN_GB/EN)
Date of print 02.07.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

2-ETHYLHEXYL ACETATE

Chemical name: 2-ethylhexyl acetate
CAS Number: 103-09-3

REACH registration number: 01-2119483620-40-0000

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Chemical

For the detailed identified uses of the product see appendix of the safety data sheet.

1.3. Details of the supplier of the safety data sheet

Company:
BASF SE
67056 Ludwigshafen
GERMANY

Contact address:
BASF plc
4th and 5th Floors, 2 Stockport Exchange
Railway Road, Stockport, SK1 3GG
UNITED KINGDOM

Telephone: +44 161 475 3000
E-mail address: product-safety-uk-and-ireland@basf.com

1.4. Emergency telephone number

International emergency number:
Telephone: +49 180 2273-112

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Skin Corr./Irrit. 2 H315 Causes skin irritation.

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Pictogram:

Signal Word:
Warning

Hazard Statement:
H315 Causes skin irritation.

Precautionary Statements (Prevention):
P280 Wear protective gloves.
P264 Wash contaminated body parts thoroughly after handling.

Precautionary Statements (Response):
P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.
P332 + P313 If skin irritation occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Hazard determining component(s) for labelling: 2-Ethylhexyl acetate

2.3. Other hazards

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

See section 12 - Results of PBT and vPvB assessment.

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Chemical nature

2-Ethylhexyl acetate
CAS Number: 103-09-3
EC-Number: 203-079-1

Hazardous ingredients (GHS)

2-Ethylhexyl acetate

Content (W/W): > 99 % - < 100 %	Skin Corr./Irrit. 2
CAS Number: 103-09-3	H315
EC-Number: 203-079-1	

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

3.2. Mixtures

Not applicable

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

Remove contaminated clothing.

If inhaled:
If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

On skin contact:
Wash thoroughly with soap and water

On contact with eyes:
Wash affected eyes for at least 15 minutes under running water with eyelids held open.

On ingestion:
Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media:
dry powder, water spray, carbon dioxide, foam

Unsuitable extinguishing media for safety reasons:
water jet

Additional information:
Use extinguishing measures to suit surroundings.

5.2. Special hazards arising from the substance or mixture

Advice: The product is combustible. Cool endangered containers with water-spray. See SDS section 7 - Handling and storage.

5.3. Advice for fire-fighters

Special protective equipment:
Wear a self-contained breathing apparatus. Special protective equipment for firefighters

Further information:
Evacuate area of all unnecessary personnel. Fight fire from maximum distance.

Extend fire extinguishing measures to the surroundings. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

SECTION 6: Accidental Release Measures

High risk of slipping due to leakage/spillage of product.

Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

6.1. Personal precautions, protective equipment and emergency procedures

Handle in accordance with good industrial hygiene and safety practice.

6.2. Environmental precautions

Discharge into the environment must be avoided.

6.3. Methods and material for containment and cleaning up

Pick up with suitable appliance and dispose of. Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:
No special precautions necessary. Substance/product is non-flammable.

7.2. Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

7.3. Specific end use(s)

See exposure scenario(s) in the attachment to this safety data sheet.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

No occupational exposure limits known.

PNEC
freshwater: 0.00827 mg/l

marine water: 0.000827 mg/l

intermittent release: 0.0827 mg/l

sediment (freshwater): 0.213 mg/kg

sediment (marine water): 0.0213 mg/kg

soil: 0.0377 mg/kg

STP: 100 mg/l

DNEL
worker:
Long-term exposure- systemic effects, Inhalation: 17 mg/m3

worker:
Long-term exposure- systemic effects, dermal: 30 mg/kg

worker:
Long- and short-term exposure - local effects, Inhalation: 71 mg/m3

consumer:
Long-term exposure- systemic effects, Inhalation: 3 mg/m3

consumer:
Long-term exposure- systemic effects, dermal: 15 mg/kg

consumer:
Long- and short-term exposure - local effects, Inhalation: 35.5 mg/m3

consumer:
Long-term exposure- systemic effects, oral: 1.5 mg/kg

8.2. Exposure controls

Personal protective equipment

Respiratory protection:
Wear respiratory protection if ventilation is inadequate. Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:
Chemical resistant protective gloves (EN ISO 374-1)
Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):
nitrile rubber (NBR) - 0.4 mm coating thickness
Manufacturer's directions for use should be observed because of great diversity of types.
Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing.

Eye protection:
Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:
Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures
Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is required additionally to the stated personal protection equipment.

Environmental exposure controls
All appropriate measures must be taken to prevent the release of this product to the environment and to limit the dispersion of any release when it occurs. Suitable risk management measures should be in place.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Form:	liquid	
Colour:	colourless	
Odour:	ester-like	
Odour threshold:	not determined	
pH value:	6.1 - 7 Literature data.	
Melting point:	-80 °C (1,013 hPa) Literature data.	
Boiling point:	198.7 °C (1,000 hPa)	
Flash point:	71 °C Literature data.	
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.	
Flammability:	hardly combustible	(derived from flash point)
Lower explosion limit:	For liquids not relevant for classification and labelling., The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Ignition temperature:	268 °C Literature data.	
Vapour pressure:	0.31 hPa (25 °C) Literature data.	(measured)
Density:	0.87 g/cm3 (20 °C) Literature data.	

Relative density:	0.87 (20 °C)	
Relative vapour density (air):	5.94 (20 °C) Heavier than air.	(calculated)
Solubility in water:	slightly soluble 0.0039 g/l (20 °C)	(Directive 92/69/EEC, A.6)
Solubility (qualitative) solvent(s):	organic solvents soluble	
Partitioning coefficient n-octanol/water (log Kow):	4.2 (25 °C)	(measured)
Self ignition:	Based on its structural properties the product is not classified as self-igniting.	Test type: Spontaneous self-ignition at room-temperature.
Thermal decomposition:	No data available.	
Viscosity, dynamic:	1.3 mPa.s (20 °C) Literature data.	
Viscosity, kinematic:	No data available.	
Explosion hazard:	Based on the chemical structure there is no indication of explosive properties.	
Fire promoting properties:	Based on its structural properties the product is not classified as oxidizing.	

9.2. Other information

Self heating ability:	not applicable, the product is a liquid	
pKA:	The substance does not dissociate.	
Adsorption/water - soil:	KOC: 222; log KOC: 2.35	(calculated)
Surface tension:	Based on chemical structure, surface activity is not to be expected.	
Grain size distribution:	The substance / product is marketed or used in a non solid or granular form.	
Molar mass:	172.27 g/mol	

SECTION 10: Stability and Reactivity

10.1. Reactivity

Corrosion to metals:	No corrosive effect on metal.	
Formation of flammable gases:	Remarks:	Forms no flammable gases in the presence of water.

10.2. Chemical stability
The product is stable if stored and handled as prescribed/indicated.

10.3. Possibility of hazardous reactions
Reacts with strong oxidizing agents.

10.4. Conditions to avoid
No special precautions other than good housekeeping of chemicals.

10.5. Incompatible materials

Substances to avoid:
strong oxidizing agents

10.6. Hazardous decomposition products

Hazardous decomposition products:
No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11: Toxicological Information

11.1. Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:
Virtually nontoxic after a single ingestion. Virtually nontoxic after a single skin contact.

Experimental/calculated data:
LD50 rat (oral): 5,140 mg/kg (other)
Literature data.

(by inhalation):No data available.

LD50 guinea pig (dermal): > 17,460 mg/kg (other)
Literature data.

Irritation

Assessment of irritating effects:
Skin contact causes irritation. Not irritating to the eyes.

Experimental/calculated data:
Skin corrosion/irritation

rabbit: Irritant. (OECD Guideline 404)

Serious eye damage/irritation
rabbit: non-irritant (OECD Guideline 405)

Respiratory/Skin sensitization

Assessment of sensitization:
The substance did not cause skin sensitization in humans. Skin sensitizing effects were not observed in animal studies. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Experimental/calculated data:
Human Maximization Test human: Non-sensitizing. (other)

Draize test guinea pig: Non-sensitizing.
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Germ cell mutagenicity

Assessment of mutagenicity:
The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture. The substance was not mutagenic in a test with mammals. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Carcinogenicity

Assessment of carcinogenicity:
The results of various animal studies gave no indication of a carcinogenic effect. The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Reproductive toxicity

Assessment of reproduction toxicity:
The results of animal studies gave no indication of a fertility impairing effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Developmental toxicity

Assessment of teratogenicity:
Animal studies gave no indication of a developmental toxic effect at doses that were not toxic to the parental animals. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Specific target organ toxicity (single exposure)

Assessment of STOT single:
Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:
No substance-specific organtoxicity was observed after repeated administration to animals. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aspiration hazard

No aspiration hazard expected.

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:
Acutely toxic for aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish:
LC50 (96 h) 8.27 mg/l, Oncorhynchus mykiss (OECD 203; ISO 7346; 84/449/EEC, C.1, semistatic)
The statement of the toxic effect relates to the analytically determined concentration.

Aquatic invertebrates:
EC50 (48 h) 22.9 mg/l, Daphnia magna (OECD Guideline 202, part 1, semistatic)
The statement of the toxic effect relates to the analytically determined concentration.

Aquatic plants:
EC50 (72 h) > 21.9 mg/l (growth rate), Selenastrum capricornutum (OECD Guideline 201)
The statement of the toxic effect relates to the analytically determined concentration.

No observed effect concentration (72 h) 10.3 mg/l (growth rate), Selenastrum capricornutum (OECD Guideline 201)
The statement of the toxic effect relates to the analytically determined concentration.

Microorganisms/Effect on activated sludge:
EC20 (180 min) > 1,000 mg/l, activated sludge, domestic (OECD Guideline 209, aquatic)
Nominal concentration.

Chronic toxicity to fish:
Study does not need to be conducted.

Chronic toxicity to aquatic invertebrates:

Study does not need to be conducted.

Assessment of terrestrial toxicity:
No data available.

12.2. Persistence and degradability

Assessment biodegradation and elimination (H2O):
Readily biodegradable (according to OECD criteria).

Elimination information:
70 % CO2 formation relative to the theoretical value (28 d) (OECD 301B; ISO 9439; 92/69/EEC, C.4-C) (aerobic, activated sludge, domestic)

Assessment of stability in water:
Substance is readily biodegradable, therefore hydrolysis is not expected to be relevant.
Information on Stability in Water (Hydrolysis):
Study does not need to be conducted.

12.3. Bioaccumulative potential

Assessment bioaccumulation potential:
Significant accumulation in organisms is not to be expected.

Bioaccumulation potential:

Bioconcentration factor (BCF): 7 - 292 (calculated)
Significant accumulation in organisms is not to be expected.

12.4. Mobility in soil

Assessment transport between environmental compartments:
Volatility: The substance will rapidly evaporate into the atmosphere from the water surface.
Adsorption in soil: Adsorption to solid soil phase is not expected.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not fulfill the criteria for PBT (Persistent/bioaccumulative/toxic) and vPvB (very persistent/very bioaccumulative). Self classification

12.6. Other adverse effects

The substance is not listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

12.7. Additional information

Adsorbable organically-bound halogen (AOX):

This product contains no organically-bound halogen.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Must be disposed of or incinerated in accordance with local regulations.

The UK Environmental Protection (Duty of Care) Regulations (EP) and amendments should be noted (United Kingdom).
This product and any uncleaned containers must be disposed of as hazardous waste in accordance with the 2005 Hazardous Waste Regulations and amendments (United Kingdom)

Contaminated packaging:
Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

SECTION 14: Transport Information

Land transport

ADR

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

RID

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

Inland waterway transport
ADN

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user:	None known

Transport in inland waterway vessel
Not evaluated

Sea transport

IMDG

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

Air transport

IATA/ICAO

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

14.1. UN number or ID number
See corresponding entries for “UN number or ID number” for the respective regulations in the tables above.

14.2. UN proper shipping name
See corresponding entries for “UN proper shipping name” for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for “Transport hazard class(es)” for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for “Packing group” for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for “Environmental hazards” for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for “Special precautions for user” for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 3

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU): Listed in above regulation: no

The data should be considered when making any assessment under the Control of Substances Hazardous to Health Regulations (COSHH), and related guidance, for example, 'COSHH Essentials' (United Kingdom).

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

15.2. Chemical Safety Assessment

Chemical Safety Assessment performed

SECTION 16: Other Information

Assessment of the hazard classes according to UN GHS criteria (most recent version)

Skin Corr./Irrit. 2
Aquatic Acute 2
Flam. Liq. 4

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Skin Corr./Irrit.	Skin corrosion/irritation
H315	Causes skin irritation.

Abbreviations
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Annex: Exposure Scenarios

Index

1. Production
IS; ERC1; PROC2, PROC4, PROC8a, PROC8b, PROC9, PROC15

2. Formulation
IS; ERC2; PROC3, PROC5, PROC19

3. Distribution of substance, (use in industrial settings)
IS; ERC2; PROC8a, PROC8b, PROC9

4. Use as laboratory reagent/agent, (use in industrial settings)
IS; ERC4; PROC15

5. Use in Cleaning Agents, (use in industrial settings)
IS; ERC4; PROC7, PROC10, PROC13

6. Use in Coatings, Use in Paints, Use in Printing inks, Use in Adhesives, (use in industrial settings)
IS; ERC4; PROC7, PROC10, PROC13

7. Distribution of substance, (use in professional settings)
PW; ERC8a, ERC8d; PROC8a, PROC8b, PROC9

8. Use as laboratory reagent/agent, (use in professional settings)
PW; ERC8a; PROC15

9. Use in Cleaning Agents, (use in professional settings)
PW; ERC8a, ERC8d; PROC10, PROC11, PROC13

10. Use in Coatings, Use in Paints, Use in Printing inks, Use in Adhesives, (use in professional settings)
PW; ERC8a, ERC8d; PROC10, PROC11, PROC13

11. Use in Agrochemicals
PW; ERC8d; PROC8a, PROC11

12. Use in Cleaning Agents, (consumer use)
C; ERC8a, ERC8d; PC4, PC9a, PC35

13. Use in Coatings, Use in Paints, Use in Printing inks, Use in Adhesives, (consumer use)
C; ERC8a, ERC8d; PC1, PC9a, PC15, PC23

14. Use in Agrochemicals, (consumer use)
C; ERC8d; PC27

****

1. Short title of exposure scenario

Production
IS; ERC1; PROC2, PROC4, PROC8a, PROC8b, PROC9, PROC15

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	PROC2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions Use domain: industrial
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0.2743 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.009143
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	7.1775 mg/m³
Risk Characterization Ratio (RCR)	0.422206
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	7.1775 mg/m³
Risk Characterization Ratio (RCR)	0.101092
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC4: Chemical production where opportunity for exposure arises Use domain: industrial
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 100 %

Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1.3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.045714
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.633309
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.151637
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	

Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2.7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.091429
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12.9195 mg/m³
Risk Characterization Ratio (RCR)	0.759971
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	21.5325 mg/m³
Risk Characterization Ratio (RCR)	0.303275
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2.7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.091429

Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.633309
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.151637
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1.3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.045714
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.633309
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.151637
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0.0686 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.002286
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.633309
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.151637
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

****

2. Short title of exposure scenario

Formulation
IS; ERC2; PROC3, PROC5, PROC19

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 2.2.v1: ESVOC SpERC 2.2.v1

Operational conditions	
Annual amount used in the EU	1,700,000 kg
Minimum emission days per year	300
Emission factor air	0.5 %
Emission factor water	0.002 %
Emission factor soil	0.01 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Air treatment measures considered suitable are, e.g.	Wet scrubber - for dusts, Filtration, Waste gas treatment by thermal oxidation, Adsorption
Wastewater treatment measures considered suitable are, e.g.	Acclimated biological treatment, Distillation
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.067039
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	84,528.5 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition Use domain: industrial
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance	31 Pa

during use	
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0.1371 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.004571
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	6.4597 mg/m³
Risk Characterization Ratio (RCR)	0.379985
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	6.4597 mg/m³
Risk Characterization Ratio (RCR)	0.090982
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC5: Mixing or blending in batch processes Use domain: industrial
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Use suitable chemically resistant	Effectiveness: 80 %

gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2.7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.091429
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.633309
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.151637
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC19: Manual activities involving hand contact Use domain: industrial
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	60 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general ventilation (not less than 3 - 5 air changes per hour)	Effectiveness: 30 %
Wear chemically resistant gloves in combination with specific activity training	Effectiveness: 95 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	7.0714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.235714
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10.0485 mg/m³
Risk Characterization Ratio (RCR)	0.591088

Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	50.2425 mg/m³
Risk Characterization Ratio (RCR)	0.707641
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

*** * * * * * * * * * * * * * * ***

3. Short title of exposure scenario

Distribution of substance, (use in industrial settings)
IS; ERC2; PROC8a, PROC8b, PROC9

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC2: Formulation into mixture For this scenario, local exposure has not been assesssed. The contribution to the regional background concentration is taken into account. Emissions to the environment from distribution activities are covered by the exposure assessments of the respective life cycle stages. Consequently, no environmental exposure estimation and risk characterisation is provided for this scenario.
Operational conditions	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Use suitable chemically resistant	Effectiveness: 80 %

gloves.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2.7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.091429
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12.9195 mg/m³
Risk Characterization Ratio (RCR)	0.759971
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	21.5325 mg/m³
Risk Characterization Ratio (RCR)	0.303275
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: industrial
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2.7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.091429
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.633309

Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.151637
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: industrial
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1.3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.045714
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.633309
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.151637
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

****

4. Short title of exposure scenario

Use as laboratory reagent/agent, (use in industrial settings)
IS; ERC4; PROC15

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SPERC 4.24.v1: ESVOC SPERC 4.24.v1
Operational conditions	
Annual amount used in the EU	100,000 kg
Minimum emission days per year	20
Emission factor air	2.5 %
Emission factor water	2 %
Emission factor soil	0.01 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Treat soil emissions to provide a typical removal efficiency of (%)	80 %
Soil treatment measures considered suitable are, e.g.	Sewage Sludge incineration
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.671063
	Risk from environmental exposure is driven by freshwater sediment.
Maximum amount of safe use	149 kg/d
Risk from environmental exposure is driven by freshwater sediment.	

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: industrial
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid

Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0.0686 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.002286
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.633309
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.151637
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

****

5. Short title of exposure scenario

Use in Cleaning Agents, (use in industrial settings)
IS; ERC4; PROC7, PROC10, PROC13

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 4.4a.v1: ESVOC SpERC 4.4a.v1
Operational conditions	
Annual amount used in the EU	300,000 kg
Minimum emission days per year	20
Emission factor air	30 %
Emission factor water	0 %

Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Air treatment measures considered suitable are, e.g.	Wet scrubber - for dusts, Waste gas treatment by thermal oxidation, Adsorption
Wastewater treatment measures considered suitable are, e.g.	Acclimated biological treatment, Distillation
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.035999
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	138,893 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 5 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Regular inspection and maintenance of equipment and machines. Clean equipment and the work area every day. Ensure that the task is not carried out by more than one worker	

simultaneously. Ensure doors and windows are opened (general ventilation). Supervision in place to check that the RMMs in place are being used correctly and OCs followed.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0.4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.014286
Assessment method	EASY TRA v4.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	11.21 mg/m³
Risk Characterization Ratio (RCR)	0.659412
Assessment method	EASY TRA v4.1, Workplace measurements
	Worker - inhalation, long-term - local
Exposure estimate	11.21 mg/m³
Risk Characterization Ratio (RCR)	0.157887
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: industrial
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 15 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic

Exposure estimate	0.8229 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.027429
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - systemic
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.633309
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - local
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.151637
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: industrial
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 15 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0.4114 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.013714
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - systemic
Exposure estimate	10.7662 mg/m³

Risk Characterization Ratio (RCR)	0.633309
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - local
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.151637
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

****

6. Short title of exposure scenario

Use in Coatings, Use in Paints, Use in Printing inks, Use in Adhesives, (use in industrial settings) IS; ERC4; PROC7, PROC10, PROC13

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 4.3a.v1: ESVOC SpERC 4.3a.v1
Operational conditions	
Annual amount used in the EU	300,000 kg
Minimum emission days per year	300
Emission factor air	98 %
Emission factor water	0.007 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Air treatment measures considered suitable are, e.g.	Wet scrubber - for dusts, Filtration, Waste gas treatment by thermal oxidation, Adsorption
Wastewater treatment measures considered suitable are, e.g.	Acclimated biological treatment, Distillation
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	

Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.380354
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	2,629.1 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	PROC7: Industrial spraying Use domain: industrial
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 5 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Regular inspection and maintenance of equipment and machines. Clean equipment and the work area every day. Ensure that the task is not carried out by more than one worker simultaneously. Ensure doors and windows are opened (general ventilation). Supervision in place to check that the RMMs in place are being used correctly and OCs followed.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0.4286 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.014286
Assessment method	EASY TRA v4.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	11.21 mg/m³
Risk Characterization Ratio (RCR)	0.659412

Assessment method	EASY TRA v4.1, Workplace measurements
	Worker - inhalation, long-term - local
Exposure estimate	11.21 mg/m³
Risk Characterization Ratio (RCR)	0.157887
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: industrial
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 15 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0.8229 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.027429
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - systemic
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.633309
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - local
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.151637
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: industrial
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 15 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0.4114 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.013714
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - systemic
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.633309
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - local
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.151637
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

****

7. Short title of exposure scenario

Distribution of substance, (use in professional settings)
PW; ERC8a, ERC8d; PROC8a, PROC8b, PROC9

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) For this scenario, local exposure has not been assesssed. The contribution to the regional background concentration is taken into account. Emissions to the environment from distribution activities are covered by the exposure assessments of the respective life cycle stages. Consequently, no environmental exposure estimation and risk characterisation is provided for this scenario.
Operational conditions	

Contributing exposure scenario	
Use descriptors covered	ERC8d: Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) For this scenario, local exposure has not been assesssed. The contribution to the regional background concentration is taken into account. Emissions to the environment from distribution activities are covered by the exposure assessments of the respective life cycle stages. Consequently, no environmental exposure estimation and risk characterisation is provided for this scenario.
Operational conditions	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: professional
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	60 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %

Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2.7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.091429
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.633309
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	53.8312 mg/m³
Risk Characterization Ratio (RCR)	0.758187
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities Use domain: professional
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	2.7429 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.091429
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12.9195 mg/m³

Risk Characterization Ratio (RCR)	0.759971
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	21.5325 mg/m³
Risk Characterization Ratio (RCR)	0.303275
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

Contributing exposure scenario	
Use descriptors covered	PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing). Use domain: professional
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	1.3714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.045714
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	12.9195 mg/m³
Risk Characterization Ratio (RCR)	0.759971
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	21.5325 mg/m³
Risk Characterization Ratio (RCR)	0.303275
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

****

8. Short title of exposure scenario

Use as laboratory reagent/agent, (use in professional settings)
PW; ERC8a; PROC15

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.17.v1: ESVOC SpERC 8.17.v1
Operational conditions	
Annual amount used in the EU	50,000 kg
Minimum emission days per year	365
Emission factor air	50 %
Emission factor water	50 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.013267
	Risk from environmental exposure is driven by freshwater sediment.
Maximum amount of safe use	0.516284 kg/d
Risk from environmental exposure is driven by freshwater sediment.	

Contributing exposure scenario	
Use descriptors covered	PROC15: Use a laboratory reagent. Use domain: professional
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance	31 Pa

during use	
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Provide a good standard of general or controlled ventilation (5 to 10 air changes per hour)	Effectiveness: 70 %
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - dermal, long-term - systemic
Exposure estimate	0.0686 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.002286
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - systemic
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.633309
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Worker
	Worker - inhalation, long-term - local
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.151637
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

****

9. Short title of exposure scenario

Use in Cleaning Agents, (use in professional settings)
PW; ERC8a, ERC8d; PROC10, PROC11, PROC13

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.4b.v1: ESVOC SpERC 8.4b.v1
Operational conditions	
Annual amount used in the EU	150,000 kg
Minimum emission days per year	365
Emission factor air	2 %
Emission factor water	0 %
Emission factor soil	0 %

Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.082757
	Risk from environmental exposure is driven by soil.
Maximum amount of safe use	1.986 kg/d
Risk from environmental exposure is driven by soil.	

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.4b.v1: ESVOC SpERC 8.4b.v1
Operational conditions	
Annual amount used in the EU	150,000 kg
Minimum emission days per year	365
Emission factor air	2 %
Emission factor water	0 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	no STP
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.012141
	Risk from environmental exposure is driven by freshwater sediment.
Maximum amount of safe use	33.8 kg/d

Risk from environmental exposure is driven by freshwater sediment.

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: professional
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 10 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0.5486 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.018286
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - systemic
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.633309
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - local
Exposure estimate	17.9437 mg/m³
Risk Characterization Ratio (RCR)	0.252729
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
Operational conditions	

Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 5 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Regular inspection and maintenance of equipment and machines. Clean equipment and the work area every day. Ensure that the task is not carried out by more than one worker simultaneously. Ensure doors and windows are opened (general ventilation). Supervision in place to check that the RMMs in place are being used correctly and OCs followed.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	1.0714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.035714
Assessment method	EASY TRA v4.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	11.21 mg/m³
Risk Characterization Ratio (RCR)	0.659412
Assessment method	EASY TRA v4.1, Workplace measurements
	Worker - inhalation, long-term - local
Exposure estimate	11.21 mg/m³
Risk Characterization Ratio (RCR)	0.157887
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: professional
Operational conditions	

Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 10 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0.2743 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.009143
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - systemic
Exposure estimate	7.1775 mg/m³
Risk Characterization Ratio (RCR)	0.422206
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - local
Exposure estimate	7.1775 mg/m³
Risk Characterization Ratio (RCR)	0.101092
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

****

10. Short title of exposure scenario

Use in Coatings, Use in Paints, Use in Printing inks, Use in Adhesives, (use in professional settings) PW; ERC8a, ERC8d; PROC10, PROC11, PROC13

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.3b.v1: ESVOC SpERC 8.3b.v1
Operational conditions	

Annual amount used in the EU	150,000 kg
Minimum emission days per year	365
Emission factor air	98 %
Emission factor water	1 %
Emission factor soil	1 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.012206
	Risk from environmental exposure is driven by freshwater sediment.
Maximum amount of safe use	1.7 kg/d
Risk from environmental exposure is driven by freshwater sediment.	

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.3b.v1: ESVOC SpERC 8.3b.v1
Operational conditions	
Annual amount used in the EU	150,000 kg
Minimum emission days per year	365
Emission factor air	98 %
Emission factor water	1 %
Emission factor soil	1 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100

Risk Management Measures	
Type of STP	no STP
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.024669
	Risk from environmental exposure is driven by freshwater sediment.
Maximum amount of safe use	8.3 kg/d
Risk from environmental exposure is driven by freshwater sediment.	

Contributing exposure scenario	
Use descriptors covered	PROC10: Roller application or brushing Use domain: professional
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 10 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	240 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0.5486 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.018286
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - systemic
Exposure estimate	10.7662 mg/m³
Risk Characterization Ratio (RCR)	0.633309
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - local
Exposure estimate	17.9437 mg/m³

Risk Characterization Ratio (RCR)	0.252729
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 5 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Regular inspection and maintenance of equipment and machines. Clean equipment and the work area every day. Ensure that the task is not carried out by more than one worker simultaneously. Ensure doors and windows are opened (general ventilation). Supervision in place to check that the RMMs in place are being used correctly and OCs followed.	
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	1.0714 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.035714
Assessment method	EASY TRA v4.1, Workplace measurements
	Worker - inhalation, long-term - systemic
Exposure estimate	11.21 mg/m³
Risk Characterization Ratio (RCR)	0.659412
Assessment method	EASY TRA v4.1, Workplace measurements
	Worker - inhalation, long-term - local
Exposure estimate	11.21 mg/m³

Risk Characterization Ratio (RCR)	0.157887
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

Contributing exposure scenario	
Use descriptors covered	PROC13: Treatment of articles by dipping and pouring. Use domain: professional
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 10 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Indoor
Risk Management Measures	
Use suitable chemically resistant gloves.	Effectiveness: 80 %
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - dermal, long-term - systemic
Exposure estimate	0.2743 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.009143
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - systemic
Exposure estimate	7.1775 mg/m³
Risk Characterization Ratio (RCR)	0.422206
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, worker, modified version, The concentration of the substance has been considered using a linear approach.
	Worker - inhalation, long-term - local
Exposure estimate	7.1775 mg/m³
Risk Characterization Ratio (RCR)	0.101092
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra Please note that a modified version has been used (see exposure estimates)	

****

11. Short title of exposure scenario

Use in Agrochemicals
PW; ERC8d; PROC8a, PROC11

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ECPA SPERC 8d.2.v2
Operational conditions	
Maximum annual application rate	0.142 kg
Minimum emission days per year	365
Emission factor air	100 %
Emission factor water	0 %
Emission factor soil	0 %
Risk Management Measures	
Type of STP	no STP
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.9
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	4.5 kg/d
Risk from environmental exposure is driven by marine water.	

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: professional
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Outdoor

Risk Management Measures	
Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	ECPA OWB tool v2.5, tractor-mounted spraying
	Worker - dermal, long-term - systemic
Exposure estimate	0.034 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.001133
Assessment method	ECPA OWB tool v2.5, tractor-mounted spraying
	Worker - inhalation, long-term - systemic
Exposure estimate	0.28 mg/m³
Risk Characterization Ratio (RCR)	0.016471
Assessment method	ECPA OWB tool v2.5, tractor-mounted spraying
	Worker - inhalation, long-term - local
Exposure estimate	0.28 mg/m³
Risk Characterization Ratio (RCR)	0.003944

Contributing exposure scenario	
Use descriptors covered	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities Use domain: professional
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Outdoor
Risk Management Measures	
Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	ECPA OWB tool v2.5, hand-held spraying
	Worker - dermal, long-term - systemic
Exposure estimate	0.044 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.001467
Assessment method	ECPA OWB tool v2.5, hand-held spraying
	Worker - inhalation, long-term - systemic
Exposure estimate	0.008 mg/m³
Risk Characterization Ratio (RCR)	0.000471
Assessment method	ECPA OWB tool v2.5, hand-held spraying
	Worker - inhalation, long-term - local
Exposure estimate	0.008 mg/m³

Risk Characterization Ratio (RCR)	0.000113

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week
Indoor/Outdoor	Outdoor
Risk Management Measures	
Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	ECPA OWB tool v2.5, tractor-mounted spraying
	Worker - dermal, long-term - systemic
Exposure estimate	6.571 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.219033
Assessment method	ECPA OWB tool v2.5, tractor-mounted spraying
	Worker - inhalation, long-term - systemic
Exposure estimate	0.072 mg/m³
Risk Characterization Ratio (RCR)	0.004235
Assessment method	ECPA OWB tool v2.5, tractor-mounted spraying
	Worker - inhalation, long-term - local
Exposure estimate	0.072 mg/m³
Risk Characterization Ratio (RCR)	0.001014

Contributing exposure scenario	
Use descriptors covered	PROC11: Non industrial spraying Use domain: professional
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 100 %
Physical state	liquid
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	480 min 5 days per week

Indoor/Outdoor	Outdoor
Risk Management Measures	
Use suitable chemically resistant gloves.	
Exposure estimate and reference to its source	
Assessment method	ECPA OWB tool v2.5, hand-held spraying
	Worker - dermal, long-term - systemic
Exposure estimate	0.866 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.028867
Assessment method	ECPA OWB tool v2.5, hand-held spraying
	Worker - inhalation, long-term - systemic
Exposure estimate	5.254 mg/m³
Risk Characterization Ratio (RCR)	0.309059
Assessment method	ECPA OWB tool v2.5, hand-held spraying
	Worker - inhalation, long-term - local
Exposure estimate	5.254 mg/m³
Risk Characterization Ratio (RCR)	0.074

****

12. Short title of exposure scenario

Use in Cleaning Agents, (consumer use)
C; ERC8a, ERC8d; PC4, PC9a, PC35

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.4c.v1: ESVOC SpERC 8.4c.v1
Operational conditions	
Annual amount used in the EU	150,000 kg
Minimum emission days per year	365
Emission factor air	95 %
Emission factor water	2.5 %
Emission factor soil	2.5 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP

Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.012477
	Risk from environmental exposure is driven by freshwater sediment.
Maximum amount of safe use	3.3 kg/d
Risk from environmental exposure is driven by freshwater sediment.	

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.4c.v1: ESVOC SpERC 8.4c.v1
Operational conditions	
Annual amount used in the EU	150,000 kg
Minimum emission days per year	365
Emission factor air	95 %
Emission factor water	2.5 %
Emission factor soil	2.5 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	no STP
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.074791
	Risk from environmental exposure is driven by freshwater sediment.
Maximum amount of safe use	5.5 kg/d
Risk from environmental exposure is driven by freshwater sediment.	

Contributing exposure scenario	
Use descriptors covered	PC4: Anti-Freeze and De-icing products.
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 10 %

Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 60 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	365 uses per year Relevant for inhalative exposure estimates
Duration and Frequency of activity	365 uses per year Relevant for dermal exposure estimates
Room size	15 m3
Ventilation rate per hour	2.5
body weight	65 kg
Uptake fraction dermal	100 %
Spray duration	24.6 sec
Contact rate	46 mg/min
Release duration	0.41 min
	Relevant for dermal exposure estimates
Risk Management Measures	
Consumer Measures	Ensure spraying away from persons.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0.029 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.001934
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model: Exposure to spray/dust
	Consumer - inhalation, long-term - systemic
Exposure estimate	0.0103 mg/m³
Risk Characterization Ratio (RCR)	0.003438
	The exposure calculation is based on the mean concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC9a: Coatings and paints, thinners, paint removers
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 5 %
Vapour pressure of the substance during use	31 Pa

Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 180 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 20 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	104 uses per year Relevant for inhalative exposure estimates
Duration and Frequency of activity	104 uses per year Relevant for dermal exposure estimates
Temperature (Application)	25 °C
body weight	65 kg
Uptake fraction dermal	100 %
Release area	100000 cm²
	Release area increases over time
Release duration	20 min
	Relevant for inhalative exposure estimates
Contact rate	1000 mg/min
Release duration	20 min
	Relevant for dermal exposure estimates
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	4.3836 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.292237
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	1.0195 mg/m³
Risk Characterization Ratio (RCR)	0.339822
	The exposure calculation is based on the mean concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC35: Washing and Cleaning Products (including solvent based products).
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 5 %
Vapour pressure of the substance during use	31 Pa

Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 0.75 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 0.3 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	365 uses per year Relevant for inhalative exposure estimates
Duration and Frequency of activity	365 uses per year Relevant for dermal exposure estimates
Temperature (Application)	25 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 0.01 g Relevant for dermal exposure estimates
Release area	20 cm²
	Release area is constant
Release duration	0.3 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0.0077 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.000513
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0.0001 mg/m³
Risk Characterization Ratio (RCR)	0.000001
	The exposure calculation is based on the mean concentration per year.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

****

13. Short title of exposure scenario

Use in Coatings, Use in Paints, Use in Printing inks, Use in Adhesives, (consumer use)
C; ERC8a, ERC8d; PC1, PC9a, PC15, PC23

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.3c.v1: ESVOC SpERC 8.3c.v1

Operational conditions	
Annual amount used in the EU	150,000 kg
Minimum emission days per year	365
Emission factor air	98.5 %
Emission factor water	1 %
Emission factor soil	0.5 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	Municipal STP
Assumed sewage treatment plant flow (m3/d)	2,000 m3/d
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.012274
	Risk from environmental exposure is driven by freshwater sediment.
Maximum amount of safe use	3.3 kg/d
Risk from environmental exposure is driven by freshwater sediment.	

Contributing exposure scenario	
Use descriptors covered	ESVOC SpERC 8.3c.v1: ESVOC SpERC 8.3c.v1
Operational conditions	
Annual amount used in the EU	150,000 kg
Minimum emission days per year	365
Emission factor air	98.5 %
Emission factor water	1 %
Emission factor soil	0.5 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100

Risk Management Measures	
Type of STP	no STP
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.0372
	Risk from environmental exposure is driven by freshwater sediment.
Maximum amount of safe use	11 kg/d
Risk from environmental exposure is driven by freshwater sediment.	

Contributing exposure scenario	
Use descriptors covered	PC1: Adhesives, Sealants
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 10 %
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 45 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 30 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	3 uses per year Relevant for inhalative exposure estimates
Duration and Frequency of activity	3 uses per year Relevant for dermal exposure estimates
Temperature (Application)	25 °C
body weight	65 kg
Uptake fraction dermal	100 %
Release area	250 cm²
	Release area increases over time
Release duration	30 min
	Relevant for inhalative exposure estimates
Contact rate	50 mg/min
Release duration	30 min
	Relevant for dermal exposure estimates
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0.019 mg/kg bw/day

Risk Characterization Ratio (RCR)	0.001264
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	0.0016 mg/m³
Risk Characterization Ratio (RCR)	0.000546
	The exposure calculation is based on the mean concentration per year.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC9a: Coatings and paints, thinners, paint removers
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 5 %
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 132 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 120 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	1 uses per year Relevant for inhalative exposure estimates
Duration and Frequency of activity	1 uses per year Relevant for dermal exposure estimates
Temperature (Application)	25 °C
body weight	65 kg
Uptake fraction dermal	100 %
Release area	100000 cm²
	Release area increases over time
Release duration	120 min
	Relevant for inhalative exposure estimates
Contact rate	30 mg/min
Release duration	120 min
	Relevant for dermal exposure estimates
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0.0076 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.000506

	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model: exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	1.6763 mg/m³
Risk Characterization Ratio (RCR)	0.558767
	The exposure calculation is based on the mean concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC15: Non-metal-surface treatment products.
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 5 %
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 30 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	Application duration: 60 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	< 1 uses per year Relevant for inhalative exposure estimates
Duration and Frequency of activity	< 1 uses per year Relevant for dermal exposure estimates
Temperature (Application)	25 °C
body weight	65 kg
Uptake fraction dermal	100 %
	Amount per use 0.25 g Relevant for dermal exposure estimates
Release area	150000 cm²
	Release area increases over time
Release duration	60 min
	Relevant for inhalative exposure estimates
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: instant application, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0.0002 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.000012
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model:

	exposure to vapour - evaporation
	Consumer - inhalation, long-term - systemic
Exposure estimate	1.4931 mg/m³
Risk Characterization Ratio (RCR)	0.497709
	The exposure calculation is based on the mean concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

Contributing exposure scenario	
Use descriptors covered	PC23: Leather tanning, dye, finishing, impregnation and care products.
Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 5 %
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 20 min Relevant for inhalative exposure estimates
Duration and Frequency of activity	2 uses per year Relevant for inhalative exposure estimates
Duration and Frequency of activity	2 uses per year Relevant for dermal exposure estimates
Room size	34 m3
Ventilation rate per hour	1.5
body weight	65 kg
Uptake fraction dermal	100 %
Spray duration	900 sec
Contact rate	100 mg/min
Release duration	15 min
	Relevant for dermal exposure estimates
Risk Management Measures	
Consumer Measures	Ensure spraying away from persons.
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Dermal model: constant application rate, Uptake model: Uptake fraction
	Consumer - dermal, long-term - systemic
Exposure estimate	0.0063 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.000421
	The calculation is based on the internal chronic dose.
Assessment method	EASY TRA v4.1, ConsExpo v4.1, Inhalation model: Exposure to spray/dust
	Consumer - inhalation, long-term - systemic

Exposure estimate	0.9895 mg/m³
Risk Characterization Ratio (RCR)	0.329821
	The exposure calculation is based on the mean concentration on the day of exposure.
Guidance to Downstream Users	
For scaling see: http://www.rivm.nl/en/healthanddisease/productsafety/ConsExpo.jsp	

****

14. Short title of exposure scenario

Use in Agrochemicals, (consumer use)
C; ERC8d; PC27

Control of exposure and risk management measures

Contributing exposure scenario	
Use descriptors covered	ECPA SPERC 8d.2.v2
Operational conditions	
Maximum annual application rate	0.142 kg/ha
Minimum emission days per year	365
Emission factor air	100 %
Emission factor water	0 %
Emission factor soil	0 %
Receive Surf. Water (Flow Rate).	18,000 m3/d
Dilution factor river	10
Dilution factor coast	100
Risk Management Measures	
Type of STP	no STP
Exposure estimate and reference to its source	
Assessment method	EASY TRA v4.1, ECETOC TRA v3.0, Environment
Risk Characterization Ratio (RCR)	0.9
	Risk from environmental exposure is driven by marine water.
Maximum amount of safe use	4.5 kg/d
Risk from environmental exposure is driven by freshwater sediment.	

Contributing exposure scenario	
Use descriptors covered	PC27: Plant Protection products.

Operational conditions	
Concentration of the substance	2-Ethylhexyl acetate Content: >= 0 % - <= 100 %
Vapour pressure of the substance during use	31 Pa
Process temperature	20 °C
Duration and Frequency of activity	Exposure duration: 6 h 1 uses per day
Exposure estimate and reference to its source	
Assessment method	ECPA OWB tool v2.5, hand-held spraying
	Consumer - dermal, long-term - systemic
Exposure estimate	0.206 mg/kg bw/day
Risk Characterization Ratio (RCR)	0.013733
Assessment method	ECPA OWB tool v2.5, hand-held spraying
	Consumer - inhalation, long-term - systemic
Exposure estimate	0.002 mg/m³
Risk Characterization Ratio (RCR)	0.000667
Guidance to Downstream Users	
For scaling see: http://www.ecetoc.org/tra	

****