We create chemistry

Safety Data Sheet
BUTYL TRIGLYCOL

1. Identification

Product identifier used on the label

BUTYL TRIGLYCOL

Recommended use of the chemical and restriction on use

Recommended use*: Chemical
Recommended use*: Chemical
Unsuitable for use: Not intended for sale to or use by the general public.

* The “Recommended use” identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number
24 Hour Emergency Response Information
CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification
Chemical family: glycols

2. Hazards Identification

According to Regulation 2024 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Eye Dam./Irrit.	1	Serious eye damage/eye irritation

Label elements

Pictogram:

Signal Word:
Danger

Hazard Statement:

H318	Causes serious eye damage.

Precautionary Statements (Prevention):

P280	Wear eye and face protection.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or physician.

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.
See section 12 - Results of PBT and vPvB assessment.

Labeling of special preparations (GHS):
Repeated exposure may cause skin dryness or cracking.

3. Composition / Information on Ingredients

According to Regulation 2024 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

2-(2-(2-butoxyethoxy)ethoxy)ethanol
CAS Number: 143-22-6
Content (W/W): >= 61.0 - <= 80.0%
Synonym: 2-[2-(2-Butoxyethoxy)ethoxy]ethanol; Triethylene glycol monobutyl ether

3,6,9,12-Tetraoxahexadecan-1-ol
CAS Number: 1559-34-8
Content (W/W): >= 15.0 - <= 33.0%
Synonym: No data available.

The actual concentration is withheld as a trade secret.

4. First-Aid Measures

Description of first aid measures

General advice:
Remove contaminated clothing.

If inhaled:
Keep patient calm, remove to fresh air. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

If on skin:
Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

If in eyes:
Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

Hold eyes open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing.

If swallowed:
Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

Information on: 2-(2-(2-butoxyethoxy)ethoxy)ethanol
Symptoms: Overexposure may cause:, corneal injury, skin corrosion, severe pain, coughing, respiratory disorders, dyspnea, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps
---

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:	Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
dry powder, water spray, carbon dioxide, alcohol-resistant foam

Unsuitable extinguishing media for safety reasons:
water jet

Additional information:
Use extinguishing measures to suit surroundings.

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
The product is combustible. Cool endangered containers with water-spray. See SDS section 7 - Handling and storage.

Advice for fire-fighters
Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear. Special protective equipment for firefighters

Further information:
Evacuate area of all unnecessary personnel. Fight fire from maximum distance.

Extend fire extinguishing measures to the surroundings. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Further accidental release measures:
High risk of slipping due to leakage/spillage of product.

Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

Personal precautions, protective equipment and emergency procedures
Handle in accordance with good industrial hygiene and safety practice.

Environmental precautions
Discharge into the environment must be avoided.

Methods and material for containment and cleaning up
Pick up with suitable appliance and dispose of. Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations.

7. Handling and Storage

Precautions for safe handling
Prevent contact with air/oxygen (formation of peroxide). Ensure thorough ventilation of stores and work areas.

Protection against fire and explosion:
No special precautions necessary. Substance/product is non-flammable.

Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

8. Exposure Controls/Personal Protection

No substance specific occupational exposure limits known.

Advice on system design:
Ensure adequate ventilation.

Personal protective equipment

Respiratory protection:
Wear respiratory protection if ventilation is inadequate. Observe OSHA regulations for respirator use (29 CFR 1910.134).

Hand protection:
Chemical resistant protective gloves

Eye protection:
Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.

Body protection:
Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

General safety and hygiene measures:
Handle in accordance with good industrial hygiene and safety practice. Remove contaminated clothing. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

Physical state:	liquid	
Form:	liquid	
Odour:	almost odourless	
Odour threshold:	not determined	
Colour:	colourless	
pH value:	(20 °C) neutral	
Melting temperature:	approx. -45 °C	
Freezing point:	No data available.	
Boiling range:	265 - 350 °C (1,013 mbar)	(DIN 53171)
Flash point:	131 °C The product has not been tested. The statement has been derived from the properties of the individual components.	(ISO 2719, closed cup)
Flammability:	hardly combustible	(derived from flash point)
Lower explosion limit:	For liquids not relevant for classification and labelling. The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Autoignition:	202 °C The product has not been tested. The statement has been derived from the properties of the individual components.	(DIN 51794)
Vapour pressure:	0.002 mbar (20 °C)	(measured)
	0.02 mbar (50 °C)	(measured)

Density:	0.9917 g/cm3 (20 °C)	(ISO 2811-3)
Relative density:	0.9917 (20 °C)	
Relative vapour density:	> 1 (20 °C) Heavier than air.	(estimated)
Partitioning coefficient n-octanol/water (log Pow):	0.51 (25 °C) The statements are based on the properties of the individual components.	(OECD Guideline 107)
Refractive index:	1.440 - 1.442 (20 °C)	
Self-ignition temperature:	Based on its structural properties the product is not classified as self-igniting.	
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Viscosity, dynamic:	10.6 mPa.s (20 °C) 9.1 mPa.s (25 °C) The product has not been tested. The statement has been derived from substances/products of a similar structure or composition., Literature data. 5.58 mPa.s (40 °C)	
Solubility in water:	989 g/l (20 °C) The product has not been tested. The statement has been derived from the properties of the individual components., Literature data.	
Miscibility with water:	(20 °C) miscible	
Solubility (qualitative):	soluble solvent(s): organic solvents,	
Molecular weight:	not applicable	
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.	

Particle characteristics
Particle size distribution: The substance / product is marketed or used in a non solid or granular form.

10. Stability and Reactivity

Reactivity
No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:
Corrosive effects to metal are not anticipated.

Oxidizing properties:
Based on its structural properties the product is not classified as oxidizing.

Formation of flammable gases:	Remarks:	Forms no flammable gases in the presence of water.

Chemical stability
The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions
Reacts with light metals, with evolution of hydrogen. Reacts with strong oxidizing agents.

Conditions to avoid
No special precautions other than good housekeeping of chemicals.

Incompatible materials
strong oxidizing agents

Hazardous decomposition products

Decomposition products:
Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:
No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity
Assessment of acute toxicity: In animal studies the substance is virtually nontoxic after a single ingestion. Of low toxicity after short-term skin contact. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard.

Oral
Type of value: LD50
Species: rat
Value: > 5,170 mg/kg (BASF-Test)
The product has not been tested. The statement has been derived from the properties of the individual components.

Inhalation
Type of value: LC0
Species: rat
Value: 3.46 mg/l (IRT)
Exposure time: 8 h

The vapour was tested.
No mortality was observed. The product has not been tested. The statement has been derived from the properties of the individual components.

Dermal
Type of value: LD50
Species: rabbit
Value: 3,540 mg/kg
The product has not been tested. The statement has been derived from the properties of the individual components.

Assessment other acute effects
Assessment of STOT single:
Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Irritation / corrosion
Assessment of irritating effects: Not irritating to the skin. May cause severe damage to the eyes.

Skin
Species: rabbit
Result: non-irritant
Method: BASF-Test
The product has not been tested. The statement has been derived from the properties of the individual components.

Eye
Species: rabbit
Result: irreversible damage
Method: OECD Guideline 405
The product has not been tested. The statement has been derived from the properties of the individual components.

Sensitization
Assessment of sensitization: No sensitizing effect.

Guinea pig maximization test
Species: guinea pig
Result: Non-sensitizing.
Method: OECD Guideline 406
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aspiration Hazard
No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity
Assessment of repeated dose toxicity: Repeated oral exposure to large quantities may affect certain organs. Repeated dermal uptake of the substance did not cause substance-related effects. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Genetic toxicity

Assessment of mutagenicity: The substance was not mutagenic in bacteria. The substance was not mutagenic in mammalian cell culture. The product has not been tested. The statement has been derived from the properties of the individual components.

Carcinogenicity
Assessment of carcinogenicity: No data available.

Reproductive toxicity
Assessment of reproduction toxicity: Animal studies gave no indication of a fertility impairing effect at doses which were not toxic to the parental animals. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Teratogenicity
Assessment of teratogenicity: Animal studies gave no indication of a developmental toxic effect at doses that were not toxic to the parental animals. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

12. Ecological Information

Toxicity

Aquatic toxicity
Assessment of aquatic toxicity:
There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish
LC50 (96 h) 2,200 - 4,600 mg/l, Leuciscus idus (DIN 38412 Part 15, static)
The details of the toxic effect relate to the nominal concentration. The product has not been tested. The statement has been derived from the properties of the individual components.

Aquatic invertebrates
EC50 (48 h) > 500 mg/l, Daphnia magna (Directive 92/69/EEC, C.2, static)
The details of the toxic effect relate to the nominal concentration. The product has not been tested. The statement has been derived from the properties of the individual components.

Aquatic plants
EC10 (72 h) 612.6 mg/l (growth rate), Desmodesmus subspicatus (DIN 38412 Part 8, static)
The details of the toxic effect relate to the nominal concentration. The product has not been tested. The statement has been derived from the properties of the individual components.

Chronic toxicity to fish
Study does not need to be conducted.

Chronic toxicity to aquatic invertebrates
Study does not need to be conducted.

Assessment of terrestrial toxicity
No data available.

Microorganisms/Effect on activated sludge

Toxicity to microorganisms

OECD Guideline 209 aquatic
activated sludge, industrial/EC10 (30 min): > 1,995 mg/l
The details of the toxic effect relate to the nominal concentration. The product has not been tested. The statement has been derived from the properties of the individual components.

Persistence and degradability

Assessment biodegradation and elimination (H2O)
Readily biodegradable (according to OECD criteria).

Elimination information

85 % BOD of the ThOD (28 d) (OECD 301D; 92/69/EWG, C.4-E) (aerobic, other bacteria)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

76 % BOD of the ThOD (28 d) (OECD 301D; 92/69/EWG, C.4-E) (aerobic, predominantly domestic sewage, non-adapted)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Assessment of stability in water
According to structural properties, hydrolysis is not expected/probable.

Bioaccumulative potential

Assessment bioaccumulation potential
Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is not to be expected.

Bioaccumulation potential
No data available.

Mobility in soil

Assessment transport between environmental compartments
No data available.
Adsorption to solid soil phase is not expected.

Additional information

Adsorbable organically-bound halogen(AOX):
This product contains no organically-bound halogen.

Other ecotoxicological advice:
Do not discharge product into the environment without control.

13. Disposal considerations

Waste disposal of substance:
Dispose of in accordance with national, state and local regulations.

Container disposal:
Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.
Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport
USDOT
Not classified as a dangerous good under transport regulations

Sea transport
IMDG
Not classified as a dangerous good under transport regulations

Air transport
IATA/ICAO
Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:
Chemical TSCA, US

All substances are TSCA listed and active.

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

EPCRA 313:

CAS Number	Chemical name
143-22-6	2-(2-(2-butoxyethoxy)ethoxy)ethanol

State regulations

State RTK	CAS Number	Chemical name
PA	143-22-6	2-(2-(2-butoxyethoxy)ethoxy)ethanol

NFPA Hazard codes:
Health: 2 Fire: 1 Reactivity: 0 Special:

HMIS III rating
Health: 2 Flammability: 1 Physical hazard: 0

Assessment of the hazard classes according to UN GHS criteria (most recent version):

Eye Dam./Irrit.	1	Serious eye damage/eye irritation
Acute Tox.	5 (dermal)	Acute toxicity

16. Other Information

SDS Prepared by:
BASF NA Product Regulations
SDS Prepared on: 2025/07/03

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

Date / Revised: 2025/07/03 Version: 3.0
Date / Previous version: 2019/03/19 Previous version: 2.0

END OF DATA SHEET