We create chemistry

Safety data sheet

BASF Safety data sheet according to UN GHS 4th rev.
Date / Revised: 19.06.2020 Version: 2.2
Product: **Basonat® HI 178 B/S NG Hardener**
(ID no. 30692903/SDS_GEN_00/EN)
Date of print 11.07.2025

1. Identification

Product identifier

Basonat® HI 178 B/S NG Hardener

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Hardener for coating materials or adhesives for industrial or professional use, Isocyanate used in the manufacturing of polyurethanes, industrial chemicals

Details of the supplier of the safety data sheet

Company:
BASF SE
67056 Ludwigshafen
GERMANY
Global Business Unit Resins and Additives

Telephone: +49 621 60-0
E-mail address: ed-psr@basf.com

Emergency telephone number

International emergency number:
Telephone: +49 180 2273-112

2. Hazards Identification

Classification of the substance or mixture

According to UN GHS criteria

Flam. Liq. 3
Acute Tox. 4 (Inhalation - mist)
Skin Sens. 1

STOT SE 3 (Vapours may cause drowsiness and dizziness.)
STOT SE 3 (irritating to respiratory system)
Aquatic Acute 3
Aquatic Chronic 3

For the classifications not written out in full in this section the full text can be found in section 16.

Label elements

Globally Harmonized System (GHS)

Pictogram:

Signal Word:
Warning

Hazard Statement:

H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H335	May cause respiratory irritation.
H402	Harmful to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves and eye protection or face protection.
P271	Use only outdoors or in a well-ventilated area.
P260	Do not breathe mist or vapour.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273	Avoid release to the environment.
P243	Take action to prevent static discharges.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P272	Contaminated work clothing should not be allowed out of the workplace.
P240	Ground and bond container and receiving equipment.
P242	Use only non-sparking tools.

Precautionary Statements (Response):

P312	Call a POISON CENTER or physician if you feel unwell.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353	IF ON SKIN (or hair): Remove or Take off immediately all contaminated clothing. Rinse skin with water or shower.
P333 + P311	If skin irritation or rash occurs: Call a POISON CENTER or physician.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use foam or dry powder for extinction.

Precautionary Statements (Storage):

P233	Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.

According to UN GHS criteria

Hazard determining component(s) for labelling: (OLIGOMER) Hexamethylene diisocyanate isocyanurate-type oligomers

Other hazards

According to UN GHS criteria

No specific dangers known, if the regulations/notes for storage and handling are considered.

3. Composition/Information on Ingredients

Substances

Not applicable

Mixtures

Chemical nature

(OLIGOMER) Hexamethylene diisocyanate isocyanurate-type oligomers
ca. 80 %

dissolved in: Solvent naphtha (petroleum), light arom., n-Butyl acetate
(1:1)

Hazardous ingredients (GHS)
According to UN GHS criteria

(OLIGOMER) Hexamethylene diisocyanate isocyanurate-type oligomers

Content (W/W): >= 75 % - <= 100 %	Acute Tox. 4 (Inhalation - mist)
	Skin Sens. 1
CAS Number: 28182-81-2	STOT SE 3 (irr. to respiratory syst.)
	H332, H317, H335

n-Butyl acetate

Content (W/W): >= 5 % - < 15 %	Flam. Liq. 3
CAS Number: 123-86-4	STOT SE 3 (drowsiness and dizziness)
EC-Number: 204-658-1	Aquatic Acute 3
INDEX-Number: 607-025-00-1	H226, H336, H402
	EUH066

Solvent naphtha (petroleum), light arom.

Content (W/W): >= 5 % - < 15 %	Asp. Tox. 1
CAS Number: 64742-95-6	Flam. Liq. 3
EC-Number: 265-199-0	STOT SE 3 (drowsiness and dizziness)
	STOT SE 3 (irr. to respiratory syst.)
	Aquatic Acute 2
	Aquatic Chronic 2
	H226, H304, H336, H335, H401, H411
	EUH066

Hexamethylene diisocyanate

Content (W/W): < 0,1 %	Acute Tox. 4 (oral)
CAS Number: 822-06-0	Acute Tox. 1 (Inhalation - mist)
EC-Number: 212-485-8	Skin Corr./Irrit. 2
INDEX-Number: 615-011-00-1	Eye Dam./Irrit. 2A
	Resp. Sens. 1
	Skin Sens. 1
	STOT SE 3 (irr. to respiratory syst.)
	H319, H315, H330, H302, H334, H317, H335
	<u>Specific concentration limit:</u>
	Skin Sens. 1: >= 0,5 %
	Resp. Sens. 1: >= 0,5 %

For the classifications not written out in full in this section the full text can be found in section 16.

4. First-Aid Measures

Description of first aid measures

Immediately remove contaminated clothing.

If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

On skin contact:
Wash thoroughly with soap and water

On contact with eyes:
Wash affected eyes for at least 15 minutes under running water with eyelids held open.

On ingestion:
Rinse mouth and then drink 200-300 ml of water. Do not induce vomiting unless told to by a poison control center or doctor.

Most important symptoms and effects, both acute and delayed
Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

Indication of any immediate medical attention and special treatment needed
Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote, administer corticosteroid dose aerosol to prevent pulmonary odema.

5. Fire-Fighting Measures

Extinguishing media
Suitable extinguishing media:
dry powder, foam

Special hazards arising from the substance or mixture
harmful vapours
Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

Advice for fire-fighters
Special protective equipment:
Wear a self-contained breathing apparatus.

Further information:
The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures
Use personal protective clothing. Breathing protection required.

Environmental precautions
Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up
For large amounts: Pump off product.
For residues: Pick up with suitable absorbent material. Dispose of absorbed material in accordance with regulations.

7. Handling and Storage

Precautions for safe handling
Avoid handling of the substance in case of known skin complaints, hypersensitivity reactions, chronic respiratory disease, asthmatic attacks or bronchial attacks. Avoid contact with the skin, eyes and clothing. Avoid inhalation of dusts/mists/vapours. Avoid frequent and direct contact with substance. Ensure good work practices are implemented. Regular inspection and maintenance of equipment and machines. Clean equipment and the work area every day. Engineering controls have to be used to reduce exposures. Minimise exposure by partial enclosure of the operation or equipment and provide extract ventilation at openings. Workers should receive a pre-placement examination and subsequent periodic medical examinations, including a pulmonary function test. Wear suitable face shield Wear an impervious suit. Use suitable eye protection. Wear chemically resistant gloves in combination with ‘basic’ employee training. Change gloves, if duration of activity exceeds break through time Use a local exhaust ventilation with adequate effectiveness. In case of insufficient ventilation, wear suitable respiratory equipment.

Protection against fire and explosion:
Sources of ignition should be kept well clear. Take precautionary measures against static discharges. If delivered in plastic packing, highest permissable emptying temperature is 5 Kelvin below the flash point.

Conditions for safe storage, including any incompatibilities
Further information on storage conditions: Keep container tightly closed and in a cool place.

Storage stability:
If moisture enters isocyanate containers, CO2 forms and pressure builds up.

8. Exposure Controls/Personal Protection

Control parameters

Components with occupational exposure limits

123-86-4: n-Butyl acetate
822-06-0: Hexamethylene diisocyanate
64742-95-6: Solvent naphtha (petroleum), light arom.

Exposure controls

Personal protective equipment

Respiratory protection:
For short-term or slight exposure, use a respiratory mask with filter, for intensive or long-term exposure wear full respiratory protection apparatus Combination filter for gases/vapours of organic compounds and solid and liquid particles (f.e. EN 14387 Type A-P2)

Hand protection:
Chemical resistant protective gloves (EN 374)
Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN 374)
nitrile rubber (NBR) - 0.4 mm coating thickness
fluoroelastomer (FKM) - 0.7 mm coating thickness
Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:
Safety glasses with side-shields (frame goggles) (f.e. EN 166) and face shield

Body protection:
Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures
Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is required additionally to the stated personal protection equipment. Do not breathe vapour/aerosol/spray mists. Ensure adequate ventilation. Clean equipment, work area and clothing regularly.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Form:	solution	
Colour:	colourless to yellowish	
Odour:	solvent-like	
Odour threshold:	Not determined since harmful by inhalation.	
pH value:	not applicable, hydrolyzes	
solidification temperature:	< -20 °C	(DTA)
boiling temperature:	130 °C (1.013 hPa) Information applies to the solvent.	

Flash point:	42,5 °C	(DIN EN ISO 13736)
Evaporation rate:	not determined	
Flammability:	Flammable liquid and vapour.	(derived from flash point)
Lower explosion limit:	For liquids not relevant for classification and labelling., The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Ignition temperature:	390 °C	(DIN 51794)
Vapour pressure:	12 hPa (20 °C) Information applies to the solvent.	
Density:	1,095 g/cm3 (20 °C)	(ISO 2811-3)
Relative density:	approx. 1,095 (20 °C)	
Relative vapour density (air):	not determined	
Solubility in water:	Reacts with water.	
Solubility (qualitative) solvent(s):	organic solvents soluble	
Partitioning coefficient n-octanol/water (log Kow):	not applicable for mixtures	
Self ignition:	not self-igniting	
Thermal decomposition:	No decomposition if used correctly.	
Viscosity, dynamic:	80 - 230 mPa.s (23 °C, 1.000 1/s)	(DIN EN ISO 3219)
Explosion hazard:	not explosive	
Fire promoting properties:	not fire-propagating	

Other information

Hygroscopy:	Non-hygroscopic	
Surface tension:	Based on chemical structure, surface activity is not to be expected.	
Grain size distribution:	The substance / product is marketed or used in a non solid or granular form.	
Solids content:	77,0 - 79,0 % (105 °C)	(DIN EN ISO 3251)

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability
The product is chemically stable.

Possibility of hazardous reactions
Reacts with alcohols. Reacts with amines. Reacts with substances which contain active hydrogen. Reacts with water, with formation of carbon dioxide. The formation of gaseous decomposition products builds up pressure in tightly closed containers.

Conditions to avoid
Avoid moisture. See SDS section 7 - Handling and storage.

Incompatible materials

Substances to avoid:
water, alcohols, amines

Hazardous decomposition products

:
No hazardous decomposition products if stored and handled as prescribed/indicated.

11. Toxicological Information

Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:
Virtually nontoxic after a single ingestion. Virtually nontoxic after a single skin contact. Of moderate toxicity after short-term inhalation. The product has not been tested. The statement has been derived from the properties of the individual components.

Experimental/calculated data:
LD50 rat (oral): > 5.000 mg/kg
The product has not been tested. The statement has been derived from the properties of the individual components.

LC50 rat (by inhalation): > 1 - 5 mg/l 4 h (OECD Guideline 403)
Determined for mist The substance from the isocyanate substance class has been tested in a form (respirable aerosol) that is different from the forms in which the product is placed on the market and used. Therefore, the test result is not adequate for the purpose of classification and labelling of the product. Based on expert judgement and available data, a modified classification and labeling for acute inhalation toxicity is justified. The generation of a respirable aerosol must be prevented! The product has not been tested. The statement has been derived from the properties of the individual components.

LD50 rat (dermal): > 5.000 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: (OLIGOMER) Hexamethylene diisocyanate isocyanurate-type oligomers
Experimental/calculated data:
LC50 rat (by inhalation): 0,467 mg/l 4 h (OECD Guideline 403)
The test result applies only to the substance transferred into respirable aerosol (particles < 20 µm).
An aerosol was tested.

Irritation

Assessment of irritating effects:
Not irritating to eyes and skin. The product has not been tested. The statement has been derived from the properties of the individual components.

Experimental/calculated data:
Skin corrosion/irritation rabbit: non-irritant (OECD Guideline 404)
The product has not been tested. The statement has been derived from the properties of the individual components.

Serious eye damage/irritation rabbit: non-irritant (OECD Guideline 405)
The product has not been tested. The statement has been derived from the properties of the individual components.

Respiratory/Skin sensitization

Assessment of sensitization:
Caused skin sensitization in animal studies. The product has not been tested. The statement has been derived from the properties of the individual components.

Experimental/calculated data:
Guinea pig maximization test guinea pig: skin sensitizing
sensitizing effect in animal tests The product has not been tested. The statement has been derived from the properties of the individual components.

Germ cell mutagenicity

Assessment of mutagenicity:
No data available concerning mutagenic effects. The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from the properties of the individual components.

Carcinogenicity

Assessment of carcinogenicity:
The whole of the information assessable provides no indication of a carcinogenic effect.

Reproductive toxicity

Assessment of reproduction toxicity:
Based on the ingredients, there is no suspicion of a toxic effect on reproduction.

Developmental toxicity

Assessment of teratogenicity:
Based on the ingredients, there is no suspicion of a teratogenic effect.

Specific target organ toxicity (single exposure)

Assessment of STOT single:
Causes temporary irritation of the respiratory tract.

Remarks: The product has not been tested. The statement has been derived from the properties of the individual components.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:
No reliable data was available concerning repeated dose toxicity.

Information on: n-Butyl acetate
Assessment of repeated dose toxicity:
After repeated exposure the prominent effect is local irritation.

Information on: Solvent naphtha (petroleum), light arom.
Assessment of repeated dose toxicity:
Effects on the kidney of male rats were detected after repeated exposure. These effects are specific for the male rat and are known to be of no relevance to humans. After repeated exposure the prominent effect is local irritation. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aspiration hazard

No aspiration hazard expected.

12. Ecological Information

Toxicity

Assessment of aquatic toxicity:
Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Toxicity to fish:
LC50 (96 h) 10 - 100 mg/l, Brachydanio rerio
The product has not been tested. The statement has been derived from the properties of the individual components.

Aquatic invertebrates:
EC50 10 - 100 mg/l, Daphnia magna
The product has not been tested. The statement has been derived from the properties of the individual components.

Aquatic plants:
EC50 (72 h) 10 - 100 mg/l, algae
The product has not been tested. The statement has been derived from the properties of the individual components.

Microorganisms/Effect on activated sludge:
EC50 (3 h) > 100 mg/l, bacteria
The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations. The product has not been tested. The statement has been derived from the properties of the individual components.

Chronic toxicity to fish:
Study scientifically not justified.

Chronic toxicity to aquatic invertebrates:
No observed effect concentration > 1 mg/l
The product has not been tested. The statement has been derived from the properties of the individual components.

Assessment of terrestrial toxicity:
No data available concerning terrestrial toxicity.

Persistence and degradability

Assessment biodegradation and elimination (H2O):
The substance can be virtually eliminated from water in suitable effluent treatment plants by biodegradation, stripping and mechanical separation. The ecotoxic component(s) is/are readily biodegradable.
The product has not been tested. The statement has been derived from the properties of the individual components.

Elimination information:
Not readily biodegradable (by OECD criteria).

Bioaccumulative potential

Assessment bioaccumulation potential:
Significant accumulation in organisms is not to be expected.
The product has not been tested. The statement has been derived from the properties of the individual components.

Mobility in soil

Assessment transport between environmental compartments:
Volatility: No data available.

Additional information

Add. remarks environm. fate & pathway:
Treatment in biological waste water treatment plants has to be performed according to local and administrative regulations.

Other ecotoxicological advice:
Do not release untreated into natural waters. The local regulations on waste-water treatment must be followed.

13. Disposal Considerations

Waste treatment methods

Must be disposed of or incinerated in accordance with local regulations.

Contaminated packaging:
Uncontaminated packaging can be re-used.
Packs that cannot be cleaned should be disposed of in the same manner as the contents.

14. Transport Information

Land transport

ADR

UN number	UN1866
UN proper shipping name:	RESIN SOLUTION
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	no
Special precautions for user:	Tunnel code: D/E

RID

UN number	UN1866
UN proper shipping name:	RESIN SOLUTION
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	no
Special precautions for user:	None known

Inland waterway transport

ADN

UN number	UN1866
UN proper shipping name:	RESIN SOLUTION
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	no
Special precautions for user:	None known

Transport in inland waterway vessel
Not evaluated

Sea transport

IMDG

UN number:	UN 1866
UN proper shipping name:	RESIN SOLUTION
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	no Marine pollutant: NO
Special precautions for user:	None known

Air transport

IATA/ICAO

UN number:	UN 1866
UN proper shipping name:	RESIN SOLUTION
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	No Mark as dangerous for the environment is needed
Special precautions for user:	None known

Transport in bulk according to Annex II of MARPOL and the IBC Code

Regulation:	Not evaluated
Shipment approved:	Not evaluated
Pollution name:	Not evaluated
Pollution category:	Not evaluated
Ship Type:	Not evaluated

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Not applicable

16. Other Information

Full text of classifications, hazard symbols and hazard statements, if mentioned in section 2 or 3:

Flam. Liq.	Flammable liquids
Acute Tox.	Acute toxicity
Skin Sens.	Skin sensitization
STOT SE	Specific target organ toxicity — single exposure
Aquatic Acute	Hazardous to the aquatic environment - acute
Aquatic Chronic	Hazardous to the aquatic environment - chronic
Asp. Tox.	Aspiration hazard
Skin Corr./Irrit.	Skin corrosion/irritation
Eye Dam./Irrit.	Serious eye damage/eye irritation
Resp. Sens.	Respiratory sensitization
H332	Harmful if inhaled.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.
H402	Harmful to aquatic life.
H304	May be fatal if swallowed and enters airways.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H330	Fatal if inhaled.
H302	Harmful if swallowed.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
EUH066	Repeated exposure may cause skin dryness or cracking.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.