We create chemistry

Safety Data Sheet
Elastollan® EXP L 1270 A 10 000

1. Identification

Product identifier used on the label

Elastollan® EXP L 1270 A 10 000

Recommended use of the chemical and restriction on use
Recommended use*: Polymer
Suitable for use in industrial sector: plastics processing industry
Unsuitable for use: Uses other than recommended

* The “Recommended use” identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number
24 Hour Emergency Response Information
CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification
Chemical family: Polymer based on: polyurethane, stabilizing agents, additives

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

No need for classification according to GHS criteria for this product.

Label elements

The product does not require a hazard warning label in accordance with GHS criteria. The dangerous ingredients are fixed in a polymer matrix. The low content of hazardous ingredients has been proven not to lead to adverse effects in the environment.

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

Labeling of special preparations (GHS):
UNDER HOT MELT PROCESSING CONDITIONS, WEAR PERSONAL PROTECTIVE EQUIPMENT TO PREVENT THERMAL BURNS.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate
CAS Number: 41556-26-7
Content (W/W): >= 0.3 - < 1.0%
Synonym: Decanedioic acid bis(1,2,2,6,6-pentamethyl-4-piperidinyl) ester

ethylene bis(oxyethylene)bis(3-(5-tert-butyl-4-hydroxy-m-tolyl)propionate)
CAS Number: 36443-68-2
Content (W/W): >= 0.1 - < 0.2%
Synonym: 3-(1,1-Dimethylethyl)-4-hydroxy-5-methylbenzenepropanoic acid 1,2-etha
nidiylbis(oxy-2,1-ethanediyl) ester; Triethylene glycol bis[3-(3-tert-butyl-4-hydroxy-5-methylphenyl)propionate]

Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
CAS Number: 82919-37-7
Content (W/W): >= 0.1 - < 0.2%
Synonym: Decanedioic acid, 1-methyl 10-(1,2,2,6,6-pentamethyl-4-piperidinyl) ester

4. First-Aid Measures

Description of first aid measures

General advice:
Avoid contact with the skin, eyes and clothing. Remove contaminated clothing.

If inhaled:
Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Seek medical attention.

If on skin:
Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention. Skin contact with hot molten substance/product may cause thermal burns.

If in eyes:
In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

If swallowed:
Immediately rinse mouth and then drink 200 - 300 ml water, do not induce vomiting, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: (Further) symptoms and / or effects are not known so far
Hazards: No hazards anticipated.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:	Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
water spray, foam, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture
Hazards during fire-fighting:
No particular hazards known.

Advice for fire-fighters
Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:
In case of fire and/or explosion do not breathe fumes.

6. Accidental release measures

Further accidental release measures:
High risk of slipping due to leakage/spillage of product.

Personal precautions, protective equipment and emergency procedures
No special precautions necessary.

Environmental precautions
No special precautions necessary.

Methods and material for containment and cleaning up
Spills should be contained and placed in suitable containers for disposal.

7. Handling and Storage

Precautions for safe handling
Provide suitable exhaust ventilation at drying process and in the surrounding of processing machines.

Protection against fire and explosion:
No special precautions necessary.

Conditions for safe storage, including any incompatibilities
Segregate from foods and animal feeds.

Suitable materials for containers: Paper/Fibreboard, High density polyethylene (HDPE), Low density polyethylene (LDPE)

Further information on storage conditions: Avoid extreme heat. Avoid deposition of dust.
From this information no suitability of the materials mentioned above for the design of installations, including containers for permanent storage, can be inferred. Special conditions apply to the selection of materials in this regard, which we can communicate on request.

Storage class according to TRGS 510 (originally VCI, Germany): (11) Combustible solids

Storage stability:
Protect against moisture.
Protect from temperatures below: 15 °C
Protect from temperatures above: 25 °C
After exceeding the temperature limit, the product is no longer free-flowing.

8. Exposure Controls/Personal Protection

No substance specific occupational exposure limits known.

Advice on system design:
Provide local exhaust ventilation to control dust.

Personal protective equipment

Respiratory protection:
Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator as needed.

Hand protection:
Wear gloves to prevent contact during mechanical processing and/or hot melt conditions.

Eye protection:
Wear splash goggles to protect from hot molten substance/product.

Body protection:
Standard work clothes and shoes., Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:
Wear protective clothing to prevent contact during mechanical processing and/or hot melt conditions. Avoid inhalation of dust. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

Form:	granules	
Odour:	odourless	
Odour threshold:	not determined	
Colour:	transparent to opaque	
pH value:	not applicable	
softening temperature:	> 120 °C	
Freezing point:	No data available.	
Melting point:	No data available.	
boiling temperature:	The product is a non-volatile solid.	
Sublimation point:	No applicable information available.	
Flash point:	not applicable, the product is a solid	
Flammability:	not flammable	(Directive 92/69/EEC, A.10)
Lower explosion limit:	For solids not relevant for classification and labelling.	
Upper explosion limit:	For solids not relevant for classification and labelling.	
Autoignition:	> 400 °C	
SADT:	Not a substance liable to self-decomposition according to UN transport regulations, class 4.1.	
Vapour pressure:	not applicable	
Density:	approx. 1.05 g/cm3 (20 °C)	
Relative density:	approx. 1.1 - 1.2 (20 °C)	
Bulk density:	500 - 700 kg/m3 (20 °C)	
Vapour density:	not applicable	
Partitioning coefficient n-octanol/water (log Pow):	not applicable	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated. > 230 °C Thermal decomposition above the indicated temperature is possible. Prolonged thermal loading can result in products of degradation being given off.	
Viscosity, dynamic:	not applicable	
Viscosity, kinematic:	not applicable, the product is a solid	
Particle size:	typically D50 4.5 - 4.7 mm	
Solubility in water:	insoluble	
Molar mass:	No data available.	
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.	

Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.

10. Stability and Reactivity

Reactivity
No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:
No corrosive effect on metal.

Oxidizing properties:
not fire-propagating

Reactions with water/air:	Reaction with:	water
	Flammable gases:	no
	Toxic gases:	no

Chemical stability
The product is chemically stable.

Peroxides:	The product does not contain peroxides. The product/the substance has not a tendency towards the formation of peroxide.

Possibility of hazardous reactions
The product is chemically stable.

Conditions to avoid
No conditions known that should be avoided.

Incompatible materials
No substances known that should be avoided.

Hazardous decomposition products

Decomposition products:
carbon monoxide, carbon dioxide, hydrogen cyanide

Thermal decomposition:
No decomposition if stored and handled as prescribed/indicated.
> 230 °C
Thermal decomposition above the indicated temperature is possible.
Prolonged thermal loading can result in products of degradation being given off.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity
Assessment of acute toxicity: Inhalation of particulates may cause respiratory tract irritation. Ingestion may cause gastrointestinal disturbances. Contact with molten product may cause thermal burns. The resin in pelleted form poses a low hazard.

Oral
Type of value: LD50
Species: rat
Value: > 5,000 mg/kg

Inhalation
No applicable information available.

Dermal
No applicable information available.

Assessment other acute effects
Assessment of STOT single:
Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Irritation / corrosion
Assessment of irritating effects: Not irritating to the eyes. Not irritating to the skin.
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Sensitization
Assessment of sensitization: The chemical structure does not suggest a sensitizing effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate
Assessment of sensitization:
Sensitization after skin contact possible.

Information on: Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
Assessment of sensitization:
Sensitization after skin contact possible.

Aspiration Hazard
No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity
Assessment of repeated dose toxicity: No known chronic effects.

Genetic toxicity
Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect.

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Carcinogenicity
Assessment of carcinogenicity: The chemical structure does not suggest a specific alert for such an effect.
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Reproductive toxicity
Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect.
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate
Assessment of reproduction toxicity: The results of animal studies suggest a fertility impairing effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
Assessment of reproduction toxicity: The results of animal studies suggest a fertility impairing effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Teratogenicity
Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect.
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Other Information
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

12. Ecological Information

Toxicity

Aquatic toxicity
Assessment of aquatic toxicity:
At the present state of knowledge, no negative ecological effects are expected. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

Toxicity to fish

Information on: ethylene bis(oxyethylene)bis(3-(5-tert-butyl-4-hydroxy-m-tolyl)propionate)
LC50 (96 h) 43 mg/l, Lepomis macrochirus (OECD Guideline 203, static)
The product has low solubility in the test medium. An aqueous solution prepared with solubilizers has been tested. The LC50 is higher than the solubility limit. No toxic effects occur within the range of solubility. The statement of the toxic effect relates to the analytically determined concentration.

Aquatic invertebrates

Information on: ethylene bis(oxyethylene)bis(3-(5-tert-butyl-4-hydroxy-m-tolyl)propionate)
EC50 (48 h) > 100 mg/l, Daphnia magna (OECD Guideline 202, part 1, static)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The product has low solubility in the test medium. A saturated solution has been tested. Limit concentration test only (LIMIT test). The details of the toxic effect relate to the nominal concentration.

Aquatic plants

Information on: ethylene bis(oxyethylene)bis(3-(5-tert-butyl-4-hydroxy-m-tolyl)propionate)
EC50 (72 h) > 100 mg/l (biomass), Scenedesmus subspicatus (Guideline 92/69/EEC, C.3, static)
The product has low solubility in the test medium. An aqueous solution prepared with solubilizers has been tested. No toxic effects occur within the range of solubility. The details of the toxic effect relate to the nominal concentration.
No observed effect concentration (72 h) 100 mg/l (biomass), Scenedesmus subspicatus (Guideline 92/69/EEC, C.3, static)
The product has low solubility in the test medium. An aqueous solution prepared with solubilizers has been tested. No toxic effects occur within the range of solubility. The details of the toxic effect relate to the nominal concentration.

Microorganisms/Effect on activated sludge

Toxicity to microorganisms

Information on: ethylene bis(oxyethylene)bis(3-(5-tert-butyl-4-hydroxy-m-tolyl)propionate)
OECD Guideline 209 static
activated sludge, domestic/EC20 (3 h): > 100 mg/l
The details of the toxic effect relate to the nominal concentration.
OECD Guideline 209 static
activated sludge, domestic/EC50 (3 h): > 100 mg/l
The details of the toxic effect relate to the nominal concentration.

Persistence and degradability

Assessment biodegradation and elimination (H2O)
Poorly biodegradable.

Elimination information

Poorly biodegradable.

Bioaccumulative potential

Assessment bioaccumulation potential
Does not significantly accumulate in organisms.

Mobility in soil

Assessment transport between environmental compartments
Adsorption to solid soil phase is not expected.

Additional information

Adsorbable organically-bound halogen(AOX):
This product contains no organically-bound halogen.

13. Disposal considerations

Waste disposal of substance:
Incinerate or dispose of in a licensed facility. Do not discharge substance/product into sewer system.

Container disposal:
Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport
USDOT
Not classified as a dangerous good under transport regulations

Sea transport
IMDG
Not classified as a dangerous good under transport regulations

Air transport
IATA/ICAO
Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:
Chemical TSCA, US

All substances are TSCA listed and active.

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including FORMALDEHYDE (GAS), which is known to the State of California to cause cancer, and METHANOL, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:
Health: 1 Fire: 0 Reactivity: 0 Special:

HMIS III rating

Health: 1 Flammability: 0 Physical hazard: 0

16. Other Information

SDS Prepared by:
BASF NA Product Regulations
SDS Prepared on: 2024/09/24

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Elastollan® EXP L 1270 A 10 000 is a registered trademark of BASF Corporation or BASF SE
IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
Trademark potentially not registered in all countries.

END OF DATA SHEET