Safety Data Sheet
BalanGut™ LS P

1. Identification

Product identifier used on the label

BalanGut™ LS P

Recommended use of the chemical and restriction on use

Recommended use*: For animal nutrition purpose
Unsuitable for use: Not intended for sale to or use by the general public.

* The “Recommended use” identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

24 Hour Emergency Response Information
CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Synonyms: Preparation based on: Mono-, Di- and Triglycerides of C4, C8 and C10 saturated fatty acids, Silicon dioxide

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Combustible Dust	Combustible Dust (1)	Combustible Dust

Label elements

Signal Word:
Warning

Hazard Statement:
May form combustible dust concentration in air.

Hazards not otherwise classified

The product is under certain conditions capable of dust explosion.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Silicon dioxide
CAS Number: 7631-86-9
Content (W/W): 30.0 - 35.0%
Synonym: Siliciumdioxid

glycerol
CAS Number: 56-81-5
Content (W/W): 19.0 - 25.0%
Synonym: 1,2,3-Propanetriol; Glycerol

4. First-Aid Measures

Description of first aid measures

General advice:
Remove contaminated clothing.

If inhaled:
Keep patient calm, remove to fresh air.

If on skin:
Wash thoroughly with soap and water

If in eyes:
Wash affected eyes for at least 15 minutes under running water with eyelids held open.

If swallowed:
Rinse mouth and then drink 200-300 ml of water.

Most important symptoms and effects, both acute and delayed

Symptoms: No data available.

Indication of any immediate medical attention and special treatment needed

Note to physician
Treatment: Symptomatic treatment (decontamination, vital functions).

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:
water jet

Additional information:
Avoid whirling up the material/product because of the danger of dust explosion.

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
harmful vapours, carbon oxides
The substances/groups of substances mentioned can be released in case of fire. Evolution of fumes/fog. Burning produces harmful and toxic fumes. Dust explosion hazard.

Advice for fire-fighters

Protective equipment for fire-fighting:
Wear a self-contained breathing apparatus.

Further information:
Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Cool endangered containers with water-spray.

Dusty conditions may ignite explosively in the presence of an ignition source causing flash fire.

6. Accidental release measures

Further accidental release measures:
Avoid dispersal of dust in the air (e.g. by clearing dusty surfaces with compressed air). Avoid the formation and build-up of dust - danger of dust explosion. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition.

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Information regarding personal protective measures, see section 8. Avoid dust formation. Avoid contact with the skin, eyes and clothing.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Contain with dust binding material and dispose of.
For large amounts: Sweep/shovel up.
Dispose of absorbed material in accordance with regulations. Avoid raising dust. Use spark-proof tools and explosion-proof equipment.

Nonsparking tools should be used.

7. Handling and Storage

Precautions for safe handling

Avoid dust formation. Provide exhaust ventilation if dust is formed.

Protection against fire and explosion:
Avoid dust formation. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids (2013 Edition) for safe handling.

Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

glycerol	OSHA Z1:	PEL 15 mg/m3 Total dust ;
	OSHA Z1:	PEL 5 mg/m3 Respirable fraction ;
Silicon dioxide	ACGIH, US:	TWA value 10 mg/m3 Inhalable particles ;
	ACGIH, US:	TWA value 3 mg/m3 Respirable particles ;
	OSHA Z3:	TWA value 15 mg/m3 Total dust ;
	OSHA Z3:	TWA value 5 mg/m3 Respirable fraction ;
	OSHA Z3:	TWA value 50 millions of particles per cubic foot of air Total dust ;
	OSHA Z3:	TWA value 15 millions of particles per cubic foot of air Respirable fraction ;
	OSHA Z3:	TWA value 0.8 mg/m3 ; The exposure limit is calculated from the equation, 80mg/m3)/(%SiO2), using a value of 100% SiO2. Lower percentages of SiO2 will yield higher exposure limits.
	OSHA Z3:	TWA value 20 millions of particles per cubic foot of air ;

Advice on system design:
It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen deficient environment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Use only appropriately classified electrical equipment and powered industrial trucks.

Personal protective equipment

Respiratory protection:
Wear a NIOSH-certified (or equivalent) respirator as necessary.

Hand protection:
Wear chemical resistant protective gloves.

Eye protection:
Wear safety goggles (chemical goggles) if there is potential for airborne dust exposures.

Body protection:
Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:
Handle in accordance with good industrial hygiene and safety practice. Wearing of closed work clothing is recommended. Avoid contact with the skin, eyes and clothing. No eating, drinking, smoking or tobacco use at the place of work. Hands and/or face should be washed before breaks and at the end of the shift. Store work clothing separately.

9. Physical and Chemical Properties

Form:	free flowing, powder	
Odour:	nutty	
Odour threshold:	not determined	
Colour:	white	
pH value:	not soluble	
Melting point:	The data refers to the carrier material.	
Freezing point:	No data available.	
Information on: Silicon dioxide		
Melting point:	1,610 °C Literature data.	(other)

Boiling point:	The substance / product decomposes therefore not determined.	
Flash point:	not applicable, the product is a solid	
Flammability:	not highly flammable	(UN Test N.1 (ready combustible solids))
Lower explosion limit:	For solids not relevant for classification and labelling.	
Upper explosion limit:	For solids not relevant for classification and labelling.	
SADT:	> 75 °C Heat accumulation / Dewar 500 ml (SADT, UN-Test H.4, 28.4.4)	
Vapour pressure:	negligible	
Density:	No information is available for the absolute density. Instead the bulk density was determined as a more relevant value.	
Bulk density:	approx. 750 kg/m3 (20 °C)	
Vapour density:	The product is a non-volatile solid.	

Partitioning coefficient n-octanol/water (log Pow):	not applicable for mixtures
Thermal decomposition:	>= 165 °C (DSC (DIN 51007)) self-accelerating reaction
Viscosity, dynamic:	not applicable, the product is a solid
Viscosity, kinematic:	not applicable, the product is a solid
Solubility in water:	insoluble
Solubility (qualitative):	partly soluble solvent(s): Ethanol, ether,
Molar mass:	No data available.
Evaporation rate:	The product is a non-volatile solid.

10. Stability and Reactivity

Reactivity
No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:
Corrosive effects to metal are not anticipated.

Oxidizing properties:
Based on its structural properties the product is not classified as oxidizing.

Minimum ignition energy:
(DIN EN 13821)
The product is capable of dust explosion.

Chemical stability
The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions
Dust can form an explosive mixture with air.

Conditions to avoid
Avoid dust formation. Avoid electro-static discharge. Avoid all sources of ignition: heat, sparks, open flame.

Incompatible materials
None known during use and storage if used according to instructions.

Hazardous decomposition products

Decomposition products:
Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:
>= 165 °C (DSC (DIN 51007))
self-accelerating reaction

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity
Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact.

Oral
Species: mouse
Value: > 6,000 mg/kg

Information on: glycerol
Type of value: LD50
Species: rat
Value: 27,200 mg/kg (other)

Inhalation
No data available.

Dermal
No data available.

Assessment other acute effects
Based on available data, the classification criteria are not met.

Irritation / corrosion
Assessment of irritating effects: Based on available data, the classification criteria are not met.

Skin
No data available.

Eye
No data available.

Sensitization
Assessment of sensitization: No data available.

Aspiration Hazard
not applicable

Chronic Toxicity/Effects

Repeated dose toxicity
Assessment of repeated dose toxicity: Based on available data, the classification criteria are not met.

Genetic toxicity
Genetic toxicity in vitro: OECD Guideline 471 Bacterial reverse mutation assay S. typhimurium, E. coli:with and without metabolic activation negative

Carcinogenicity
Assessment of carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity
Assessment of reproduction toxicity: Based on available data, the classification criteria are not met.

Teratogenicity
Assessment of teratogenicity: Based on available data, the classification criteria are not met.

Other Information
The product has not been tested. The statement has been derived from the properties of the individual components.

12. Ecological Information

Toxicity

Aquatic toxicity
Assessment of aquatic toxicity:
There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statement has been derived from the properties of the individual components.

Microorganisms/Effect on activated sludge

Toxicity to microorganisms
OECD Guideline 209 aerobic
activated sludge, domestic, non-adapted/EC10 (3 h): > 1,000 mg/l

Persistence and degradability

Assessment biodegradation and elimination (H2O)
Readily biodegradable (according to OECD criteria).

Elimination information

83 % CO2 formation relative to the theoretical value (28 d) (OECD 301B; ISO 9439; 92/69/EWG, C.4-C) (aerobic, activated sludge, domestic, non-adapted) Readily biodegradable (according to OECD criteria).

Bioaccumulative potential

Assessment bioaccumulation potential
Significant accumulation in organisms is not to be expected.
The product has not been tested. The statement has been derived from the properties of the individual components.

Mobility in soil

Assessment transport between environmental compartments
The substance will not evaporate into the atmosphere from the water surface.
The product has not been tested. The statement has been derived from the properties of the individual components.

13. Disposal considerations

Waste disposal of substance:
Observe national and local legal requirements.

Container disposal:
Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport
USDOT

Not classified as a dangerous good under transport regulations

Sea transport
IMDG

Not classified as a dangerous good under transport regulations

Air transport
IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Feed	TSCA, US	released / exempt
Chemical	TSCA, US	blocked / not listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

CERCLA RQ	CAS Number	Chemical name
5000 LBS	107-92-6	butyric acid

State regulations

State RTK	CAS Number	Chemical name
NJ	56-81-5	glycerol
PA	56-81-5	glycerol
	7631-86-9	Silicon dioxide

NFPA Hazard codes:
Health: 0 Fire: 1 Reactivity: 0 Special:

HMIS III rating
Health: 0 Flammability: 1 Physical hazard: 0

16. Other Information

SDS Prepared by:
BASF NA Product Regulations
SDS Prepared on: 2023/10/13

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
Any other intended applications should be discussed with the manufacturer.
Corresponding occupational protection measurements must be followed.

END OF DATA SHEET