We create chemistry

Safety data sheet

1. Substance/preparation and manufacturer/supplier identification

Product name:
Basoflux® RD 5119 T

Use: Performance Chemicals for Oilfield Applications

Manufacturer/supplier:
BASF (Thai) Limited
23rd Floor, Emporium Tower, 622, Sukhumvit 24 Rd.,
Klongton, Klongtoey, Bangkok 10110, THAILAND
Telephone: +66 2624-1999
Telefax number: +66 2664-9254
E-mail address: Thailand-SDS-info@basf.com

Emergency information:
International emergency number:
Telephone: +49 180 2273-112

2. Hazard identification

Classification according to UN GHS 2009

Classification of the substance and mixture:
Flammable liquids: Cat.4
Specific target organ toxicity — single exposure: Cat.3 (May cause drowsiness and dizziness.)
Hazardous to the aquatic environment - acute: Cat.3
Hazardous to the aquatic environment - chronic: Cat.3

Label elements and precautionary statement:

Pictogram:

Signal Word:
Warning

Hazard Statement:

H227	Combustible liquid.
H336	May cause drowsiness or dizziness.
H402	Harmful to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P271	Use only outdoors or in a well-ventilated area.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves and eye protection or face protection.
P273	Avoid release to the environment.
P261	Avoid breathing mist or vapour or spray.

Precautionary Statements (Response):

P312	Call a POISON CENTER or physician if you feel unwell.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P370 + P378	In case of fire: Use foam or dry powder for extinction.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.

Other hazards which do not result in classification:
If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.
The product does not contain a substance above legal limits fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

Repeated exposure may cause skin dryness or cracking. Product contains the following components and may cause carcinogenicity:
naphthalene

3. Composition/information on ingredients

Chemical nature

Substance nature: mixture

Preparation based on: polyacrylate, solvent(s)

Hazardous ingredients

Distillates (petroleum), hydrotreated light
Content (W/W): >= 25 % - < 50 % Asp. Tox.: Cat. 1
CAS Number: 64742-47-8 Flam. Liq.: Cat. 4

solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified
Content (W/W): >= 20 % - < 25 % Asp. Tox.: Cat. 1
CAS Number: 64742-94-5 Flam. Liq.: Cat. 4
STOT SE: Cat. 3 (drowsiness and dizziness)
Aquatic Acute: Cat. 2
Aquatic Chronic: Cat. 2

1,2,4-trimethylbenzene
Content (W/W): >= 1 % - < 3 % Asp. Tox.: Cat. 1
CAS Number: 95-63-6 Flam. Liq.: Cat. 3
Acute Tox.: Cat. 4 (Inhalation - vapour)
Skin Irrit.: Cat. 2
Aquatic Chronic: Cat. 2
Eye Irrit.: Cat. 2A
STOT SE: Cat. 3 (irr. to respiratory syst.)
Aquatic Acute: Cat. 2

naphthalene (as a component of solvent naphtha heavy)
Content (W/W): > 0 % - < 0.3 % Flam. Sol.: Cat. 2
CAS Number: 91-20-3 Acute Tox.: Cat. 4 (oral)
Carc.: Cat. 2
Aquatic Acute: Cat. 1
Aquatic Chronic: Cat. 1
M-factor acute: 1
M-factor chronic: 1

4. First-Aid Measures

General advice:
Immediately remove contaminated clothing.

If inhaled:
Keep patient calm, remove to fresh air, seek medical attention.

On skin contact:
Wash thoroughly with soap and water

On contact with eyes:
Wash affected eyes for at least 15 minutes under running water with eyelids held open.

On ingestion:
Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Note to physician:

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far
Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Suitable extinguishing media:
dry powder, foam

Specific hazards:
harmful vapours, carbon oxides, hydrocarbons
Generation of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

Special protective equipment:
Wear a self-contained breathing apparatus.

Further information:
The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental Release Measures

Personal precautions:
Use personal protective clothing.Breathing protection required.Avoid inhalation.Avoid contact with skin.Ensure adequate ventilation.Sources of ignition should be kept well clear.

Environmental precautions:
Contain contaminated water/firefighting water.Do not discharge into drains/surface waters/groundwater.

Methods for cleaning up or taking up:
For large amounts: Pump off product.
For residues: Pick up with suitable absorbent material. Dispose of absorbed material in accordance with regulations.

7. Handling and Storage

Handling

Ensure thorough ventilation of stores and work areas. Avoid skin contact. Avoid inhalation of the product. Wear suitable personal protective equipment.

No eating, drinking, smoking or tobacco use at the place of work. Remove contaminated clothing and protective equipment before entering eating areas. Wash hands before breaks and at end of work.

Protection against fire and explosion:
Sources of ignition should be kept well clear. Take precautionary measures against static discharges. If delivered in plastic packing, highest permissable emptying temperature is 5 Kelvin below the flash point.

Storage

Segregate from foods and animal feeds. Segregate from nitrites.
Further information on storage conditions: Keep container tightly closed and in a cool place.

Storage stability:
Storage temperature: <= 50 °C

The packed product is not damaged by low temperatures or by frost.
Protect from temperatures above: 50 °C
Changes in the properties of the product may occur if substance/product is stored above indicated temperature for extended periods of time.

8. Exposure controls and personal protection

Components with occupational exposure limits

1,2,4-trimethylbenzene, 95-63-6;
TWA value 10 ppm (ACGIHTLV)

Solvent naphtha (petroleum), heavy arom., 64742-94-5;
TWA value 200 mg/m3 (ACGIHTLV), Non-aerosol
Measured as: total hydrocarbon vapor
Application restricted to conditions in which there are negligible aerosol exposures.
Skin Designation (ACGIHTLV), Non-aerosol
Measured as: total hydrocarbon vapor
Danger of cutaneous absorption
Skin Designation (ACGIHTLV), Non-aerosol
Measured as: total hydrocarbon vapor
Danger of cutaneous absorption
TWA value 200 mg/m3 (ACGIHTLV), Non-aerosol
Measured as: total hydrocarbon vapor
Application restricted to conditions in which there are negligible aerosol exposures.

Distillates (petroleum), hydrotreated light, 64742-47-8;

TWA value 200 mg/m3 (ACGIHTLV), Non-aerosol
Measured as: total hydrocarbon vapor
Application restricted to conditions in which there are negligible aerosol exposures.
Skin Designation (ACGIHTLV), Non-aerosol
Measured as: total hydrocarbon vapor
Danger of cutaneous absorption

Personal protective equipment

Respiratory protection:
Suitable respiratory protection for lower concentrations or short-term effect: Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Hand protection:
Chemical resistant protective gloves
Suitable materials also with prolonged, direct contact (Recommended: Protective index 6, corresponding > 480 minutes of permeation time according to EN ISO 374-1):
fluoroelastomer (FKM) - 0.7 mm coating thickness
Polyethylene-Laminate (PE laminate) - ca. 0.1 mm coating thickness
Suitable materials for short-term contact (recommended: At least protective index 2, corresponding > 30 minutes of permeation time according to EN ISO 374-1)
nitrile rubber (NBR) - 0.4 mm coating thickness
Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:
Safety glasses with side-shields.

Body protection:
Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures:
Wearing of closed work clothing is required additionally to the stated personal protection equipment.
Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

Form:	liquid to waxy
Colour:	colourless to yellowish
Odour:	mineral oil-like
Odour threshold:	not determined
pH value:	not applicable, insoluble
Melting point:	17 - 23 °C

Boiling point:	> 190 °C	
Flash point:	62.5 °C The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.	(ISO 2719)
Evaporation rate:	not determined	
Flammability (solid/gas):	Combustible liquid.	(derived from flash point)
Lower explosion limit:	For liquids not relevant for classification and labelling., The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Ignition temperature:	> 230 °C	(DIN 51794)
Thermal decomposition:	375 °C , > 200 J/g self-accelerating reaction	(DSC (DIN 51007))
Self ignition:	not self-igniting	
Explosion hazard:	not explosive	
Fire promoting properties:	not fire-propagating	
Vapour pressure:	approx. 5.96 hPa (20 °C) static approx. 17.82 hPa (50 °C) static approx. 20.98 hPa (55 °C) static	
Density:	0.89 g/cm3 (15 °C)	(ISO 2811-3)
	0.879 g/cm3 (20 °C)	(ISO 2811-3)
	0.8581 g/cm3 (50 °C)	(ISO 2811-3)
Relative vapour density (air):	> 1 (20 °C) Heavier than air.	(estimated)
Solubility in water:	dispersible when hot	
Hygroscopy:	Non-hygroscopic	
Solubility (qualitative) solvent(s):	aromatic hydrocarbons soluble	
Partitioning coefficient n-octanol/water (log Pow):	not applicable for mixtures	

Viscosity, dynamic:	932 mPa.s (23 °C)	
Viscosity, kinematic:	approx. 1,060 mm2/s (23 °C)	(calculated (from dynamic viscosity))

Particle characteristics

Particle size distribution: The substance / product is marketed or used in a non solid or granular form. -

10. Stability and Reactivity

Conditions to avoid:
Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

Thermal decomposition: 375 °C, > 200 J/g (DSC (DIN 51007))
self-accelerating reaction

Substances to avoid:
strong acids, strong bases, strong oxidizing agents

Corrosion to metals: No corrosive effect on metal.

Hazardous reactions:
No hazardous reactions when stored and handled according to instructions.

Hazardous decomposition products:
No hazardous decomposition products if stored and handled as prescribed/indicated.

Chemical stability:
The product is stable if stored and handled as prescribed/indicated.

Reactivity:
No hazardous reactions if stored and handled as prescribed/indicated.

11. Toxicological Information

Routes of exposure

Acute oral toxicity

Experimental/calculated data:
ATE (oral): > 5,000 mg/kg

Acute dermal toxicity

ATE (dermal): > 5,000 mg/kg

Information on: solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified

Acute oral toxicity

Experimental/calculated data:

LD50 rat (oral): 6,318 mg/kg (OECD Guideline 401)

Information on: Distillates (petroleum), hydrotreated light

Acute oral toxicity

Experimental/calculated data:
LD50 rat (oral): > 5,000 mg/kg (OECD Guideline 420)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified

Acute inhalation toxicity

Experimental/calculated data:
LC50 rat (by inhalation): > 4.688 mg/l (OECD Guideline 403)

Information on: Distillates (petroleum), hydrotreated light

Acute inhalation toxicity

Experimental/calculated data:
LC50 rat (by inhalation): > 5.28 mg/l 4 h (OECD Guideline 403)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition. The vapour was tested.

Information on: solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified

Acute dermal toxicity

Experimental/calculated data:
LD50 rabbit (dermal): > 2,000 mg/kg (OECD Guideline 402)

Information on: Distillates (petroleum), hydrotreated light

Acute dermal toxicity

Experimental/calculated data:
LD50 rabbit (dermal): > 2,000 mg/kg (OECD Guideline 402)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Symptoms

Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.
(Further) symptoms and / or effects are not known so far

Irritation

Assessment of irritating effects:
May cause slight irritation to the skin. May cause slight irritation to the eyes. May cause slight irritation to the respiratory tract.

Respiratory/Skin sensitization

Assessment of sensitization:

Based on available data, the classification criteria are not met.

Information on: solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified
Assessment of sensitization:
No sensitizing effect.

Information on: Distillates (petroleum), hydrotreated light
Assessment of sensitization:
Skin sensitizing effects were not observed in animal studies. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Germ cell mutagenicity

Assessment of mutagenicity:
Based on the ingredients, there is no suspicion of a mutagenic effect.

Information on: solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified
Assessment of mutagenicity:
Based on available data, the classification criteria are not met.

Information on: Distillates (petroleum), hydrotreated light
Assessment of mutagenicity:
In the majority of tests performed (bacteria/microorganisms/cell cultures) a mutagenic effect was not found. A mutagenic effect was also not observed in in-vivo assays. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Carcinogenicity

Assessment of carcinogenicity:
Based on available data, the classification criteria are not met.

Information on: solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified
Assessment of carcinogenicity:
Based on available data, the classification criteria are not met.

Information on: Distillates (petroleum), hydrotreated light
Assessment of carcinogenicity:
Long-term exposure to highly irritating concentrations resulted in skin tumors in animals. A carcinogenic effect in humans can be excluded after brief skin contact. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Reproductive toxicity

Assessment of reproduction toxicity:
Based on the ingredients, there is no suspicion of a toxic effect on reproduction.

Information on: solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified
Assessment of reproduction toxicity:
Based on available data, the classification criteria are not met.

Information on: Distillates (petroleum), hydrotreated light

Assessment of reproduction toxicity:
The results of animal studies gave no indication of a fertility impairing effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Developmental toxicity

Assessment of teratogenicity:
Based on the ingredients, there is no suspicion of a teratogenic effect.

Information on: solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified
Assessment of teratogenicity:
Based on available data, the classification criteria are not met.

Information on: Distillates (petroleum), hydrotreated light
Assessment of teratogenicity:
No indications of a developmental toxic / teratogenic effect were seen in animal studies. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Specific target organ toxicity (single exposure)

Possible narcotic effects (drowsiness or dizziness).

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:
Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Aspiration hazard

No aspiration hazard expected.

Other relevant toxicity information

The product has not been tested. The statements on toxicology have been derived from the properties of the individual components. Has a degreasing effect on skin.

12. Ecological Information

Ecotoxicity

Assessment of aquatic toxicity:
Acutely harmful for aquatic organisms. Harmful to aquatic life with long lasting effects.

Information on: solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified
Toxicity to fish:
LL50 (96 h) 2 mg/l, Oncorhynchus mykiss

LL50 (96 h) < 5 mg/l, Oncorhynchus mykiss

Information on: solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified
Aquatic invertebrates:
EL50 (48 h) 3 mg/l, Daphnia magna

EL50 (48 h) < 10 mg/l, Daphnia magna

Information on: solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified
Chronic toxicity to fish:
NOEL (28 d) 0.441 mg/l, Oncorhynchus mykiss

Information on: solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified
Chronic toxicity to aquatic invertebrates:
NOEL (21 d), 0.771 mg/l, Daphnia magna

Mobility

Assessment transport between environmental compartments:
No data available.

Persistence and degradability

Assessment biodegradation and elimination (H2O):
Not readily biodegradable (by OECD criteria).

Bioaccumulation potential

Assessment bioaccumulation potential:
Accumulation in organisms is expected.

Information on: Distillates (petroleum), hydrotreated light
Assessment bioaccumulation potential:
Accumulation in organisms is expected.

Additional information

Other ecotoxicological advice:
The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components. Do not discharge product into the environment without control.

13. Disposal Considerations

Must be disposed of or incinerated in accordance with local regulations.

Contaminated packaging:
Uncontaminated packaging can be re-used.

Packs that cannot be cleaned should be disposed of in the same manner as the contents.

14. Transport Information

Domestic transport:

	Not classified as a dangerous good under transport regulations
UN number or ID number	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

Sea transport
IMDG

	Not classified as a dangerous good under transport regulations
UN number or ID number:	Not applicable
UN proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable Marine pollutant: no
Special precautions for user	None known

Air transport
IATA/ICAO

	Not classified as a dangerous good under transport regulations
UN number or ID number	Not applicable
Proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group:	Not applicable
Environmental hazards:	Not applicable
Special precautions for user	None known

Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

15. Regulatory Information

Other regulations

16. Other Information

Vertical lines in the left hand margin indicate an amendment from the previous version.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.