Safety Data Sheet
Basoflux® RD 5119 T

1. Identification

Product identifier used on the label

Basoflux® RD 5119 T

Recommended use of the chemical and restriction on use

Recommended use*: Performance Chemicals for Oilfield Applications
Unsuitable for use: None known

* The “Recommended use” identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
BASF Mexicana S.A. de C.V.
Av. Insurgentes Sur 975
Col. CD. De Los Deportes,
C.P. 03710 Ciudad de México
MÉXICO
Global Oilfield Chemicals

Telephone: +49 621 60-0
E-mail address: RegXcellenceOilfieldChemicals@basf.com

Emergency telephone number
24 Hour Emergency Response Information
SETIQ: 1800-00-214-(Rep. Mexicana) or 55-59-15-88 (CDMX)
Telephone: +1-800-849-5204 or +1-833-229-1000

Other means of identification
Chemical family: Preparation based on: polyacrylate

2. Hazards Identification

According to Regulation NOM-018-STPS-2015

Classification of the product

Flam. Liq.	4	Flammable liquids

Carc.	2	Carcinogenicity
STOT SE	3 (Vapours may cause drowsiness and dizziness.)	Specific target organ toxicity — single exposure
Aquatic Acute	3	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic

Label elements

Pictogram:

Signal Word:
Warning

Hazard Statement:

H227	Combustible liquid.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H402	Harmful to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P201	Obtain special instructions before use.
P271	Use only outdoors or in a well-ventilated area.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273	Avoid release to the environment.
P261	Avoid breathing mist or vapour or spray.
P202	Do not handle until all safety precautions have been read and understood.

Precautionary Statements (Response):

P312	Call a POISON CENTER or physician if you feel unwell.
P308 + P313	IF exposed or concerned: Get medical attention.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P370 + P378	In case of fire: Use foam or dry powder for extinction.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents/container in accordance with local regulations.

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Labeling of special preparations (GHS):
Repeated exposure may cause skin dryness or cracking.

3. Composition / Information on Ingredients

According to Regulation NOM-018-STPS-2015

Distillates, petroleum
CAS Number: 64742-47-8
Content (W/W): >= 25.0 - < 50.0%
Synonym: No data available.

solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified
CAS Number: 64742-94-5
Content (W/W): >= 20.0 - < 25.0%
Synonym: No data available.

naphthalene
CAS Number: 91-20-3
Content (W/W): >= 0.0 - < 0.3%
Synonym: Naphthalin

4. First-Aid Measures

Description of first aid measures

General advice:
Immediately remove contaminated clothing.

If inhaled:
Keep patient calm, remove to fresh air, seek medical attention.

If on skin:
Remove contaminated clothing. Rinse skin immediately with plenty of water for 15 - 20 minutes. If irritation develops, seek medical attention.

If in eyes:
Wash affected eyes for at least 15 minutes under running water with eyelids held open.

Hold eyes open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing. Seek medical attention.

If swallowed:
Rinse mouth immediately with water. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Do not induce vomiting due to aspiration hazard. Seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11., (Further) symptoms and / or effects are not known so far

Information on: solvent naphtha
Symptoms: Overexposure may cause:, unconsciousness, vomiting, lethargy, confusion, nausea, headache, dizziness

Information on: naphthalene
Symptoms: Overexposure may cause:, perspiration, methaemoglobinaemia, loss of appetite, hemoglobinuria, hemolytic anemia, corneal injury, nausea, headache
---
Hazards: No applicable information available.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:	Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
dry powder, foam

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
harmful vapours, carbon oxides, hydrocarbons
Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

Advice for fire-fighters

Protective equipment for fire-fighting:
Wear a self-contained breathing apparatus.

Further information:
The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Can release flammable vapours. Wind direction should be noted. Avoid all sources of ignition: heat, sparks, open flame. Use antistatic tools. Use personal protective clothing. Breathing protection required.

Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For large amounts: Pump off product.
For residues: Pick up with suitable absorbent material. Dispose of absorbed material in accordance with regulations.

7. Handling and Storage

Precautions for safe handling

Ensure thorough ventilation of stores and work areas. Avoid skin contact. Avoid inhalation of the product. Wear suitable personal protective equipment.

No eating, drinking, smoking or tobacco use at the place of work. Remove contaminated clothing and protective equipment before entering eating areas. Wash hands before breaks and at end of work.

Protection against fire and explosion:
Sources of ignition should be kept well clear. Take precautionary measures against static discharges. If delivered in plastic packing, highest permissable emptying temperature is 5 Kelvin below the flash point.

Conditions for safe storage, including any incompatibilities

Segregate from foods and animal feeds. Segregate from nitrites.

Further information on storage conditions: Keep container tightly closed and in a cool place.

Storage stability:
Storage temperature: <= 50 °C
The packed product is not damaged by low temperatures or by frost.
Protect from temperatures above: 50 °C
Changes in the properties of the product may occur if substance/product is stored above indicated temperature for extended periods of time.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

naphthalene	OEL, MX:	Skin Designation ; The substance can be absorbed through the skin.
	OEL, MX:	TWA value 10 ppm ;
	OEL, MX:	STEL value 15 ppm ;
Solvent naphtha (petroleum), heavy arom.	OEL, MX:	Skin Designation ; The substance can be absorbed through the skin.
	OEL, MX:	TWA value 200 mg/m3 ;

Advice on system design:
No applicable information available.

Personal protective equipment

Respiratory protection:
Wear respiratory protection if ventilation is inadequate. Respiratory protection in case of vapour/aerosol release. Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection:
Wear impermeable chemical resistant protective gloves., fluoroelastomer (FKM) - 0.7 mm coating thickness, Suitable materials for short-term contact (recommended: At least protective index 2,

corresponding > 30 minutes of permeation time according to EN ISO 374-1), nitrile rubber (NBR) - 0.4 mm coating thickness, Supplementary note: The specifications are based on tests, literature data and information of glove manufacturers or are derived from similar substances by analogy. Due to many conditions (e.g. temperature) it must be considered, that the practical usage of a chemical-protective glove in practice may be much shorter than the permeation time determined through testing., Manufacturer's directions for use should be observed because of great diversity of types., When there is a risk of frostbite from escaping gas, use thermally insulated gloves (EN 511).

Eye protection:
Safety glasses with side-shields.

Body protection:
Body protection must be chosen based on level of activity and exposure., Protective coverall and/or impermeable apron and boots as necessary.

General safety and hygiene measures:
Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

Form:	liquid to waxy	
Odour:	mineral oil-like	
Odour threshold:	not determined	
Colour:	colourless to yellowish	
pH value:	not applicable, insoluble	
Melting point:	17 - 23 °C	
Freezing point:	No applicable information available.	
Boiling point:	> 190 °C	
Sublimation point:	No applicable information available.	
Flash point:	62.5 °C The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.	(ISO 2719)
Flammability:	Combustible liquid.	(derived from flash point)
Lower explosion limit:	For liquids not relevant for classification and labelling. The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Autoignition:	> 230 °C	(DIN 51794)
Vapour pressure:	approx. 5.96 hPa (20 °C) static approx. 17.82 hPa (50 °C) static approx. 20.98 hPa (55 °C) static	
Density:	0.89 g/cm3 (15 °C)	(ISO 2811-3)

	0.879 g/cm3 (20 °C)	(ISO 2811-3)
	0.8581 g/cm3 (50 °C)	(ISO 2811-3)
Vapour density:	> 1 (20 °C) Heavier than air.	(estimated)
Partitioning coefficient n-octanol/water (log Pow):	not applicable for mixtures	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	375 °C, > 200 J/g (DSC (DIN 51007)) self-accelerating reaction	
Viscosity, dynamic:	932 mPa.s (23 °C)	
Viscosity, kinematic:	No applicable information available.	
	approx. 1,060 mm2/s (23 °C)	(calculated (from dynamic viscosity))
Particle size:	The substance / product is marketed or used in a non solid or granular form.	
Solubility in water:	dispersible when hot	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	soluble solvent(s): aromatic hydrocarbons,	
Molar mass:	No applicable information available.	
Evaporation rate:	not determined	

10. Stability and Reactivity

Reactivity
No applicable information available.
No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:
No corrosive effect on metal.

Oxidizing properties:
not fire-propagating

Chemical stability
The product is stable if stored and handled as prescribed/indicated.

Peroxides: 0 %
The product does not contain peroxides.

Possibility of hazardous reactions
No hazardous reactions when stored and handled according to instructions.
The product is chemically stable.

Conditions to avoid
Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

Incompatible materials
strong acids, strong bases, strong oxidizing agents

Hazardous decomposition products

Decomposition products:
Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:
375 °C, 2.5 K/min (DSC (DIN 51007))
self-accelerating reaction

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Oral
Type of value: ATE
Value: > 5,000 mg/kg

Information on: solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified
Type of value: LD50
Species: rat
Value: 6,318 mg/kg (OECD Guideline 401)

Information on: Distillates, petroleum
Type of value: LD50
Species: rat
Value: > 5,000 mg/kg (OECD Guideline 420)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Inhalation
No applicable information available.

Information on: solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified
Type of value: LC50
Species: rat
Value: > 4.688 mg/l (OECD Guideline 403)

Information on: Distillates, petroleum
Type of value: LC50
Species: rat
Value: > 5.28 mg/l (OECD Guideline 403)
Exposure time: 4 h
The vapour was tested.
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Dermal
No applicable information available.

Information on: solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified
Type of value: LD50
Species: rabbit
Value: > 2,000 mg/kg (OECD Guideline 402)

Information on: Distillates, petroleum
Type of value: LD50
Species: rabbit
Value: > 2,000 mg/kg (OECD Guideline 402)
The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Assessment other acute effects
Assessment of STOT single:
Possible narcotic effects (drowsiness or dizziness).

Irritation / corrosion
Assessment of irritating effects: May cause slight irritation to the skin. May cause slight irritation to the eyes. May cause slight irritation to the respiratory tract.

Sensitization
Assessment of sensitization: Based on available data, the classification criteria are not met.

Information on: solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified
Assessment of sensitization:
No sensitizing effect.

Information on: Distillates, petroleum
Assessment of sensitization:
Skin sensitizing effects were not observed in animal studies. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aspiration Hazard
No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity
Assessment of repeated dose toxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Genetic toxicity
Assessment of mutagenicity: Based on the ingredients, there is no suspicion of a mutagenic effect.

Information on: solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified
Assessment of mutagenicity: Based on available data, the classification criteria are not met.

Information on: Distillates, petroleum

Assessment of mutagenicity: The substance was not mutagenic in bacteria. The substance was not genotoxic in mammalian cell culture. The substance was not mutagenic in mammalian cell culture. The substance was not genotoxic in a test with mammals. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Carcinogenicity
Assessment of carcinogenicity: Contains a compound classified as IARC Group 2B (possibly carcinogenic to humans).

Information on: naphthalene
Assessment of carcinogenicity: In long-term studies in rats and mice in which the substance was given by inhalation, a carcinogenic effect was observed. EU-classification The substance was classified as a group 3 carcinogen by the German MAK-Commission (substances for which a suspicion of a carcinogenic potential exists). IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).
IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).

Reproductive toxicity
Assessment of reproduction toxicity: Based on the ingredients, there is no suspicion of a toxic effect on reproduction.

Information on: solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified
Assessment of reproduction toxicity: Based on available data, the classification criteria are not met.

Information on: Distillates, petroleum
Assessment of reproduction toxicity: No reproductive toxic effects reported. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Teratogenicity
Assessment of teratogenicity: Based on the ingredients, there is no suspicion of a teratogenic effect.

Information on: solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified
Assessment of teratogenicity: Based on available data, the classification criteria are not met.

Information on: Distillates, petroleum
Assessment of teratogenicity: No indications of a developmental toxic / teratogenic effect were seen in animal studies. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Other Information
The product has not been tested. The statements on toxicology have been derived from the properties of the individual components. Has a degreasing effect on skin.

12. Ecological Information

Toxicity

Aquatic toxicity
Assessment of aquatic toxicity:
Acutely harmful for aquatic organisms. Harmful to aquatic life with long lasting effects.

Toxicity to fish

Information on: solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified
LL50 (96 h) 2 mg/l, Oncorhynchus mykiss
LL50 (96 h) < 5 mg/l, Oncorhynchus mykiss

Aquatic invertebrates

Information on: solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified
EL50 (48 h) 3 mg/l, Daphnia magna
EL50 (48 h) < 10 mg/l, Daphnia magna

Chronic toxicity to fish

Information on: solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified
NOEL (28 d) 0.441 mg/l, Oncorhynchus mykiss

Chronic toxicity to aquatic invertebrates

Information on: solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified
NOEL (21 d) 0.771 mg/l, Daphnia magna

Bioaccumulative potential

Assessment bioaccumulation potential
Accumulation in organisms is expected.

Assessment bioaccumulation potential

Information on: Distillates, petroleum

Because of the n-octanol/water distribution coefficient (log Pow) accumulation in organisms is possible.

Accumulation in organisms is expected.

Mobility in soil

Assessment transport between environmental compartments
No data available.

Additional information

Other ecotoxicological advice:

The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components. Do not discharge product into the environment without control.

13. Disposal considerations

Waste disposal of substance:
Dispose of in accordance with national, state and local regulations.

Container disposal:
WARNING: Empty containers may still contain hazardous residue.

14. Transport Information

Land transport
TDG

Not classified as a dangerous good under transport regulations

Sea transport
IMDG

Not classified as a dangerous good under transport regulations

Air transport
IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Not applicable

NFPA Hazard codes:
Health: 2 Fire: 2 Reactivity: 0 Special:

HMIS III rating
Health: 2¤ Flammability: 2 Physical hazard: 0

16. Other Information

SDS Prepared by:
BASF NA Product Regulations
SDS Prepared on: 2023/07/18

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring

the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Basoflux® RD 5119 T is a registered trademark of BASF Mexicana or BASF SE

This information is considered accurate but is not exhaustive and shall only be used as a guideline based on current knowledge of the chemical substance or mixture. Safety precautions suitable for the product must be applied.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET