## 1. Identification

### Product identifier used on the label

## Styropor® P 426 C BMB

### Recommended use of the chemical and restriction on use

Recommended use*: industrial chemicals
Recommended use*: for industrial processing only; Expanding-agent containing plastic for the production of foam plastics
Unsuitable for use: Not intended for sale to or use by the general public.

* The “Recommended use” identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

### Details of the supplier of the safety data sheet

Company:
BASF Mexicana S.A. de C.V.
Av. Insurgentes Sur 975
Col. CD. De Los Deportes,
C.P. 03710 Ciudad de México
MÉXICO

Telephone: +52 55 5325 2600

### Emergency telephone number
24 Hour Emergency Response Information
SETIQ: 1800-00-214-(Rep. Mexicana) or 55-59-15-88 (CDMX)
Telephone: +1-800-849-5204 or +1-833-229-1000

### Other means of identification
Synonyms: expandable polystyrene

## 2. Hazards Identification

**According to Regulation NOM-018-STPS-2015**

### Classification of the product

No need for classification according to GHS criteria for this product.

### Label elements

The product does not require a hazard warning label in accordance with GHS criteria.

### Hazards not otherwise classified

May cause some eye irritation which should cease after removal of the product. In use may form flammable/explosive vapour-air mixture.

## 3. Composition / Information on Ingredients

**According to Regulation NOM-018-STPS-2015**

Pentane
CAS Number: 109-66-0
Content (W/W): < 5.3%
Synonym: n-Pentan

isopentane
CAS Number: 78-78-4
Content (W/W): < 1.4%
Synonym: 2-Methylbutane

## 4. First-Aid Measures

### Description of first aid measures

**General advice:**
No special precautions necessary.

**If inhaled:**
Keep patient calm, remove to fresh air. If difficulties occur: Seek medical attention.

**If on skin:**
Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

**If in eyes:**
In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

**If swallowed:**
No hazards anticipated. Rinse mouth and then drink 200-300 ml of water. If difficulties occur: Seek medical attention.

### Most important symptoms and effects, both acute and delayed

Symptoms: headache, dizziness, coordination disorder, dazed state, Eye irritation, skin irritation
Hazards: No hazards anticipated.

### Indication of any immediate medical attention and special treatment needed

Note to physician
Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

## 5. Fire-Fighting Measures

### Extinguishing media

Suitable extinguishing media:
water spray, foam, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:
water jet

Additional information:
Use extinguishing measures to suit surroundings.

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:
carbon monoxide, carbon dioxide, Styrene, aliphatic hydrocarbons
The substances/groups of substances mentioned can be released in case of fire.

### Advice for fire-fighters

Protective equipment for fire-fighting:
Wear self-contained breathing apparatus and chemical-protective clothing.

**Further information:**
Product will burn on contact with flame or exposure to high temperature. Burns with dense emission of soot. Containers/tanks should be cooled with water spray. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Flammable concentrations of propellant may accumulate on storage in closed containers.

## 6. Accidental release measures

Further accidental release measures:
High risk of slipping due to leakage/spillage of product. Shut off or stop source of leak. Substance/product can form explosive mixture with air.

### Personal precautions, protective equipment and emergency procedures

Sources of ignition should be kept well clear. Ensure adequate ventilation. Note that this gas is heavier than air and can spread along the ground in the direction of the wind. Beware of pits and confined spaces. Use antistatic tools. Vapours are heavy and collect in low areas. Avoid all sources of ignition: heat, sparks, open flame.

### Environmental precautions

Do not allow to enter drains or waterways. Discharge into the environment must be avoided.

### Methods and material for containment and cleaning up

For small amounts: Sweep/shovel up. Pack in tightly closed containers for disposal.

For large amounts: Pick up with vacuum equipment approved for use in hazardous locations. Pack in tightly closed containers for disposal.
Ensure adequate ventilation. Dispose of absorbed material in accordance with regulations. Avoid raising dust.

## 7. Handling and Storage

### Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. Upon delivery, trailer and/or container should be opened and allowed to vent for a minimum of one (1) hour before unloading. The substance/product in bead or expanded form generates static charges during handling which are difficult to dissipate due to the insulating properties. Take precautionary measures against static discharges. Use antistatic tools. Provide good room ventilation even at ground level (vapours are heavier than air). Containers should be opened carefully in well-ventilated areas to avoid static discharge. Maintain air circulation and ventilation at a minimum rate of six air changes per hour to prevent the formation of flammable concentrations. Ensure adequate ventilation. The substance/ product may be handled only by appropriately trained personnel.

Protection against fire and explosion:
The product is combustible. Vapours may form ignitable mixture with air. Keep away from heat. Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy. Avoid all sources of ignition: heat, sparks, open flame. Containers should be earthed during decanting operations. It is recommended that all conductive parts of the machinery are grounded. All parts of the plant and equipment should be electrically bonded together and grounded. Electrical continuity should be checked at regular intervals. Higher line velocity can increase the build-up of static electric charge. Avoid flammable gas mixtures. Ensure an efficient ventilation (at least one air change per hour). Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition. Because of danger of explosion, avoid vapours reaching the cellar, sewage water and pits. Empty containers may contain flammable residue.

### Conditions for safe storage, including any incompatibilities

Segregate from strong oxidizing agents.

Suitable materials for containers: High density polyethylene (HDPE), Low density polyethylene (LDPE), Paper/Fibreboard, Stove-lacquer RDL 50, Stove-lacquer R 78433, Carbon steel (Iron), Stainless steel 1.4301 (V2), Stainless steel 1.4361, Stainless steel 1.4401, Stainless steel 1.4439, Stainless steel 1.4539, Stainless steel 1.4541, Stainless steel 1.4571, Stainless steel 1.4306 (V2A), Stainless steel 1.4307, Stainless steel 1.4311, Stainless steel 1.4404, Polyamide (PA)

Further information on storage conditions: Protect against heat. Keep away from sources of ignition - No smoking. Keep only in the original container. Keep container tightly sealed. Protect against moisture. Avoid direct sunlight. Protect containers from physical damage. The authority permits and storage regulations must be observed. Store protected against freezing. Keep tanks under inert gas. Air monitoring should be used to alert any build up of explosive mixtures. Equipment to be installed in an environment with potentially explosive atmospheres should conform to the requirements of ATEX Directive 94/9/EC. Ventilate freight container with open door for 30 minutes before unloading.

Storage stability:
Keep container tightly closed and dry.
Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.

## 8. Exposure Controls/Personal Protection

**Components with occupational exposure limits**

| | | |
|---|---|---|
| isopentane | OEL, MX: | TWA value 600 ppm ; |
| Pentane | OEL, MX: | TWA value 600 ppm ; |

**Advice on system design:**
Provide local exhaust ventilation to control vapours/mists.

**Personal protective equipment**

**Respiratory protection:**
Respiratory protection may not be required under normal operating conditions if adequate ventilation is provided. Wear respiratory protection if ventilation is inadequate. Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

**Hand protection:**
Chemical resistant protective gloves, non-static gloves (e.g. of leather)

**Eye protection:**
Safety glasses with side-shields. Tightly fitting safety goggles (chemical goggles).

**Body protection:**
Anti-static protective clothing, Antistatic safety shoes

**General safety and hygiene measures:**
Avoid inhalation of dusts/mists/vapours. When using do not eat or drink. When using do not smoke.

## 9. Physical and Chemical Properties

| | | |
|---|---|---|
| Form: | beads | |
| Odour: | almost odourless | |
| Odour threshold: | not determined | |
| Colour: | white | |
| pH value: | not soluble | |
| softening temperature: | approx. 70 °C | |
| Melting point: | No data available. | |
| Freezing point: | No data available. | |
| onset of boiling: | The substance / product decomposes therefore not determined. | |
| Sublimation point: | not applicable | |
| Flash point: | Vapours are flammable. | |
| Flammability: | not highly flammable | (UN Test N.1 (ready combustible solids)) |
| Flammability of Aerosol Products: | not applicable, the product does not form flammable aerosoles | |
| Lower explosion limit: | Product not examined: Value is calculated from the data of the components. | |

| | | |
|---|---|---|
| Upper explosion limit: | Product not examined: Value is calculated from the data of the components. | |
| Autoignition: | 285 °C | (DIN 51794) |
| Vapour pressure: | not applicable | |
| Density: | approx. 1.02 - 1.05 g/cm3<br>( 20 °C) | |
| Relative density: | 1.02 - 1.05<br>( 20 °C) | |
| Bulk density: | approx. 600 kg/m3<br>( 20 °C) | |
| Vapour density: | 2.5<br>Heavier than air. | |
| Partitioning coefficient n-octanol/water (log Pow): | not applicable | |
| Self-ignition temperature: | not self-igniting | |
| Thermal decomposition: | approx. 220 °C<br>No decomposition if used as directed. | |
| Viscosity, dynamic: | not applicable, the product is a solid | |
| Viscosity, kinematic: | not applicable, the product is a solid | |
| Particle size: | No data available. | |
| Solubility in water: | not soluble<br>not soluble | |
| Miscibility with water: | immiscible | |
| Solubility (quantitative): | No applicable information available. | |
| Solubility (qualitative): | soluble<br>solvent(s): aromatic hydrocarbons, ketones, organic solvents, | |
| Evaporation rate: | The product is a non-volatile solid. | |

## 10. Stability and Reactivity

### Reactivity
No hazardous reactions if stored and handled as prescribed/indicated., Vapours may form explosive mixture with air.

Corrosion to metals:
No corrosive effect on metal.

Oxidizing properties:
not fire-propagating

### Chemical stability
The product is stable if stored and handled as prescribed/indicated.

### Possibility of hazardous reactions
Formation of explosive gas/air mixtures.

### Conditions to avoid
> 70 degrees Celsius
Avoid all sources of ignition: heat, sparks, open flame. Avoid direct sunlight. Avoid electro-static discharge.

### Incompatible materials

explosive substances according UN transport regulations class 1, Propellant release will be boosted with increasing temperature.

### Hazardous decomposition products

Decomposition products:
Possible thermal decomposition products: Pentane, styrene monomers, Heated product evolves combustible vapours.

Thermal decomposition:
approx. 220 °C
No decomposition if used as directed.

## 11. Toxicological information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

### Acute Toxicity/Effects

Acute toxicity
Assessment of acute toxicity: Contact with heated product can cause thermal burns.

*Information on: isopentane*
*Assessment of acute toxicity:Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.*
---

Oral
Type of value: LD50
Value: > 2,000 mg/kg

Inhalation
Type of value: LC50
Value: > 5 mg/l

Dermal
Type of value: LD50
Value: > 2,000 mg/kg

Assessment other acute effects
No applicable information available.

Irritation / corrosion
Assessment of irritating effects: Frequent and prolonged contact can lead to skin irritation.
Irritation is possible when the product comes in contact with the skin, respiratory tract or the eyes.

Skin
Prolonged contact with the product can result in skin irritation.

Eye

Similar findings as for skin apply to eyes.

Sensitization
Assessment of sensitization: There is no evidence of a skin-sensitizing potential.

### Chronic Toxicity/Effects

Repeated dose toxicity
Assessment of repeated dose toxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

*Information on: isopentane*
*Assessment of repeated dose toxicity: Chronic overexposure has been shown to cause adverse kidney effects in experimental animals.*
---

Genetic toxicity
Assessment of mutagenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Carcinogenicity
Assessment of carcinogenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Reproductive toxicity
Assessment of reproduction toxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Other Information
No reports of ill effects provided product was correctly handled and processed.

*Information on: Pentane*
*Has a degreasing effect on skin.*
---

## 12. Ecological Information

### Toxicity

Aquatic toxicity
Assessment of aquatic toxicity:
There is a high probability that the product is not acutely harmful to aquatic organisms. No toxic effects occur within the range of solubility.

Aquatic invertebrates
EC50 (48 h) > 100 mg/l, Daphnia magna (OECD Guideline 202, part 1, static)
Nominal concentration. The product has low solubility in the test medium. An eluate has been tested. No toxic effects occur within the range of solubility. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aquatic plants
EC50 (72 h) > 100 mg/l (growth rate), Desmodesmus subspicatus (OECD Guideline 201, static) Nominal concentration. The product has low solubility in the test medium. An eluate has been tested. No toxic effects occur within the range of solubility. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Aquatic toxicity

*Information on: Pentane*
*Assessment of aquatic toxicity:*
*Acutely toxic for aquatic organisms. Toxic to aquatic life with long lasting effects.*
*EU-classification*
---

### Persistence and degradability

Assessment biodegradation and elimination (H2O)
In accordance with the required stability the product is not readily biodegradable. The product has not been tested. The statement has been derived from the structure of the product. The product is virtually insoluble in water and can thus be separated from water mechanically in suitable effluent treatment plants.

On the basis of the data available concerning eliminability/degradation and bioaccumulation potential, longer-term harm to the environment is improbable. No data available concerning biodegradation and elimination.

### Bioaccumulative potential

Bioaccumulation potential
The product will not be readily bioavailable due to its consistency and insolubility in water.

### Mobility in soil

Assessment transport between environmental compartments
Study scientifically not justified.

### Additional information

Add. remarks environm. fate & pathway:
Because of the product's consistency and low water solubility, bioavailability is improbable.

Other ecotoxicological advice:
At the present state of knowledge, no negative ecological effects are expected. No toxic effects occur within the range of solubility.

*Information on: Pentane*
*Other ecotoxicological advice:*
*The substance has a very low Global Warming Potential and no Ozone Depleting Potential.*
---

## 13. Disposal considerations

**Waste disposal of substance:**
Dispose of in a licensed facility. Observe all local regulations.

**Container disposal:**
Remove all packaging for recovery or disposal

## 14. Transport Information

**Land transport**
TDG

| | |
|---|---|
| Hazard class: | 9 |
| Packing group: | III |
| ID number: | UN 2211 |
| Hazard label: | 9 |
| Proper shipping name: | POLYMERIC BEADS, EXPANDABLE |

**Sea transport**
IMDG

| | |
|---|---|
| Hazard class: | 9 |
| Packing group: | III |
| ID number: | UN 2211 |
| Hazard label: | 9 |
| Marine pollutant: | NO |
| Proper shipping name: | POLYMERIC BEADS, EXPANDABLE |

**Air transport**
IATA/ICAO

| | |
|---|---|
| Hazard class: | 9 |
| Packing group: | III |
| ID number: | UN 2211 |
| Hazard label: | 9 |
| Proper shipping name: | POLYMERIC BEADS, EXPANDABLE |

## 15. Regulatory Information

**Federal Regulations**

Not applicable

**NFPA Hazard codes:**
Health: 1 Fire: 2 Reactivity: 0 Special:

**HMIS III rating**
Health: 1 Flammability: 2 Physical hazard: 0

**Assessment of the hazard classes according to UN GHS criteria (most recent version):**

## 16. Other Information

**SDS Prepared by:**
BASF NA Product Regulations
SDS Prepared on: 2024/06/26

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---


Styropor® P 426 C BMB is a registered trademark of BASF Mexicana or BASF SE


This information is considered accurate but is not exhaustive and shall only be used as a guideline based on current knowledge of the chemical substance or mixture. Safety precautions suitable for the product must be applied.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET