We create chemistry

Safety data sheet

BASF Safety data sheet according to UN GHS 4th rev.
Date / Revised: 16.09.2019 Version: 1.0
Product: **2EH Lights PA**
(ID no. 30675398/SDS_GEN_00/EN)
Date of print 04.07.2025

1. Identification

Product identifier

2EH Lights PA

Chemical name: 2EH Lights PA

Details of the supplier of the safety data sheet

Company:
BASF SE
67056 Ludwigshafen
GERMANY
Operating Division Petrochemicals

Telephone: +49 621 60-42151
E-mail address: sds-petrochemicals@basf.com

Emergency telephone number

International emergency number:
Telephone: +49 180 2273-112

2. Hazards Identification

Classification of the substance or mixture

According to UN GHS criteria

Flam. Liq. 3
Acute Tox. 5 (oral)
Acute Tox. 4 (Inhalation - mist)
Acute Tox. 5 (dermal)
Skin Corr./Irrit. 2
Eye Dam./Irrit. 1

Skin Sens. 1B
STOT SE 3 (Vapours may cause drowsiness and dizziness.)
STOT SE 3 (irritating to respiratory system)
Aquatic Acute 3

For the classifications not written out in full in this section the full text can be found in section 16.

Label elements

Globally Harmonized System (GHS)

Pictogram:

Signal Word:
Danger

Hazard Statement:

H318	Causes serious eye damage.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H335	May cause respiratory irritation.
H303 + H313	May be harmful if swallowed or in contact with skin

Precautionary Statements (Prevention):

P280	Wear protective gloves and eye/face protection.
P271	Use only outdoors or in a well-ventilated area.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P310	Immediately call a POISON CENTER or doctor/physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P352	IF ON SKIN (or hair): Wash with plenty of soap and water.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.

Labeling of special preparations (GHS):
The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 0 - 1 %, dermal
The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 0 - 1 %, oral
The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 0 - 1 %, Inhalation - vapour
The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 0 - 1 %, Inhalation - mist

3. Composition/Information on Ingredients

Substances

Chemical nature

Hazardous ingredients (GHS)
According to UN GHS criteria

Butan-1-ol

Content (W/W): >= 25 % - <= 100 %	Flam. Liq. 3
CAS Number: 71-36-3	Acute Tox. 5 (oral)
EC-Number: 200-751-6	Acute Tox. 5 (dermal)
	Skin Corr./Irrit. 2
	Eye Dam./Irrit. 1
	STOT SE 3 (drowsiness and dizziness)
	STOT SE 3 (irr. to respiratory syst.)
	H226, H318, H315, H336, H335, H303 + H313

2-Methylpropan-1-ol

Content (W/W): >= 3 % - < 10 %	Asp. Tox. 2
CAS Number: 78-83-1	Flam. Liq. 3
EC-Number: 201-148-0	Acute Tox. 5 (oral)
	Acute Tox. 5 (dermal)
	Skin Corr./Irrit. 2
	Eye Dam./Irrit. 1
	STOT SE 3 (drowsiness and dizziness)
	STOT SE 3 (irr. to respiratory syst.)
	H226, H318, H315, H305, H336, H335, H303 + H313

2-Ethylhexan-1-ol

Content (W/W): >= 0,1 % - < 50 %	Flam. Liq. 4
CAS Number: 104-76-7	Acute Tox. 5 (oral)
EC-Number: 203-234-3	Acute Tox. 4 (Inhalation - mist)
	Skin Corr./Irrit. 2
	Eye Dam./Irrit. 2A
	STOT SE 3 (irr. to respiratory syst.)
	Aquatic Acute 3
	H227, H319, H315, H332, H303, H335, H402

2-Ethylhexanal

Content (W/W): >= 0 % - < 3 %	Flam. Liq. 3
CAS Number: 123-05-7	Acute Tox. 5 (oral)
EC-Number: 204-596-5	Skin Sens. 1B
	Repr. 2 (unborn child)
	Aquatic Acute 2
	H226, H303, H317, H361, H401

Heptan-4-one

Content (W/W): >= 0 % - < 3 %	Flam. Liq. 3
CAS Number: 123-19-3	Acute Tox. 4 (Inhalation - vapour)
EC-Number: 204-608-9	Acute Tox. 5 (oral)
INDEX-Number: 606-027-00-X	Skin Corr./Irrit. 2
	Eye Dam./Irrit. 2A
	H226, H319, H315, H332, H303

2-Ethylhex-2-enal

Content (W/W): >= 0 % - < 1 %	Flam. Liq. 4
CAS Number: 645-62-5	Acute Tox. 5 (oral)
EC-Number: 211-448-3	Skin Corr./Irrit. 2
	Skin Sens. 1B
	Aquatic Acute 3
	Aquatic Chronic 3
	H227, H315, H303, H317, H402, H412

For the classifications not written out in full in this section the full text can be found in section 16.

Mixtures

Not applicable

4. First-Aid Measures

Description of first aid measures

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

On skin contact:
Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

On contact with eyes:
Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

On ingestion:
Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
water spray, dry powder, alcohol-resistant foam, carbon dioxide

Special hazards arising from the substance or mixture

Vapours may form explosive mixture with air.

Advice for fire-fighters

Special protective equipment:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:
Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Keep containers cool by spraying with water if exposed to fire. Foam should be applied in large quantities as it is broken down to some extent by the product.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Avoid inhalation. Avoid contact with the skin, eyes and clothing.

Environmental precautions

Discharge into the environment must be avoided.

Methods and material for containment and cleaning up

Spills should be contained, solidified, and placed in suitable containers for disposal.

7. Handling and Storage

Precautions for safe handling

Ensure thorough ventilation of stores and work areas.

Protection against fire and explosion:
Containers should be grounded against electrostatic charge. Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy.

Conditions for safe storage, including any incompatibilities

Suitable materials for containers: Stove-lacquer KNS L-5X, Stove-lacquer Valspar HXR008F red, Carbon steel (Iron), tinned carbon steel (Tinplate), glass
Further information on storage conditions: Keep away from sources of ignition - No smoking. Keep container tightly closed in a cool, well-ventilated place. Storage containers should be grounded.

8. Exposure Controls/Personal Protection

Control parameters

Components with occupational exposure limits

71-36-3: Butan-1-ol
78-83-1: 2-Methylpropan-1-ol
104-76-7: 2-Ethylhexan-1-ol
123-05-7: 2-Ethylhexanal
123-19-3: Heptan-4-one

Exposure controls

Personal protective equipment

Respiratory protection:
Wear respiratory protection if ventilation is inadequate.

Hand protection:
Chemical resistant protective gloves
Suitable materials
chloroprene rubber (Neoprene)

Eye protection:
Tightly fitting safety goggles (chemical goggles)., Wear face shield if splashing hazard exists.

Body protection:
Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

General safety and hygiene measures

Work place should be equipped with a shower and an eye wash. Avoid inhalation of vapours/mists. Wear protective clothing as necessary to prevent contact.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Form:	liquid	
Colour:	almost colourless	
Odour:	alcohol-like	
pH value:	7	
Flash point:	31 - 35 °C	
Vapour pressure:	7,33 hPa	
Density:	0,8278 g/cm3	
Solubility in water:	partly soluble (25 °C)	
Explosion hazard:	not explosive	(other)
Fire promoting properties:	not fire-propagating	(other)

10. Stability and Reactivity

Reactivity
No applicable information available.

Chemical stability
No applicable information available.

Possibility of hazardous reactions
Reacts with strong oxidizing agents. Reacts with reducing agents. Reacts with sulfuric acid. Reacts with nitrites.

Conditions to avoid
Avoid all sources of ignition: heat, sparks, open flame.

Incompatible materials

Substances to avoid:
No applicable information available.

Hazardous decomposition products

:
No applicable information available.

11. Toxicological Information

Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:
Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact. Virtually nontoxic after a single ingestion.

The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 0 - 1 %

The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 0 - 1 %

The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 0 - 1 %

The following percentage of the mixture consists of components(s) with unknown hazards regarding the acute toxicity: 0 - 1 %

Irritation

Assessment of irritating effects:
Causes serious eye damage. Causes skin irritation.

Information on: Butan-1-ol
Assessment of irritating effects:
Skin contact causes irritation. Risk of serious damage to eyes.

Information on: 2-Methylpropan-1-ol
Assessment of irritating effects:
May cause severe damage to the eyes. Skin contact causes irritation.

Information on: 2-Ethylhexan-1-ol
Assessment of irritating effects:
Eye contact causes irritation. Skin contact causes irritation.

Information on: Heptan-4-one
Assessment of irritating effects:
Eye contact causes irritation. Skin contact causes irritation.

Respiratory/Skin sensitization

Assessment of sensitization:
May cause allergic skin reaction.

Information on: 2-Ethylhexanal

Assessment of sensitization:
sensitizing effect in animal tests

Germ cell mutagenicity

Assessment of mutagenicity:
Based on available Data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:
Based on available Data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity:
Based on available Data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Assessment of STOT single:
Possible narcotic effects (drowsiness or dizziness). Causes temporary irritation of the respiratory tract.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:
Based on available Data, the classification criteria are not met.

Other relevant toxicity information

The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

12. Ecological Information

Toxicity

Assessment of aquatic toxicity:
Harmful to aquatic life.

Information on: 2-Ethylhexan-1-ol
Assessment of aquatic toxicity:
Acutely harmful for aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Additional information

Other ecotoxicological advice:
Acutely toxic for aquatic organisms. Do not discharge substance/product into sewer system. The product has not been tested. The statement has been derived from the properties of the individual components.

13. Disposal Considerations

Waste treatment methods

Dispose of in a RCRA-licensed facility.

Contaminated packaging:
Empty containers with less than 1 inch of residue may be landfilled at a licensed facility.
Recommend crushing, puncturing or other means to prevent unauthorized use of used containers.

14. Transport Information

Land transport

ADR

UN number	UN1993
UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (contains N-BUTANOL, 2-METHYLPROPAN-1-OL)
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	no
Special precautions for user:	Tunnel code: D/E

RID

UN number	UN1993
UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (contains N-BUTANOL, 2-METHYLPROPAN-1-OL)
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	no
Special precautions for user:	None known

Inland waterway transport
ADN

UN number	UN1993

UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (contains N-BUTANOL, 2-METHYLPROPAN-1-OL)
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	no
Special precautions for user:	None known

Transport in inland waterway vessel
Not evaluated

Sea transport

IMDG

UN number:	UN 1993
UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (contains N-BUTANOL, 2-METHYLPROPAN-1-OL)
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	no Marine pollutant: NO
Special precautions for user:	None known

Air transport

IATA/ICAO

UN number:	UN 1993
UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (contains N-BUTANOL, 2-METHYLPROPAN-1-OL)
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	No Mark as dangerous for the environment is needed
Special precautions for user:	None known

Transport in bulk according to Annex II of MARPOL and the IBC Code

Regulation:	Not evaluated
Shipment approved:	Not evaluated
Pollution name:	Not evaluated
Pollution category:	Not evaluated
Ship Type:	Not evaluated

15. Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Not applicable

16. Other Information

Full text of classifications, hazard symbols and hazard statements, if mentioned in section 2 or 3:

Flam. Liq.	Flammable liquids
Acute Tox.	Acute toxicity
Skin Corr./Irrit.	Skin corrosion/irritation
Eye Dam./Irrit.	Serious eye damage/eye irritation
Skin Sens.	Skin sensitization
STOT SE	Specific target organ toxicity — single exposure
Aquatic Acute	Hazardous to the aquatic environment - acute
Asp. Tox.	Aspiration hazard
Repr.	Reproductive toxicity
Aquatic Chronic	Hazardous to the aquatic environment - chronic
H226	Flammable liquid and vapour.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H335	May cause respiratory irritation.
H303 + H313	May be harmful if swallowed or in contact with skin
H305	May be harmful if swallowed and enters airways.
H227	Combustible liquid.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H303	May be harmful if swallowed.
H402	Harmful to aquatic life.
H317	May cause an allergic skin reaction.
H361	Suspected of damaging the unborn child.
H401	Toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.