Safety Data Sheet
Dihydrodicyclopentadienyl Acrylate (DCPA)

1. Identification

Product identifier used on the label

Dihydrodicyclopentadienyl Acrylate (DCPA)

Recommended use of the chemical and restriction on use

Recommended use*: Monomer.
Recommended use*: Monomer.
Unsuitable for use: Not intended for sale to or use by the general public.

* The “Recommended use” identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

24 Hour Emergency Response Information
CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: acrylates

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Skin Corr./Irrit.	2	Skin corrosion/irritation
Skin Sens.	1	Skin sensitization
STOT SE	3 (irritating to respiratory system)	Specific target organ toxicity — single exposure

Aquatic Acute	2	Hazardous to the aquatic environment - acute
Aquatic Chronic	2	Hazardous to the aquatic environment - chronic

Label elements

Pictogram:

Signal Word:
Warning

Hazard Statement:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves.
P261	Avoid breathing mist or vapour or spray.
P273	Avoid release to the environment.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P264	Wash contaminated body parts thoroughly after handling.

Precautionary Statements (Response):

P312	Call a POISON CENTER or physician if you feel unwell.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P333 + P313	If skin irritation or rash occurs: Get medical attention.
P332 + P313	If skin irritation occurs: Get medical attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P391	Collect spillage.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents/container in accordance with local regulations.

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.
See section 12 - Results of PBT and vPvB assessment.

Labeling of special preparations (GHS):
Risk of hazardous polymerization under certain conditions (e.g. elevated temperatures, low inhibitor and oxygen concentration). Do not blanket with nitrogen.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

hexahydro-4,7-methano-1H-indenyl acrylate
CAS Number: 12542-30-2
Content (W/W): >= 95.0 - <= 100.0%
Synonym: 2-Propenoic acid, hexahydro-4,7-methano-1H-indenyl ester

acrylic acid
CAS Number: 79-10-7
Content (W/W): < 1.0%
Synonym: 2-Propenoic acid; Acrylic acid

dicyclopentadiene
CAS Number: 77-73-6
Content (W/W): >= 0.01 - <= 0.5%
Synonym: Dicyclopentadien

4. First-Aid Measures

Description of first aid measures

General advice:
First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:
Keep patient calm, remove to fresh air, seek medical attention.

If on skin:
Wash thoroughly with soap and water

If in eyes:
Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:
Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: Overexposure may cause:, Eye irritation, skin irritation, erythema, allergic contact dermatitis, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps, Inhalation may provoke the following symptoms:, irritation of respiratory tract, coughing
Hazards: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11. (Further) symptoms and / or effects are not known so far

Indication of any immediate medical attention and special treatment needed

Note to physician
Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
dry powder, water spray, carbon dioxide, foam

Unsuitable extinguishing media for safety reasons:
water jet

Additional information:
Use extinguishing measures to suit surroundings.

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
Risk of violent self-polymerization if overheated in a container. Cool endangered containers with water-spray.

The product is combustible. See SDS section 7 - Handling and storage.

Advice for fire-fighters

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear. Special protective equipment for firefighters

Further information:
Extend fire extinguishing measures to the surroundings. Fight fire from maximum distance. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

In case of a fire in the vicinity a restabilization system should be used if the temperature in the bulk storage-tank reaches 45°C. Evacuate area of all unnecessary personnel. In case of a fire in the vicinity evacuate all personnel in a greater area if the temperature in the bulk storage-tank reaches 60°C.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Further accidental release measures:
High risk of slipping due to leakage/spillage of product.

Release of substance/product can cause fire or explosion. Shut off or stop source of leak. Shut off or stop released substance/product under safe conditions.

Pack in tightly closed containers for disposal.

Personal precautions, protective equipment and emergency procedures

Handle in accordance with good industrial hygiene and safety practice.

Avoid all sources of ignition: heat, sparks, open flame. Use antistatic tools.

Environmental precautions
Discharge into the environment must be avoided.

Methods and material for containment and cleaning up
For large amounts: Pump off product.
Spills should be contained, solidified, and placed in suitable containers for disposal. Dispose of absorbed material in accordance with regulations. Ensure adequate ventilation. Suppress gases/vapours/mists with water spray jet. Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Cleaning operations should be carried out only while wearing breathing apparatus. Pick up with suitable appliance and dispose of.

7. Handling and Storage

Precautions for safe handling
The substance/ product may be handled only by appropriately trained personnel. Facility parts must be checked for polymer residues and cleaned on regular basis in order to avoid hazardous reactions.

Ensure thorough ventilation of stores and work areas. Encapsulation or exhaust ventilation required. When filling, transferring, or emptying of containers, adequate local exhaust ventilation is necessary. Vent waste air to atmosphere only through suitable separators. Check the condition of seals and connector screw threads.

The temperatures which must be avoided are to be considered. Protect against heat. Protect from direct sunlight. Protect contents from the effects of light. Do not open warm or swollen product containers. Remove persons to safety and alert fire brigade.

Ensure adequate inhibitor and dissolved oxygen level.

Avoid inhalation of dusts/mists/vapours. Avoid aerosol formation. Avoid all direct contact with the substance/product.

Protection against fire and explosion:
Avoid all sources of ignition: heat, sparks, open flame. Substance/product can form explosive mixture with air. Ground all transfer equipment properly to prevent electrostatic discharge. It is recommended that all conductive parts of the machinery are grounded. Explosion-proof equipment is not necessary when loading and processing of the product takes place at a minimum of 5 °C below the flash point.

Heated containers should be cooled to prevent polymerization. If exposed to fire, keep containers cool by spraying with water. Emergency cooling must be provided for the eventuality of a fire in the vicinity.

Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

Conditions for safe storage, including any incompatibilities
No applicable information available.

Further information on storage conditions: Prior to storage ensure that the transfer equipment used and the intended storage containers do not contain other substances/products. Before transfer to

stock the identity of the product must be proved to be without doubt. The entrance to storage rooms is to be granted only to appropriately trained personnel.
The stabilizer is only effective in the presence of oxygen. Maintain contact with atmosphere containing 5 - 21% oxygen. Never use tanks with inert-gas installation for storage.
Risk of polymerization. Protect against heat. Protect from direct sunlight. Avoid UV-light and other radiation with high energy. Protect against contamination.
In case of bulk storage, the storage-tanks should at least be equipped with two high temperature alert devices.
Even if the product is stored and handled as prescribed/indicated it should be used up within the indicated duration of storage.

Storage stability:
Storage temperature: < 35 °C
Storage duration: 12 Months
The stated storage temperature should be noted.
Avoid prolonged storage.
The stated storage temperature should be noted.
Avoid prolonged storage.
This product should be processed as soon as possible.
Ensure adequate inhibitor and dissolved oxygen level.
Do not store with less than 10 % headspace above liquid.
Storage stability is based upon ambient temperatures and conditions described.
It is recommended to keep a safe distance of +2 degrees above the crystallization range.
The product is stabilized, the shelf life should be noted.
Storage temperature: 45 °C
A restabilization system should be used if the temperature in the bulk storage-tank reaches the indicated value.
Storage temperature: 60 °C
All personnel in a greater area should be evacuated if the temperature in the bulk storage-tank reaches the indicated value.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

dicyclopentadiene	ACGIH, US:	TWA value 5 ppm ;
	ACGIH, US:	STEL value 1 ppm ;
	ACGIH, US:	TWA value 0.5 ppm ;
acrylic acid	ACGIH, US:	TWA value 2 ppm ;
	ACGIH, US:	Skin Designation ; Danger of cutaneous absorption

Advice on system design:
Provide local exhaust ventilation to maintain recommended P.E.L.

Personal protective equipment

Respiratory protection:
Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator as needed. At concentrations < 250 ppm, use a chemical cartridge respirator. At concentrations > 250 ppm, use an air-supplied or self-contained breathing apparatus.

Hand protection:
Chemical resistant protective gloves

Eye protection:
Tightly fitting safety goggles (chemical goggles).

Body protection:
light protective clothing

General safety and hygiene measures:
Avoid contact with the skin, eyes and clothing. Avoid inhalation of vapour. Wearing of closed work clothing is required additionally to the stated personal protection equipment. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

Form:	liquid	
Odour:	acrylic-like pungent	
Odour threshold:	not determined	
Colour:	colourless	
pH value:	not applicable, of low solubility	
Melting temperature:	-40 °C Literature data.	
Freezing point:	No data available.	
Melting point:	No data available.	
boiling temperature:	80.9 °C (0.705 hPa)	(measured)
Boiling point:	No data available.	
Boiling range:	No data available.	
Sublimation point:	No applicable information available.	
Flash point:	125.5 °C	(ISO 2719, closed cup)
Flammability:	not readily ignited	(derived from flash point)
Lower explosion limit:	For liquids not relevant for classification and labelling. The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Autoignition:	440 °C	(DIN 51794)
SADT:	Not a substance/mixture liable to self-decomposition according to GHS.	
Vapour pressure:	0.0088 hPa (20 °C) Extrapolated value	(OECD Guideline 104)
Density:	1.0488 g/cm3 (50 °C)	(OECD Guideline 109)
	1.0748 g/cm3 (20 °C)	(ISO 2811-3)
Relative density:	1.0748 (20 °C)	

Vapour density:	7.04 (20 °C) Heavier than air.	(calculated)
Partitioning coefficient n-octanol/water (log Pow):	4.4 (23 °C)	(OECD Guideline 117)
Self-ignition temperature:	20 °C not self-igniting	
Thermal decomposition:	155 °C, > 300 kJ/kg (DSC (OECD 113))	
Viscosity, dynamic:	14.4 mPa.s (20 °C) The value was determined by calculation from the detected kinematic viscosity.	(OECD Guideline 114)
Viscosity, kinematic:	No applicable information available.	
Particle size:	The substance / product is marketed or used in a non solid or granular form.	
Solubility in water:	0.04 g/l (20 °C)	
Solubility (quantitative):	No applicable information available.	
Solubility (qualitative):	miscible solvent(s): organic solvents,	
Molar mass:	204.27 g/mol	
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.	

10. Stability and Reactivity

Reactivity
No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:
No corrosive effect on metal.

Oxidizing properties:
not fire-propagating

Formation of flammable gases:	Remarks:	Forms no flammable gases in the presence of water.

Chemical stability
The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions
Explosion and fire hazard exists under confined conditions. Ignitable air mixtures can form when the product is heated above the flash point and/or when sprayed or atomized. Formation of explosive gas/air mixtures.
Polymerization coupled with heat formation.
Risk of spontaneous polymerization by oxygen depletion of the liquid phase. Risk of spontaneous polymerization when heated or in the presence of UV radiation. Risk of spontaneous and violent self-polymerization if inhibitor is lost or product is exposed to excessive heat. Polymerization produces gases which may burst closed or confined containers. Reactions may cause ignition.

Risk of spontaneous polymerization in the presence of starters for radical chain reactions (e.g. peroxides). Reacts with nitric acid. Risk of spontaneous polymerization in the presence of oxidizing agents.
Hazardous reactions in presence of mentioned substances to avoid.
The product is stabilized against spontaneous polymerization prior to despatch. The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid
Avoid heat. Avoid oxygen content above the product of less than 5 %. Avoid UV-light and other radiation with high energy. Avoid direct sunlight. Avoid prolonged storage. Avoid inhibitor loss. Avoid excessive temperatures. Avoid all sources of ignition: heat, sparks, open flame. Avoid freezing. Avoid moisture.
Do not blanket with nitrogen.

Incompatible materials
radical formers, free radical initiators, peroxides, mercaptans, nitro-compounds, perborates, azides, ether, ketones, aldehydes, amines, nitrates, nitrites, oxidizing agents, reducing agents, strong bases, alkaline reactive substances, acid anhydrides, acid chlorides, concentrated mineral acids, metal salts polyvinylchloride
Inert gas

Hazardous decomposition products

Decomposition products:
Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:
155 °C, 2.5 K/min (DSC (OECD 113))

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity
Assessment of acute toxicity: Virtually nontoxic after a single ingestion. The inhalation of a highly enriched/saturated vapor-air-mixture represents an unlikely acute hazard. Of low toxicity after short-term skin contact.

Oral
Type of value: LD50
Species: rat
Value: approx. 10,000 mg/kg (OECD Guideline 401)

Inhalation
Type of value: LC0
Species: rat
Value: >= 1 mg/l (IRT)

Exposure time: 7 h
No mortality within the stated exposition time as shown in animal studies.

Dermal
Type of value: LD50
Species: rabbit (male)
Value: 4,881 mg/kg (other)

Assessment other acute effects
Assessment of STOT single:
Causes temporary irritation of the respiratory tract.

Irritation / corrosion
Assessment of irritating effects: Skin contact causes irritation. Not irritating to the eyes. The European Union (EU) has classified the substance as "irritating to skin and eyes".

Skin
Species: rabbit
Result: Irritant.
Method: BASF-Test

Eye
Species: rabbit
Result: non-irritant
Method: similar to OECD guideline 405

Sensitization
Assessment of sensitization: Sensitization after skin contact possible.

Species: In vitro assay
Result: sensitizing
Method: In vitro skin sensitization test battery

Aspiration Hazard
not applicable

Chronic Toxicity/Effects

Repeated dose toxicity
Assessment of repeated dose toxicity: No substance-specific organtoxicity was observed after repeated administration to animals.

Genetic toxicity
Assessment of mutagenicity: No mutagenic effect was found in various tests with bacteria and mammalian cell culture.

Carcinogenicity
Assessment of carcinogenicity: The chemical structure does not suggest a specific alert for such an effect.

Reproductive toxicity
Assessment of reproduction toxicity: The results of animal studies gave no indication of a fertility impairing effect. The results were determined in a Screening test (OECD 421/422).

Teratogenicity

Assessment of teratogenicity: No indications of a developmental toxic / teratogenic effect were seen in animal studies. The results were determined in a Screening test (OECD 421/422).

Information on: dicyclopentadiene
Assessment of teratogenicity: Indications of possible developmental toxicity/teratogenicity were seen in animal studies.
---

12. Ecological Information

Toxicity

Aquatic toxicity
Assessment of aquatic toxicity:
Acutely toxic for aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.
Toxic to aquatic organisms based on long-term (chronic) toxicity study data.

Toxicity to fish
LC50 (96 h) 2.06 mg/l, Brachydanio rerio (OECD 203; ISO 7346; 92/69/EWG, C.1, semistatic)

Aquatic invertebrates
EC50 (48 h) 6.93 mg/l, Daphnia magna (OECD Guideline 202, part 1, static)

Aquatic plants
EC50 (72 h) 2.99 mg/l (growth rate), Pseudokirchneriella subcapitata (OECD Guideline 201, static)

Chronic toxicity to fish
Study does not need to be conducted.

Chronic toxicity to aquatic invertebrates
EC10 (21 d) 0.551 mg/l, Daphnia magna (OECD Guideline 211, semistatic)

Assessment of terrestrial toxicity
No data available.

Microorganisms/Effect on activated sludge

Toxicity to microorganisms
OECD Guideline 209 aerobic
activated sludge, domestic/EC50 (180 min): > 1,000 mg/l

Persistence and degradability

Assessment biodegradation and elimination (H2O)
Moderately/partially biodegradable.

Elimination information

50 - 60 % CO2 formation relative to the theoretical value (60 d) (OECD 301B; ISO 9439; 92/69/EWG, C.4-C) (aerobic, activated sludge) Moderately/partially biodegradable.

Assessment of stability in water
In contact with water the substance will hydrolyse slowly.

Information on Stability in Water (Hydrolysis)
$t_{1/2}$ > 365 d (25 °C, pH value 7), (calculated, pH 7)

Bioaccumulative potential

Assessment bioaccumulation potential
Significant accumulation in organisms is not to be expected.

Bioaccumulation potential
Bioconcentration factor: 60.18 (calculated)
Significant accumulation in organisms is not to be expected.

Mobility in soil

Assessment transport between environmental compartments
The substance will slowly evaporate into the atmosphere from the water surface.
Adsorption to solid soil phase is possible.

Additional information

Adsorbable organically-bound halogen(AOX):
This product contains no organically-bound halogen.

Other ecotoxicological advice:
Do not release untreated into natural waters.

Do not discharge product into the environment without control.

13. Disposal considerations

Waste disposal of substance:
Incinerate or dispose of in a RCRA-licensed facility. Do not discharge into drains/surface waters/groundwater.

Container disposal:
Empty containers with less than 1 inch of residue may be landfilled at a licensed facility. Recommend crushing, puncturing or other means to prevent unauthorized use of used containers. If containers are not empty, they must be disposed of in a RCRA-licensed facility.

Dispose of in accordance with national, state and local regulations.

RCRA: None

14. Transport Information

Land transport
USDOT

Not classified as a dangerous good under transport regulations

Sea transport
IMDG

Hazard class:	9
Packing group:	III
ID number:	UN 3082

Hazard label:	9, EHSM
Marine pollutant:	YES
Proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains HEXAHYDRO-4,7-METHANO-1H-INDENYL ACRYLATE, STABILIZED)

Air transport

IATA/ICAO	
Hazard class:	9
Packing group:	III
ID number:	UN 3082
Hazard label:	9, EHSM
Proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains HEXAHYDRO-4,7-METHANO-1H-INDENYL ACRYLATE, STABILIZED)

15. Regulatory Information

Federal Regulations

Registration status:
Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

CERCLA RQ	CAS Number	Chemical name
100 LBS	77-73-6	dicyclopentadiene

State regulations

State RTK	CAS Number	Chemical name
NJ	79-10-7	acrylic acid
PA	79-10-7	acrylic acid

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including CATECHOL, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:
Health: 2 Fire: 1 Reactivity: 2 Special:

HMIS III rating
Health: 2 Flammability: 1 Physical hazard: 1

Assessment of the hazard classes according to UN GHS criteria (most recent version):

Skin Corr./Irrit.	2	Skin corrosion/irritation
STOT SE	3 (irritating to respiratory system)	Specific target organ toxicity — single exposure
Aquatic Acute	2	Hazardous to the aquatic environment - acute
Aquatic Chronic	2	Hazardous to the aquatic environment - chronic

Skin Sens.	1	Skin sensitization
Acute Tox.	5 (dermal)	Acute toxicity

16. Other Information

SDS Prepared by:
BASF NA Product Regulations
SDS Prepared on: 2024/06/27

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
This product is of industrial quality and unless otherwise specified or agreed intended exclusively for industrial use.
Any other intended applications should be discussed with the manufacturer.
Safe Handling and Storage aspects are covered in a brochure which is available on request.

END OF DATA SHEET