

Material Safety Data Sheet

Canada
English

Section 1. Chemical product and company identification

Product name	Stray Light Test Kit; part of 'UV Test Kit, 280 nm, 10 mm'		
Catalogue Number	18-1129-69	 9 0 1 8 1 1 2 9 6 9	
Synonym	Propan-2-one; propanone; 2-Propanone; Ketone propane; Dimethyl ketone; 2-propanone; β-ketonepropane; acetone; dimethylketone; methyl ketone; propanone; pyroacetic acid; pyroacetic ether;		
Material uses	Industrial applications: Analytical chemistry. Research. Other non-specified industry: CHEMICALS (METHYL ISOBUTYL KETONE, METHYLISOBUTYL CARBINOL; METHYL METHACRYLATE; BISPHENOL-A); PAINT, VARNISH AND LACQUER SOLVENT; CELLULOSE ACETATE, ESPECIALLY AS SPINNING SOLVENT; TO CLEAN AND DRY PARTS OF PRECISION EQUIPMENT; SOLVENT FOR POTASSIUM IODIDE AND PERMANGANATE; DELUSTERANT FOR CELLULOSE ACETATE FIBERS; SPECIFICATION TESTING OF VULCANIZED RUBBER PRODUCTS.		
Product type	Liquid.		
Validation date	4 May 2015		
Print date	04 May 2015		
Supplier	GE Healthcare UK Ltd Amersham Place Little Chalfont Buckinghamshire HP7 9NA England +44 0870 606 1921		
In case of emergency	US	ChemTrec (US)	1-800-424-9300
	Canada	ChemTrec (US)	1-703-527-3887

2. Hazards identification

Physical state	Liquid.
Color	Colorless.
Odor	Fragrance-like.
Signal word	DANGER!
Hazard statements	<p>EXTREMELY FLAMMABLE LIQUID AND VAPOR. FLAMMABLE. VAPOR MAY CAUSE FLASH FIRE. CAUSES EYE IRRITATION. CAN CAUSE TARGET ORGAN DAMAGE.</p>
Precautionary measures	<p>Do not breathe vapor or mist. Use only with adequate ventilation. Do not eat, drink or smoke when using this product. Avoid contact with eyes. Keep away from heat, sparks and flame. Keep container tightly closed. Wash thoroughly after handling.</p>
Routes of entry	<p>Dermal contact. Eye contact. Inhalation. Ingestion.</p>
Potential acute health effects	
Eyes	Irritating to eyes.
Skin	May cause skin irritation.
Inhalation	No known significant effects or critical hazards.
Ingestion	No known significant effects or critical hazards.
Potential chronic health effects	
Chronic effects	<p>Can cause target organ damage.</p>
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.
Target organs	<p>Causes damage to the following organs: kidneys, liver.</p> <p>May cause damage to the following organs: blood, upper respiratory tract, skin, eyes, central nervous system (CNS), eye, lens or cornea.</p>



Inhalation	No specific data.
Ingestion	No specific data.
Skin	No specific data.
Eyes	Adverse symptoms may include the following: pain or irritation watering redness
Medical conditions aggravated by over-exposure	Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

See toxicological information (Section 11)

3. Composition/information on ingredients

Name		CAS number	% by weight
Acetone	67-64-1	100	-

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Section 4. First aid measures

Eye contact	Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
Skin contact	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
Inhalation	Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
Ingestion	Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Section 5. Fire-fighting measures

Flammability of the product	Extremely flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.
Extinguishing media	
Suitable	Use dry chemical, CO ₂ , water spray (fog) or foam.
Not suitable	Do not use water jet.
Special exposure hazards	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Hazardous combustion products	Decomposition products may include the following materials: carbon dioxide carbon monoxide
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods for cleaning up	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.
Small spill	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.



Section 7. Handling and storage

Handling


Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.


Section 8. Exposure controls/personal protection

Occupational exposure limits

Ingredient	List name	TWA (8 hours)			STEL (15 mins)			Ceiling			Notations
		ppm	mg/ m ³	Other	ppm	mg/ m ³	Other	ppm	mg/ m ³	Other	
 acetone	US ACGIH 6/2013	500	1188	-	750	1782	-	-	-	-	
	AB 4/2009	500	1200	-	750	1800	-	-	-	-	
	BC 7/2013	250	-	-	500	-	-	-	-	-	
	ON 1/2013	500	1188	-	750	1782	-	-	-	-	
	QC 12/2012	500	1190	-	1000	2380	-	-	-	-	

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures

 If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Engineering measures

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Hygiene measures


Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection


Respiratory

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.


Hands

 Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Eyes

 Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin

 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Other protection

Not available.

Personal protective equipment (Pictograms)

Not available.



Section 9. Physical and chemical properties

Physical state	Liquid.
Flash point	Closed cup: -18.1°C (-0.58°F)
Burning time	<input checked="" type="checkbox"/> Not applicable.
Burning rate	<input checked="" type="checkbox"/> Not applicable.
Auto-ignition temperature	464.9°C (868.8°F)
Flammable limits	Lower: 2% Upper: 13%
Color	Colorless.
Odor	Fragrance-like.
Molecular weight	<input checked="" type="checkbox"/> 58.09 g/mole
Molecular formula	<input checked="" type="checkbox"/> C ₅ H ₈ O
Boiling/condensation point	56°C (132.8°F)
Melting/freezing point	-94°C (-137.2°F)
Critical temperature	234.9°C (454.8°F)
Relative density	0.791
Vapor pressure	<input checked="" type="checkbox"/> 53.3 kPa (400 mm Hg) [room temperature]
Vapor density	2 [Air = 1]
Volatility	100% (v/v)
Odor threshold	62 to 130 ppm
Evaporation rate	6.06 (butyl acetate = 1)
SADT	<input checked="" type="checkbox"/> Not available.
Solubility	Easily soluble in the following materials: cold water, hot water and acetone.
Aerosol product	
Heat of combustion	<input checked="" type="checkbox"/> 28.49 kJ/g

Section 10. Stability and reactivity

Chemical stability	The product is stable.
Incompatible materials	Highly reactive or incompatible with the following materials: oxidizing materials
Possibility of hazardous reactions	<input checked="" type="checkbox"/> Under normal conditions of storage and use, hazardous reactions will not occur.

Section 11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
<input checked="" type="checkbox"/> Acetone	LD50 Oral	Rat	5800 mg/kg	-

Conclusion/Summary Not available.

Chronic toxicity

Not available.

Conclusion/Summary Not available.

Irritation/Corrosion

Not available.

Conclusion/Summary Not available.

Sensitizer

Not available.

Conclusion/Summary Not available.

Carcinogenicity

Not available.

Conclusion/Summary Not available.

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
<input checked="" type="checkbox"/> Acetone	A4	-	D	-	-	-

Mutagenicity

Not available.



Article Number

18112969-1



Page: 4/7

Validation date 4 May 2015


Version 4.2

Conclusion/Summary	Not available.
<u>Teratogenicity</u>	
Not available.	
Conclusion/Summary	Not available.
<u>Reproductive toxicity</u>	
Not available.	
Conclusion/Summary	Not available.
Synergistic products	Not available.

Section 12. Ecological information

Environmental effects  Readily biodegradable This product shows a low bioaccumulation potential.

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
 Acetone	Acute EC50 20.565 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute LC50 6000000 µg/l Fresh water	Crustaceans - Gammarus pulex	48 hours
	Acute LC50 10000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 100 mg/l Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 4.95 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.016 ml/L Fresh water	Crustaceans - Daphniidae	21 days
	Chronic NOEC 0.1 ml/L Fresh water	Daphnia - Daphnia magna - Neonate	21 days
	Chronic NOEC 5 µg/l Marine water	Fish - Gasterosteus aculeatus - Larvae	42 days
Conclusion/Summary	Not available.		


Persistence/degradability

Partition coefficient: n-octanol/water -27

Bioconcentration factor  10

Other adverse effects No known significant effects or critical hazards.

Section 13. Disposal considerations

Waste disposal  The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

RCRA classification Not available.

United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS #	Status	Reference number
 Acetone (I); 2-Propanone (I)	67-64-1	Listed	U002

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
------------------------	-----------	----------------------	---------	-----	-------	------------------------



Article Number







18112969-1



Page: 5/7

Validation date 4 May 2015

Version 4.2

DOT Classification	UN1090	ACETONE RQ	3	II		Reportable quantity 5000 lbs / 2270 kg [758.12 gal / 2869.8 L] Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements. Limited quantity Yes. Packaging instruction Passenger aircraft Quantity limitation: 5 L Cargo aircraft Quantity limitation: 60 L Special provisions IB2, T4, TP1
TDG Classification	UN1090	ACETONE	3	II		-
Mexico Classification	UN1090	Acetone	3	II		-
ADR/RID Class	UN1090	ACETONE	3	II		Hazard identification number 33 Limited quantity LQ4
IMDG Class	UN1090	ACETONE (ACETONE SOLUTIONS)	3	II		-
IATA-DGR Class	UN1090	ACETONE	3	II		Passenger and Cargo Aircraft Quantity limitation: 5 L Cargo Aircraft Only Quantity limitation: 60 L Limited Quantities - Passenger Aircraft Quantity limitation: 1 L

PG* : Packing group

Section 15. Regulatory information

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS (Canada) Class B-2: Flammable liquid
Class D-2B: Material causing other toxic effects (Toxic).

Canadian lists

Canadian NPRI ☒ This material is listed.
CEPA Toxic substances ☒ This material is listed.
Canada inventory ☒ This material is listed or exempted.

International regulations

International lists ☒ **Australia inventory (AICS):** This material is listed or exempted.
China inventory (IECSC): This material is listed or exempted.
Japan inventory: This material is listed or exempted.
Korea inventory: This material is listed or exempted.
Malaysia Inventory (EHS Register): This material is listed or exempted.
New Zealand Inventory of Chemicals (NZIoC): This material is listed or exempted.
Philippines inventory (PICCS): This material is listed or exempted.
Taiwan inventory (CSNN): Not determined.

Chemical Weapons Convention List Schedule I Chemicals ☒ Not listed

Chemical Weapons Convention List Schedule II Chemicals ☒ Not listed



Article Number

18112969-1



9 5 1 8 1 1 2 9 6 9 1

Page: 6/7

Validation date 4 May 2015

Version 4.2

Chemical Weapons Convention	Not listed
List Schedule III Chemicals	

Section 16. Other information

The customer is responsible for determining the PPE code for this material.



Indicates information that has changed from previously issued version.

History

Date of printing	04 May 2015	Date of previous issue	25 August 2010
Date of issue	04 May 2015	Version	4.2

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

