GF Healthcare

SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II - Switzerland

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name Stray Light Test Kit; part of 'UV Test Kit, 280 nm,

10 mm'

Catalogue Number 18-1129-69

Index number 606-001-00-8 200-662-2 EC number CAS number 67-64-1 Not available. **Product description** Product type Liquid.

Other means of identification propan-2-one; propanone; 2-Propanone; Ketone propane; Dimethyl ketone; 2-propanone; β-

ketonepropane; acetonum; dimethylketone; methyl ketone; propanone; pyroacetic acid; pyroacetic ether;

Chemical formula C_3H_6O

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Use in laboratories

1.3 Details of the supplier of the safety data sheet

Supplier GE Healthcare UK Ltd Hours of operation 08.30 - 17.00

Amersham Place Little Chalfont Buckinghamshire HP7 9NA

England

+44 0870 606 1921

Person who prepared the MSDS: msdslifesciences@ge.com

1.4 Emergency telephone number

0848 8028 10 Switzerland GE Healthcare Europe GmbH

> Europastrasse 31 CH-8152 Glattbrugg

National advisory body/Poison Centre

Switzerland Centre Suisse d'Information Toxicologique

(Swiss Toxicological Information Centre)

Freiestrasse 16 CH-8032 Zurich

Telephone: +41 44 251 66 66

Emergency telephone: +41 44 251 51 51 (145 from within Switzerland and Liechtenstein)

Fax: +41 44 252 88 33 E-mail: info@toxi.ch Web site: http://www.toxi.ch



Article Number 18112969-1

Validation date 4 May 2015

Page: 1/11

Version 4.2

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition Mono-constituent substance

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Lig. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Classification according to Directive 67/548/EEC [DSD]

Xi; R36 R66, R67

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms





Signal word Danger

Hazard statements Highly flammable liquid and vapour.

Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary statements

Prevention Wear protective gloves. Wear eye or face protection. Keep away from heat, sparks, open flames and hot

surfaces. - No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling

Response IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF ON

SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Storage

Disposal Dispose of contents and container in accordance with all local, regional, national and international

regulations.

Supplemental label elements Repeated exposure may cause skin dryness or cracking.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures

and articles

Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant fastenings

Not applicable.

Tactile warning of danger Not applicable.

2.3 Other hazards

Substance meets the criteria for PBT according to Regulation (EC)

No. 1907/2006, Annex XIII

No

P: Not available. B: No. T: Yes.

Substance meets the criteria for

vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

vP: Not available. vB: No.

Other hazards which do not result None known.

in classification



Article Number

18112969-1



Page: 2/11

SECTION 3: Composition/information on ingredients

Substance/mixture

Mono-constituent substance

			Classification		
Product/ingredient name	Identifiers	%	67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	Туре
acetone	EC: 200-662-2 CAS: 67-64-1 Index: 606-001-00-8	100	F; R11 Xi; R36 R66, R67	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[A]
			See Section 16 for the full text of the R-phrases declared above.	See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

Type

[A] Constituent

[B] Impurity

[C] Stabilising additive

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for

and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that

fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated

clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes

thoroughly before reuse.

Ingestion Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a

position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If

unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aidersNo action shall be taken involving any personal risk or without suitable training. If it is suspected that

fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact Causes serious eye irritation.

Inhalation Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.

Skin contact Defatting to the skin. May cause skin dryness and irritation.

Ingestion Can cause central nervous system (CNS) depression. Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

Eye contact Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation Adverse symptoms may include the following:

nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness



Article Number

18112969-1

Validation date 4 May 2015

Version 4.2

Page: 3/11

Skin contact nptoms may include the following

> irritation dryness cracking

No specific data. Ingestion

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been Notes to physician

ingested or inhaled.

Specific treatments No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Use dry chemical, CO2, water spray (fog) or foam.

Unsuitable extinguishing media Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or

mixture

Highly flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapour/gas is heavier than air and will spread along the ground. Vapours may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Hazardous combustion products

Decomposition products may include the following materials:

carbon dioxide carbon monoxide

5.3 Advice for firefighters

Special precautions for fire-

fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire

area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for

fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

Small spill Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof

equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a

licensed waste disposal contractor.

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof Large spill

equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.



Article Number

Page: 4/11

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Seveso II Directive - Reporting thresholds (in tonnes)

Named substances

Name
Notification and MAPP threshold
petroleum products - gasoline and naphthas - kerosenes (including jet 2500 25000

fuels) - gas oils (including diesel fuels, home heating oils and gas oil blending streams)-heavy fuel oils

7.3 Specific end use(s)

Recommendations Analytical chemistry. Laboratory chemicals Research and Development

Industrial sector specific solutions Not available.

SECTION 8: Exposure controls/personal protection

The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
acetone	SUVA (Switzerland, 6/2013). Notes: not temporary STEL: 2400 mg/m³ 15 minutes. STEL: 1000 ppm 15 minutes. TWA: 1200 mg/m³ 8 hours. TWA: 500 ppm 8 hours.

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

No DELs available.

PNECs

No PECs available.

8.2 Exposure controls



Article Number

18112969-1



Page: 5/11

Appropriate engineering controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eve/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product

Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state Liquid.

Colour Colourless.

Odour Fragrance-like.

Odour threshold 62 to 130 ppm

PH Not available.

Melting point/freezing point -94°C

Initial boiling point and boiling

range

56°C

Flash point Closed cup: -18.1° C Evaporation rate 6.06 (butyl acetate = 1)

Flammability (solid, gas) Highly flammable in the presence of the following materials or conditions: open flames, sparks and static

discharge and heat.

Burning time Not applicable.

Burning rate Not applicable.

Upper/lower flammability or explosive limits Lower: 2% Upper: 13%

Vapour pressure 53.3 kPa [room temperature]

Vapour density 2 [Air = 1] Relative density 0.791

Solubility(ies) Easily soluble in the following materials: cold water, hot water and acetone.

Partition coefficient: n-octanol/

water

-27

Auto-ignition temperature 464.9°C **Decomposition temperature** Not available.



Article Number Page: 6/11

18112969-1 Validation date 4 May 2015

Version 4.2



Viscosity Not available

Explosive propertiesNot considered to be a product presenting a risk of explosion.

Oxidising properties Not available

9.2 Other information

Heat of combustion -28.49 kJ/g

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability The product is stable.

10.3 Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill,

grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or

confined areas.

10.5 Incompatible materials Reactive or incompatible with the following materials:

oxidizing materials

10.6 Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
acetone	LD50 Oral	Rat	5800 mg/kg	-

Conclusion/Summary Not available.

Irritation/Corrosion

Conclusion/Summary Not available.

Sensitisation

Conclusion/Summary Not available.

Mutagenicity

Conclusion/Summary Not available.

<u>Carcinogenicity</u>

Conclusion/Summary Not available.

Reproductive toxicity

Conclusion/Summary Not available.

Teratogenicity

Conclusion/Summary Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
acetone	Category 3	Not applicable.	Narcotic effects

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of Routes of entry anticipated: Oral, Dermal, Inhalation.

exposure

Potential acute health effects

InhalationCan cause central nervous system (CNS) depression. May cause drowsiness or dizziness.IngestionCan cause central nervous system (CNS) depression. Irritating to mouth, throat and stomach.

Skin contact Defatting to the skin. May cause skin dryness and irritation.



Article Number Page: 7/11

18112969-1 Validation date 4 May 2015



Lye contactCauses serious eye irritation

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation Adverse symptoms may include the following:

nausea or vomiting headache

drowsiness/fatigue dizziness/vertigo unconsciousness No specific data.

Skin contact Adverse symptoms may include the following:

irritation dryness cracking

Eye contact Adverse symptoms may include the following:

pain or irritation watering

redness

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Ingestion

Potential immediate effects Not available.

Potential delayed effects

Not available.

Long term exposure

Potential immediate effects Not available.

Potential delayed effects

Not available.

Potential chronic health effects

Not available.

Conclusion/Summary Not available.

General Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.TeratogenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

Other information Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
acetone	Acute EC50 20.565 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute LC50 6000000 µg/l Fresh water	Crustaceans - Gammarus pulex	48 hours
	Acute LC50 10000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 100 mg/l Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 4.95 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.016 ml/L Fresh water	Crustaceans - Daphniidae	21 days
	Chronic NOEC 0.1 ml/L Fresh water Chronic NOEC 5 µg/l Marine water	Daphnia - Daphnia magna - Neonate Fish - Gasterosteus aculeatus - Larvae	21 days 42 days

Conclusion/Summary Not available.

12.2 Persistence and degradability

Conclusion/Summary Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
acetone	-	-	Readily

12.3 Bioaccumulative potential



18112969-1

Article Number

Validation date 4 May 2015

Page: 8/11

Product/ingredient name	LogPow	BCF	Potential
acetone	-27	<10	low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc} Not available.

)

Mobility Not available.

12.5 Results of PBT and vPvB assessment

PBT No.

P: Not available. B: No. T: Yes.

vPvB No

vP: Not available. vB: No.

12.6 Other adverse effects No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal The generation of waste should be avoided or minimised wherever possible. Disposal of this product,

solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with

jurisdiction.

Hazardous waste The classification of the product may meet the criteria for a hazardous waste.

Packaging

Methods of disposal The generation of waste should be avoided or minimised wherever possible. Waste packaging should be

recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautionsThis material and its container must be disposed of in a safe way. Care should be taken when handling

emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil,

waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN1090	UN1090	UN1090	UN1090
14.2 UN proper shipping name	ACETONE	ACETONE	ACETONE (ACETONE SOLUTIONS)	ACETONE
14.3 Transport hazard class(es)	3	3	3	3
14.4 Packing group	II	II	II	II
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	Hazard identification number 33 Limited quantity LQ4	-	-	Passenger and Cargo Aircraft Quantity limitation: 5 L Cargo Aircraft Only Quantity limitation: 60 L Limited Quantities - Passenger Aircraft Quantity limitation: 1 L



Article Number

18112969-1



Page: 9/11

Validation date 4 May 2015

14.6 Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC

Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Not applicable.

Other EU regulations

Europe inventory This material is listed or exempted.

 Black List Chemicals
 Not listed

 Priority List Chemicals
 Not listed

 Integrated pollution prevention
 Listed

and control list (IPPC) - Air

Integrated pollution prevention Not listed

and control list (IPPC) - Water

Seveso II Directive

This product is controlled under the Seveso II Directive.

Named substances

Name

petroleum products - gasoline and naphthas - kerosenes (including jet fuels) - gas oils (including diesel fuels, home heating oils and gas oil blending streams)-heavy fuel oils

National regulations

VOC content Liberated.

Chemical Weapons Convention Not listed
List Schedule I Chemicals

Chemical Weapons Convention List Schedule II Chemicals Not listed

Chemical Weapons Convention List Schedule III Chemicals

Not listed

15.2 Chemical Safety

Assessment

Not available.



18112969-1

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation (Regulation (EC) No. 1272/2008)

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	Expert judgment Expert judgment Expert judgment

Full text of abbreviated H H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. statements H336 May cause drowsiness or dizziness.

Full text of classifications [CLP/

GHS]

Eye Irrit. 2, H319 Flam. Liq. 2, H225 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 FLAMMABLE LIQUIDS - Category 2

STOT SE 3, H336 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Narcotic effects]

- Category 3

Full text of abbreviated R phrases

R11- Highly flammable. R36- Irritating to eyes.

R66- Repeated exposure may cause skin dryness or cracking.

R67- Vapours may cause drowsiness and dizziness.

Full text of classifications [DSD/

DPD]

F - Highly flammable Xi - Irritant

04 May 2015

Date of issue/ Date of revision 04 May 2015

Date of previous issue No previous validation

Version

Notice to reader

Date of printing

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



18112969-1

Validation date 4 May 2015