GE Healthcare

SAFETY DATA SHEET

New Zealand

Section 1. Identification

Product name Stray Light Test Kit; part of 'UV Test Kit, 254 nm,

10 mm'

Catalogue Number 18_1129_68

18-1129-68

Chemical name acetone

Other means of identification propan-2-one; propanone; 2-Propanone; Ketone propane; Dimethyl ketone; 2-propanone; β-

ketonepropane; acetonum; dimethylketone; methyl ketone; propanone; pyroacetic acid; pyroacetic ether;

Product type Liquid.

Identified usesUse in laboratories

<u>Supplier</u>

GE Healthcare UK Ltd GE Healthcare Bio-Sciences
Amersham Place 8 Tangihua Street
Little Chalfont Auckland 1010

Buckinghamshire HP7 9NA

England

+44 0870 606 1921

Person who prepared the MSDS: Emergency telephone number (with hours of operation)

msdslifesciences@ge.com 0800 733 893 (10am - 7pm)

Section 2. Hazards identification

HSNO Classification 3.1 - FLAMMABLE LIQUIDS - Category B

6.1 - ACUTE TOXICITY: ORAL - Category E 6.3 - SKIN IRRITATION - Category B 6.4 - EYE IRRITATION - Category A (Irritant)

This material is classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001 and has been classified according to the Hazardous Substances (Classifications) Regulations 2001.

GHS label elements

Signal word Danger

Hazard statements Highly flammable liquid and vapour.

May be harmful if swallowed. Causes mild skin irritation. Causes serious eye irritation.

Precautionary statements

Prevention Wear protective gloves. Wear eye or face protection. Keep away from ignition sources such as heat/

sparks/open flame. - No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static

discharge. Keep container tightly closed.

Response IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/

shower. If skin irritation occurs: Get medical adviće/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Wash hands after handling. Call a POISON CENTER or doctor/

physician if you feel unwell.

Store in a well-ventilated place. Keep cool.

Disposal Dispose of contents and container in accordance with all local, regional, national and international

regulations.



Storage

Article Number Page: 1/8

18112968-1 Validation date 4 May 2015



Version 4.2





Other hazards which do not result

in classification

None known.

Section 3. Composition/information on ingredients

Substance/mixtureSubstanceChemical nameacetone

Other means of identification propan-2-one; propanone; 2-Propanone; Ketone propane; Dimethyl ketone; 2-propanone; β-

ketonepropane; acetonum; dimethylketone; methyl ketone; propanone; pyroacetic acid; pyroacetic ether;

CAS number/other identifiers

 CAS number
 67-64-1

 EC number
 200-662-2

 Product code
 18-1129-68

Ingredient name%CAS numberacetone10067-64-1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

Description of necessary first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if

breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as

a collar, tie, belt or waistband.

Ingestion Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a

position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to

rinse for at least 10 minutes. Get medical attention if adverse health effects persist or are severe. Wash

clothing before reuse. Clean shoes thoroughly before reuse.

Eye contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for

and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Inhalation No known significant effects or critical hazards.

Ingestion May be harmful if swallowed. Irritating to mouth, throat and stomach.

Skin contactCauses mild skin irritation.Eye contactCauses serious eye irritation.

Over-exposure signs/symptoms

InhalationNo specific data.IngestionNo specific data.

Skin Adverse symptoms may include the following:

irritation redness

Eyes Adverse symptoms may include the following:

pain or irritation watering redness

Indication of immediate medical attention and special treatment needed, if necessary



Article Number Page: 2/8

18112968-1 Validation date 4 May 2015



Specific treatments

Notes to physician

No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable Use dry chemical, CO₂, water spray (fog) or foam.

Not suitable Do not use water iet.

Specific hazards arising from the

chemical

Highly flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapour/gas is heavier than air and will spread along the ground. Vapours may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition

products

Hazchem code

Decomposition products may include the following materials:

carbon dioxide carbon monoxide Not available.

Special precautions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus

(SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency

procedures

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only nonsparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage, including any incompatibilities Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.



Article Number 18112968-1

Page: 3/8

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name Exposure limits

acetone NZ OSH (New Zealand, 2/2013).

WES-STEL: 2375 mg/m³ 15 minutes. WES-STEL: 1000 ppm 15 minutes. WES-TWA: 1185 mg/m³ 8 hours. WES-TWA: 500 ppm 8 hours.

engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below

any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls Emissions from ventilation or work process equipment should be checked to ensure they comply with the

requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable

levels.

Individual protection measures

Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking

and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that

eyewash stations and safety showers are close to the workstation location.

Respiratory protection Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk

assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times

when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the

protection time of the gloves cannot be accurately estimated.

Eye protection Safety eyewear complying with an approved standard should be used when a risk assessment indicates

this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection:

chemical splash goggles.

Skin protection Personal protective equipment for the body should be selected based on the task being performed and

the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection

from static discharges, clothing should include anti-static overalls, boots and gloves.

Section 9. Physical and chemical properties

Appearance

Physical state Liquid.
Colour Colourless.

Odour Fragrance-like.

Odour threshold 62 to 130 ppm

pH Not available.

Melting point -94°C (-137.2°F)

Boiling point 56°C (132.8°F)

Flash point Closed cup: -18.1°C (-0.58°F)

Burning rateNot applicable.Burning timeNot applicable.Evaporation rate6.06 (butyl acetate = 1)

Flammability (solid, gas) Highly flammable in the presence of the following materials or conditions: open flames, sparks and static

discharge and heat. Lower: 2%

Lower and upper explosive

(flammable) limits Upper: 13%

Vapour pressure 53.3 kPa (400 mm Hg) [room temperature]

Vapour density 2 [Air = 1] Relative density 0.791

Solubility Easily soluble in the following materials: cold water, hot water and acetone.

Solubility in water Not available.



Article Number Page: 4/8

18112968-1 Validation date 4 May 2015



Partition coefficient: n-octanol/

water

Auto-ignition temperature464.9°C (868.8°F)Decomposition temperatureNot available.SADTNot available.ViscosityNot available.

Aerosol product

Type of aerosol Not applicable.

Heat of combustion -28.49 kJ/g

Ignition distance Not applicable.

Enclosed space ignition - Time Not applicable.

equivalent

Enclosed space ignition - Deflagration density

Not applicable.

Flame height Not applicable.
Flame duration Not applicable.

Section 10. Stability and reactivity

Chemical stability The product is stable.

Possibility of hazardous reactions Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill,

grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or

confined areas.

Incompatible materials Reactive or incompatible with the following materials:

oxidizing materials

Hazardous decomposition products Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on the likely routes of exposure

Inhalation No known significant effects or critical hazards.

Ingestion May be harmful if swallowed. Irritating to mouth, throat and stomach.

Skin contactCauses mild skin irritation.Eye contactCauses serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

InhalationNo specific data.IngestionNo specific data.

Skin contact Adverse symptoms may include the following:

irritation redness

Eye contact Adverse symptoms may include the following:

pain or irritation watering redness

Delayed and immediate effects and also chronic effects from short and long term exposure

Acute toxicity

Product/ingredient nameResultSpeciesDoseExposureacetoneLD50 OralRat5800 mg/kg-

Irritation/Corrosion

Not available.

Sensitisation

Not available.

Potential chronic health effects



Article Number Page: 5/8

18112968-1 Validation date 4 May 2015



No known significant effects or critical hazards Inhalation No known significant effects or critical hazards. Ingestion No known significant effects or critical hazards. Skin contact No known significant effects or critical hazards. No known significant effects or critical hazards. Eye contact No known significant effects or critical hazards. Carcinogenicity Mutagenicity No known significant effects or critical hazards. **Teratogenicity** No known significant effects or critical hazards. **Developmental effects** No known significant effects or critical hazards. Fertility effects No known significant effects or critical hazards.

Chronic toxicity

Not available.

Carcinogenicity

Not available.

Mutagenicity

Not available.

Teratogenicity

Not available.

Reproductive toxicity

Not available.

Specific target organ toxicity

Not available.

Aspiration hazard

Not available.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Other information Adverse symptoms include the following: kidney abnormalities liver abnormalities

Section 12. Ecological information

Ecotoxicity Readily biodegradable This product shows a low bioaccumulation potential.

Aquatic and terrestrial toxicity

Product/ingredient name	Result	Species	Exposure
acetone	Acute EC50 20.565 mg/l Marine water Acute LC50 6000000 µg/l Fresh water Acute LC50 10000 µg/l Fresh water Acute LC50 100 mg/l Fresh water	Algae - Ulva pertusa Crustaceans - Gammarus pulex Daphnia - Daphnia magna Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours 48 hours 48 hours 96 hours
	Chronic NOEC 4.95 mg/l Marine water Chronic NOEC 0.016 ml/L Fresh water Chronic NOEC 0.1 ml/L Fresh water Chronic NOEC 5 µg/l Marine water	Algae - Ulva pertusa Crustaceans - Daphniidae Daphnia - Daphnia magna - Neonate Fish - Gasterosteus aculeatus - Larvae	96 hours 21 days 21 days 42 days

Persistence/degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
acetone	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
acetone	-27	<10	low

Mobility in soil



Article Number Page: 6/8
18112968-1 Validation date 4 May 2015



Version 4.2

Soil/water partition coefficient (Koc)

Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transpo	rt information				
Regulatory information	UN number	Proper shipping	name	Classes	PG*
New Zealand Class	UN1090	Acetone		3	П
	FLAMMABLE J		-		
ADG Class	UN1090	ACETONE		3	II
	FLAMMABLE UIOUD 3		-		
UN Class	UN1090	Acetone		3	II
	3		-		
ADR/RID Class	UN1090	ACETONE		3	II
	<u>&</u>		Hazard identific	cation number	
	3		<u>Limited quantit</u> LQ4	<u>v</u>	
IATA Class	UN1090	ACETONE		3	II
	<u>&</u>		Cargo Aircraft (Cargo Aircraft Quantity lin Only Quantity limitation: 60 cies - Passenger Aircraft Q) L
IMDG Class	UN1090	ACETONE (ACETO	ONE SOLUTIONS)	3	II
	<u>&</u>		-		
	3				
PG* : Packing group					



18112968-1



Page: 7/8

Section 15. Regulatory information

New Zealand Inventory of

Chemicals (NZIoC)

This material is listed or exempted.

HSNO Approval Number HSR001070 **HSNO Group Standard** Not available.

HSNO Classification 3.1 - FLAMMABLE LIQUIDS - Category B

6.1 - ACUTE TOXICITY: ORAL - Category E 6.3 - SKIN IRRITATION - Category B 6.4 - EYE IRRITATION - Category A (Irritant)

Australia inventory (AICS) This material is listed or exempted.

Safety, health and environmental regulations specific for the product No known specific national and/or regional regulations applicable to this product (including its

ingredients).

Section 16. Other information

History

Date of printing 4 May 2015 Date of issue/ Date of revision 04 May 2015 Date of previous issue 9/23/2013. Version 42

Key to abbreviations ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland

Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified

by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

UN = United Nations

References Not available.

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



Article Number

Validation date 4 May 2015

18112968-1



Page: 8/8