

GREAT STUFF PRO™ SERIES

STRONG BOND, WET OR DRY

GREAT STUFF PRO™ CONSTRUCTION ADHESIVE

Sticking points

The secure bond created with GREAT STUFF PRO™ Construction Adhesive helps reduce nail pops in drywall, and floor and stair squeaks – which will help minimize callbacks. In addition to its ability to adhere to dry, damp or frozen lumber, GREAT STUFF PRO™ Construction Adhesive features:

- All-weather formulation with freeze-thaw stability
- Excellent bonding to wood, metal, masonry, glass and most plastics
- Seals subfloors, drywall, paneling, foam panels and most construction materials
- Tack-free in 14-minutes¹; fully cured in 24 hours
- Reusable for 30 days when left attached to GREAT STUFF PRO™ Dispensing Gun

GREAT STUFF PRO™ Construction Adhesive is a premium-grade, heavy-duty adhesive for interior and exterior use. Its all-weather formulation with freeze-thaw stability means it bonds lumber, plywood, particle board, masonry, drywall, concrete and foam panels in dry, damp and frozen conditions.

A firm, all-around grip

GREAT STUFF PRO™ Construction Adhesive adheres to wood, metal, masonry, glass and most plastics. It is designed to bond:

- Plywood and OSB subflooring to wood joists
- Foam panels, drywall, OSB and plywood to wood framing
- Masonry, tile and concrete substrates to OSB, plywood, foam panels and drywall

GREAT STUFF PRO™ Construction Adhesive is available in gun-applied formulation and, in the United States, with a reusable straw applicator.

Cream in color, GREAT STUFF PRO™ Construction Adhesive is available in 26.5 oz (751 g) cans. One can of GREAT STUFF PRO™ Construction Adhesive (gun-applied) equals up to 16 nominal quart tubes of traditional caulk adhesive, helping stretch the building budget even further.*



Get unbeatable reach with GREAT STUFF PRO™ 14 XL Dispensing Gun featuring an extra long barrel that guides the tip, providing precision and control, even while standing.

*Field demonstrated yield comparison. If theoretical yield is compared, one can of GREAT STUFF PRO™ Construction Adhesive (26.5 oz/751 g) (gun-applied formulation) applied at 1/4-inch bead diameter will equal up to 16 nominal quart tubes of caulk adhesive (28 oz/794 g) applied at 1/4-inch bead diameter.

A long reach

Stand up when applying GREAT STUFF PRO™ Construction Adhesive with the PRO 14XL Series long-barrel dispensing gun (40-inch [1 m] barrel). A guide tip, specially designed for PRO 14XL, helps control the position of the bead. Like the short barrel PRO 14 Series gun, PRO 14XL features:

- Designed to access hard-to-reach areas
- Lightweight, high-strength aluminum body with a metal trigger
- Flow-control mechanism dispenses beads from 1/8-inch to 3-inch
- Non-stick coated can adapter and needle
- Large flow control knob with secured back-screw system
- Replaceable smooth dispensing nozzle
- Works with all GREAT STUFF PRO™ cans
- No-drip dispensing
- Includes forked guide tip

Across-the-board adhesion

GREAT STUFF PRO™ Construction Adhesive is compatible with rigid foam insulation from DuPont as well as lumber, plywood, particleboard, masonry, drywall and concrete. And its excellent bonding power means fewer fasteners may be required. GREAT STUFF PRO™ Construction Adhesive can be applied in a single 1/2-inch bead on joists and studs. For optimum performance, apply adhesive bead in a continuous zigzag, ensuring adhesive layer will completely cover joists and framing on sistered joists or studs or wherever wood panels and drywall edges meet.



PRO Series Foam Dispensing Guns

GREAT STUFF PRO™ 14 Dispensing Guns

GREAT STUFF PRO™ 14XL Long Barrel Dispensing Gun

- Precision application
- High yield
- No-drip dispensing
- 30-day restartability



Formulated for the Pros

Count on GREAT STUFF PRO™ Polyurethane Foams to help you handle the toughest jobs.

- GREAT STUFF PRO™ Construction Adhesive
- GREAT STUFF PRO™ Gaps & Cracks
- GREAT STUFF PRO™ Window & Door
- GREAT STUFF PRO™ Pestblock
- GREAT STUFF PRO™ Foam Cleaner



*Not for sale in the South Coast Air Quality Management District of California.

For more information, visit us at greatstuff.com or call 1-866-583-2583

NOTICE: No freedom from any patent owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries or regions. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DUPONT. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release DuPont Specialty Products USA, LLC or its affiliates, of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business.

DuPont Polyurethane Foam Insulation and Sealants

CAUTION: When cured, these products are combustible and will burn if exposed to open flame or sparks from high-energy sources. Do not expose to temperatures above 240°F (116°C). For more information, consult (Material) Safety Data Sheet ((M)SDS), call DuPont at 1-866-583-BLUE (2583) or contact your local building inspector. In an emergency, call 1-989-636-4400 in the U.S. or 1-519-339-3711 in Canada.

Great Stuff™ contains isocyanate and a flammable blowing agent. Read all instructions and (Material) Safety Data Sheet ((M)SDS), carefully before use. Eliminate all sources of ignition before use. Cover all skin. Wear long sleeves, gloves, and safety glasses or goggles. Not for use in aviation, or food/beverage contact, or as structural support in marine applications. Provide adequate ventilation or wear proper respiratory protection. Contents under pressure. Not to be used for filling closed cavities or voids such as behind walls and under tub surrounds; this improper use of the product could result in the accumulation of flammable vapors and/or uncured material. Failure to follow the warnings and instructions provided with the product, and/or all applicable rules and regulations, can result in injury or death.

Building and/or construction practices unrelated to building materials could greatly affect moisture and the potential for mold formation. No material supplier including DuPont can give assurance that mold will not develop in any specific system.

© 2021 DuPont. All rights reserved. DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted.