

DuPont™ Styrofoam™ Brand Tongue and Groove Insulation

Lightweight, Easy To Install Type IV XPS Foam Insulation
U.S. HFC Regulation Compliant Formulation

FEATURES/BENEFITS

Description

DuPont™ Styrofoam™ Brand Tongue and Groove Insulation* features tongue and groove edges on all four sides of 2' x 8' boards 1" thick or less and on the long edges of all other boards. The lightweight, moisture-resistant and thermally efficient Type IV extruded polystyrene foam insulation is suited for a wide range of residential and commercial construction applications.

Ease of Installation

Styrofoam™ Brand Tongue and Groove Insulation goes up quickly and easily with grooves on all four edges to lock into the next sheet and gives more coverage per board. It's easy to install with high compressive strength for above and below grade applications.

Styrofoam™ Brand Tongue and Groove Insulation boards are easy to handle, cut using a utility knife or serrated blade, and install.

Available Sizes

- Width and length: 2' x 8' and 4' x 8'
- Thickness: .75", 1", 1.5", 2"

Not all product sizes are available in all parts of the country. Contact your local DuPont representative for details.

Sustainable Solutions

Styrofoam™ Brand Tongue and Groove Insulation boards are designed to help ensure energy efficiency and minimize on-site cutting and waste. Styrofoam™ Brand Tongue and Groove Insulation uses BluEdge™ technology. Styrofoam™ Brand Tongue and Groove Insulation is designed to be compliant with U.S. state HFC regulations where sold. It uses enhanced level of sustainable blowing agents, and BluEdge™ flame retardant technology.

It is hydrochlorofluorocarbon (HCFC) free with zero ozone-depletion potential. Styrofoam™ Brand Tongue and Groove Insulation is reusable in many applications. Styrofoam™ Brand Insulation products produced in North America contain an average of 20% pre-consumer recycled content certified by UL Environment Inc.

PROPERTIES

Review all instructions and Safe Handling document on [BeyondBlue.DuPont.com](https://www.beyondblue.dupont.com) before use.

TABLE 1: Physical Properties of Styrofoam™ Brand Tongue and Groove Insulation

Test Method	Property	Typical Value	Units
ASTM C518	Thermal Resistance ¹ per inch		
	@ 75°F mean temp.	5.0	ft ² ·h·°F/Btu, R-value**, min.
	@ 40°F mean temp.	5.4	
	@ 25°F mean temp.	5.6	
ASTM D1621	Compressive Strength ²	25	psi, min.
ASTM C272	Water Absorption	0.1	% by volume, max.
ASTM E96	Water Vapor Permeance ³	1.5	perm, max.
–	Maximum Use Temperature	165	°F
ASTM D696	Coefficient of Linear Thermal Expansion	3.5 x 10 ⁻⁵	in/in·°F
ASTM C203	Flexural Strength	50	psi, min.
ASTM E84	Surface Burning Characteristics for both foam core and finished product	Class A	
	Flame Spread	25	
	Smoke Developed	<450	

* R means resistance to heat flow. The higher the R-value, the greater the insulating power. R-value determined by ASTM C518.

¹ R-values are consistent with criteria of ASTM C578 and the requirements of the FTC R-value rule (16 CFR Part 460).

² Vertical compressive strength is measured at 10 percent deformation or at yield, whichever occurs first.

³ Based on 1" thickness.

INSTALLATION

Use Conditions

DuPont™ Styrofoam™ Brand Tongue and Groove Insulation is suitable for use in pervious, semi-pervious and practically impervious soils.

Preparation

It is recommended that any masonry irregularities or jagged surfaces on the foundation wall or slab be removed prior to installation. Below-grade walls should be protected from moisture leakage and dampness prior to installation of **Styrofoam™ Brand Tongue and Groove Insulation**. Code-approved drainage systems should be installed. Ensure foundation drainage meets local codes.

Application

Use a polystyrene-compatible adhesive to hold the boards in place during backfilling. Apply caulk or mastic to the top of the board to prevent water infiltration behind the insulation. To complete the installation, parge the above-grade portions of **Styrofoam™ Brand Tongue and Groove Insulation** to protect from solar radiation.

TESTING

Applicable Standards

Styrofoam™ Brand Tongue and Groove Insulation meets **ASTM C578**, Type IV – Standard Specification for Rigid Cellular Polystyrene Thermal Insulation. Applicable standards include:

- **C518** – Standard Test Method for Steady-State Thermal Transmission Properties by Means of the Heat Flow Meter Apparatus
- **D1621** – Standard Test Method for Compressive Properties of Rigid Cellular Plastics
- **E96** – Standard Test Methods for Water Vapor Transmission of Materials
- **D696** – Standard Test Method for Coefficient of Linear Thermal Expansion of Plastics Between -30°C and 30°C with a Vitreous Silica Dilatometer
- **C203** – Standard Test Methods for Breaking Load and Flexural Properties of Block-Type Thermal Insulation
- **D2126** – Standard Test Method for Response of Rigid Cellular Plastics to Thermal and Humid Aging
- **C272** – Standard Test Method for Water Absorption of Core Materials for Structural Sandwich Constructions

Notice

Styrofoam™ Brand Tongue and Groove Insulation complies with the following codes:

- International Residential Code (IRC) and International Building Code (IBC) See ESR-4755
- Underwriters Laboratories, Inc. (UL) Classified, see Classification Certificate D369
- Calif. Std. Reg. # CA T1535 Florida Building Code FL 16357

Contact your local DuPont sales representative or local authorities for state and local building code requirements and related acceptances.

Warranty

In the United States, a 50-year thermal limited warranty is available on Styrofoam™ products 1.5 inches and greater. For thickness less than 1.5 inches, other warranties may apply. Warranties are available as described at building.dupont.com/warranties.

HANDLING

WARNING: For Professional Use Only. Read and follow the entire Safety, Handling, and Storage section and Safe Handling document on **BeyondBlue.DuPont.com** carefully before use. The information below is designed to protect the user and allow for safe use and handling of DuPont products. Follow all applicable federal, state, local and employer regulations.

Precautionary Statements

Styrofoam™ Brand Tongue and Groove Insulation is combustible; protect from high heat sources. A protective barrier or thermal barrier may be required as specified in the local building codes. Read and follow the entire Handling section and Safe Handling document on **BeyondBlue.DuPont.com** carefully before use.

Shelf Life and Storage

When stored outdoors, keep insulation boards tarped or covered to protect from weather and weighted down to prevent boards from being blown around by the wind. Store above standing water.

Cover exposed Styrofoam™ with a light opaque covering to protect from weather and sunlight. Do not use clear plastic covering

Disposal

Dispose of any residual DuPont product, coated debris, or solvent in accordance with applicable federal, state, and local government regulations.



**For more information visit us at
styrofoam.com
or call 1-833-338-7668**

NOTICE: No freedom from any patent owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries or regions. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DUPONT. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release DuPont Specialty Products USA, LLC or its affiliates, of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business.

DuPont™ Styrofoam™ Brand Tongue and Groove Insulation

CAUTION: This product is combustible. Protect from high heat sources. A protective barrier or thermal barrier may be required as specified in the appropriate building code. For more information call the DuPont Contact Center at 866-583-2583 or contact your local building inspector. For emergencies contact Chemtrec 800-424-9300, CCN (Contract Number) 7442.

WARNING: Rigid foam insulation does not constitute a working walkable surface or qualify as a fall protection product.

Building and/or construction practices unrelated to building materials could greatly affect moisture and the potential for mold formation. No material supplier including DuPont can give assurance that mold will not develop in any specific system.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. © 2024 DuPont.

43-D100998-enUS-0624 CDP