

The hardest-working tape is now a liquid.

Introducing DuPont™ LiquidArmor™ CM Flashing and Sealant



Goes on as a liquid. Protects like a coat of armor.

Our building material scientists are always looking for new solutions to the challenges you face on your building projects. One challenge was to find an easy way to flash and seal surfaces that provides a long-lasting protective barrier. The solution turned out to be a whole new kind of material with new properties that's extremely easy to apply. It's an innovative elastomeric spray, appropriately named DuPont™ LiquidArmor™ CM Flashing and Sealant.

Sprays over contours and corners

- DuPont™ LiquidArmor™ – CM easily seals tough areas like awkward corners and complex details with an airless paint sprayer.
- You can seal up to ¼" gaps with one or two passes of LiquidArmor™ CM.*
- There is no cutting, and there are fewer worries about rough or uneven surfaces.



Ready for a "deminar"?

Ask your DuPont sales representative about the next lunchtime demonstration-seminar near you.

Built for the long run

- The advanced formulation of LiquidArmor™ CM is flexible and more tolerant as buildings naturally move and settle.
- It creates a durable bond to withstand tough weather conditions.
- It provides consistent, seamless adhesion.

Now let's talk application.

Exceptional sealing, inside and out

- DuPont™ LiquidArmor™ CM is designed to work with
- DuPont™ Thermax™ (ci) Exterior Insulation and DuPont™ Styrofoam™ Brand Cavitymate™ Ultra Insulation.
- It sprays effortlessly from one type of surface to another.
- It's also suited for steel studs, exterior-grade gypsum, OSB, masonry tile and other substrates.
- It self-seals around nails, veneer anchors and penetrating fasteners.
- Because it sprays on as a liquid, it dries as a smooth surface, allowing almost anything to go on top of it.

Forms an airtight, watertight barrier

- LiquidArmor™ CM doesn't just spray on—it penetrates between surfaces and dries as a tough yet flexible material, forming an airtight, durable bond.
- It's proven to effectively seal out air, moisture and water for an exceptional performing barrier.**

A focus on safety

- LiquidArmor™ CM is a nonhazardous, low-VOC formulation.
- You can spray it without any special ventilation requirements.

Ease

- It sprays on quickly, so it saves labor hours.
- If you overspray or misapply LiquidArmor™ CM, you can wipe it off with a damp rag or wash it off with water before it cures.
- It provides consistent, seamless adhesion.



Undeniably DuPont

- For over 60 years, DuPont Performance Building Solutions has taken a leading role in the research and development of new building envelope solutions that outperform current building materials and methods.
- You'll have all the dedicated technical sales and customer support you need—from the first discussion to the final detail.

Ask your DuPont sales representative for a free demonstration seminar, and see firsthand just how tough and easy to use DuPont™ LiquidArmor™ CM really is.



**For more information visit
building.dupont.com
or call 1-866-583-2583**

NOTICE: No freedom from infringement of any patent owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release DuPont of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business. CAUTION: This product is combustible and shall only be used as specified by the local building code with respect to flame spread classification and to the use of a suitable thermal barrier. For more information, consult (Material) Safety Data Sheet ((M)SDS), call DuPont at 1-866-583-BLUE (2583), or contact your local building inspector. In an emergency, call 1-989-636-4400.

*DuPont™ LiquidArmor™ CM bridges up to 1/4" gaps without the need of mesh or a backer rod. Larger gaps may need the addition of common backer rods. Read all instructions and (Material) Safety Data Sheets carefully before use. It is recommended that spray applicators and those working in the spray area wear eye protection. Contact with exposed skin may cause skin discoloration and dryness. Gloves are recommended for prolonged exposure. Ensure adequate ventilation during spray applications. LiquidArmor™ CM is a combustible material. Ensure product application complies with local building codes.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. © 2019 DuPont.