

# DuPont™ Styrofoam™ Brand Tape

Durable, Pliable Sealing Tape with Superior Tack

## OVERVIEW

### Description

DuPont™ Styrofoam™ Brand Tape is a durable sealing tape with excellent adhesion properties to help protect homes and buildings against moisture and air intrusion.

Styrofoam™ Brand Tape is pliable – ensuring a tight seal, even at extremely low temperatures – and its oriented polypropylene backing is formulated with a UV-treated film to help resist degradation from exposure to sunlight.

Styrofoam™ Brand Tape is the recommended tape for sealing joints and seams of Styrofoam™ Brand XPS Insulation. It provides a tight bond to sheathing boards to seal seams and enhance resistance to moisture and air infiltration.



### Features and Benefits

- **Application and Service Temperature:** Pliable, for a tight seal even at low temperatures.
- **High Performance Durability:** Excellent tack with enhanced grip. Strong, durable and impact resistant. Versatile and easy to apply.

### Sustainable Solutions

- Styrofoam™ Brand Tape can be used to repair damaged foam insulation, reducing material costs and job-site waste. For the greatest energy savings potential and weather resistance, tape or patch any tears, holes, breaks or damage created during normal construction.

### Applications

- Used to seal seams of Styrofoam™ Brand XPS Insulation

### Complete System

- Styrofoam™ Brand Tape is part of the complete lineup from DuPont – products designed to enhance the performance of the building envelope.

## Standard Sizes

Unit	Width	Length	Units per Case	Cases per Pallet	Units per Pallet
Roll	3 3/4 in.	165 ft.	12	36	432

## TESTING AND CODE COMPLIANCE

DuPont™ Styrofoam™ Brand Tape™ Review all instructions and (Material) Safety Data Sheet ((M)SDS) before use. Please contact DuPont at 1-833-338-7668 when additional guidance is required for writing specifications that include this product.

TEST METHOD	TEST TITLE	PROPERTY	RESULTS
STRENGTH			
ASTM D882	Standard Test Method for Tensile Properties of Thin Plastic Sheeting	Tensile Strength	27 lb/in, min.
ADHESION			
ASTM D3330	Standard Test Method for Peel Adhesion of Pressure-Sensitive Tape	Typical Adhesion Stainless Steel (no dwell time 180 degrees)	>35 oz/in, min

---

## INSTALLATION

### Use Conditions

- Taping horizontal seams is recommended just prior to siding.
- Apply to clean and dry surfaces, after evaporation of morning dew.
- When sealing the joints between two boards of insulated sheathing, center the tape over the joint to cover nails on both sides.
- Apply at temperatures over 15 °F (-9 °C). After application, tape will perform in temperatures of -40 °F (-40 °C) to 220 °F (104 °C).

### Curing

- Maximum adhesion will be achieved after 72-hour cure.
- For best adhesion, apply pressure to the tape/sealed area.
- After each use, fold 1 inch of the tape end onto itself. Before reusing the tape, trim the folded end with a utility knife or scissors.

### Equipment

- For maximum protection against air infiltration and moisture, use Great Stuff Pro™ Gaps & Cracks in addition to DuPont™ Styrofoam™ Brand Tape around ducts and other penetrations.



**For more information, visit us at**  
**[building.dupont.com](https://building.dupont.com)**  
**or call us at 1-833-338-7668**

**NOTICE:** No freedom from any patent owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries or regions. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DUPONT. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release DuPont de Nemours, Inc. or its affiliates of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. © 2025 DuPont. 43-D100064-enNA-1025 CDP

Issue  
Date:

Print Date: 5/16/2025