NALCO An Ecolab Company

SAFETY DATA SHEET

NALSTRIP® 231MS

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : NALSTRIP® 231MS

Other means of identification : formerly Felteccel 231MS

Recommended use : CLEANER

Restrictions on use : Refer to available product literature or ask your local Sales

Representative for restrictions on use and dose limits.

Company : Nalco Company

1601 W. Diehl Road

Naperville, Illinois 60563-1198

USA

TEL: (630)305-1000

Emergency telephone

number

(800) 424-9300 (24 Hours) CHEMTREC

Issuing date : 06/17/2014

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Corrosive to metals : Category 1
Skin corrosion : Category 1A
Serious eye damage/eye : Category 1

irritation

GHS Label element

Hazard pictograms :



Signal Word : Danger

Hazard Statements : May be corrosive to metals.

Causes severe skin burns and eye damage.

Precautionary Statements : **Prevention:**

Keep only in original container. Wash skin thoroughly after handling. Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse. Absorb

spillage to prevent material damage.

NALSTRIP® 231MS

Storage:

Store locked up. Store in corrosive resistant stainless steel

container with a resistant inner liner.

Disposal:

Dispose of contents/ container to an approved waste disposal

plant.

Other hazards : None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name CAS-No. Concentration: (%)

 Sodium Hydroxide
 1310-73-2
 10 - 30

 1-Methoxy-2-Propanol
 107-98-2
 1 - 5

 Organic Salt
 Proprietary
 1 - 5

SECTION 4. FIRST AID MEASURES

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Get medical attention immediately.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes.

Use a mild soap if available. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention

immediately.

If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give

anything by mouth to an unconscious person. Get medical attention

immediately.

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if

symptoms occur.

Protection of first-aiders : In event of emergency assess the danger before taking action. Do

not put yourself at risk of injury. If in doubt, contact emergency responders. Use personal protective equipment as required.

Notes to physician : Treat symptomatically.

See toxicological information (Section 11)

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: None known.

Specific hazards during

firefighting

: Not flammable or combustible.

Hazardous combustion

products

: Carbon oxides

for firefighters

Special protective equipment : Use personal protective equipment.

NALSTRIP® 231MS

Specific extinguishing methods

: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Environmental precautions

: Do not allow contact with soil, surface or ground water.

Methods and materials for containment and cleaning up

: Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not ingest. Do not breathe dust/fume/gas/mist/vapours/spray. Do

not get in eyes, on skin, or on clothing. Wash hands thoroughly after

handling. Use only with adequate ventilation.

Conditions for safe storage : Do not store near acids. Keep out of reach of children. Keep

container tightly closed. Store in suitable labeled containers.

Suitable material : Keep in properly labelled containers.

Unsuitable material : not determined

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
Sodium Hydroxide	1310-73-2	Ceiling	2 mg/m3	ACGIH
		Ceiling	2 mg/m3	NIOSH REL
		TWA	2 mg/m3	OSHA Z1
1-Methoxy-2-Propanol	107-98-2	TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm 540 mg/m3	NIOSH REL
		TWA	100 ppm 360 mg/m3	NIOSH REL

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations

below occupational exposure standards.

NALSTRIP® 231MS

Personal protective equipment

Eye protection : Safety goggles

Face-shield

Hand protection : Wear the following personal protective equipment:

Standard glove type.

Gloves should be discarded and replaced if there is any indication of

degradation or chemical breakthrough.

: Personal protective equipment comprising: suitable protective Skin protection

gloves, safety goggles and protective clothing

Respiratory protection : When workers are facing concentrations above the exposure limit

they must use appropriate certified respirators.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

> practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes

and body in case of contact or splash hazard.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquid Colour : Clear

Amber

Odour : Mild

: > 100 °C Flash point

pΗ : 13.5, 100 %

Odour Threshold : no data available : no data available Melting point/freezing point

Initial boiling point and boiling

range

: 100 °C

: similar to water Evaporation rate Flammability (solid, gas) : no data available Upper explosion limit : no data available Lower explosion limit : no data available

Vapour pressure : no data available Relative vapour density : no data available Relative density : 1.1675 (25 °C)

Density : no data available Water solubility : completely soluble Solubility in other solvents : no data available Partition coefficient: n-

octanol/water

: no data available

Auto-ignition temperature : no data available

NALSTRIP® 231MS

Thermal decomposition : Carbon oxides : 4.5 mPa.s Viscosity, dynamic

Viscosity, kinematic : no data available

VOC : 0%

0 g/l

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No dangerous reaction known under conditions of normal use.

Conditions to avoid : None known.

Incompatible materials : Contact with strong acids (e.g. sulfuric, phosphoric, nitric,

hydrochloric, chromic, sulfonic) may generate heat, splattering or

boiling and toxic vapors.

Hazardous decomposition

products

: Oxides of carbon Oxides of nitrogen

SECTION 11. TOXICOLOGICAL INFORMATION

exposure

Information on likely routes of : Inhalation, Eye contact, Skin contact

Potential Health Effects

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns.

Ingestion : Causes digestive tract burns.

Inhalation : May cause nose, throat, and lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

Toxicity

Product

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Acute inhalation toxicity : Acute toxicity estimate : > 40 mg/l

Exposure time: 4 h

NALSTRIP® 231MS

Acute dermal toxicity : no data available

Skin corrosion/irritation : no data available

Serious eye damage/eye

irritation

: no data available

Respiratory or skin

sensitization

: no data available

Carcinogenicity : no data available

Reproductive effects : no data available

: no data available Germ cell mutagenicity

Teratogenicity : no data available

STOT - single exposure : no data available

STOT - repeated exposure : no data available

Aspiration toxicity : no data available

Components

Acute dermal toxicity : 1-Methoxy-2-Propanol

LD50 rabbit: > 13,000 mg/kg

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxicity to fish : no data available

Toxicity to daphnia and other : no data available

aquatic invertebrates

: no data available Toxicity to algae

Components

Toxicity to fish : 1-Methoxy-2-Propanol

LC50 Fish: > 1,000 mg/l Exposure time: 96 h

Organic Salt

LC50 Fish: 121 mg/l Exposure time: 96 h

Persistence and degradability

The organic portion of this preparation is expected to be readily biodegradable.

Mobility

NALSTRIP® 231MS

The environmental fate was estimated using a level III fugacity model embedded in the EPI (estimation program interface) Suite TM, provided by the US EPA. The model assumes a steady state condition between the total input and output. The level III model does not require equilibrium between the defined media. The information provided is intended to give the user a general estimate of the environmental fate of this product under the defined conditions of the models.

If released into the environment this material is expected to distribute to the air, water and soil/sediment in the approximate respective percentages;

Air : <5% Water : 30 - 50% Soil : 50 - 70%

The portion in water is expected to be soluble or dispersible.

Bioaccumulative potential

This preparation or material is not expected to bioaccumulate.

Other information

no data available

SECTION 13. DISPOSAL CONSIDERATIONS

If this product becomes a waste, it could meet the criteria of a hazardous waste as defined by the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Before disposal, it should be determined if the waste meets the criteria of a hazardous waste.

Hazardous Waste: : D002

Disposal methods : Where possible recycling is preferred to disposal or

incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an

approved waste disposal facility.

Disposal considerations : Dispose of as unused product. Empty containers should be

taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (DOT)

The presence of an RQ component (Reportable Quantity for U.S. EPA and DOT) in this product causes it to be regulated with an additional description of RQ for road, or as a class 9 for road and air, ONLY when the net weight in the package exceeds the calculated RQ for the product.

Proper shipping name : SODIUM HYDROXIDE SOLUTION

Technical name(s)

.

UN/ID No. : UN 1824 Transport hazard class(es) : 8

Packing group : II

Reportable Quantity (per : 8,000 lbs

package)

RQ Component : SODIUM HYDROXIDE

NALSTRIP® 231MS

Air transport (IATA)

The presence of an RQ component (Reportable Quantity for U.S. EPA and DOT) in this product causes it to be regulated with an additional description of RQ for road, or as a class 9 for road and air, ONLY when the net weight in the package exceeds the calculated RQ for the product.

Proper shipping name : SODIUM HYDROXIDE SOLUTION

Technical name(s)

UN/ID No. : UN 1824

Transport hazard class(es) : 8
Packing group : II

Reportable Quantity (per

package)

: 8,000 lbs

RQ Component : SODIUM HYDROXIDE

Sea Transport (IMDG/IMO)

Proper shipping name : SODIUM HYDROXIDE SOLUTION

Technical name(s)

UN/ID No. : UN 1824

Transport hazard class(es) : 8
Packing group : II

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ
			(lbs)
Sodium Hydroxide	1310-73-2	1000	7899

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard

SARA 302 : SARA 302: No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313: This material does not contain any chemical components

with known CAS numbers that exceed the threshold (De Minimis)

reporting levels established by SARA Title III, Section 313.

California Prop 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

INTERNATIONAL CHEMICAL CONTROL LAWS:

TOXIC SUBSTANCES CONTROL ACT (TSCA)

The substances in this preparation are included on or exempted from the TSCA 8(b) Inventory (40 CFR 710)


CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA)

The substance(s) in this preparation are included in or exempted from the Domestic Substance List (DSL).

NALSTRIP® 231MS

SECTION 16: OTHER INFORMATION

NFPA:



Special hazard.

HMIS III:

HEALTH	3
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight, 2 = Moderate, 3 = High

2 = Moderate, 3 = High 4 = Extreme, * = Chronic

Revision Date : 06/17/2014

Version Number : 1.0

Prepared By : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

For additional copies of an MSDS visit www.nalco.com and request access.