

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/22/2015

Reviewed on 07/22/2015

1 Identification

- **Product identifier**
- **Trade name:** STERI FAB®
- **Article number:** No other identifiers
- **Recommended use and restriction on use**
- **Recommended use:** Disinfectant
- **Restrictions on use:** No further relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Noble Pine Products, Inc. - Castoleum Corporation
P.O. BOX 41 - CENTUCK STATION
YONKERS, NY 10710-0041
914-664-5877
- **Emergency telephone number:**
ChemTel Inc.
(800)255-3924, +1 (813)248-0585

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Additional information:**

There are no other hazards not otherwise classified that have been identified.

0 percent of the mixture consists of ingredient(s) of unknown toxicity.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning

- **Hazard-determining components of labeling:**

propan-2-ol

- **Hazard statements**

H226 Flammable liquid and vapor.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/22/2015

Reviewed on 07/22/2015

Trade name: STERI FAB®

(Contd. of page 1)

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, sparks, open flames, and hot surfaces. - No smoking.

P261 Avoid breathing mist, vapors, or spray.

P264 Wash thoroughly after handling.

P280 Wear protective gloves and eye protection.

P233 Keep container tightly closed.

P271 Use only outdoors or in a well-ventilated area.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312 Call a poison center/doctor if you feel unwell.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:**NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 3

Reactivity = 0

HMIS-ratings (scale 0 - 4)

Health = 1

Fire = 3

Reactivity = 0

* - Indicates a long term health hazard from repeated or prolonged exposures.

Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-63-0	propan-2-ol	60-80%
	Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	

(Contd. on page 3)

Safety Data Sheet



acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/22/2015

Reviewed on 07/22/2015

Trade name: STERI FAB®

(Contd. of page 2)

26002-80-2	3-phenoxybenzyl 2-dimethyl-3-(methylpropenyl)cyclopropanecarboxylate	<1.0%
7173-51-5	didecyldimethylammonium chloride	<1.0%
	 Skin Corr. 1B, H314  Acute Tox. 4, H302	

· **Additional information:**

For the listed ingredient(s), the identity and exact percentage(s) are being withheld as a trade secret.

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:**

Immediately rinse with water.

If skin irritation is experienced, consult a doctor.

· **After eye contact:**

Protect unharmed eye.

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

Headache

Breathing difficulty

Dizziness

Coughing

Irritant to eyes.

Gastric or intestinal disorders when ingested.

Nausea

Acidosis

Disorientation

· **Danger** Vapors have narcotic effect.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

Alcohol resistant foam

Water

Carbon dioxide

Gaseous extinguishing agents

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/22/2015

Reviewed on 07/22/2015

Trade name: STERI FAB®

(Contd. of page 3)

- **For safety reasons unsuitable extinguishing agents:** None.
- **Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information**
Eliminate all ignition sources if safe to do so.
Cool endangered receptacles with water in flooding quantities.
Use large quantities of foam as it is partially destroyed by the product.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation.
Keep away from ignition sources.
Protect from heat.
- **Environmental precautions:** No special measures required.
- **Methods and material for containment and cleaning up:**
Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).
Dispose contaminated material as waste according to item 13.
Send for recovery or disposal in suitable receptacles.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Use only in well ventilated areas.
Prevent formation of aerosols.
Avoid splashes or spray in enclosed areas.
- **Information about protection against explosions and fires:**
Highly flammable liquid and vapor.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Avoid storage near extreme heat, ignition sources or open flame.
Provide ventilation for receptacles.
- **Information about storage in one common storage facility:**
Store away from foodstuffs.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/22/2015

Reviewed on 07/22/2015

Trade name: STERI FAB®

(Contd. of page 4)

Store away from oxidizing agents.

- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

Components with limit values that require monitoring at the workplace:

67-63-0 propan-2-ol

PEL (USA)	Long-term value: 980 mg/m ³ , 400 ppm
REL (USA)	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV (USA)	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm
EL (Canada)	Short-term value: 400 ppm Long-term value: 200 ppm
EV (Canada)	Short-term value: 400 ppm Long-term value: 200 ppm
LMPE (Mexico)	Short-term value: 400 ppm Long-term value: 200 ppm A4, IBE

Ingredients with biological limit values:

67-63-0 propan-2-ol

BEI (USA)	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----------	---

- **Additional information:** The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Do not inhale gases / fumes / aerosols.

- **Engineering controls:** No further relevant information available.

Breathing equipment:

Not required under normal conditions of use.
 Use suitable respiratory protective device when high concentrations are present.
 For large spills, respiratory protection may be advisable.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/22/2015

Reviewed on 07/22/2015

Trade name: STERI FAB®

(Contd. of page 5)

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Eye protection:**

Safety glasses

· **Body protection:**

Not required under normal conditions of use.

Protection may be required for spills.

· **Limitation and supervision of exposure into the environment** Avoid release to the environment.· **Risk management measures** See Section 7 for additional information.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

Form:

Liquid

Color:

Colorless

· **Odor:**

Alcohol-like

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

80 °C (176 °F)

· **Flash point:**

28 °C (82 °F)

· **Flammability (solid, gaseous):**

Not applicable.

· **Auto-ignition temperature:**

Not determined.

· **Decomposition temperature:**

Not determined.

· **Auto igniting:**

Product is not self-igniting.

· **Danger of explosion:**

Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower:

Not determined.

Upper:

Not determined.

· **Vapor pressure at 20 °C (68 °F):**

59 mmHg

· **Density at 20 °C (68 °F):**<1 g/cm³ (<8.345 lbs/gal)· **Relative density**

Not determined.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/22/2015

Reviewed on 07/22/2015

Trade name: STERI FAB®

(Contd. of page 6)

- **Vapour density** Not determined.
- **Evaporation rate** Not determined.
- **Solubility in / Miscibility with Water:** Fully miscible.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
Keep away from heat, sparks, open flames, and hot surfaces. - No smoking.
- **Possibility of hazardous reactions**
Flammable liquid and vapor.
Reacts violently with oxidizing agents.
Toxic fumes may be released if heated above the decomposition point.
Used empty containers may contain product gases which form explosive mixtures with air.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
- **Conditions to avoid**
Keep ignition sources away - Do not smoke.
Store away from oxidizing agents.
- **Incompatible materials:** Oxidizing agents
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

LD/LC50 values that are relevant for classification:

67-63-0 propan-2-ol

Oral	LD50	5045 mg/kg (rat)
Dermal	LD50	12800 mg/kg (rabbit)
Inhalative	LC50/4h	30 mg/l (rat)

- **Primary irritant effect:**
 - on the skin:** Slight irritant effect on skin and mucous membranes.
 - on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Subacute to chronic toxicity:** No further relevant information available.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/22/2015

Reviewed on 07/22/2015

Trade name: STERI FAB®

(Contd. of page 7)

- **Additional toxicological information:**

Irritant

Inhalation of concentrated vapors as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

- **Carcinogenic categories**

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

- **Probable Routes of Exposure**

Inhalation.

Eye contact.

Skin contact.

- **Acute effects (acute toxicity, irritation and corrosivity):**

Vapors have narcotic effect.

Irritating to eyes.

- **Repeated Dose Toxicity:** No further relevant information available.

- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):** None.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** The product contains materials that are harmful to the environment.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Ecotoxicological effects:**

- **Remark:** Harmful to algae

- **Additional ecological information:**

- **General notes:**

This statement was deduced from the properties of the single components.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Due to available data on eliminability/decomposition and bioaccumulation potential a prolonged damage of the environment is unlikely.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Smaller quantities can be disposed of with household waste.

Small amounts may be diluted with plenty of water and washed away. Dispose of bigger amounts in accordance with Local Authority requirements.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/22/2015

Reviewed on 07/22/2015

Trade name: **STERI FAB®**

(Contd. of page 8)

Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA**
- **UN proper shipping name**

UN1993



Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 5 L (1.3 gal).

- **DOT**
- **ADR**
- **IMDG, IATA**
- **Transport hazard class(es)**

Flammable liquids, n.o.s. (Isopropanol mixture)
 1993 FLAMMABLE LIQUID, N.O.S. (Isopropanol mixture)
 FLAMMABLE LIQUID, N.O.S. (Isopropanol mixture)

- **DOT**



- **Class**
- **Label**

3 Flammable liquids
 3

- **ADR**



- **Class**
- **Label**

3 (F1) Flammable liquids
 3

- **IMDG, IATA**



- **Class**
- **Label**
- **Packing group**
- **DOT, ADR, IMDG, IATA**
- **Environmental hazards:**
- **Marine pollutant:**
- **Special precautions for user**

3 Flammable liquids
 3
 III
 No
 Warning: Flammable liquids

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/22/2015

Reviewed on 07/22/2015

Trade name: STERI FAB®

(Contd. of page 9)

- **Danger code (Kemler):** 30
- **EMS Number:** F-E, S-E
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **UN "Model Regulation":** UN1993, Flammable liquids, n.o.s. (Isopropanol mixture), 3, III

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

67-63-0 | propan-2-ol

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

Ethanol - listing refers specifically to alcoholic beverage consumption and is not applicable for product.

64-17-5 | ethanol

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

Ethanol - listing refers specifically to alcoholic beverage consumption and is not applicable for product.

64-17-5 | ethanol

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA)**

EPA Product Registration : 397-13.

This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label:

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING:

Causes substantial but temporary eye injury. Do not get in eyes or on clothing. Harmful if absorbed through skin. Harmful if inhaled. Avoid contact with skin. Avoid breathing vapor or spray mist. Wear goggles or face shield, long sleeved shirt, long pants, socks, shoes and chemical-resistant gloves made of any waterproof material. Remove and wash contaminated clothing before reuse. Wash thoroughly with

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/22/2015

Reviewed on 07/22/2015

Trade name: STERI FAB®

(Contd. of page 10)

soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and aquatic invertebrates. Do not apply directly to water, or to areas where surface water is present, or to inter-tidal areas below the mean high water mark. See Directions for Use for additional precautions and requirements.

Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARDS

Flammable. Keep away from heat and open flame.

FIRST AID

If in eyes: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first five minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

If on skin or clothing: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

If inhaled: Move person to fresh air. If person is not breathing call 911 or ambulance, then give artificial respiration, preferably by mouth to mouth, if possible.

If swallowed: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person.

Note to physician: Probable mucosal damage may contraindicate the use of gastric lavage.

HOT LINE NUMBERS

Have the product container or label with you when calling a poison control center or going for treatment. You may also contact CHEMTEL 1-800-255-3924 for emergency medical treatment information.

STORAGE AND DISPOSAL**PESTICIDE STORAGE**

Keep from freezing. Store in ventilated areas. Do not contaminate water, food or feed by storage and disposal. Dispose leftovers in landfill approved for pesticides.

CONTAINER DISPOSAL

Nonrefillable container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or mix tank and drain for 10 seconds after the flow begins to drip. Fill the container 1/4 full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times. Offer for recycling, if available or discard in trash.

· IARC (International Agency for Research on Cancer)

67-63-0 | propan-2-ol

3

· TLV (Threshold Limit Value established by ACGIH)

67-63-0 | propan-2-ol

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· State Right to Know Listings

None of the ingredients is listed.

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 07/22/2015

Reviewed on 07/22/2015

Trade name: STERI FAB®

(Contd. of page 11)

· **Canadian substance listings:**

· **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

· **Canadian Ingredient Disclosure list (limit 0.1%)**

None of the ingredients is listed.

· **Canadian Ingredient Disclosure list (limit 1%)**

67-63-0 | propan-2-ol

· **Other regulations, limitations and prohibitive regulations**

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 07/22/2015 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

· **Sources**

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com