



SAFETY DATA SHEET

Issuing date 14-Oct-2011

Revision Date 27-Feb-2015

Version 2

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name Swisher Shoot Out Carpet Spotter

Other means of identification

Product Code 41770

UN/ID No UN1950

Document 41770

Recommended use of the chemical and restrictions on use

Recommended use Aerosol- Carpet Spotter

Details of the supplier of the safety data sheet

Distributor

Swisher Hygiene Inc.
4725 Piedmont Row Drive
Suite 400
Charlotte, NC 28210

Emergency telephone number

24 Hour Emergency Phone Number CHEMTREC: 1-800-424-9300 (NORTH AMERICA)
1-703-527-3887 (INTERNATIONAL)

Company Phone Number 800-444-4138

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Category 1	Flammable aerosols

Label elements

Emergency Overview

Danger

Hazard Statements

Causes skin irritation
Causes serious eye irritation
Extremely flammable aerosol

**Appearance** Compressed liquefied gas.**Physical state** Gas**Odor** Butyl Odor**Precautionary Statements - Prevention**

- Keep away from heat/sparks/open flames/hot surfaces. — No smoking
- Do not spray on an open flame or other ignition source
- Pressurized container: Do not pierce or burn, even after use
- Wash hands thoroughly after handling
- Wear eye/face protection
- Wear protective gloves

Precautionary Statements - Response

- Immediately call a POISON CENTER or doctor/physician
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- If skin irritation occurs: Get medical advice/attention
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

Precautionary Statements - Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to approved disposal facility

Hazards not otherwise classified (HNOC)**Other information**

Unknown Acute Toxicity

Expected to be a low hazard for usual industrial or commercial handling by trained personnel.

3. COMPOSITION/INFORMATION ON INGREDIENTS

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Chemical Name	CAS-No	Weight-%	Trade Secret
Propane	74-98-6	1% - 2.5%	*
N-Butane	106-97-8	2.5% - 10%	*
Diethylene glycol monobutyl ether	112-34-5	2.5% - 10%	*
2-Butoxyethanol	111-76-2	2.5% - 10%	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures for different exposure routes**General advice**

Show this safety data sheet to the doctor in attendance.

Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops or persists.
Skin contact	Take off immediately all contaminated clothing. Wash off immediately with plenty of water for at least 15 minutes. Call a physician or Poison Control Center immediately. Remove/Take off immediately all contaminated clothing. Wash contaminated clothing before reuse.
Inhalation	Remove to fresh air. Seek medical attention if symptoms persist.
Ingestion	IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Get medical attention immediately if symptoms occur.
Protection of First-aiders	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Most important symptoms/effects, acute and delayed

Main Symptoms	Skin Irritation. Causes serious eye irritation, Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
----------------------	--

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Water Fog. Dry chemical. Carbon dioxide (CO₂).

Unsuitable Extinguishing Media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. Thermal decomposition can lead to release of irritating and toxic gases and vapors. Extremely flammable.

Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective Equipment and Precautions for Firefighters

Wear self contained breathing apparatus and full protective clothing. Keep containers cool with water spray.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal precautions	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.
Other information	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Environmental precautions Do not discharge into drains/surface waters/groundwater. .

Methods and materials for containment and cleaning up

Methods for Containment Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable.

Methods for cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Do not handle or store near an open flame, heat or other sources of ignition. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not spray on a naked flame or any other incandescent material. Use only in well-ventilated areas. Provide adequate ventilation. Avoid breathing dust/fume/gas/mist/vapors/spray. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not re-use empty containers. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Keep away from heat, sparks and open flame. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Level 1 Aerosol.

Incompatible products Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines Review Section 3 & 4 for Exposure Guidelines.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
N-Butane 106-97-8	STEL: 1000 ppm	-	TWA: 800 ppm TWA: 1900 mg/m ³
Diethylene glycol monobutyl ether 112-34-5	TWA: 10 ppm inhalable fraction and vapor	-	-
2-Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³

NIOSH IDLH: Immediately Dangerous to Life or Health

Appropriate engineering controls

Engineering Measures Explosion-proof general and local exhaust ventilation. Facilities storing or utilizing this material should be equipped with an eyewash facility and safety shower.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields. Tightly fitting safety goggles.

Skin and body protection Wear appropriate chemical resistant clothing and chemical resistant gloves. Wear appropriate thermal protective clothing, when necessary.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Hygiene measures

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and chemical properties

Physical state	Gas	Odor	Butyl Odor
Appearance	Compressed liquefied gas.	Odor Threshold	No information available
Color	Colorless		
<u>Property</u>	<u>Values</u>	<u>Remarks • Methods</u>	
pH	No information available		
Melting/freezing point	No information available		
Boiling point/boiling range	106.04 °C / 223 °F		
Flash Point	-104.4 °C / -156 °F		
Evaporation rate	No information available		
Flammability (solid, gas)	No information available		
Flammability Limits in Air			
Upper flammability limit	No information available		
Lower flammability limit	No information available		
Vapor pressure	50-60 @70F		
Vapor density	No information available		
Specific Gravity	0.958		
Water solubility	Appreciable		
Solubility in other solvents	No information available		
Partition coefficient: n-octanol/water	No information available		
Autoignition temperature	230 446		
Decomposition temperature	No information available		
Viscosity, kinematic	No information available		
Viscosity, dynamic	No information available		
Explosive properties	No information available		
Oxidizing Properties	No information available		

Other information

Softening point	No information available
Molecular Weight	No information available
VOC Content(%)	No information available
Density VALUE	No information available
Bulk Density VALUE	No information available

10. STABILITY AND REACTIVITY

Reactivity

The product is stable and non-reactive under normal conditions of use, storage, and transport.

Chemical stability

Stable under normal conditions.

Possibility of hazardous reactions

None under normal processing. Hazardous polymerization does not occur.

Conditions to Avoid

Avoid heat, sparks, open flames, and other ignition sources. Contact with incompatible materials. Fire or intense heat may cause violent rupture of packages.

Incompatible Materials

Strong oxidizing agents.

Hazardous Decomposition Products

No information available.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	Causes serious eye irritation Causes skin irritation
Inhalation	No adverse effects due to inhalation are expected.
Eye contact	Causes serious eye irritation.
Skin contact	Causes skin irritation.
Ingestion	Expected to be a low ingestion hazard.

Chemical Name	Oral LD50	Dermal LD50	LC50 Inhalation
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h
N-Butane 106-97-8	-	-	= 658 g/m ³ (Rat) 4 h
Diethylene glycol monobutyl ether 112-34-5	= 3384 mg/kg (Rat)	= 2700 mg/kg (Rabbit)	-
2-Butoxyethanol 111-76-2	= 470 mg/kg (Rat)	= 99 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h

Information on toxicological effects

Symptoms	Skin irritation. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
-----------------	--

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	No information available.
Mutagenic effects	No information available.
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
2-Butoxyethanol 111-76-2	A3	Group 3	-	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Chronic toxicity	Unconsciousness. Conjunctiva. Cyanosis (blue tissue condition, nails, lips, and/or skin). May be harmful if absorbed through skin. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. May cause delayed lung injury.
Aspiration hazard	No information available.

Numerical measures of toxicity - Product Information

Unknown Acute Toxicity	Expected to be a low hazard for usual industrial or commercial handling by trained personnel.
-------------------------------	---

12. ECOLOGICAL INFORMATION

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Ecotoxicity

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Diethylene glycol monobutyl ether 112-34-5	100: 96 h Desmodesmus subspicatus mg/L EC50	1300: 96 h Lepomis macrochirus mg/L LC50 static	2850: 24 h Daphnia magna mg/L EC50 >100: 48 h Daphnia magna mg/L EC50
2-Butoxyethanol 111-76-2	-	1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50	1698 - 1940: 24 h Daphnia magna mg/L EC50 >1000: 48 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Propane 74-98-6	2.3
N-Butane 106-97-8	2.89
2-Butoxyethanol 111-76-2	0.81

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment**Waste Disposal Methods**

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. The waste code should be assigned in discussion between the user, the producer and the waste disposal company. Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Since emptied containers may retain product residue, follow label warnings even after container is emptied.

Contaminated packaging

Do not reuse container.

14. TRANSPORT INFORMATION

Note

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

DOT

UN/ID No	Regulated UN1950
Proper shipping name	Aerosols Flammable
Hazard class	2.1
Packing Group	II
Reportable Quantity (RQ)	LTD QTY
Marine Pollutant	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Emergency Response Guide Number	126

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - All components of this product are listed or are exempt or excluded from listing on the United States Toxic Substances Control Act Section 8(b) Inventory.

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	SARA 313 - Threshold Values %
Diethylene glycol monobutyl ether - 112-34-5	1.0
2-Butoxyethanol - 111-76-2	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	no
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	no

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

CERCLA (Superfund) reportable quantity - None

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely hazardous substance - No

Section 311 hazardous chemical - Yes

U.S. State Regulations

California Proposition 65

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

U.S. - Pennsylvania - RTK (Right to Know) List

2-Butoxyethanol 111-76-2 Present

Diethylene Glycol Monobutyl Ether 112-34-5 Environmental hazard

n-Butane 106-97-8 Present

U.S. State Right-to-Know Regulations

This product contains substances regulated by state right-to-know regulations.

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Propane 74-98-6	X	X	X
N-Butane 106-97-8	X	X	X
Diethylene glycol monobutyl ether 112-34-5	X	-	X
2-Butoxyethanol 111-76-2	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA	Health Hazards 1	Flammability 2	Instability 0	Physical and chemical hazards -
HMIS	Health hazard 1	Flammability 2	Physical Hazards 0	Personal protection X

Prepared By

Swisher Hygiene Inc.
4725 Piedmont Row Drive
Suite 400
Charlotte, NC 28210

Issuing date

14-Oct-2011

Revision Date

27-Feb-2015

Revision Note

2

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet