

# **SMARTPOWER PRESOAK LIQUID PREMIX**

### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : SMARTPOWER PRESOAK LIQUID PREMIX

Other means of identification : Not applicable

Recommended use : Intermediate

Restrictions on use : Reserved for industrial and professional use.

Product dilution information : Product is sold ready to use.

Company : Ecolab Inc.

1 Ecolab Place

St. Paul, Minnesota USA 55102

1-800-352-5326

Emergency health

information

: 1-800-328-0026 (US/Canada), 1-651-222-5352 (outside US)

Issuing date : 08/14/2024

### **SECTION 2. HAZARDS IDENTIFICATION**

#### **GHS Classification**

Eye irritation : Category 2A Skin sensitization : Category 1

### **GHS** label elements

Hazard pictograms



Signal Word : Warning

Hazard Statements : May cause an allergic skin reaction.

Causes serious eye irritation.

Precautionary Statements : Prevention:

Avoid breathing mist or vapors. Wash skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/ eye protection/ face protection.

Response:

IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards : Do not mix with bleach or other chlorinated products – will cause

chlorine gas.

# **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

919708 1 / 9

## SMARTPOWER PRESOAK LIQUID PREMIX

Pure substance/mixture : Mixture

**Chemical name** CAS-No. Concentration (%) 2-Butenedioic acid (2Z)-, homopolymer 26099-09-2 10 - 30 2-butanedioic acid potassium salt 26099-08-1 1 - 5 maleic acid 110-16-7 1 - 5 Limonene 5989-27-5 1 - 5 Geraniol 106-24-1 0.1 - 1

### **SECTION 4. FIRST AID MEASURES**

In case of eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. If eye

irritation persists: Get medical advice/ attention.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Use

a mild soap if available. Wash clothing before reuse. Thoroughly clean

shoes before reuse. Get medical attention.

If swallowed : Rinse mouth. Get medical attention if symptoms occur.

If inhaled : Get medical attention if symptoms occur.

Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal

protective equipment.

Notes to physician : Treat symptomatically.

Most important symptoms and effects, both acute and

delayed

: See Section 11 for more detailed information on health effects and

symptoms.

### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: None known.

Specific hazards during fire

fighting

: Not flammable or combustible.

Hazardous combustion

products

Decomposition products may include the following materials:

Carbon oxides

Nitrogen oxides (NOx) Oxides of phosphorus

Special protective equipment

for fire-fighters

: Use personal protective equipment.

Specific extinguishing

methods

: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire

and/or explosion do not breathe fumes.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, : Ensure clean-up is conducted by trained personnel only. Refer to

919708 2/9

# SMARTPOWER PRESOAK LIQUID PREMIX

protective equipment and emergency procedures

protective measures listed in sections 7 and 8.

Environmental precautions : Do not allow contact with soil, surface or ground water.

Methods and materials for containment and cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with noncombustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain

material to ensure runoff does not reach a waterway.

### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Do not get in eyes, on skin, or on clothing. Wash hands thoroughly

> after handling. Do not mix with bleach or other chlorinated products will cause chlorine gas. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective

Equipment (PPE).

Conditions for safe storage : Keep out of reach of children. Store in suitable labeled containers.

Storage temperature : 0 °C to 50 °C

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
Limonene	5989-27-5	TWA	30 ppm	AIHA WEEL

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations

below occupational exposure standards.

# Personal protective equipment

Eye protection : Safety glasses with side-shields

Hand protection : Wear the following personal protective equipment:

Standard glove type.

Gloves should be discarded and replaced if there is any indication of

degradation or chemical breakthrough.

Skin protection : No special protective equipment required.

: No personal respiratory protective equipment normally required. Respiratory protection

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. Wash face, hands and any exposed skin thoroughly after

handling.

# **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

# SMARTPOWER PRESOAK LIQUID PREMIX

Color : transparent, blue

Odor mild

3.05 - 3.75, (100 %) рΗ

Flash point : Not applicable, Does not sustain combustion.

Odor Threshold : No data available : No data available Melting point/freezing point

Initial boiling point and

boiling range

: > 100 °C

Evaporation rate

Relative vapor density

: No data available Flammability (solid, gas) : Not applicable Upper explosion limit : No data available Lower explosion limit : No data available Vapor pressure : No data available

: 1.15 - 1.3 Relative density Water solubility : soluble

: No data available Solubility in other solvents Partition coefficient: n-: No data available

octanol/water

: No data available

: No data available Autoignition temperature Thermal decomposition : No data available Viscosity, kinematic : No data available Explosive properties : No data available : No data available Oxidizing properties Molecular weight : No data available VOC : No data available

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

: Stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

: Do not mix with bleach or other chlorinated products - will cause

chlorine gas.

Conditions to avoid : None known.

Incompatible materials : Strong bases

Hazardous decomposition

products

: In case of fire hazardous decomposition products may be produced

such as:

Carbon oxides

Nitrogen oxides (NOx) Oxides of phosphorus

## **SECTION 11. TOXICOLOGICAL INFORMATION**

# SMARTPOWER PRESOAK LIQUID PREMIX

exposure

Information on likely routes of : Inhalation, Eye contact, Skin contact

#### **Potential Health Effects**

Eyes : Causes serious eye irritation.

Skin : May cause allergic skin reaction.

: Health injuries are not known or expected under normal use. Ingestion

Inhalation : Health injuries are not known or expected under normal use.

Chronic Exposure : Health injuries are not known or expected under normal use.

### **Experience with human exposure**

Eye contact : Redness, Pain, Irritation

Skin contact : Redness, Irritation, Allergic reactions

Ingestion : No symptoms known or expected.

Inhalation : No symptoms known or expected.

## **Toxicity**

**Product** 

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Acute inhalation toxicity : No data available

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Skin corrosion/irritation : No data available Serious eye damage/eye : No data available

irritation

Respiratory or skin

sensitization

: No data available

: No data available Carcinogenicity Reproductive effects : No data available Germ cell mutagenicity : No data available : No data available Teratogenicity STOT-single exposure : No data available : No data available STOT-repeated exposure : No data available Aspiration toxicity

# SECTION 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

**Environmental Effects** : Harmful to aquatic life with long lasting effects.

### **Product**

# SMARTPOWER PRESOAK LIQUID PREMIX

Toxicity to fish : No data available Toxicity to daphnia and other : No data available

aquatic invertebrates

Toxicity to algae : No data available

Components

Toxicity to fish : 2-Butenedioic acid (2Z)-, homopolymer

96 h LC50 Fish: 580 mg/l

maleic acid

96 h LC50 Oncorhynchus mykiss (rainbow trout): 75 mg/l Test substance: Information given is based on data obtained from

similar substances.

Components

aquatic invertebrates

Toxicity to daphnia and other : 2-Butenedioic acid (2Z)-, homopolymer

48 h EC50 Aquatic Invertebrate: > 1,000 mg/l

maleic acid

48 h EC50 Daphnia magna (Water flea): 42.81 mg/l

Limonene

48 h EC50 Daphnia magna (Water flea): 0.307 mg/l

Components

Toxicity to algae : maleic acid

72 h EC50 Pseudokirchneriella subcapitata (algae): 74.35 mg/l

Limonene

72 h EC50 Pseudokirchneriella subcapitata (algae): 0.32 mg/l

Geraniol

72 h EC50: 5.93 mg/l

Persistence and degradability

Poorly biodegradable

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

**SECTION 13. DISPOSAL CONSIDERATIONS** 

Disposal methods : Do not contaminate ponds, waterways or ditches with chemical or

> used container. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste

disposal facility.

Disposal considerations : Dispose of as unused product. Empty containers should be taken to

an approved waste handling site for recycling or disposal. Do not re-

# SMARTPOWER PRESOAK LIQUID PREMIX

use empty containers. Dispose of in accordance with local, state, and federal regulations.

# **SECTION 14. TRANSPORT INFORMATION**

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

## Land transport (DOT)

Not dangerous goods

## Sea transport (IMDG/IMO)

Not dangerous goods

### **SECTION 15. REGULATORY INFORMATION**

### **EPCRA - Emergency Planning and Community Right-to-Know**

## **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

# SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Respiratory or skin sensitization

Serious eye damage or eye irritation

SARA 302 : This material does not contain any components with a section 302

EHS TPQ.

SARA 313 : This material does not contain any chemical components with known

CAS numbers that exceed the threshold (De Minimis) reporting levels

established by SARA Title III, Section 313.

## California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

## California Cleaning Product Right to Know Act of 2017 (SB 258)

This regulation applies to this product.

Hazardous ingredients	CAS-No.	Function	List(s)
water	7732-18-5	Diluent	Not Applicable
2-Butenedioic acid (2Z)-,	26099-09-2	Cleaning Agent	Not Applicable
homopolymer			
Sugar	Withheld	Stabilizer	Not Applicable
maleic acid	110-16-7	Cleaning Agent	Not Applicable
Limonene	5989-27-5	Fragrance	FRA
Citral	5392-40-5	Fragrance	FRA
Pigment	Withheld	Dye	Not Applicable
Geraniol	106-24-1	Fragrance	FRA
Citronellol	106-22-9	Fragrance	FRA
Glycol	Withheld	Dye	Not Applicable
Amine	Withheld	Dye	Not Applicable
Amine	Withheld	Dye	Not Applicable

919708 7 / 9

# SMARTPOWER PRESOAK LIQUID PREMIX

Linalool	78-70-6	Fragrance	FRA
acrylic acid	79-10-7	Cleaning Agent	4. 18. 20. NFC

<sup>\*</sup>refer to ecolab.com/sds for electronic links to designated lists

#### The ingredients of this product are reported in the following inventories:

#### **United States TSCA Inventory:**

All components are listed or exempted.

#### Canadian Domestic Substances List (DSL):

This product contains one or several components listed in the Canadian NDSL.

## Australia. Australian Industrial Chemicals Introduction Scheme (AICIS):

not determined

### New Zealand. Inventory of Chemical Substances:

not determined

## Japan. ENCS - Existing and New Chemical Substances Inventory:

not determined

# Korea. Korean Existing Chemicals Inventory (KECI):

not determined

# Philippines Inventory of Chemicals and Chemical Substances (PICCS):

not determined

### China. Inventory of Existing Chemical Substances in China (IECSC):


not determined

### Taiwan Chemical Substance Inventory (TCSI):

not determined

## **SECTION 16. OTHER INFORMATION**

### NFPA:



#### HMIS III:

HEALTH	2*
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, \* = Chronic

: 08/14/2024 Issuing date

Version : 2.1

Prepared by : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

# **SMARTPOWER PRESOAK LIQUID PREMIX**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

919708 9 / 9