

## SOLVAXX PRO-300LF

## **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : SOLVAXX PRO-300LF

Other means of identification : Not applicable

Recommended use : Cleaning product

Restrictions on use : Reserved for industrial and professional use.

Product dilution information : No dilution information provided.

Company : Ecolab Inc.

1 Ecolab Place

St. Paul, Minnesota USA 55102

1-800-352-5326

Emergency health

information

: 1-800-328-0026 (US/Canada), 1-651-222-5352 (outside US)

Issuing date : 09/07/2022

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### **GHS Classification**

Skin corrosion : Category 1A
Serious eye damage : Category 1
Skin sensitization : Category 1

#### **GHS** label elements

Hazard pictograms :





Signal Word : Danger

Hazard Statements : Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Precautionary Statements : Prevention:

Avoid breathing mist or vapors. Wash skin thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/ protective clothing/ eye protection/ face

protection. Response:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. If skin irritation or rash occurs: Get medical advice/ attention. Wash contaminated clothing

before reuse.

Storage:

Store locked up.

917903-02 1 / 10

## SOLVAXX PRO-300LF

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards : None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Pure substance/mixture Mixture

Chemical name	CAS-No.	Concentration (%)
Sodium hydroxide	1310-73-2	5 - 10
2-(2-ethoxyethoxy)ethanol	111-90-0	1 - 5
2-(2-butoxyethoxy)ethanol	112-34-5	1 - 5
benzenesulfonic acid, methyl-, potassium salt	30526-22-8	1 - 5
Sodium Xylenesulfonate	1300-72-7	1 - 5
Carboxylated alcohol alcoxylate	Proprietary Ingredient	0.1 - 1
Sodium hydroxide	1310-73-2	5 - 10
2-(2-ethoxyethoxy)ethanol	111-90-0	1 - 5
2-(2-butoxyethoxy)ethanol	112-34-5	1 - 5
benzenesulfonic acid, methyl-, potassium salt	30526-22-8	1 - 5
Sodium Xylenesulfonate	1300-72-7	1 - 5
potassium hydroxide	1310-58-3	0.1 - 1
Carboxylated alcohol alcoxylate		0.1 - 1

#### **SECTION 4. FIRST AID MEASURES**

: Rinse immediately with plenty of water, also under the eyelids, for at In case of eye contact

least 15 minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Get medical attention immediately.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes.

Wash clothing before reuse. Thoroughly clean shoes before reuse.

Get medical attention immediately.

If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give

anything by mouth to an unconscious person. Get medical attention

immediately.

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention if

symptoms occur.

Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal

protective equipment.

Notes to physician : Treat symptomatically.

Most important symptoms and effects, both acute and

: See Section 11 for more detailed information on health effects and symptoms.

delayed

## **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: None known.

917903-02 2/10

## SOLVAXX PRO-300LF

Specific hazards during fire

fighting

: Not flammable or combustible.

Hazardous combustion

products

: Decomposition products may include the following materials:

Carbon oxides Sulfur oxides

Special protective equipment

for fire-fighters

: Use personal protective equipment.

Specific extinguishing

methods

: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire

and/or explosion do not breathe fumes.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures

listed in sections 7 and 8.

**Environmental precautions** 

: Do not allow contact with soil, surface or ground water.

Methods and materials for containment and cleaning up

: Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain

material to ensure runoff does not reach a waterway.

## **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Do not

breathe dust/ fume/ gas/ mist/ vapors/ spray. Use only with adequate ventilation. Wash hands thoroughly after handling. In case of mechanical malfunction, or if in contact with unknown dilution of

product, wear full Personal Protective Equipment (PPE).

Conditions for safe storage : Do not store near acids. Keep out of reach of children. Store in

suitable labeled containers.

Storage temperature : 0 °C to 50 °C

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
sodium hydroxide	1310-73-2	С	2 mg/m3	ACGIH
		С	2 mg/m3	NIOSH REL
		TWA	2 mg/m3	OSHA Z-1
		С	2 mg/m3	OSHA P0
		С	2 mg/m3	
2-(2-ethoxyethoxy)ethanol	111-90-0	TWA	25 ppm	US WEEL

917903-02 3 / 10

## SOLVAXX PRO-300LF

2-(2-butoxyethoxy)ethanol	112-34-5	TWA (Inhalable fraction and vapor)	10 ppm	ACGIH
potassium hydroxide	1310-58-3	С	2 mg/m3	ACGIH
		С	2 mg/m3	NIOSH REL
		С	2 mg/m3	OSHA P0
		С	2 mg/m3	

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations

below occupational exposure standards.

#### Personal protective equipment

Eye protection : Wear eye protection and/or face protection.

Hand protection : Wear the following personal protective equipment:

Standard glove type.

Gloves should be discarded and replaced if there is any indication of

degradation or chemical breakthrough.

Skin protection : Personal protective equipment comprising: suitable protective gloves,

safety goggles and protective clothing

Respiratory protection : When workers are facing concentrations above the exposure limit they

must use appropriate certified respirators.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes

and body in case of contact or splash hazard.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid
Color : tan
Odor : slight

pH : 14.0, (100 %)
Flash point : Not applicable
Odor Threshold : No data available
Melting point/freezing point : No data available
Initial boiling point and : No data available

boiling range

: No data available

Evaporation rate : No data available
Flammability (solid, gas) : Not applicable
Upper explosion limit : No data available
Lower explosion limit : No data available
Vapor pressure : No data available
Relative vapor density : No data available

917903-02 4 / 10

## SOLVAXX PRO-300LF

Relative density : 1.12 Water solubility : soluble

Solubility in other solvents : No data available Partition coefficient: n-: No data available

octanol/water

Autoignition temperature : No data available Thermal decomposition : No data available : No data available Viscosity, kinematic Explosive properties : No data available

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available VOC : No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.

: Stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

: No dangerous reaction known under conditions of normal use.

Conditions to avoid : None known.

Incompatible materials : Acids

Hazardous decomposition

products

: In case of fire hazardous decomposition products may be produced

such as: Carbon oxides Sulfur oxides

## **SECTION 11. TOXICOLOGICAL INFORMATION**

exposure

Information on likely routes of : Inhalation, Eye contact, Skin contact

#### **Potential Health Effects**

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns. May cause allergic skin reaction.

Ingestion : Causes digestive tract burns.

Inhalation : May cause nose, throat, and lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

## **Experience with human exposure**

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Irritation, Corrosion, Allergic reactions

917903-02 5/10

# SOLVAXX PRO-300LF

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

**Toxicity** 

**Product** 

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Acute inhalation toxicity : No data available

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg

Skin corrosion/irritation : No data available
Serious eye damage/eye : No data available

irritation

Respiratory or skin

sensitization

: No data available

Carcinogenicity : No data available
Reproductive effects : No data available
Germ cell mutagenicity : No data available
Teratogenicity : No data available
STOT-single exposure : No data available
STOT-repeated exposure : No data available

#### **SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity** 

Aspiration toxicity

Environmental Effects : This product has no known ecotoxicological effects.

: No data available

**Product** 

Toxicity to fish : No data available

Toxicity to daphnia and other : No data available

aquatic invertebrates

Toxicity to algae : No data available

Components

Toxicity to fish : 2-(2-ethoxyethoxy)ethanol

96 h LC50 Ictalurus punctatus (channel catfish): 6,010 mg/l

2-(2-butoxyethoxy)ethanol 96 h LC50 Fish: 1,300 mg/l

benzenesulfonic acid, methyl-, potassium salt

96 h LC50 Fish: > 100 mg/l

Carboxylated alcohol alcoxylate

96 h LC50: 140 mg/l

2-(2-ethoxyethoxy)ethanol

96 h LC50 Ictalurus punctatus (channel catfish): 6,010 mg/l

2-(2-butoxyethoxy)ethanol

917903-02 6 / 10

## SOLVAXX PRO-300LF

96 h LC50 Fish: 1,300 mg/l

benzenesulfonic acid, methyl-, potassium salt

96 h LC50 Fish: > 100 mg/l

Carboxylated alcohol alcoxylate

96 h LC50: 140 mg/l

#### Components

Toxicity to daphnia and other aquatic invertebrates

: Sodium hydroxide

48 h EC50 Daphnia magna (Water flea): 40 mg/l

2-(2-ethoxyethoxy)ethanol

48 h LC50 Daphnia magna (Water flea): 1,982 mg/l

Carboxylated alcohol alcoxylate

48 h EC50 Daphnia magna (Water flea): 240 mg/l

Sodium hydroxide

48 h EC50 Daphnia magna (Water flea): 40 mg/l

2-(2-ethoxyethoxy)ethanol

48 h LC50 Daphnia magna (Water flea): 1,982 mg/l

Carboxylated alcohol alcoxylate

48 h EC50 Daphnia magna (Water flea): 240 mg/l

#### Components

Toxicity to algae

: 2-(2-ethoxyethoxy)ethanol

96 h EC50 Desmodesmus subspicatus (green algae): > 100 mg/l Test substance: Information given is based on data obtained from

similar substances.

96 h NOEC Desmodesmus subspicatus (green algae): > 100 mg/l Test substance: Information given is based on data obtained from

similar substances.

Sodium Xylenesulfonate 96 h EC50: 230 mg/l

2-(2-ethoxyethoxy)ethanol

96 h EC50 Desmodesmus subspicatus (green algae): > 100 mg/l Test substance: Information given is based on data obtained from

similar substances.

96 h NOEC Desmodesmus subspicatus (green algae): > 100 mg/l Test substance: Information given is based on data obtained from

similar substances.

Sodium Xylenesulfonate 96 h EC50: 230 mg/l

#### Persistence and degradability

Biodegradable

#### **Bioaccumulative potential**

No data available

## Mobility in soil

917903-02 7 / 10

## SOLVAXX PRO-300LF

No data available

#### Other adverse effects

No data available

# **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods : Where possible recycling is preferred to disposal or incineration. If

recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.

Disposal considerations : Dispose of as unused product. Empty containers should be taken to

an approved waste handling site for recycling or disposal. Do not reuse empty containers. Dispose of in accordance with local, state, and

federal regulations.

RCRA - Resource : D002 (Corrosive)

Conservation and Recovery Authorization Act Hazardous

waste

# **SECTION 14. TRANSPORT INFORMATION**

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

#### **SECTION 15. REGULATORY INFORMATION**

## **EPCRA - Emergency Planning and Community Right-to-Know**

#### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Sodium hydroxide	1310-73-2	1000	11542

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Respiratory or skin sensitization

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 302 : This material does not contain any components with a section 302

EHS TPQ.

SARA 313 : The following components are subject to reporting levels established

by SARA Title III, Section 313:

2-(2-ethoxyethoxy)ethanol 111-90-0 1 - 5 % 2-(2-butoxyethoxy)ethanol 112-34-5 1 - 5 %

#### California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

#### California Cleaning Product Right to Know Act of 2017 (SB 258)

This regulation does not apply to this product.

917903-02 8 / 10

## SOLVAXX PRO-300LF

#### The ingredients of this product are reported in the following inventories:

## **United States TSCA Inventory:**

All substances listed as active on the TSCA inventory

#### Canadian Domestic Substances List (DSL):

On the inventory, or in compliance with the inventory

#### Australia. Australian Industrial Chemicals Introduction Scheme (AICIS):

not determined

#### New Zealand. Inventory of Chemical Substances:

not determined

#### Japan. ENCS - Existing and New Chemical Substances Inventory :

not determined

#### Korea. Korean Existing Chemicals Inventory (KECI):

not determined

## Philippines Inventory of Chemicals and Chemical Substances (PICCS):

not determined

## China. Inventory of Existing Chemical Substances in China (IECSC):


not determined

# Taiwan Chemical Substance Inventory (TCSI):

not determined

## **SECTION 16. OTHER INFORMATION**

#### NFPA:



#### HMIS III:

HEALTH	3*
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, \* = Chronic

Issuing date : 09/07/2022

Version : 1.0

Prepared by : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is

917903-02 9 / 10

# **SOLVAXX PRO-300LF**

not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

917903-02 10 / 10